



Representative

Catalog Number: DS3504MP000/JG64
Product ID: 7TAA057030R0651
UPC Number: 70891730915
Status: A

MaxGard Male Plug, 30 Amp, 4 Pole 5 Wire, 30Y 277/480V, 60Hz, with 3/4 Inch Bushing

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	Russellstoll Hazardous Locations
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	For use in "People Movers" which require air conditioning and heater unit power when docked at end of line locations for maintenance and overhaul, ex: Dulles Airport.
Number Of Poles	4
Number Of Wires	5
Amperage Rating	30 Amps
Voltage Rating	277 V
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Construction type	Plug
Number of poles	4

Packaging

Outer Quantity	1
Outer Dimensions (inches)	8.63x4.75x4.63
Weight Uom	3 lbs. Each

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com