



Representative

Catalog Number: Product ID: UPC Number: EAN Number: Status: **DS3504MP00K**

7TAA057020R0039 70891713487 05415022252286 Active

MaxGard Male Plug with Control Contacts, 30 Amp, 4 Pole 5 Wire, 30Y 277/480V, 60Hz

UNSPSC Specifications	
UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Туре	Russellstoll Hazardous Locations
Special Features	Waterproof construction provides environmen-
	tal separation at the front of each device (they
	don't have to be connected together just to
	be called "watertight").
Application	For use in "People Movers" which re-
	quire aire conditioning and heater unit power when
	docked at end of line locations for maintenance and
	overhaul, ex: Dulles Airport.
Material	Cast Aluminum
ETIM Specifications	
ETIM	EC001322 Round socket/plug for high currents

ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Construction type	Plug
Number of poles	4

Packaging

Outer Quantity	1
Outer Dimensions (inches)	8.63x4.75x4.63
Weight Uom	2.78 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com