

Russellstoll

MaxGard Interconnection Systems

T&B Catalog Number:

DS4404MP000

UPC Number:

70891715945

Status:

Active

Description:

MaxGard Male Plug, 400 Amp, 3 Pole 4 Wire, 30 480V, 60Hz

Features

Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").

Two optional pilot/control pins for contractors, load monitor circuits, shunt trip or any other communication functions you need.

Center ground contacts: make FIRST, break LAST
Standard delayed action pull and turn withdrawal offers all plugs an XP rating (30-100 amps).

Application

Shore power to marine vessels-sightseeing boats
For use in applications where outdoor, severe or high abuse environments exist.

Shore power to marine vessels-sightseeing boats

General

Style	Load Breaking Male Plug
Material	Copper Free, Cast Aluminum, Epoxy Powder-Coated Housing
Material_1	Standard Neoprene O-ring interior components
Material_2	Pin and sleeves are made from CDA 360 and Marine-grade CDA 485 brass (200a nd 400 amp lines are silver-plated as well).
Frequency	60 Hz
Amperage	400 Amp
Pole/Wire	3P/4W
System	Heavy Industrial & Marine

Dimension Information

Overall Dimensions Available on Website

Specifications

Voltage 3 Phase 480 Volts AC

Engineering Specifications Available on Website

Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	22.53 lbs. Each

Application Support

Overview Available on Website

Russellstoll Application Guide Available on Website

Certifications



RoHS Compliance

No

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com