



Representative

Catalog Number: DS4514FP00K
Product ID: 7TAA057030R0734
UPC Number: 70891733248
Status: A

MaxGard Female Connector with Control Contacts, 400 Amp, 4 Pole 5 Wire, 30Y 347/600V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	Shore power to marine vessels-sightseeing boats
Number Of Poles	4
Number Of Wires	5
Amperage Rating	400 Amp
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	400A
Number of poles	4

Packaging

Outer Quantity	1
Outer Dimensions (inches)	14.63x14.63x18.75
Weight Uom	35 lbs. Each

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com