



Actual

Catalog Number: DSRE1404NA000
Product ID: 7TAA057070R0245
UPC Number: 70891718650
Status: A

MaxGard Explosion-Proof Interlocked Receptacle Class I, Class II, 100 Amp, 3 Pole 4 Wire, 30 480V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	Explosion-proof waterproof non-interlocked receptacle O-ring sealed along with optional control contacts fully UL listed.
Application	Power for trade show exhibits and concerts, Electrical hook-up of mobile medical imaging (MMI trailers)
Standard	UL E68085
Number Of Poles	3
Number Of Wires	4
Amperage Rating	100 Amp
Voltage Rating	480V
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	100A
Number of poles	3

Packaging

Outer Quantity	1
Weight Uom	45 lbs. Each

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com