



Actual

Catalog Number: DSR54414NA0K0
Product ID: 7TAA057060R0019
UPC Number: 70891731423
Status: Active

MaxGard Interlocked Receptacle with Switch and Control Contacts, 400 Amp, 3 Pole 4 Wire, 30 600V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	Power for trade show exhibits and concerts, Electrical hook-up of mobile medical imaging (MMI trailers)
Number Of Poles	3
Number Of Wires	4
Amperage Rating	400 Amp
Voltage Rating	600V
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	400A
Number of poles	3

Packaging

Outer Quantity	1
Outer Dimensions (inches)	34.25x26.38x26
Weight Uom	7.19 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com