



Actual

Catalog Number: DSR54421NA000
Product ID: 7TAA057070R0296
UPC Number: 70891730081
Status: A

MaxGard Interlocked Receptacle with Switch, 400 Amp, 3 Pole 4 Wire, 30 440V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	MaxGard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	Power for trade show exhibits and concerts, Electrical hook-up of mobile medical imaging (MMI trailers)
Number Of Poles	3
Number Of Wires	4
Amperage Rating	400 Amp
Voltage Rating	440V
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	400A
Number of poles	3

Packaging

Outer Quantity	1
Outer Dimensions (inches)	32x15.5x11.88
Weight Uom	115 lbs. Each

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com