

Representative

Catalog Number: Product ID:

JCS334H

7TAA057100R0042

**UPC Number:** Status:

70891720072

J-Line Connector Watertight Screw Cap, 30 Amp, 3 Pole 4 , with 0.875 Inch Bushing I.D.

North American Specifications (UNSPSC)	
UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Туре	J-Line Interconnection Systems
Special Features	One-piece interior assemblies interchangeable from
	regular to reverse service in the field with a screw-
	driver. Reversed contacts flexibility within any hous-
	ing.
Application	Value alternative to MaxGard< in 3 Pole 4 Wire,
	30 to 200 Amp applications with less severe need.
Number Of Poles	3
Number Of Wires	4
Amperage Rating	30 Amps
Voltage Rating	600 V
Material	Cast Aluminum

European Specifications (ETIM)	
ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Number of poles	3
Packaging	
Outer Quantity	1
Weight Uom	2 lbs. Each

## For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50

860 Ridge Lake Blvd. Memphis, TN 38120

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com