



Representative

## Catalog Number: Product ID: UPC Number: Status:

**JRSA634H** 7TAA057090R0033 70891719948 Active

J-Line Receptacle Watertight (Screw Cover), 60 Amp, 3 Pole 4 , with 1.1875 Inch Bushing I.D.

UNSPSC Specifications	
UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Туре	J-Line Interconnection Systems
Special Features	One-piece interior assemblies interchangeable from regular to reverse service in the field with a screw- driver. Reversed contacts flexibility within any hous- ing.
Application	Value alternative to MaxGard< in 3 Pole 4 Wire, 30 to 200 Amp applications with less severe need.
Material	Cast Aluminum
ETIM Specifications	
ETIM	EC001322 Round socket/plug for high currents
Amperage	60A
Number of poles	3
Packaging	
Outer Quantity	1
Weight Uom	4.7 lbs. Each

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com