



# **LAMP SPECIFICATION GUIDE**

We are pleased to present the latest edition of our Lamp Specification Guide. Many new lamps and accessories have been added, and each section is color-coded and arranged to make finding the right product easy.

# Brilliance

Satco is committed to providing unsurpassed quality, service and product assortment. Many of our product categories are supported by merchandising systems, displays and a selection of attention-getting point of purchase materials. These efforts, along with our strategic locations, make Satco the preferred choice in light sources and electrical related products.

## Six convenient locations

### WASHINGTON

4710 116th St. S.W.  
Mukilteo, Washington 98275  
800-437-2826  
(425) 789-3300 FAX: (425) 789-3310

### NEW YORK CORPORATE OFFICES

110 Heartland Blvd.  
Brentwood, N.Y. 11717  
800-437-2826  
(631) 243-2022 FAX: (631) 243-2027

### CALIFORNIA

31288 San Benito St.  
Hayward, California 94544  
800-437-2826  
(510) 487-4822 FAX: (510) 487-8955

### TEXAS

2000 Valwood Parkway  
Farmers Branch, Texas 75234  
800-437-2826  
(972) 247-2437 FAX: (972) 247-5408

### FLORIDA

900 N.W. 159th Drive  
Miami, Florida 33169  
800-437-2826  
(305) 624-2044 FAX: (305) 623-0286

### PUERTO RICO

Bldg 3, Compeche St. 22  
Julio N. Matos Industrial Park  
Carolina, PR 00984  
800-437-2826  
(787) 757-3510 Fax: (787) 757-3540

## Contents

<b>About Satco</b>	<b>2</b>
<b>Retail Support</b>	<b>6</b>
Fluorescent	10
CFL	28
Halogen	48
Incandescent	72
HID	96
Miniatures and Sealed Beams	108
HID / Fluorescent Ballasts	120
<b>Index</b>	<b>128</b>

# At Satco, our business isn't about us. It's about you and your business.

Satco and our Nuvo® and Hygrade™ brands have grown to be industry leaders by offering you the widest selection of lamps, fixtures and lighting components.

## **The most innovative technology.**

The highest standards of quality and efficiency. And a reputation for service earned one customer at a time for almost 50 years.

## **Satco. Setting the standards.**

With a vast catalog of products built to the highest quality standards, massive inventories, a highly automated nationwide distribution network, and a growing investment in research and development, few lighting manufacturers can match Satco's depth of industry experience.


## **The widest selection.**

Satco keeps homes across North America lit through the thousands of retail outlets we supply with replacements lamps and consumer lighting accessories.

The residential and commercial building trades rely on Satco's comprehensive line of fixtures, track and outdoor lighting and lamps, which are widely available through electrical distributors across the country.

Lighting fixture manufacturers turn to Satco Logistics for on-time shipping of thousands of component parts in orders of any size, including lamps, ballasts, sockets, switches, cords, canopies and glassware of every description.





## The most innovative technology.

Over the years, Satco's robust R&D programs have moved lighting technology forward with patented innovations that have been widely adopted throughout the industry that includes breaking new ground in the design and manufacture of high-efficiency LED lamps.

## The highest quality and efficiency.

Every Satco product is designed, manufactured and tested to meet or exceed the highest industry standards for quality and performance. And we offer hundreds of products that have earned ENERGY STAR® certification. In fact, we were selected ENERGY STAR® Partner of the Year in 2009.

## Over a million square feet of warehouse space.

The Satco brand has stood for quality, innovation and value in lighting products since 1966. From a 3,000 square foot warehouse in Elmont, NY, to more than 1.2 million square feet of U.S. Distribution space today. To be certain you'll have the parts you need where you need them, Satco maintains enormous amounts of inventories at our major distribution and sales centers in New York, Miami, Dallas, San Francisco, Seattle and San Juan, Puerto Rico, and at Satco Express stocking locations in Canton MA, Cincinnati OH, Charlotte NC, Chicago IL, Cleveland OH, La Mirada CA, Lavergne TN, Ridgeland MS and Syracuse NY.



## Satco. An innovative family of brands.

### LED lamps that only experience can deliver.

With one of the industry's largest R&D programs behind it, Satco is producing LED replacement lamps that meet all of the newest efficiency standards – and exceed user expectations for light output, color temperature, beam pattern, diffusion, and overall reliability.



### Hygrade. The leader in commercial lighting.

Hygrade has been a trusted name in commercial and industrial lighting for more than a century. From fluorescent and compact fluorescent lamps to high intensity discharge bulbs of every description, Hygrade offers a variety of cost effective, energy efficient products for virtually any commercial application.



### Nuvo. Inspired designs. Enlightened engineering.

Nuvo Lighting was launched in 2005 with more than 1,500 new lighting fixtures – one of the largest catalogs of any manufacturer – and our product line has continued to grow every year since. Today offering more than 3,000 chandeliers, pendants and sconces in designs that range from classic to contemporary, from elegant to understated and from simple to stylish.



As an ongoing effort on behalf of Satco Products, Inc. to remain dedicated to the improvement of our products, we reserve the right to change specifications. The information contained in this specification guide is subject to change without notice. We cannot be responsible for typographical errors.



**Energy Efficient Lamps and Fixtures Counter Card**  
Item # SA1458



**Energy Efficient Lamps Counter Card**  
Item # SA1207



**Paint Department Counter Card**  
Item # SA1456

### Counter cards

Place these informative cards in other busy departments to remind customers about their lighting needs.

At Satco we don't just bring great products and great value to market. We help our products sell! We offer powerful in-store selling tools to help make the lighting center a focal point and profit center.

## Educate customers and increase sales!

Satco hanging signs and gondola headers clearly call-out the lighting center while shelf strips and aisle flags indicate lamp technologies to help customers find exactly what they're looking for. And the shelf strips correspond to the attractive, informative Satco packaging! Our educational gondola headers educate consumers about all the current lighting technologies, the energy efficiency of each and what energy savings they can expect from each.

Counter cards, hanging signs, shelf-talkers and gondola aisle flags all help customers find the exact replacement lamp they need.

Let Satco help you increase your lighting sales dramatically! For information and how to order, please contact your Satco sales representative.

### Logo banners

Measuring 5' x 2', Satco logo banners can be strategically placed, indoors or out, to direct customers to the lighting aisle or simply make customers aware you carry Satco lighting products.



**Satco Brand Logo Banner**  
Item # SA1296



<b>HID</b>	<b>HID</b>	<b>HID</b>	SA1265/1
<b>LED</b>	<b>LED</b>	<b>LED</b>	SA1265/2
<b>CFL</b>	<b>CFL</b>	<b>CFL</b>	SA1265/3
<b>HALOGEN</b>	<b>HALOGEN</b>	<b>HALOGEN</b>	SA1265/4
<b>INCANDESCENT</b>	<b>INCANDESCENT</b>	<b>INCANDESCENT</b>	SA1265/5

**Lighting Technology Gondola Shelf Strips**

(Can be ordered separately)  
Each strip measures 12" long  
Item # SA1265

**Packaging**

Satco retail packaging is informative and attractive, creating an easy to navigate presentation for your customers. Coupled with consistent branding, lamp technology types are clearly indicated and all government regulations are adhered to for lumen output, wattage and cost to operate. Satco packaging makes choosing the right lamp easy.

**Gondola shelf technology strips**

Indicate what technologies are on what shelves. Grouping products by their technology has been shown to help customers find the products they want easily.

**Shelf talkers**

Are an important silent salesman, explaining a sale or calling attention to a new product.



**Energy Efficient Shelf Talker**  
Item # SA1205

# RETAIL SUPPORT



**Generic Lighting Center Gondola Header**  
Item # SA1098

Header mounting hardware available



**Energy Efficient Gondola Header**  
Item # SA1206

Header mounting hardware available



**LED Gondola Header**  
Item # SA2006

Header mounting hardware available

## Gondola headers

Clearly call out your lighting center, and our educational versions help explain new vs. old lighting technologies and the savings your customers can expect from them. Customers making more informed decisions will be pleased with their purchase and remember the help they received in your store.

## Product photos

Satco offers our entire library of product photos for use in your flyers and advertising. Our high-quality product and packaging images will show customers exactly what you're offering.

## Aisle flags

Help define what's on each section of shelving for easy product location.



**Lighting Technology Aisle Violator Tags**  
Item # SA1292  
Mounting hardware available

SA1292/1    SA1292/2    SA1292/3    SA1292/4    SA1292/5    SA1292/6



### Lamp Technology Wattage Comparison www.satco.com

INCANDESCENT - Life: 1,000 Hours			HALOGEN - Life: 1,000 Hours - GOOD			CFL - Life: 10,000 Hours - BETTER			LED - Life: 25,000+ Hours - BEST		
Standard Wattage	Lumens/Brightness	Cost to Operate/Yr*	Wattage	Lumens/Brightness	Cost to Operate/Yr*	Wattage	Lumens/Brightness	Cost to Operate/Yr*	Wattage	Lumens/Brightness	Cost to Operate/Yr*
25W = 200		\$3.01				5W = 280		\$0.84	3W = 180		\$0.36
40W <sup>†</sup> = 450		\$4.82	29W = 410		\$3.49	9W = 550		\$1.08	8W = 450		\$0.96
60W <sup>†</sup> = 800		\$7.23	43W = 750		\$5.18	13W = 900		\$1.57	10W = 800		\$1.20
75W <sup>†</sup> = 1,100		\$9.03	53W = 1,050		\$6.38	18W = 1,200		\$2.17	13W = 1,100		\$1.57
100W <sup>†</sup> = 1,600		\$12.05	72W = 1,490		\$8.67	23W = 1,600		\$2.77	17W = 1,600		\$2.05

\* Discontinued technology  
† Estimated yearly energy cost is based on 3 hrs/day, 0.11¢ kWh. Cost depends on rates and use.

SA1285/1  
Lamp Comparison Guide





### Lamp Savings Comparison-per lamp, per year\* www.satco.com

INCANDESCENT Standard Wattage	Savings for Halogen Life = 1,000 Hours	Savings for CFL Life = 10,000 Hours	Savings for LED Life = 25,000 Hours	SAVE MORE
25W =		\$2.17	\$2.65	<b>Long life = Less replacement lamps</b>
40W =	\$1.33	\$3.74	\$3.86	
60W =	\$2.05	\$5.66	\$6.03	
75W =	\$2.65	\$6.86	\$7.46	
100W =	\$3.38	\$9.28	\$10.00	

\* Estimated yearly energy cost is based on 3 hrs/day, 0.11¢ kWh. Cost depends on rates and use.

SA1285/2  
Lamp Savings Comparison

### Lamp Feature Comparison www.satco.com

 <p><b>INCANDESCENT</b></p> <ul style="list-style-type: none"> <li>• Good light quality</li> <li>• Low initial cost</li> <li>• Dimmable</li> <li>• Shortest life</li> <li>• Least Efficient</li> </ul>	 <p><b>HALOGEN</b></p> <ul style="list-style-type: none"> <li>• Great light quality</li> <li>• Dimmable</li> <li>• Same bulb shape</li> <li>• Energy savings: <b>GOOD</b></li> </ul>	 <p><b>CFL (COMPACT FLUORESCENT)</b></p> <ul style="list-style-type: none"> <li>• Big jump in energy savings</li> <li>• Instant on</li> <li>• Long bulb life, recyclable</li> <li>• Energy savings: <b>BETTER</b></li> </ul>	 <p><b>LED (LIGHT EMITTING DIODE)</b></p> <ul style="list-style-type: none"> <li>• Most energy efficient</li> <li>• Immediate full brightness</li> <li>• Dimmable</li> <li>• Costs the least to operate</li> <li>• Longest bulb life available</li> <li>• Energy savings: <b>BEST</b></li> </ul>
---	---	---	---

SA1285/3  
Lamp Features Comparison

### Long Life = Less Replacements www.satco.com

**1 CFL lasts as long as 10 Incandescents**



= 10 incandescent bulbs

A 13W CFL costs \$1.57 per year to operate in energy costs vs. a 60W incandescent that costs \$7.23 per year.\*

**1 LED lasts as long as 25 Incandescents**



= 25 incandescent bulbs

An 8W LED costs \$0.96 per year to operate in energy costs vs. a 60W incandescent that costs \$7.23 per year.\*

\*Estimated yearly energy cost is based on 3 hrs/day, 0.11¢ kWh. Cost depends on rates and use.

SA1285/4  
Long Life = Less Replacements




SA1285/5  
Lumens: The new way to shop for light


### Choosing Color Temperature www.satco.com

**Lighting sets the mood in your room.**


COLOR TEMPERATURE SCALE			
Soft White	Bright White	Natural Light	
2700K	3000K	3500K	5000K - 7500K
<b>Warm</b> 2700K is inviting, warm, friendly and relaxing. • Homes • Restaurants	<b>Neutral</b> 3000K is inviting, comfortable and relaxing. • Homes • Showrooms • Reception • Offices	<b>Cool</b> 4100K is efficient, clean and organized. • Offices • Hospitals • Conference rooms	<b>Daylight</b> 5000K is exacting, refreshing, bright and alert. • Galleries • Jewelry displays




Warm



Neutral



Cool



Daylight

SA1285/6  
Choosing Color Temperature

**Lamp Comparison Gondola Headers**

SET: 6

(Can be ordered separately)

Item # SA1285

Header mounting hardware available

# FLUORESCENT LAMPS


## Quality, efficiency, taken to great lengths.

At Satco we stock an unprecedented variety of fluorescent lamps. Everything from T5 to T12 sizes, including our Hygrade™, Circline and U-bend styles. There are high-output, rapid start, and instant versions sure to fill any commercial or residential application. Our germicidal and other specialty fluorescents complete one of the most extensive selections in the industry. Our fluorescent lamps are energy efficient, manufactured to the highest standards, and we're stocked to ensure quick deliveries, whatever the quantity.

### Fluorescent lamp features:

- Available in all standard and high-output wattages from 4 to 215 Watts
- Superior CRI levels
- Virtually all industry sizes
- Manufactured to RoHS standards and Federal TCLP standards
- CEE listed High Performance and Reduced Wattage options to meet Energy Efficient Commercial Lighting System conversions
- High lumen maintenance levels
- Long Life – up to 48,000 hour life\*
- Environmentally friendly – low UV and low Mercury
- Full range of color temperatures from 2455K to 6500K
- Lamps for both commercial and residential applications

\* Life dependent on ballast and hours per start



T8  
Med. Bi Pin

## Reduced Wattage, High Performance/High Lumen, and Long Life T8 Lamps

### T8 Instant/Rapid Start Energy Saving Lamps\* (Electronic Ballast) 48"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
<b>25</b>	T8	Med. Bi Pin	<b>S8438**</b>	F32/25WT8/830/ES/ENV	Warm White	3000	85	30000	2400	48	47 ¾	30	4, 12, 13
			<b>S8439**</b>	F32/25WT8/835/ES/ENV	Neutral White	3500	85	30000	2400	48	47 ¾	30	4, 12, 13
			<b>S8440**</b>	F32/25WT8/841/ES/ENV	Cool White	4100	85	30000	2400	48	47 ¾	30	4, 12, 13
			<b>S8441**</b>	F32/25WT8/850/ES/ENV	Natural Light	5000	85	30000	2375	48	47 ¾	30	4, 12, 13
			<b>S8442**</b>	F32/25WT8/865/ES/ENV	Daylight	6500	85	30000	2300	48	47 ¾	30	4, 12, 13
<b>28</b>	T8	Med. Bi Pin	<b>S8422**</b>	F28T8/830/ES/ENV	Warm White	3000	85	30000	2725	48	47 ¾	30	4, 12, 13
			<b>S8423**</b>	F28T8/835/ES/ENV	Neutral White	3500	85	30000	2725	48	47 ¾	30	4, 12, 13
			<b>S8424**</b>	F28T8/841/ES/ENV	Cool White	4100	85	30000	2725	48	47 ¾	30	4, 12, 13
			<b>S8425**</b>	F28T8/850/ES/ENV	Natural Light	5000	85	30000	2700	48	47 ¾	30	4, 12, 13
			<b>S8437</b>	F28T8/865/ES/ENV	Daylight	6500	85	30000	2650	48	47 ¾	30	4, 12, 13

### T8 Instant/Rapid Start High Lumen Lamps\* (Electronic Ballast) 48"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
<b>32</b>	T8	Med. Bi Pin	<b>S8426**</b>	F32T8/830/HL/ENV	Warm White	3000	85	30000	3100	48	47 ¾	30	4, 12, 13
			<b>S8427**</b>	F32T8/835/HL/ENV	Neutral White	3500	85	30000	3100	48	47 ¾	30	4, 12, 13
			<b>S8428**</b>	F32T8/841/HL/ENV	Cool White	4100	85	30000	3100	48	47 ¾	30	4, 12, 13
			<b>S8429**</b>	F32T8/850/HL/ENV	Natural Light	5000	85	30000	3100	48	47 ¾	30	4, 12, 13
			<b>S8430**</b>	F32T8/865/HL/ENV	Daylight	6500	85	30000	3000	48	47 ¾	30	4, 12, 13

### T8 Instant/Rapid Start Long Life Lamps\* (Electronic Ballast) 48"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
<b>32</b>	T8	Med. Bi Pin	<b>S8443</b>	F32T8/830/XL/ENV	Warm White	3000	82	36000	3050	48	47 ¾	30	4, 12, 13
			<b>S8444</b>	F32T8/835/XL/ENV	Neutral White	3500	82	36000	3000	48	47 ¾	30	4, 12, 13
			<b>S8445</b>	F32T8/841/XL/ENV	Cool White	4100	82	36000	3000	48	47 ¾	30	4, 12, 13
			<b>S8446</b>	F32T8/850/XL/ENV	Natural Light	5000	82	36000	2900	48	47 ¾	30	4, 12, 13
			<b>S8447</b>	F32T8/865/XL/ENV	Daylight	6500	82	36000	2900	48	47 ¾	30	4, 12, 13

\* Shatter Proof is available on all Fluorescent Lamps.

\*\* CEE Listed





T8  
Med. Bi Pin

## Standard T8 Lamps

### T8 Instant/Rapid Start Lamps\* (Electronic Ballast) 24"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
17	T8	Med. Bi Pin	<b>S6520</b> ▲	F17T8/730/ECO	Warm White	3000	75	24000	1300	24	23 ¾	30	11, 12, 13
			<b>S8404</b>	F17T8/830/ENV	Warm White	3000	85	20000	1450	24	23 ¾	30	11, 12, 13
			<b>S6523</b> ▲	F17T8/830/ECO	Warm White	3000	82	24000	1400	24	23 ¾	30	11, 12, 13
			<b>S6521</b> ▲	F17T8/735/ECO	Neutral White	3500	75	24000	1300	24	23 ¾	30	11, 12, 13
			<b>S8405</b>	F17T8/835/ENV	Neutral White	3500	85	20000	1450	24	23 ¾	30	11, 12, 13
			<b>S6524</b> ▲	F17T8/835/ECO	Neutral White	3500	82	24000	1400	24	23 ¾	30	11, 12, 13
			<b>S6522</b> ▲	F17T8/741/ECO	Cool White	4100	75	24000	1300	24	23 ¾	30	11, 12, 13
			<b>Shatter Proof</b> <b>S6583</b> ▲	F17T8/741/TF/ECO	Cool White	4100	75	24000	1300	24	23 ¾	30	9, 11, 12, 13
			<b>S8406</b>	F17T8/841/ENV	Cool White	4100	85	20000	1450	24	23 ¾	30	11, 12, 13
			<b>S6525</b> ▲	F17T8/841/ECO	Cool White	4100	82	24000	1400	24	23 ¾	30	11, 12, 13
			<b>Shatter Proof</b> <b>S6693</b> ▲	F17T8/841/TF/ECO	Cool White	4100	82	24000	1400	24	23 ¾	30	11, 12, 13
			<b>S8432</b>	F17T8/850/ENV	Natural Light	5000	82	20000	1400	24	23 ¾	30	11, 12, 13
			<b>S8433</b>	F17T8/865/ENV	Daylight	6500	82	20000	1300	24	23 ¾	30	11, 12, 13
			<b>S2913</b> ■	F17T8/TL	Daylight	6250	94.5	14000	750	24	23 ¾	30	11, 12, 13

### T8 Instant/Rapid Start Lamps\* (Electronic Ballast) 36"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
25	T8	Med. Bi Pin	<b>S6526</b> ▲	F25T8/730/ECO	Warm White	3000	75	24000	2025	36	35 ¾	30	11, 12, 13
			<b>S8410</b>	F25T8/830/ENV	Warm White	3000	85	20000	2300	36	35 ¾	30	11, 12, 13
			<b>S6529</b> ▲	F25T8/830/ECO	Warm White	3000	82	24000	2150	36	35 ¾	30	11, 12, 13
			<b>S6527</b> ▲	F25T8/735/ECO	Neutral White	3500	75	24000	2025	36	35 ¾	30	11, 12, 13
			<b>S8411</b>	F25T8/835/ENV	Neutral White	3500	85	20000	2300	36	35 ¾	30	11, 12, 13
			<b>S6530</b> ▲	F25T8/835/ECO	Neutral White	3500	82	24000	2150	36	35 ¾	30	11, 12, 13
			<b>S6528</b> ▲	F25T8/741/ECO	Cool White	4100	75	24000	2025	36	35 ¾	30	11, 12, 13
			<b>Shatter Proof</b> <b>S6584</b> ▲	F25T8/741/TF/ECO	Cool White	4100	75	24000	2025	36	35 ¾	30	9, 11, 12, 13
			<b>S8412</b>	F25T8/841/ENV	Cool White	4100	85	20000	2300	36	35 ¾	30	11, 12, 13
			<b>Shatter Proof</b> <b>S6692</b> ▲	F25T8/841/TF/ECO	Cool White	4100	82	24000	2150	36	35 ¾	30	11, 12, 13
			<b>S6531</b> ▲	F25T8/841/ECO	Cool White	4100	82	24000	2150	36	35 ¾	30	11, 12, 13
			<b>S8434</b>	F25T8/850/ENV	Natural Light	5000	82	20000	2200	36	35 ¾	30	11, 12, 13
			<b>S8435</b>	F25T8/865/ENV	Daylight	6500	82	20000	2150	36	35 ¾	30	11, 12, 13

\* Shatter Proof is available on all Fluorescent Lamps.



T8  
Med. Bi Pin

## Standard T8 Lamps

### T8 Instant/Rapid Start Lamps\* (Electronic Ballast) 48"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes	
32	T8	Med. Bi Pin	<b>S8418</b>	F32T8/830/ENV	Warm White	3000	85	24000	2950	48	47 3/4	30	11, 12, 13	
			<b>S6535▲</b>	F32T8/830/ECO	Warm White	3000	82	24000	2950	48	47 3/4	30	11, 12, 13	
			<b>S2915▲</b>	F32T8/830/XP/ECO	Warm White	3000	85	24000	3000	48	47 3/4	30	11, 12, 13	
			<b>S8419</b>	F32T8/835/ENV	Neutral White	3500	85	24000	2950	48	47 3/4	30	11, 12, 13	
			<b>S8478</b>	F32T8/835/ENV/2PK	Neutral White	3500	85	24000	2950	48	47 3/4	15/2	11, 12, 13	
			<b>S6536▲</b>	F32T8/835/ECO	Neutral White	3500	82	24000	2950	48	47 3/4	30	11, 12, 13	
			<b>S2916▲</b>	F32T8/835/XP/ECO	Neutral White	3500	85	24000	3000	48	47 3/4	30	11, 12, 13	
			<b>S8420</b>	F32T8/841/ENV	Cool White	4100	85	24000	2950	48	47 3/4	30	11, 12, 13	
			<b>S8479</b>	F32T8/841/ENV/2PK	Cool White	4100	85	24000	2950	48	47 3/4	15/2	11, 12, 13	
			<b>S6537▲</b>	F32T8/841/ECO	Cool White	4100	82	24000	2950	48	47 3/4	30	11, 12, 13	
			<b>S2917▲</b>	F32T8/841/XP/ECO	Cool White	4100	85	24000	3000	48	47 3/4	30	11, 12, 13	
			<b>Shatter Proof</b>	<b>S6691▲</b>	F32T8/841/TF/ECO	Cool White	4100	82	24000	2950	48	47 3/4	30	11, 12, 13
			<b>S8421</b>	F32T8/850/ENV	Natural Light	5000	85	24000	2900	48	47 3/4	30	11, 12, 13	
			<b>S2919▲</b>	F32T8/850/ECO	Natural Light	5000	80	24000	2800	48	47 3/4	30	11, 12, 13	
<b>S2920▲</b>	F32T8/850/XP/ECO	Natural Light	5000	85	24000	2950	48	47 3/4	30	11, 12, 13				
<b>S2922■</b>	F32T8/SUN	Daylight	6000	85	20000	3000	48	47 3/4	12	11, 12, 13				
<b>S8436</b>	F32T8/865/ENV	Daylight	6500	82	24000	2850	48	47 3/4	30	11, 12, 13				

\* Shatter Proof is available on all Fluorescent Lamps.



T8 U-Bend  
1 5/8" Leg  
Med. Bi Pin



T8 U-Bend  
6" Leg  
Med. Bi Pin

## T8 U-Bend Instant/Rapid Start Lamps\* (Electronic Ballast)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes	
<b>28</b>	T8	Med. Bi Pin	<b>S8471**</b>	FB32T8/830/ENV/28W	Warm White	3000	85	20000	2600	22 1/2	6	16	11, 12, 13	
			<b>S8472**</b>	FB32T8/835/ENV/28W	Neutral White	3500	85	20000	2600	22 1/2	6	16	11, 12, 13	
			<b>S8473**</b>	FB32T8/841/ENV/28W	Cool White	4100	85	20000	2600	22 1/2	6	16	11, 12, 13	
			<b>S8474</b>	FB32T8/850/ENV/28W	Natural Light	5000	85	20000	2550	22 1/2	6	16	11, 12, 13	
			<b>S8475</b>	FB32T8/865/ENV/28W	Daylight	6500	85	20000	2500	22 1/2	6	16	11, 12, 13	
<b>31</b>	T8	Med. Bi Pin	<b>S8450</b>	FB31T8/830	Warm White	3000	82	20000	2750	22 9/16	1 5/8	15	11, 12, 13	
			<b>S6550 ▲</b>	FB031/830	Warm White	3000	82	20000	2725	22 9/16	1 5/8	15	11, 12, 13	
			<b>S8451</b>	FB31T8/835	Neutral White	3500	82	20000	2750	22 9/16	1 5/8	15	11, 12, 13	
			<b>S6551 ▲</b>	FB031/835	Neutral White	3500	82	20000	2725	22 9/16	1 5/8	15	11, 12, 13	
			<b>S8452</b>	FB31T8/841	Cool White	4100	82	20000	2750	22 9/16	1 5/8	15	11, 12, 13	
			<b>S6552 ▲</b>	FB031/841	Cool White	4100	82	20000	2725	22 9/16	1 5/8	15	11, 12, 13	
			<b>S8459</b>	FB31T8/850	Natural Light	5000	82	20000	2700	22 9/16	1 5/8	15	11, 12, 13	
<b>32</b>	T8	Med. Bi Pin	<b>S8453</b>	FB32T8/730/U6/ENV	Warm White	3000	75	20000	2750	22 9/16	6	16	11, 12, 13	
			<b>S6553 ▲</b>	FB032/730/6/ECO	Warm White	3000	75	20000	2750	22 9/16	6	16	11, 12, 13	
			<b>S8456</b>	FB32T8/830/U6/ENV	Warm White	3000	82	20000	3000	22 9/16	6	16	11, 12, 13	
			<b>S6556 ▲</b>	FB032/830/6/ECO	Warm White	3000	82	20000	2850	22 9/16	6	16	11, 12, 13	
			<b>S8454</b>	FB32T8/735/U6/ENV	Neutral White	3500	75	20000	2750	22 9/16	6	16	11, 12, 13	
			<b>S6554 ▲</b>	FB032/735/6/ECO	Neutral White	3500	75	20000	2750	22 9/16	6	16	11, 12, 13	
			<b>S8457</b>	FB32T8/835/U6/ENV	Neutral White	3500	82	20000	3000	22 9/16	6	16	11, 12, 13	
			<b>S6557 ▲</b>	FB032/835/6/ECO	Neutral White	3500	82	20000	2850	22 9/16	6	16	11, 12, 13	
			<b>S8455</b>	FB32T8/741/U6/ENV	Cool White	4100	75	20000	2750	22 9/16	6	16	11, 12, 13	
			<b>S6555 ▲</b>	FB032/741/6/ECO	Cool White	4100	75	20000	2750	22 9/16	6	16	11, 12, 13	
			<b>S8458</b>	FB32T8/841/U6/ENV	Cool White	4100	82	20000	3000	22 9/16	6	16	11, 12, 13	
			<b>S6558</b>	FB032/841/6/ECO	Cool White	4100	82	20000	2850	22 9/16	6	16	11, 12, 13	
			<b>Shatter Proof</b>	<b>S6594 ▲ †</b>	FB032/741/6/TF/ECO	Cool White	4100	75	20000	2750	22 9/16	6	16	9, 11, 12, 13
			<b>Shatter Proof</b>	<b>S6699</b>	FB032/841/6/ECO	Cool White	4100	82	20000	2850	22 9/16	6	16	11, 12, 13
				<b>S8460</b>	FB32T8/750/ENV	Natural Light	5000	75	20000	2700	22 9/16	6	16	11, 12, 13
				<b>S2924</b>	FB032/750/6/ECO	Natural Light	5000	75	20000	2625	22 9/16	6	16	11, 12, 13
	<b>S8462</b>	FB32T8/850/ENV	Natural Light	5000	82	20000	2940	22 9/16	6	16	11, 12, 13			
	<b>S8461</b>	FB32T8/765/ENV	Daylight	6500	75	20000	2650	22 9/16	6	16	11, 12, 13			
	<b>S8463</b>	FB32T8/865/ENV	Daylight	6500	82	20000	2880	22 9/16	6	16	11, 12, 13			

\* Shatter Proof is available on all Fluorescent Lamps.

\*\* CEE Listed






T5  
Mini Bi Pin

## T5 High Performance Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
14	T5	Mini Bi Pin	<b>S8125</b>	F14T5/830/ENV	Warm White	3000	85	30000	1350	24	22 ½	40	11, 12, 13
			<b>S6425 ▲</b>	FP14/830/ECO	Warm White	3000	82	25000	1275	24	22 ½	40	11, 12, 13
			<b>S8126</b>	F14T5/835/ENV	Neutral White	3500	85	30000	1350	24	22 ½	40	11, 12, 13
			<b>S6426 ▲</b>	FP14/835/ECO	Neutral White	3500	82	25000	1275	24	22 ½	40	11, 12, 13
			<b>S8127</b>	F14T5/841/ENV	Cool White	4100	85	30000	1350	24	22 ½	40	11, 12, 13
			<b>S6427 ▲</b>	FP14/841/ECO	Cool White	4100	82	25000	1275	24	22 ½	40	11, 12, 13
			<b>S8110</b>	F14T5/850/ENV	Natural Light	5000	85	30000	1350	24	22 ½	40	11, 12, 13
			<b>S8111</b>	F14T5/865/ENV	Daylight	6500	85	30000	1350	24	22 ½	40	11, 12, 13
21	T5	Mini Bi Pin	<b>S8128</b>	F21T5/830/ENV	Warm White	3000	85	30000	2100	36	34	40	11, 12, 13
			<b>S6428 ▲</b>	FP21/830/ECO	Warm White	3000	82	25000	2000	36	34	40	11, 12, 13
			<b>S8129</b>	F21T5/835/ENV	Neutral White	3500	85	30000	2100	36	34	40	11, 12, 13
			<b>S6429 ▲</b>	FP21/835/ECO	Neutral White	3500	82	25000	2000	36	34	40	11, 12, 13
			<b>S8130</b>	F21T5/841/ENV	Cool White	4100	85	30000	2100	36	34	40	11, 12, 13
			<b>S6430 ▲</b>	FP21/841/ECO	Cool White	4100	82	25000	2000	36	34	40	11, 12, 13
			<b>S8112</b>	F21T5/850/ENV	Natural Light	5000	85	30000	2100	36	34	40	11, 12, 13
			<b>S8113</b>	F21T5/865/ENV	Daylight	6500	85	30000	2100	36	34	40	11, 12, 13
28	T5	Mini Bi Pin	<b>S8131</b>	F28T5/830/ENV	Warm White	3000	85	30000	2900	48	45 ½	40	11, 12, 13
			<b>S6431 ▲</b>	FP28/830/ECO	Warm White	3000	82	30000	2750	48	45 ½	40	11, 12, 13
			<b>S8132</b>	F28T5/835/ENV	Neutral White	3500	85	30000	2900	48	45 ½	40	11, 12, 13
			<b>S6432 ▲</b>	FP28/835/ECO	Neutral White	3500	82	30000	2750	48	45 ½	40	11, 12, 13
			<b>S8133</b>	F28T5/841/ENV	Cool White	4100	85	30000	2900	48	45 ½	40	11, 12, 13
			<b>S6433 ▲</b>	FP28/841/ECO	Cool White	4100	82	30000	2750	48	45 ½	40	11, 12, 13
			<b>S8114</b>	F28T5/850/ENV	Natural Light	5000	85	30000	2900	48	45 ½	40	11, 12, 13
			<b>S8115</b>	F28T5/865/ENV	Daylight	6500	85	30000	2900	48	45 ½	40	11, 12, 13
35	T5	Mini Bi Pin	<b>S8134</b>	F35T5/830/ENV	Warm White	3000	85	30000	3650	60	57 ⅞	40	11, 12, 13
			<b>S6434 ▲</b>	FP35/830/ECO	Warm White	3000	82	25000	3425	60	57 ⅞	40	11, 12, 13
			<b>S8135</b>	F35T5/835/ENV	Neutral White	3500	85	30000	3650	60	57 ⅞	40	11, 12, 13
			<b>S6435 ▲</b>	FP35/835/ECO	Neutral White	3500	82	25000	3425	60	57 ⅞	40	11, 12, 13
			<b>S8136</b>	F35T5/841/ENV	Cool White	4100	85	30000	3650	60	57 ⅞	40	11, 12, 13
			<b>S6436 ▲</b>	FP35/841/ECO	Cool White	4100	82	25000	3425	60	57 ⅞	40	11, 12, 13
			<b>S8116</b>	F35T5/850/ENV	Natural Light	5000	85	30000	3650	60	57 ⅞	40	11, 12, 13
			<b>S8117</b>	F35T5/865/ENV	Daylight	6500	85	30000	3650	60	57 ⅞	40	11, 12, 13

\* Shatter Proof is available on all Fluorescent Lamps.



# FLUORESCENT



## T5 HO High Performance Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
24	T5	Mini Bi Pin	<b>S8137</b>	F24T5/830/HO/ENV	Warm White	3000	85	30000	2000	24	22 ½	40	11, 12, 13
			<b>S6437 ▲</b>	FP24/830/HO/ECO	Warm White	3000	82	30000	1875	24	22 ½	40	11, 12, 13
			<b>S8138</b>	F24T5/835/HO/ENV	Neutral White	3500	85	30000	2000	24	22 ½	40	11, 12, 13
			<b>S6438 ▲</b>	FP24/835/HO/ECO	Neutral White	3500	82	30000	1875	24	22 ½	40	11, 12, 13
			<b>S8139</b>	F24T5/841/HO/ENV	Cool White	4100	85	30000	2000	24	22 ½	40	11, 12, 13
			<b>S6439 ▲</b>	FP24/841/HO/ECO	Cool White	4100	82	30000	1875	24	22 ½	40	11, 12, 13
			<b>S8118</b>	F24T5/850/HO/ENV	Natural Light	5000	85	30000	2000	24	22 ½	40	11, 12, 13
			<b>S8119</b>	F24T5/865/HO/ENV	Daylight	6500	85	30000	2000	24	22 ½	40	11, 12, 13
39	T5	Mini Bi Pin	<b>S8140</b>	F39T5/830/HO/ENV	Warm White	3000	85	30000	3500	36	34	40	11, 12, 13
			<b>S6440 ▲</b>	FP39/830/HO/ECO	Warm White	3000	82	30000	3300	36	34	40	11, 12, 13
			<b>S8141</b>	F39T5/835/HO/ENV	Neutral White	3500	85	30000	3500	36	34	40	11, 12, 13
			<b>S6441 ▲</b>	FP39/835/HO/ECO	Neutral White	3500	82	30000	3300	36	34	40	11, 12, 13
			<b>S8142</b>	F39T5/841/HO/ENV	Cool White	4100	85	30000	3500	36	34	40	11, 12, 13
			<b>S6442 ▲</b>	FP39/841/HO/ECO	Cool White	4100	82	30000	3300	36	34	40	11, 12, 13
			<b>S8120</b>	F39T5/850/HO/ENV	Natural Light	5000	85	30000	3500	36	34	40	11, 12, 13
			<b>S8121</b>	F39T5/865/HO/ENV	Daylight	6500	85	30000	3500	36	34	40	11, 12, 13
54	T5	Mini Bi Pin	<b>S8143</b>	F54T5/830/HO/ENV	Warm White	3000	85	30000	5000	48	45 ½	40	11, 12, 13
			<b>S6443 ▲</b>	FP54/830/HO/ECO	Warm White	3000	82	40000	4725	48	45 ½	40	11, 12, 13
			<b>S8144</b>	F54T5/835/HO/ENV	Neutral White	3500	85	30000	5000	48	45 ½	40	11, 12, 13
			<b>S6444 ▲</b>	FP54/835/HO/ECO	Neutral White	3500	82	40000	4725	48	45 ½	40	11, 12, 13
			<b>S8145</b>	F54T5/841/HO/ENV	Cool White	4100	85	30000	5000	48	45 ½	40	11, 12, 13
			<b>S6445 ▲</b>	FP54/841/HO/ECO	Cool White	4100	82	40000	4725	48	45 ½	40	11, 12, 13
			<b>S8122</b>	F54T5/850/HO/ENV	Natural Light	5000	85	30000	5000	48	45 ½	40	11, 12, 13
			<b>S8123</b>	F54T5/865/HO/ENV	Daylight	6500	85	30000	5000	48	45 ½	40	11, 12, 13
80	T5	Mini Bi Pin	<b>S6446 ▲</b>	FP80/830/HO/ECO	Warm White	3000	82	25000	6575	60	57 ¾	40	11, 12, 13
			<b>S6447 ▲</b>	FP80/835/HO/ECO	Neutral White	3500	82	25000	6575	60	57 ¾	40	11, 12, 13
			<b>S6448 ▲</b>	FP80/841/HO/ECO	Cool White	4100	82	25000	6575	60	57 ¾	40	11, 12, 13

\* Shatter Proof is available on all Fluorescent Lamps.



## T5 Circline High Performance Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
22	T5	2GX13	<b>S8155</b>	FC22T5/830	Warm White	3000	82	12000	1900	9	9	12	11, 12, 13
			<b>S2955 ▲</b>	FPC22/830	Warm White	3000	82	12000	1800	9	9	12	11, 12, 13
			<b>S2956 ▲</b>	FPC22/835	Neutral White	3500	82	12000	1800	9	9	12	11, 12, 13
			<b>S8156</b>	FC22T5/835	Neutral White	3500	82	12000	1900	9	9	12	11, 12, 13
			<b>S8157</b>	FC22T5/841	Cool White	4100	82	12000	1900	9	9	12	11, 12, 13
		G10q	<b>S8166</b>	FC22T5/865/G10q	Daylight	6500	82	12000	1800	9	9	12	11, 12, 13
40	T5	G10q	<b>S8164</b>	FC40T5/827/G10q	Warm White	2700	82	12000	3300	12	12	12	11, 12, 13
		2GX13	<b>S8158</b>	FC40T5/830	Warm White	3000	82	12000	3300	12	12	12	11, 12, 13
			<b>S8159</b>	FC40T5/835	Neutral White	3500	82	12000	3300	12	12	12	11, 12, 13
			<b>S2959 ▲</b>	FPC40/835	Neutral White	3500	82	12000	3200	12	12	12	11, 12, 13
			<b>S8160</b>	FC40T5/841	Cool White	4100	82	12000	3300	12	12	12	11, 12, 13
55	T5	2GX13	<b>S8161</b>	FC55T5/H0/830	Warm White	3000	82	12000	4200	12	12	12	11, 12, 13
			<b>S2961 ▲</b>	FPC55/830/H0	Warm White	3000	82	12000	4000	12	12	12	11, 12, 13
			<b>S8162</b>	FC55T5/H0/835	Neutral White	3500	82	12000	4200	12	12	12	11, 12, 13
			<b>S2962 ▲</b>	FPC55/835/H0	Neutral White	3500	82	12000	4000	12	12	12	11, 12, 13
			<b>S8163</b>	FC55T5/H0/841	Cool White	4100	82	12000	4200	12	12	12	11, 12, 13


## T2 SubMini Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
8	T2	Axial	<b>S6490 ▲</b>	FM8/830	Warm White	3000	80	10000	540	12 7/8	12 7/8	20	5, 12
			<b>S6491 ▲</b>	FM8/841	Cool White	4100	80	10000	540	12 7/8	12 7/8	20	5, 12
11	T2	Axial	<b>S6492 ▲</b>	FM11/830	Warm White	3000	80	10000	750	16 5/16	16 5/8	20	5, 12
			<b>S6493 ▲</b>	FM11/841	Cool White	4100	80	10000	750	16 5/16	16 5/8	20	5, 12
13	T2	Axial	<b>S6494 ▲</b>	FM13/830	Warm White	3000	80	10000	930	20 5/16	20 7/8	20	5, 12
			<b>S2903 ▲</b>	FM13/835	Neutral White	3500	80	10000	930	20 5/16	20 7/8	20	5, 12

\* Shatter Proof is available on all Fluorescent Lamps.



# FLUORESCENT



## T5 Preheat Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
<b>4</b>	T5	Mini Bi Pin	<b>S1900</b>	F4T5/CW	Cool White	4100	60	5000	130	6	5 15/16	20	12, 13
			<b>S2908</b>	F4T5/D	Daylight	6500	75	5000	115	6	5 15/16	20	12, 13
<b>6</b>	T5	Mini Bi Pin	<b>S1902</b>	F6T5/CW	Cool White	4000	62	5000	260	9	8 15/16	20	12, 13
			<b>S2909</b>	F6T5/D	Daylight	6500	76	5000	260	9	8 15/16	20	12, 13
<b>8</b>	T5	Mini Bi Pin	<b>S1904</b>	F8T5/CW	Cool White	4000	62	5000	380	12	11 15/16	20	12, 13
			<b>S1905</b>	F8T5/WW	Warm White	3000	52	5000	380	12	11 15/16	20	12, 13
			<b>S2910</b>	F8T5/D	Daylight	6500	76	5000	350	12	11 15/16	20	12, 13
<b>13</b>	T5	Mini Bi Pin	<b>S1907</b>	F13T5/WW	Warm White	3000	52	5000	880	21	20 15/16	20	12, 13
			<b>S1906</b>	F13T5/CW	Cool White	4200	62	5000	860	21	20 15/16	20	12, 13
			<b>S2911</b>	F13T5/D	Daylight	6500	76	5000	780	21	20 15/16	20	12, 13

## T6 and T8 Instant Start Slimline Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
<b>25</b>	T6	Single Pin	<b>S6470 ▲</b>	F42T6/WW	Warm White	3000	52	7500	1825	42	40	24	12, 13
			<b>S6471 ▲</b>	F42T6/CW	Cool White	4200	62	7500	1750	42	40	24	12, 13
			<b>Shatter Proof S6591 ▲</b>	F42T6/CW/TF	Cool White	4200	62	7500	1750	42	40	24	9, 12, 13
<b>38</b>	T6	Single Pin	<b>S6475 ▲</b>	F64T6/CW	Cool White	4200	62	7500	2800	64	62	24	12, 13
			<b>Shatter Proof S6592 ▲</b>	F64T6/CW/TF	Cool White	4200	62	7500	2800	64	62	24	9, 12, 13
	T8	Single Pin	<b>S6476 ▲</b>	F72T8/D	Daylight	6500	76	7500	2288	72	70	24	12, 13

\* Shatter Proof is available on all Fluorescent Lamps.



T8  
Single Pin

## T8 Preheat Lamps\*


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
15	T8	Med. Bi Pin	<b>S7925</b>	F15T8/WW	Warm White	3000	52	7500	845	18	17 ¾	24	12, 13
			<b>S6512 ▲</b>	F15T8/WW	Warm White	3000	52	7500	845	18	17 ¾	24	12, 13
			<b>S7949</b>	F15T8/CW	Cool White	4100	62	7500	850	18	17 ¾	24	12, 13
			<b>S6510 ▲</b>	F15T8/CW	Cool White	4100	62	7500	850	18	17 ¾	24	12, 13
			<b>S6665 ■</b>	F15T8/SUN	Daylight	6250	94.5	12000	600	18	17 ¾	6	12, 13
			<b>S7950</b>	F15T8/D	Daylight	6500	76	7500	750	18	17 ¾	24	12, 13
			<b>S6511 ▲</b>	F15T8/D	Daylight	6500	76	7500	750	18	17 ¾	24	12, 13
18	T8	Med. Bi Pin	<b>S6513 ▲</b>	F18T8/CW/K24	Cool White	4100	62	7500	1035	24	23 ¾	24	3, 12, 13
			<b>S6514 ▲</b>	F18T8/CW/K26	Cool White	4100	62	7500	1079	26	25 ¾	24	3, 12, 13
			<b>S6515 ▲</b>	F18T8/CW/K28	Cool White	4100	62	7500	1131	28	27 ¾	24	3, 12, 13
			<b>S6516 ▲</b>	F18T8/CW/K30	Cool White	4100	62	7500	1200	30	29 ¾	24	3, 12, 13
30	T8	Med. Bi Pin	<b>S6519 ▲</b>	F30T8/WW	Warm White	3000	52	7500	2150	36	35 ¾	24	12, 13
			<b>S6517 ▲</b>	F30T8/CW	Cool White	4100	62	7500	1380	36	35 ¾	24	12, 13
			<b>S6518 ▲</b>	F30T8/D	Daylight	6500	76	7500	2180	36	35 ¾	24	12, 13

## T8 Instant/Rapid Start Lamps\* (Electronic Ballast) 60" & 96"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
40	T8	Med. Bi Pin	<b>S6544 ▲</b>	F40T8/730/ECO	Warm White	3000	75	24000	3550	60	59 ⅝	30	11, 12, 13
			<b>S6547 ▲</b>	F40T8/830/ECO	Warm White	3000	82	24000	3650	60	59 ⅝	30	11, 12, 13
			<b>S6545 ▲</b>	F40T8/735/ECO	Neutral White	3500	75	24000	3550	60	59 ⅝	30	11, 12, 13
			<b>S6548 ▲</b>	F40T8/835/ECO	Neutral White	3500	82	24000	3650	60	59 ⅝	30	11, 12, 13
			<b>S6546 ▲</b>	F40T8/741/ECO	Cool White	4100	75	24000	3550	60	59 ⅝	30	11, 12, 13
			<b>S6549 ▲</b>	F40T8/841/ECO	Cool White	4100	82	24000	3650	60	59 ⅝	30	11, 12, 13

\* Shatter Proof is available on all Fluorescent Lamps.

# FLUORESCENT



## T8 Instant/Rapid Start Lamps\* (Electronic Ballast) 60" & 96" (continued)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
59	T8	Single Pin	<b>S6541 ▲</b>	F96T8/830/ECO	Warm White	3000	82	18000	5900	96	94	24	11, 12, 13
			<b>S6542 ▲</b>	F96T8/835/ECO	Neutral White	3500	82	18000	5900	96	94	24	11, 12, 13
			<b>S6543 ▲</b>	F96T8/841/ECO	Cool White	4100	82	18000	5900	96	94	24	11, 12, 13
			<b>S6577 ▲</b>	F96T8/850/ECO	Natural Light	5000	80	18000	5900	96	94	24	11, 12, 13

## T10 and T12 Preheat Lamps\*


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
40	T10	Med. Bi Pin	<b>S7928</b>	F40T10/EX50	Natural Light	5000	88	20000	3600	48	48	25	12, 13
			<b>S7929</b>	F40T10/EX41	Cool White	4100	84	20000	3600	48	48	25	12, 13
14	T12	Med. Bi Pin	<b>S6561 ▲</b>	F14T12/WW	Warm White	3000	52	7500	660	15	14 ¾	30	12, 13
			<b>S6559 ▲</b>	F14T12/CW	Cool White	4100	62	7500	650	15	14 ¾	30	12, 13
15	T12	Med. Bi Pin	<b>S6564 ▲</b>	F15T12/WW	Warm White	3000	52	7500	770	18	17 ¾	30	12, 13
			<b>S6562 ▲</b>	F15T12/CW	Cool White	4100	62	7500	750	18	17 ¾	30	12, 13
			<b>S6563 ▲</b>	F15T12/D	Daylight	6500	76	7500	660	18	17 ¾	30	12, 13
20	T12	Med. Bi Pin	<b>S6567 ▲</b>	F20T12/WW	Warm White	3000	52	9000	1250	24	23 ¾	30	12, 13
			<b>S6565 ▲</b>	F20T12/CW	Cool White	4100	62	9000	1220	24	23 ¾	30	12, 13
			<b>S6579 ▲</b>	F20T12/CW/TF	Cool White	4100	62	9000	1220	24	23 ¾	30	9, 12, 13
			<b>S6666 ▲</b>	F20T12SUN	Sunlight	6250	94.5	14000	800	24	23 ¾	6	12, 13
			<b>S6566 ▲</b>	F20T12/D	Daylight	6500	76	9000	1075	24	23 ¾	30	12, 13
25	T12	Med. Bi Pin	<b>S6568 ▲</b>	F25T12/CW/28	Cool White	4100	62	7500	1670	28	27 ¾	30	12, 13
			<b>S6569 ▲</b>	F25T12/CW/30	Cool White	4100	62	7500	1730	30	29 ¾	30	12, 13
			<b>S6570 ▲</b>	F25T12/CW/33	Cool White	4100	62	7500	1750	33	32 ¾	30	12, 13

## T12 Rapid Start Lamps\* 36"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
30	T12	Med. Bi Pin	<b>S6573 ▲</b>	F30T12/WW/RS	Warm White	3000	52	18500	2275	36	35 ¾	30	12, 13
			<b>S6575 ▲</b>	F30T12/D35/RS	Neutral White	3500	70	18000	2250	36	35 ¾	30	12, 13
			<b>S6571 ▲</b>	F30T12/CW/RS	Cool White	4200	62	18000	2200	36	35 ¾	30	12, 13
			<b>S6580 ▲</b>	F30T12/CW/RS/TF	Cool White	4200	62	18000	2200	36	35 ¾	30	9, 12, 13
			<b>S6667 ▲</b>	F30T12SUN/RS	Daylight	6250	94	22000	1650	36	35 ¾	30	12, 13
			<b>S6572 ▲</b>	F30T12/D/RS	Daylight	6500	76	18000	1900	36	35 ¾	30	12, 13

\* Shatter Proof is available on all Fluorescent Lamps.





### T12 Rapid Start Lamps\* 48"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
40	T12	Med. Bi Pin	<b>Y21376</b> ▲	F40T12/930/ECO	Cool White	4100	88	20000	3000	48	47 ¾	30	12, 13
			<b>S6637</b>	F40T12/CWX	Cool White	4100	90	24000	2550	48	47 ¾	30	12, 13
			<b>S2927</b> ▲	F40T12/CWX	Cool White	4100	87	20000	2150	48	47 ¾	30	12, 13
			<b>S6610</b> ▲	F40T12/DSGN50	Natural Light	5000	90	20000	2200	48	47 ¾	30	12, 13
			<b>S6668</b> ▲	F40T12/SUN	Daylight	6250	94.5	26000	2100	48	47 ¾	30	12, 13
			<b>S6638</b>	F40T12/DX	Daylight	6500	90	24000	2100	48	47 ¾	30	12, 13
			<b>S6608</b> ▲	F40T12/DX	Daylight	6500	88	20000	2180	48	47 ¾	30	12, 13

### T12 Rapid Start U-Bend Lamps\*


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
34	T12	Med. Bi Pin	<b>Y24965</b> ▲	FB34/930/6/SS/ECO	Warm White	3000	90	18000	2600	22 ½	6	12	6, 12, 13
			<b>S6593</b> ▲†	FB34/CW/6/SS/TF	Cool White	4200	62	18000	2600	22 ½	6	12	6, 9, 12, 13
40	T12	Med. Bi Pin	<b>S6686</b> ▲	FB40/DX/6	Daylight	6500	88	18000	2300	22 ½	6	12	12, 13
			<b>Y24004</b> ▲	FB40/CWX/6	Cool White	4100	87	18000	2100	22 ½	6	12	6, 9, 12, 13

### T9 Circline Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
20	T9	4-Pin	<b>S2950</b>	FC6T9/WW/RS	Warm White	3000	52	12000	810	6 ½	6 ½	12	12, 13
			<b>S6509</b>	FC6T9/CW/RS	Cool White	4100	62	12000	750	6 ½	6 ½	12	12, 13
22	T9	4-Pin	<b>S6502</b>	FC8T9/WW/RS	Warm White	3000	52	12000	1150	8	8	12	12, 13
			<b>S6500</b>	FC8T9/CW/RS	Cool White	4100	62	12000	1120	8	8	12	12, 13
			<b>S6501</b>	FC8T9/D/RS	Daylight	6500	76	12000	980	8	8	12	12, 13
30	T9	4-Pin	<b>S6507</b>	FC30/SW FCL30	Warm White	3000	82	12000	1900	9	9	12	12, 13

\* Shatter Proof is available on all Fluorescent Lamps.

# FLUORESCENT



## T9 Circline Lamps\* (continued)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
32	T9	4-Pin	<b>S6505</b>	FC12T9/WW/RS	Warm White	3000	52	12000	2150	12	12	12	12, 13
			<b>S6503</b>	FC12T9/CW/RS	Cool White	4100	62	12000	1930	12	12	12	12, 13
			<b>S6504</b>	FC12T9/D/RS	Daylight	6500	76	12000	1670	12	12	12	12, 13
40	T9	4-Pin	<b>S2954</b>	FC16T9/WW/RS	Warm White	3000	52	12000	3100	16	16	12	12, 13
			<b>S6506</b>	FC16T9/CW/RS	Cool White	4100	62	12000	2950	16	16	12	12, 13

## 2C Circline Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
40	T6	4-Pin	<b>S6508</b>	FC402C/SW/TC	Warm White	3000	82	12000	2650	7 ½	7 ½	12	12, 13
55	T6	4-Pin	<b>S6596</b>	FC552C/SW/TC	Warm White	3000	82	12000	3800	9	9	12	12, 13

## T12 Instant Start Slimline Lamps\* 24" – 84"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
30	T12	Single Pin	<b>S6472 ▲</b>	F36T12/CW	Cool White	4200	62	7500	1970	36	34	30	12, 13
39	T12	Single Pin	<b>S6660 ▲</b>	F48T12/CW	Cool White	4200	62	9000	2875	48	46	30	12, 13
			<b>Shatter Proof S6586 ▲</b>	F48T12/CW/TF	Cool White	4200	62	9000	2875	48	46	30	9, 12, 13
50	T12	Single Pin	<b>S6661 ▲</b>	F60T12/CW	Cool White	4200	62	12000	3700	60	58	30	12, 13
			<b>S6483 ▲</b>	F60T12/D	Daylight	6500	76	12000	3000	60	58	30	12, 13
52	T12	Single Pin	<b>S6662 ▲</b>	F64T12/CW	Cool White	4200	62	12000	3900	64	62	30	12, 13
			<b>S6485 ▲</b>	F64T12/D	Daylight	6500	76	12000	3300	64	62	30	12, 13
55	T12	Single Pin	<b>S6631 ▲</b>	F72T12/WW	Warm White	3000	52	12000	3900	72	70	15	12, 13
			<b>S6630 ▲</b>	F72T12/CW	Cool White	4200	62	12000	4500	72	70	15	12, 13
			<b>S6632 ▲</b>	F72T12/D	Daylight	6500	76	12000	4150	72	70	15	12, 13
70	T12	Single Pin	<b>S6663 ▲</b>	F84T12/CW	Cool White	4200	62	12000	5300	84	82	15	12, 13

\* Shatter Proof is available on all Fluorescent Lamps.



T12  
Single Pin



T12  
Rec. DC

## T12 Instant Start Slimline Lamps\* 96"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
75	T12	Single Pin	<b>Y23504</b> ▲	F96T12/WX	Neutral White	3500	87	12000	4200	96	96	15	12, 13
			<b>Y29478</b> ▲	F96T12/CWX	Cool White	4100	87	12000	4400	96	96	15	12, 13
			<b>S6651</b> ▲	F96T12/DSGN50	Natural Light	5000	90	12000	4400	96	94	15	12, 13
			<b>S6650</b> ▲	F96T12/DX	Daylight	6500	88	12000	4310	96	94	15	12, 13

## T12 HO High Output (800 mA) Rapid Start Lamps\* 18" – 64"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
25	T12	Rec. DC	<b>S2933</b> ■	F18T12/CW/HO	Cool White	4200	62	9000	1100	18	15 15/16	30	12, 13
35	T12	Rec. DC	<b>S6449</b> ▲	F24T12/CW/HO	Cool White	4200	62	9000	1650	24	22	30	12, 13
			<b>S6450</b> ▲	F24T12/D/HO	Daylight	6500	76	9000	1400	24	21 15/16	30	12, 13
42	T12	Rec. DC	<b>S6451</b> ▲	F30T12/CW/HO	Cool White	4200	62	9000	2250	30	27 15/16	30	12, 13
45	T12	Rec. DC	<b>S6452</b> ▲	F36T12/CW/HO	Cool White	4200	62	9000	2850	36	33 15/16	30	12, 13
			<b>S2937</b> ▲	F36T12/D/HO	Daylight	6500	76	9000	2500	36	33 15/16	30	12, 13
55	T12	Rec. DC	<b>S6453</b> ▲	F42T12/CW/HO	Cool White	4200	62	9000	3400	42	33 15/16	30	12, 13
			<b>S6454</b> ▲	F42T12/D/HO	Daylight	6500	76	9000	3050	42	40	30	12, 13
60	T12	Rec. DC	<b>S6670</b> ▲	F48T12/CW/HO	Cool White	4200	62	12000	4050	48	46	30	12, 13
			<b>Shatter Proof S6587</b> ▲	F48T12/CW/HO/TF	Cool White	4200	62	12000	4050	48	46	30	9, 12, 13
			<b>S2940</b> ▲	F48T12/D/HO	Daylight	6500	76	12000	3600	48	46	30	12, 13
75	T12	Rec. DC	<b>S6671</b> ▲	F60T12/CW/HO	Cool White	4200	62	12000	5200	60	57 15/16	30	12, 13
			<b>S6457</b> ▲	F60T12/D/HO	Daylight	6500	76	12000	4600	60	57 15/16	30	12, 13
80	T12	Rec. DC	<b>S6672</b> ▲	F64T12/CW/HO	Cool White	4200	62	12000	5750	64	61 15/16	30	12, 13
			<b>S6458</b> ▲	F64T12/D/HO	Daylight	6500	76	12000	4900	64	61 15/16	30	12, 13

\* Shatter Proof is available on all Fluorescent Lamps.



T12  
Rec. DC

## T12 HO High Output (800 mA) Rapid Start Lamps\* 72" – 120"

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
85	T12	Rec. DC	<b>S2944 ▲</b>	F72T12/D35/HO	Neutral White	3500	70	12000	6650	72	69 15/16	15	12, 13
			<b>S6673 ▲</b>	F72T12/CW/HO	Cool White	4200	62	12000	6250	72	69 15/16	15	12, 13
			<b>S6460 ▲</b>	F72T12/D/HO	Daylight	6500	76	12000	5550	72	69 15/16	15	12, 13
100	T12	Rec. DC	<b>S6674 ▲</b>	F84T12/CW/HO	Cool White	4200	62	12000	7550	84	81 15/16	15	12, 13
			<b>S6461 ▲</b>	F84T12/D/HO	Daylight	6500	76	12000	6700	84	81 15/16	15	12, 13
110	T12	Rec. DC	<b>S6676 ▲</b>	F96T12/CW/HO/CT	Cool White	4200	62	12000	8600	96	93 15/16	15	10, 12, 13
			<b>Shatter Proof S6589 ▲</b>	F96T12/CW/HO/CT/TF	Cool White	4200	62	12000	8600	96	93 15/16	15	9,10,12,13
			<b>S2946 ▲</b>	F96T12/DSGN50/HO	Natural Light	5000	90	12000	6450	96	93 15/16	15	12, 13
			<b>S6462 ▲</b>	F96T12/D/HO/CT	Daylight	6500	76	12000	7600	96	93 15/16	15	10, 12, 13
124	T12	Rec. DC	<b>S5454 ■</b>	F108T12/CW/HO	Cool White	4200	62	12000	10350	108	105	10	12, 13
			<b>S5255 ■</b>	F108T12/D/HO	Daylight	6500	76	12000	8800	108	105	10	12, 13
132	T12	Rec. DC	<b>S5256 ■</b>	F117T12/CW/HO	Cool White	4200	62	12000	11200	117	114	10	12, 13
			<b>S5257 ■</b>	F117T12/D/HO	Daylight	6500	76	12000	9500	117	114	10	12, 13
135	T12	Rec. DC	<b>S5224 ■</b>	F120T12/CW/HO	Cool White	4200	62	12000	11500	120	117	10	12, 13
			<b>S5227 ■</b>	F120T12/D/HO	Daylight	6500	76	12000	9750	120	117	10	12, 13


## T12 HO Very High Output (1500 mA) Rapid Start Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
115	T12	Rec. DC	<b>S6463 ▲</b>	F48T12/CW/VHO	Cool White	4200	62	10000	6600	48	45 15/16	30	12, 13
			<b>S6595 ▲</b>	F48T12/CW/VHO/TF	Cool White	4200	62	20000	7400	48	45 15/16	30	12, 13
160	T12	Rec. DC	<b>S6466 ▲</b>	F72T12/CW/VHO	Cool White	4200	62	10000	10600	72	70	15	12, 13
195	T12	Rec. DC	<b>S6467 ▲</b>	F96T12/CW/VHO/SS	Cool White	4200	62	10000	13000	96	93 15/16	15	12, 13
215	T12	Rec. DC	<b>S6677 ▲</b>	F96T12/CW/VHO	Cool White	4200	62	10000	14000	96	93 15/16	15	12, 13
			<b>Shatter Proof S6590 ▲</b>	F96T12/CW/VHO/TF	Cool White	4200	62	10000	14000	96	93 15/16	15	12, 13


\* Shatter Proof is available on all Fluorescent Lamps.



T5  
Mini Bi Pin



T8  
Med. Bi Pin



T12  
Med. Bi Pin

## Specialty Fluorescent Lamps

### T8 and T12 Lamps for Plant and Aquarium Purposes\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
15	T8	Med. Bi Pin	<b>S6888</b> ▲	F15T8/GRO/AQ/RP	Purple	—	66	7500	325	18	17 ¾	6	12, 13
20	T12	Med. Bi Pin	<b>S6889</b> ▲	F20/GRO/AQ/RP	Purple	—	66	9000	480	24	23 ¾	6	12, 13
40	T12	Med. Bi Pin	<b>S6892</b> ▲	F40/GRO/AQ/RP	Purple	—	66	20000	1200	48	47 ¾	6	12, 13
			<b>S6893</b> ▲	F40/GRO/AQ/WS/RP	Pink	3400	89	20000	1700	48	47 ¾	6	8, 12, 13

### Blacklight Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
4	T5	Mini. Bi Pin	<b>S2904</b> ■	F4T5/BL	Black Light	5000	6	6	5 1/16	1	12, 13
6	T5	Mini. Bi Pin	<b>S2905</b> ■	F6T5/BL	Black Light	5000	9	9	8 1/16	1	12, 13
15	T8	Med. Bi Pin	<b>S4574</b> ■	F15T8/BL	Black Light	7500	18	18	17 ¾	1	12, 13
20	T12	Med. Bi Pin	<b>S2925</b> ▲	F20T12/350BL	Black Light	9000	24	24	23 ¾	24	12, 13
22	T12	Med. Bi Pin	<b>S6874</b> ▲	F15" T12/350BL/500/PH	Black Light	—	15	15	17 ¾	30	12, 13
25	T8	Med. Bi Pin	<b>S6875</b> ▲	F25T8/350BL/18"	Black Light	—	18	18	17 ¾	24	12, 13
30	T8	Med. Bi Pin	<b>S6876</b> ▲	F30T8/350BL	Black Light	7500	36	36	35 ¾	24	12, 13
32	T12	Med. Bi Pin	<b>S6877</b> ▲	F18" T12/350BL/700/PH	Black Light	—	18	18	17 ¾	30	12, 13
40	T12	Med. Bi Pin	<b>S2926</b> ▲	F40/350BL	Black Light	20000	48	48	47 ¾	30	12, 13


### Blacklight Blue Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Color	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Carton	Notes
4	T5	Mini. Bi Pin	<b>S6405</b> ■	F4T5/BLB	Blk. Lt. Blue	5000	6	6	5 1/16	2	12, 13
6	T5	Mini. Bi Pin	<b>S2907</b> ■	F6T5/BLB	Blk. Lt. Blue	5000	9	9	8 1/16	2	12, 13
8	T5	Mini. Bi Pin	<b>S6406</b> ■	F8T5/BLB	Blk. Lt. Blue	5000	12	12	11 1/16	2	12, 13
15	T8	Med. Bi Pin	<b>S6407</b> ■	F15T8/BLB	Blk. Lt. Blue	7500	18	18	17 ¾	2	12, 13
20	T12	Med. Bi Pin	<b>S6408</b> ■	F20T12/BLB	Blk. Lt. Blue	9000	24	24	23 ¾	2	12, 13
40	T12	Med. Bi Pin	<b>S6409</b> ▲	F40/BLB/RP	Blk. Lt. Blue	20000	48	48	47 ¾	6	12, 13

\* Shatter Proof is available on all Fluorescent Lamps.



# FLUORESCENT



## Germicidal Preheat Lamps\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Avg. Rated Hours	Nominal Length Inches	M.O.L. Inches	Carton	Notes
8	T5	Mini. Bi Pin	<b>S6885</b> ■	G8T5	8000	12	11 15/16	24	7
15	T8	Med. Bi Pin	<b>S6886</b> ■	G15T8	7500	18	17 3/4	24	7
30	T8	Med. Bi Pin	<b>S6887</b> ■	G30T8	7500	36	35 3/4	24	7

## Polycarbonate Tube Guards With End Caps

Type	Satco Prod. #	Lamp Code	Description	Length Inches	Carton
FG40	<b>S7870</b> ■	FG40 TUBEGUARD	FG40 TUBEGUARD 4FT T12	48	24
FG408	<b>S7997</b> ■	FG408 TUBEGUARD	FG408 TUBEGUARD 4FT T8	48	24
FG96	<b>S7966</b> ■	FG96 TUBEGUARD	FG96 TUBEGUARD 8FT T12	96	24
FG968	<b>S7967</b> ■	FG968 TUBEGUARD	FG968 TUBEGUARD 8FT T8	96	24
FG405	<b>S7994</b> ■	FG405 TUBEGUARD NON HO	FG405 TUBEGUARD 4FT T5 NON HO	48	50

Not for use with HO or VHO lamps.

## Lighting Product Recycling Program – Drop Ship Program

Satco Prod. #	Lamp Code	Size Inches
<b>4SBAKPAK</b> ■	4ft. Lamp Recycling Small Corrugated Box / Holds (32) T8 – (18) T12 (4ft. Lamps)	7 1/2 x 6 x 48
<b>4BAKPAK</b> ■	4ft. Lamp Recycling Standard Corrugated Box / Holds (100) T8 – (50) T12 (4ft. Lamps)	13 1/2 x 7 3/4 x 48
<b>8BAKPAK</b> ■	8ft. Lamp Recycling Standard Corrugated Box / Holds (60) T8 – (30) T12 (8ft. Lamps)	10 1/2 x 8 x 94 1/4
<b>MULTIBAKPAK</b> ■	Miscellaneous Lamp Recycling Corrugated Box / (Holds U's, HID's, Biax, etc.)	25 x 15 x 23
<b>COMBAKPAK</b> ■	5 Gallon Pail / Holds 70lbs. (Up to 90 CFLs)	11 x 14
<b>BALBAKPAK</b> ■	5 Gallon Pail / Holds 70lbs. Lighting Ballasts	11 x 14

\* Shatter Proof is available on all Fluorescent Lamps.

**General Fluorescent Notes**

- = Product by a manufacturer other than Satco
- ▲ = Product by one of the Primary lamp manufacturers
- † = To be discontinued when inventory is depleted due to legislation requirements.

Due to the fragile nature of fluorescent tubes, please discuss shipping issues, and packing charges for all fluorescent lamps 48" or longer. Some items can only be shipped in full cases.

ECO and ENV fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local and state regulations. For more information, please visit [lamprecycle.org](http://lamprecycle.org). At this time, much of the fluorescent product line is transitioning from non-ECO product to ECO product, if this is a critical issue for your application, call customer service to confirm ECO availability.

**Fluorescent Notes**

- 1 The UV radiation of Black Light excites the fluorescent paints, fabrics, and other materials used for theatrical special effects. Black Light lamps are also used in bars and restaurants for lighting effects. Black Light lamps are also used in Bug Zappers, and by Pest Control professionals.  
**CAUTION:** This lamp emits ultraviolet (UV) power during operation and is in Risk Group 1 per ANSI/IESNA RP-27.3-96. Exposure at less than 0.25 meters (10 inches) should be limited; for example exposure at 0.14m (6 inches) should not exceed 4 hours in an 8 hour interval (see ANSI/IESNA RP-27.1-96). Certain medications and chemicals can increase an individual's sensitivity. Consult your physician for specific information. Protective eyewear should be worn in occupational situations involving long term exposure in close proximity to the lamp. This lamp is not intended and should not be used for diagnostic, therapeutic or cosmetic purposes.
- 2 Black Light Blue is similar to Black Light, but with a filter in the glass to filter out visible light. Used by psychedelic shops for lighting fluorescent posters, displays, etc. In the theatre Black Light Blue is used where only fluorescent materials in clothing and objects, most white clothing, teeth, and whites of the eye, are desired for effect. These are often used in bars, restaurants, bowling alleys, and Mini golf venues to achieve similar effects.  
**CAUTION:** This lamp emits ultraviolet (UV) power during operation and is in Risk Group 1 per ANSI/IESNA RP-27.3-96. Exposure at less than 0.25 meters (10 inches) should be limited; for example exposure at 0.14m (6 inches) should not exceed 4 hours in an 8 hour interval (see ANSI/IESNA RP-27.1-96). Certain medications and chemicals can increase an individual's sensitivity. Consult your physician for specific information. Protective eyewear should be worn in occupational situations involving long term exposure in close proximity to the lamp. This lamp is not intended and should not be used for diagnostic, therapeutic or cosmetic purposes.

3 Fluorescent T8 Appliance Lamp Cross References

Satco	Sylvania	Phillips	GE
S6513	F18T8CW/K24	F15T8/CW/24	F24"T8/CW/4
S6514	F18T8CW/K26	F16T8/CW/26	F26"T8/CW/4
S6515	F18T8CW/K28	F17T8/CW/28	F28"T8/CW/4
S6516	F18T8CW/K30	F18T8/CW/30	F30"T8/CW/4

- 4 Rated life of T8 lamps when used on Rapid Start or Programmed Rapid Start ballasts based on 3 hours per cycle. When used on Instant Start ballasts, hours are 24,000 based on 3 hours per cycle. At 12 hours per cycle, life is 36,000 hours on Rapid Start or Programmed Rapid Start ballasts and 30,000 on Instant Start ballasts.
- 5 Due to their small diameter, T2 Mini fluorescent lamps operate at higher surface temperatures than other fluorescent lamps. To avoid possible burns, do not touch the lamp during operation and allow sufficient cooling time before removing the lamp from the fixture. The typical bulb wall temperature during operation is 120 degrees at the ends. The maximum allowable bulb wall temperature is 150 degrees C.
- 6 The F34 and FB34 lamps were previously known as energy saving F40, and FB40 lamps. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low power factor ballasts, (3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless any of the above equipment is specifically listed for use with 34 watt lamps.
- 7 **▲WARNING:** To prevent possible serious injury, eY and skin should not be exposed to direct or reflected ultraviolet power emitted by this lamp. This lamp is in Risk Group 3 per ANSI/IESNA RP-27.3-96. Adequate protection should be provided by clothing, gloves, opaque materials, and ordinary window glass. Although this lamp will operate in standard fluorescent fixtures, it should not be used for general lighting applications.
- 8 Grow Light wide spectrum lamps are also used for retail meat case applications.
- 9 **ShatterProof** lamps are designed for any application where lamps are at risk of being broken. The rubber coating will contain the glass particles and phosphors should the lamp break, keeping it from falling into food, or elsewhere. Many jurisdictions now require the use of coated lamps in all food preparation, and service areas. This coating also has the added benefit of blocking all UV emissions from 100 to 380 nanometers, common to fluorescent technology.
- 10 Labeled for cold temperature (below 60°F) operation only per EPACT.
- 11 The average rated hours are based on 3 hours per start when used on an instant start ballast meeting ANSI specifications. The average hours will increase when operated on longer operating cycles.
- 12 Initial lumens are measured after 100 hours of operation.
- 13 Consult the ballast manufacturer for minimum starting temperature, which is a function of the ballast.

# COMPACT FLUORESCENT LAMPS

## Lamps that keep on saving.

Compact fluorescent lamps have become one of the most popular lamp types available. With lumen output similar to that of incandescent lamps, but only using about one quarter of the wattage, it's easy to see why. Satco carries hundreds of variations of high quality, energy efficient compact fluorescent lamps from 5W mini spirals, to decorative types, to our HI-PRO high-wattage spirals suitable for almost any commercial application.

There's also a wide selection of twin, triple, and quad tube pin-based lamps in the Satco/Hygrade™ family. For sure, Satco has a CFL for virtually every lighting application.

### CFL features:

- Lamps from 5 to 105 Watts
- Complete choice of color temperatures
- Energy efficient – uses up to 75% less energy than incandescent technology
- Long life – up to 12,000 hours
- Excellent color rendering
- Lamps for consumer and industrial use
- Environmentally friendly – low Mercury
- Virtually all industry standard base types available





Nuvo Lighting's Harlow five light chandelier in Hazel Bronze with Khaki fabric shades. Nuvo item number 60-4725. [www.nuvolighting.com](http://www.nuvolighting.com)

Energy efficient bulbs are recommended in five of the most used residential fixtures or locations – kitchen, living room, bathroom, bedroom, and outdoor. Since these areas of the home have the highest energy use for lighting, these “high five” are good places to start, with plenty of options to suit most applications.

Nuvo Lighting's Odeon five light chandelier in Brushed Nickel with Satin White glass. Nuvo item number 60-3806. [www.nuvolighting.com](http://www.nuvolighting.com)



# COMPACT FLUORESCENT



Mini Spiral  
Med.

## T2 Ultra Mini Spiral – 4 Bulb Value Pack

Suitable for enclosed fixtures

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
<b>13</b>	Mini Spiral	Med.	<b>S6235</b>	60W	13T2/27	120	2700	82	12000	900	4 ½	1 ½	Box	12- 4pks
			<b>S5547</b>	60W	13T2/27	120	2700	82	12000	900	4 ½	1 ½	Clamshell	24- 4pks
			<b>S6238</b>	60W	13T2/35	120	3500	82	12000	900	4 ½	1 ½	Box	12- 4pks
			<b>S6236</b>	60W	13T2/41	120	4100	82	12000	880	4 ½	1 ½	Box	12- 4pks
			<b>S6237</b>	60W	13T2/50	120	5000	82	12000	880	4 ½	1 ½	Box	12- 4pks
			<b>S5549</b>	60W	13T2/50	120	5000	82	12000	880	4 ½	1 ⅜	Clamshell	24- 4pks

## T2 Ultra Mini Spiral – 3 Bulb Value Pack

Suitable for enclosed fixtures

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
<b>18</b>	Mini Spiral	Med.	<b>S6271</b>	75W	18T2/27	120	2700	82	12000	1140	4 ½	2 ½	Box	12- 3pks
			<b>S5541</b>	75W	18T2/27	120	2700	82	12000	1140	4 ½	2 ½	Clamshell	24- 3pks
			<b>S6272</b>	75W	18T2/41	120	4100	82	10000	1200	4 ½	2 ½	Box	12- 3pks
			<b>S6273</b>	75W	18T2/50	120	5000	82	10000	1200	4 ½	2 ½	Box	12- 3pks
			<b>S5543</b>	75W	18T2/50	120	5000	82	10000	1200	4 ½	2 ½	Clamshell	24- 3pks
<b>23</b>	Mini Spiral	Med.	<b>S6274</b>	100W	23T2/27	120	2700	82	12000	1600	4 ¾	2 ½	Box	12- 3pks
			<b>S5544</b>	100W	23T2/27	120	2700	82	12000	1600	4 ¾	2 ½	Clamshell	24- 3pks
			<b>S6284</b>	100W	23T2/35	120	3500	82	12000	1600	4 ¾	2 ½	Box	12- 3pks
			<b>S6275</b>	100W	23T2/41	120	4100	82	12000	1600	4 ¾	2 ½	Box	12- 3pks
			<b>S6276</b>	100W	23T2/50	120	5000	82	12000	1600	4 ¾	2 ½	Box	12- 3pks
			<b>S5546</b>	100W	23T2/50	120	5000	82	12000	1600	4 ¾	2 ½	Clamshell	24- 3pks

## T2 Ultra Mini Spiral – 8 Bulb Value Pack

Suitable for enclosed fixtures

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
<b>13</b>	Mini Spiral	Med.	<b>S6277</b>	60W	13T2/27	120	2700	82	12000	900	4 ½	1 ½	Box	18- 8pks
<b>18</b>	Mini Spiral	Med.	<b>S6278</b>	75W	18T2/27	120	2700	82	12000	1140	4 ½	2 ½	Box	15- 8pks
<b>23</b>	Mini Spiral	Med.	<b>S6279</b>	100W	23T2/27	120	2700	82	12000	1600	4 ¾	2 ½	Box	15- 8pks





Mini Spiral  
Cand.



Mini Spiral  
Med.

## Screw In Lamps

### T2 Ultra Mini Spiral Lamps

Suitable for enclosed fixtures

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
5	Mini Spiral	Cand.	<b>S7264</b>	25W	5T2C/27	120	2700	82	10000	280	3 7/16	1 3/8	Box	48/12
			<b>S7265</b>	25W	5T2C/41	120	4100	82	10000	280	3 7/16	1 3/8	Box	48/12
			<b>S7266</b>	25W	5T2C/50	120	5000	82	10000	280	3 7/16	1 3/8	Box	48/12
	Med.	<b>S7261</b>	25W	5T2/27	120	2700	82	10000	280	3 7/16	1 3/8	Box	48/12	
		<b>S5501</b>	25W	5T2/27	120	2700	82	10000	280	3 7/16	1 3/8	Clamshell	24/6	
		<b>S7262</b>	25W	5T2/41	120	4100	82	10000	280	3 7/16	1 3/8	Box	48/12	
		<b>S7263</b>	25W	5T2/50	120	5000	82	10000	280	3 7/16	1 3/8	Box	48/12	
		<b>S5503</b>	25W	5T2/50	120	5000	82	10000	280	3 7/16	1 3/8	Clamshell	24/6	
		9	Mini Spiral	Cand.	<b>S7361</b>	40W	9T2C/27	120	2700	82	12000	550	4	1 1/16
<b>S7362</b>	40W				9T2C/41	120	4100	82	12000	550	4	1 1/16	Box	48/12
<b>S7363</b>	40W				9T2C/50	120	5000	82	10000	570	4	1 1/16	Box	48/12
Med.	<b>S7211</b>		40W	9T2/27	120	2700	82	12000	550	4	1 1/2	Box	48/12	
	<b>S5504</b>		40W	9T2/27	120	2700	82	12000	550	4	1 1/16	Clamshell	24/6	
	<b>S7212</b>		40W	9T2/41	120	4100	82	12000	550	4	1 1/2	Box	48/12	
	<b>S7213</b>		40W	9T2/50	120	5000	82	10000	570	4	1 1/16	Box	48/12	
	<b>S5506</b>		40W	9T2/50	120	5000	82	10000	570	4	1 1/16	Clamshell	24/6	
	11		Mini Spiral	Med.	<b>S7214</b>	40W	11T2/27	120	2700	82	10000	730	4	1 13/16
<b>S5507</b>		40W			11T2/27	120	2700	82	10000	730	4	1 13/16	Clamshell	24/6
<b>S7215</b>		40W			11T2/41	120	4100	82	10000	730	4	1 13/16	Box	48/12
<b>S7216</b>		40W			11T2/50	120	5000	82	10000	730	4	1 13/16	Box	48/12
<b>S5509</b>		40W			11T2/50	120	5000	82	10000	730	4	1 13/16	Clamshell	24/6
13	Mini Spiral	Cand.	<b>S7364</b>	60W	13T2C/27	120	2700	82	12000	900	4 1/8	1 13/16	Box	48/12
			<b>S7365</b>	60W	13T2C/41	120	4100	82	12000	880	4 1/8	1 13/16	Box	48/12
			<b>S7366</b>	60W	13T2C/50	120	5000	82	12000	880	4 1/8	1 1/2	Box	48/12
	Med.	<b>S7411</b>	60W	13T2/27/230V	230	2700	82	12000	900	4 1/4	1 1/2	Box	48/12	
		<b>S7412</b>	60W	13T2/50/230V	230	5000	82	12000	880	4 1/4	1 13/16	Box	48/12	
		<b>S7217</b>	60W	13T2/27	120	2700	82	12000	900	4 1/8	1 13/16	Box	48/12	
		<b>S7268</b>	60W	13T2/27/12V	12	2700	82	10000	710	4 1/8	1 13/16	Box	48/12	
		<b>S5516</b>	60W	13T2/27	120	2700	82	12000	900	4 1/8	1 13/16	Clamshell	24/6	
		<b>S7218</b>	60W	13T2/41	120	4100	82	12000	880	4 1/8	1 13/16	Box	48/12	
		<b>S7219</b>	60W	13T2/50	120	5000	82	12000	880	4 1/8	1 13/16	Box	48/12	
		<b>S5518</b>	60W	13T2/50	120	5000	82	12000	880	4 1/8	1 13/16	Clamshell	24/6	

† To be discontinued when inventory is depleted.

# COMPACT FLUORESCENT



Mini Spiral  
Med.

## T2 Ultra Mini Spiral Lamps (continued)

Suitable for enclosed fixtures

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/ Inner Carton
<b>15</b>	Mini Spiral	Med.	<b>S5519</b>	75W	15T2/27	120	2700	82	12000	1100	4 3/8	2 1/8	Clamshell	24/6
			<b>S7221</b>	75W	15T2/27	120	2700	82	12000	1100	4 3/8	2 1/8	Box	48/12
			<b>S7222</b>	75W	15T2/41	120	4100	82	10000	1100	4 3/8	2 1/8	Box	48/12
			<b>S7223</b>	75W	15T2/50	120	5000	82	10000	1100	4 3/8	2 1/8	Box	48/12
<b>18</b>	Mini Spiral	Med.	<b>S7413</b>	75W	18T2/27/230V	230	2700	82	12000	1200	4 5/8	2 1/8	Box	48/12
			<b>S7417</b>	75W	18T2/50/230V	230	5000	82	12000	1200	4 5/8	2 1/8	Box	48/12
			<b>S5523</b>	75W	18T2/27	120	2700	82	12000	1140	4 1/2	2 1/8	Clamshell	24/6
			<b>S7224</b>	75W	18T2/27	120	2700	82	12000	1140	4 1/2	2 1/8	Box	48/12
			<b>S7225</b>	75W	18T2/41	120	4100	82	10000	1200	4 1/2	2 1/8	Box	48/12
			<b>S5525</b>	75W	18T2/50	120	5000	82	10000	1200	4 1/2	2 1/8	Clamshell	24/6
<b>20</b>	Mini Spiral	Med.	<b>S5401</b>	75W	20T2/27	120	2700	82	12000	1330	4 7/16	2 1/8	Clamshell	24/6
			<b>S7234</b>	75W	20T2/27	120	2700	82	12000	1330	4 7/16	2 1/8	Box	48/12
			<b>S7235</b>	75W	20T2/41	120	4100	82	10000	1300	4 7/16	2 1/8	Box	48/12
			<b>S7236</b>	75W	20T2/50	120	5000	82	10000	1300	4 7/16	2 1/8	Box	48/12
<b>23</b>	Mini Spiral	Med.	<b>S5526</b>	100W	23T2/27	120	2700	82	12000	1600	4 7/8	2 1/8	Clamshell	24/6
			<b>S7227</b>	100W	23T2/27	120	2700	82	12000	1600	4 7/8	2 1/8	Box	48/12
			<b>S7228</b>	100W	23T2/41	120	4100	82	12000	1600	4 7/8	2 1/8	Box	48/12
			<b>S5528</b>	100W	23T2/50	120	5000	82	12000	1600	4 7/8	2 1/8	Clamshell	24/6
			<b>S7229</b>	100W	23T2/50	120	5000	82	12000	1600	4 7/8	2 1/8	Box	48/12
<b>26</b>	Mini Spiral	Med.	<b>S7418</b>	100W	26T2/27/230V	230	2700	82	12000	1750	5 3/16	2 1/8	Box	48/12
			<b>S7414</b>	100W	26T2/50/230V	230	5000	82	12000	1750	5 3/16	2 1/8	Box	48/12
			<b>S5529</b>	100W	26T2/27	120	2700	82	12000	1750	5 1/16	2 1/8	Clamshell	24/6
			<b>S7231</b>	100W	26T2/27	120	2700	82	12000	1750	5 1/16	2 1/8	Box	48/12
			<b>S7232</b>	100W	26T2/41	120	4100	82	10000	1750	5 1/16	2 1/8	Box	48/12
			<b>S5532</b>	100W	26T2/50	120	5000	82	10000	1750	5 1/16	2 1/8	Clamshell	24/6
			<b>S7233</b>	100W	26T2/50	120	5000	82	10000	1750	5 1/16	2 1/8	Box	48/12

† To be discontinued when inventory is depleted.



Half-full Spiral Med.



Mini Spiral Med.



Hi-Pro Spiral Med.



Hi-Pro Spiral Mog.

## T2 Half-full Spiral – 12 Bulb Contractor Pack

Suitable for enclosed fixtures

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
13	Half-full Spiral	Med.	<b>S7436</b>	60W	13T2/27	120	2700	80	10000	800	4 3/16	1 13/16	Box	4 -12pks
20	Half-full Spiral	Med.	<b>S7437</b>	75W	20T2/27	120	2700	80	10000	1200	4 7/16	2 1/4	Box	4 -12pks
23	Half-full Spiral	Med.	<b>S7438</b>	100W	23T2/27	120	2700	80	10000	1600	4 5/8	2 1/4	Box	4 -12pks

T2 Half-full Spiral – 12 Bulb Contractor Pack – 1 Unit = 12 Lamps.

## T2 Ultra Mini Specialty Spiral (Colors)

Suitable for enclosed fixtures

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	CRI	Avg. Rated Hours	Color	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
13	Mini Spiral	Med.	<b>S5511</b>	60W	13T2/Bug	120	82	10000	Bug Yellow	4 1/8	1 13/16	Clamshell	24/6
			<b>S7267</b>	60W	13T2/Bug	120	82	10000	Bug Yellow	4 1/8	1 13/16	Box	48/12
			<b>S5512</b>	60W	13T2/Red	120	82	10000	Red	4 1/8	1 13/16	Clamshell	24/6
			<b>S7271</b>	60W	13T2/Red	120	82	10000	Red	4 1/8	1 13/16	Box	48/12
			<b>S5513</b>	60W	13T2/Green	120	82	10000	Green	4 1/8	1 13/16	Clamshell	24/6
			<b>S7272</b>	60W	13T2/Green	120	82	10000	Green	4 1/8	1 13/16	Box	48/12
			<b>S5514</b>	60W	13T2/Blue	120	82	10000	Blue	4 1/8	1 13/16	Clamshell	24/6
			<b>S7273</b>	60W	13T2/Blue	120	82	10000	Blue	4 1/8	1 13/16	Box	48/12
			<b>S5515</b>	60W	13T2/BLB	120	82	10000	Blacklight	4 1/8	1 13/16	Clamshell	24/6
			<b>S7277</b>	60W	13T2/BLB	120	82	10000	Blacklight	4 1/8	1 13/16	Box	48/12

## Hi-Pro Spiral / Med. and Mog. Base

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
32	Hi-Pro Spiral	Med.	<b>S7331</b>	100W	32T4/27	120	2700	82	10000	2000	6 3/4	2 5/8	Box	48/12
			<b>S7332</b>	100W	32T4/41	120	4100	82	10000	2000	6 3/4	2 5/8	Box	48/12
			<b>S7423</b>	125W	32T4/41	277	4100	82	10000	2000	6 3/4	2 5/8	Box	48/12
			<b>S7333</b>	100W	32T4/50	120	5000	82	10000	2000	6 3/4	2 5/8	Box	48/12
			<b>S7425</b>	125W	32T4/50	277	5000	82	10000	2000	6 3/4	2 5/8	Box	48/12
		Mog.	<b>S7424</b>	125W	32T4/41	277	4100	82	10000	2000	6 15/16	2 5/8	Box	48/12
			<b>S7426</b>	125W	32T4/50	277	5000	82	10000	2000	6 15/16	2 5/8	Box	48/12

# COMPACT FLUORESCENT



Hi-Pro Spiral  
Med.



Hi-Pro Spiral  
Mog.

## Hi-Pro Spiral / Med. and Mog. Base (continued)

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton	
<b>40</b>	Hi-Pro Spiral	Med.	<b>S7334</b>	150W	40T4/27	120	2700	82	10000	2600	7 5/8	2 5/8	Box	48/12	
			<b>S7335</b>	150W	40T4/41	120	4100	82	10000	2600	7 5/8	2 5/8	Box	48/12	
			<b>S7427</b>	150W	40T4/41	277	4100	82	10000	2600	7 5/8	2 5/8	Box	48/12	
			<b>S7336</b>	150W	40T4/50	120	5000	82	10000	2600	7 5/8	2 5/8	Box	48/12	
			<b>S7429</b>	150W	40T4/50	277	5000	82	10000	2600	7 5/8	2 5/8	Box	48/12	
			Mog.	<b>S7428</b>	150W	40T4/41	277	4100	82	10000	2600	7 1/2	2 5/8	Box	48/12
	<b>S7430</b>	150W		40T4/50	277	5000	82	10000	2600	7 1/2	2 5/8	Box	48/12		
	<b>55</b>	Hi-Pro Spiral	Med.	<b>S7337</b>	300W	55T5/27	120	2700	82	10000	3700	9 5/8	3 1/8	Box	48/12
<b>S7338</b>				300W	55T5/41	120	4100	82	10000	3700	9 5/8	3 1/8	Box	48/12	
<b>S7339</b>				300W	55T5/50	120	5000	82	10000	3700	9 5/8	3 1/8	Box	48/12	
<b>65</b>	Hi-Pro Spiral	Med.	<b>S7384</b>	300W	65T5/27	120	2700	82	10000	4300	9 7/8	3 3/8	Box	48/12	
			<b>S7385</b>	300W	65T5/41	120	4100	82	10000	4300	9 7/8	3 3/8	Box	48/12	
			<b>S7386</b>	300W	65T5/50	120	5000	82	10000	4300	9 7/8	3 3/8	Box	48/12	
			Mog.	<b>S7387</b>	300W	65T5/27	120	2700	82	10000	4300	9 7/8	3 3/8	Box	48/12
				<b>S7388</b>	300W	65T5/41	120	4100	82	10000	4300	9 7/8	3 3/8	Box	48/12
			Non-ballasted Mog.	<b>S7389</b>	300W	65T5/50	120	5000	82	10000	4300	9 7/8	3 3/8	Box	48/12
	<b>S7379</b>	250W		65T5/65	120	6500	82	10000	3900	8 9/16	3 3/8	Box	48/12		
	<b>85</b>	Hi-Pro Spiral	Med.	<b>S7397</b>	350W	85T5/27	120	2700	82	10000	5700	9 5/8	4	Box	12/6
<b>S7398</b>				350W	85T5/41	120	4100	82	10000	5700	9 5/8	4	Box	12/6	
<b>S7399</b>				350W	85T5/50	120	5000	82	10000	5700	9 5/8	4	Box	12/6	
Mog.				<b>S7391</b>	350W	85T5/27	120	2700	82	10000	5700	10 1/2	4	Box	12/6
				<b>S7392</b>	350W	85T5/41	120	4100	82	10000	5700	10 1/2	4	Box	12/6
Non-ballasted Mog.		<b>S7393</b>	350W	85T5/50	120	5000	82	10000	5700	10 1/2	4	Box	12/6		
		<b>105</b>	Hi-Pro Spiral	Med.	<b>S7375</b>	400W	105T5/27	120	2700	82	10000	7000	10 3/4	4	Box
<b>S7376</b>	400W				105T5/41	120	4100	82	10000	7000	10 3/4	4	Box	12/6	
<b>S7377</b>	400W				105T5/50	120	5000	82	10000	7000	10 3/4	4	Box	12/6	
Mog.	<b>S7394</b>				400W	105T5/27	120	2700	82	10000	7000	11 1/4	4	Box	12/6
	<b>S7395</b>				400W	105T5/41	120	4100	82	10000	7000	11 1/4	4	Box	12/6
Non-ballasted Mog.	<b>S7415</b>				400W	105T5/41/277	277	4100	82	10000	7000	11 1/4	4	Box	12/6
	<b>S7396</b>		400W	105T5/50	120	5000	82	10000	7000	11 1/4	4	Box	12/6		
Non-ballasted Mog.	<b>S7416</b>		400W	105T5/50/277	277	5000	82	10000	7000	11 1/4	4	Box	12/6		



3-Way Spiral  
Med.



Mini Spiral  
GU24 Base



Squat Spiral  
GU24 Base

### 3-Way Spiral

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
<b>12/20/26</b>	Spiral	Med.	<b>S7341</b>	30/70/100W	12/20/26T4/27	120	2700	82	10000	660/1200/1600	6	2 3/8	Box	48/12
			<b>S7342</b>	30/70/100W	12/20/26T4/41	120	4100	82	10000	660/1200/1600	6	2 3/8	Box	48/12
			<b>S7343</b>	30/70/100W	12/20/26T4/50	120	5000	82	10000	660/1200/1600	6	2 3/8	Box	48/12



### GU24 Base Mini & Squat Spiral

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
<b>9</b>	Mini Spiral	GU24	<b>S8201</b>	40W	9GU24/27	120	2700	82	10000	500	3 7/8	1 1/8	Box	48/12
<b>11</b>	Mini Spiral	GU24	<b>S8202</b>	40W	11GU24/27	120	2700	82	10000	650	3 7/8	1 13/16	Box	48/12
<b>13</b>	Mini Spiral	GU24	<b>S5301</b>	60W	13GU24/27	120	2700	82	10000	800	3 5/8	1 13/16	Clamshell	24/6
			<b>S8203</b> △	60W	13GU24/27	120	2700	82	10000	800	3 5/8	1 13/16	Box	48/12
			<b>S8226</b>	60W	13T2GU24/35	120	3500	82	10000	900	3 5/8	1 13/16	Box	48/12
			<b>S8208</b>	60W	13T2GU24/41	120	4100	82	10000	880	3 5/8	1 13/16	Box	48/12
	Squat Spiral	GU24	<b>S8227</b> △	60W	13T2GU24/27/Squat	120	2700	82	10000	850	2 1/2	2 3/4	Box	48/12
<b>15</b>	Mini Spiral	GU24	<b>S8204</b>	60W	15GU24/27	120	2700	82	10000	1000	3 7/8	2 1/8	Box	48/12
<b>18</b>	Mini Spiral	GU24	<b>S5302</b>	75W	18GU24/27	120	2700	82	10000	1200	4 1/2	2 1/8	Clamshell	24/6
			<b>S8205</b> △	75W	18GU24/27	120	2700	82	10000	1200	4 1/2	2 1/8	Box	48/12
			<b>S8229</b>	75W	18GU24/35	120	3500	82	10000	1200	4 5/8	2 1/8	Box	48/12
			<b>S8209</b>	75W	18GU24/41	120	4100	82	10000	1200	4 1/8	2 1/8	Box	48/12
	Squat Spiral	GU24	<b>S8228</b> △	75W	18T2GU24/27/Squat	120	2700	82	10000	1100	2 13/16	2 3/4	Box	48/12
<b>23</b>	Mini Spiral	GU24	<b>S8206</b>	100W	23GU24/27	120	2700	82	10000	1600	4 15/16	2 1/8	Box	48/12
			<b>S8232</b>	100W	23GU24/35	120	3500	82	10000	1600	4 15/16	2 1/8	Box	48/12
			<b>S8210</b>	100W	23GU24/41	120	4100	82	10000	1600	4 7/8	2 1/8	Box	48/12
<b>26</b>	Mini Spiral	GU24	<b>S8207</b>	120W	26GU24/27	120	2700	82	10000	1750	5 3/8	2 1/8	Box	48/12
			<b>S8233</b>	120W	26GU24/35	120	3500	82	10000	1750	5 3/8	2 1/8	Box	48/12

△ Certified Subcomponent Database (CSD) Listed.



# COMPACT FLUORESCENT



## R20 Reflector


Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
5	R20	Med.	S7257	30W	5R20/27	120	2700	82	10000	260	3 7/8	2 1/2	Box	24/6
			S7258	30W	5R20/41	120	4100	82	10000	260	3 7/8	2 1/2	Box	24/6
			S7259	30W	5R20/50	120	5000	82	10000	260	3 7/8	2 1/2	Box	24/6
11	R20	Med.	S7254	40W	11R20/27	120	2700	82	10000	350	4 7/16	2 1/2	Box	24/6
			S7255	40W	11R20/41	120	4100	82	10000	330	4 7/16	2 1/2	Box	24/6
			S7256	40W	11R20/50	120	5000	82	10000	330	4 7/16	2 1/2	Box	24/6
13	R20	Med.	S7401	45W	13R20/27	120	2700	82	10000	430	4 5/8	2 1/2	Box	24/6
			S7402	45W	13R20/41	120	4100	82	10000	430	4 5/8	2 1/2	Box	24/6
			S7403	45W	13R20/50	120	5000	82	10000	430	4 5/8	2 1/2	Box	24/6

## R30 Reflector

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
15	R30	Med.	S7247	65W	15R30/27	120	2700	82	10000	700	5 3/8	3 3/4	Box	24/6
			S7248	65W	15R30/41	120	4100	82	10000	700	5 3/8	3 3/4	Box	24/6
			S7249	65W	15R30/50	120	5000	82	10000	700	5 3/8	3 3/4	Box	24/6
			S7278	65W	15R30/27/2PK	120	2700	82	10000	700	5 3/8	3 3/4	Box	24/2
		GU24	S8224	65W	15R30/27/GU24	120	2700	82	10000	690	4 3/4	3 3/4	Box	24/6

## R40 Reflector

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
23	R40	Med.	S7241	85W	23R40/27	120	2700	82	10000	1090	6 1/2	5	Box	24/6
			S7242	85W	23R40/41	120	4100	82	10000	1090	6 1/2	5	Box	24/6
			S7243	85W	23R40/50	120	5000	82	10000	1090	6 1/2	5	Box	24/6



### BR38 Reflector (U.L. Wet Location)

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/ Inner Carton
23	BR38	Med.	<b>S7274</b>	85W	23BR38/27	120	2700	82	10000	1070	6 ½	4 ¾	Box	24/6
			<b>S7275</b>	85W	23BR38/41	120	4100	82	10000	1070	6 ½	4 ¾	Box	24/6
			<b>S7276</b>	85W	23BR38/50	120	5000	82	10000	1070	6 ½	4 ¾	Box	24/6

### PAR Lamps (U.L. Wet Location)

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/ Inner Carton
11	PAR20	Med.	<b>S7421</b>	45W	11PAR20/27/230V	230	2700	82	10000	380	4	2 ½	Box	12/6
			<b>S7207</b>	50W	11PAR20/27	120	3500	82	10000	380	3 ¾	2 ½	Box	12/6
			<b>S7208</b>	50W	11PAR20/41	120	4100	82	10000	380	3 ¾	2 ½	Box	12/6
			<b>Shatter Proof S7238</b>	50W	11PAR20/41	120	4100	82	10000	380	3 ¾	2 ½	Box	12/6
			<b>S7209</b>	50W	11PAR20/50	120	5000	82	10000	380	3 ¾	2 ½	Box	12/6
15	PAR30	Med.	<b>S7204</b>	50W	15PAR30/27	120	2700	82	10000	700	4 ½	3 ¾	Box	12/6
			<b>S7294</b>	50W	15PAR30/35	120	3500	82	10000	700	4 ½	3 ¾	Box	12/6
			<b>S7205</b>	50W	15PAR30/41	120	4100	82	10000	720	4 ½	3 ¾	Box	12/6
			<b>Shatter Proof S7237</b>	50W	15PAR30/41	120	4100	82	10000	720	4 ½	3 ¾	Box	12/6
			<b>S7206</b>	50W	15PAR30/50	120	5000	82	10000	700	4 ½	3 ¾	Box	12/6
23	PAR38	Med.	<b>S7432</b>	75W	23PAR38/27/230V	230	2700	82	10000	1100	5 ⅝	4 ¾	Box	12/6
			<b>S7422</b>	75W	23PAR38/50/230V	230	5000	82	10000	1100	5 ⅝	4 ¾	Box	12/6
			<b>S7201</b>	75W	23PAR38/27	120	2700	82	10000	1100	5 ⅝	4 ¾	Box	12/6
			<b>S7279</b>	75W	23PAR38/27/2PK	120	2700	82	10000	1100	5 ⅝	4 ¾	Box	12/2
			<b>S7202</b>	75W	23PAR38/41	120	4100	82	10000	1100	5 ⅝	4 ¾	Box	12/6
			<b>S7203</b>	75W	23PAR38/50	120	5000	82	10000	1100	5 ⅝	4 ¾	Box	12/6

### A-Type Lamps

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/ Inner Carton
7	A-Type	Med.	<b>S7281</b>	25W	7A19/27	120	2700	82	12000	410	4 ¼	2 ½	Box	48/12
			<b>S7282</b>	25W	7A19/41	120	4100	82	10000	400	4 ¼	2 ½	Box	48/12
			<b>S7283</b>	25W	7A19/50	120	5000	82	10000	400	4 ¼	2 ½	Box	48/12


# COMPACT FLUORESCENT




A-Type  
Med.



A-Type  
GU24 Base



Globe  
Med.




Globe  
GU24 Base

## A-Type Lamps (continued)

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
<b>9</b>	A-Type	Med.	<b>S5568</b>	40W	9A19/27	120	2700	82	6000	450	4 3/16	2 3/16	Clamshell	24/6
			<b>S7284</b>	40W	9A19/27	120	2700	82	6000	450	4 3/16	2 1/2	Box	48/12
			<b>S7285</b>	40W	9A19/41	120	4100	82	10000	450	4 3/16	2 1/2	Box	48/12
			<b>S7286</b>	40W	9A19/50	120	5000	82	10000	450	4 3/16	2 1/2	Box	48/12
<b>11</b>	A-Type	Med.	<b>S5572</b>	40W	11A19/27	120	2700	82	10000	540	4 3/16	2 7/16	Clamshell	24/6
			<b>S7287</b>	40W	11A19/27	120	2700	82	10000	540	4 3/16	2 3/16	Box	48/12
			<b>S7288</b>	40W	11A19/41	120	4100	82	10000	540	4 3/16	2 3/16	Box	48/12
			<b>S7289</b>	40W	11A19/50	120	5000	82	10000	540	4 3/16	2 3/16	Box	48/12
<b>15</b>	A-Type	Med.	<b>S5575</b>	60W	15A19/27	120	2700	82	10000	975	4 3/8	2 1/4	Clamshell	24/6
			<b>S7291</b>	60W	15A19/27	120	2700	82	10000	975	4 3/8	2 1/4	Box	48/12
			<b>S7292</b>	60W	15A19/41	120	4100	82	10000	800	4 3/8	2 1/4	Box	48/12
			<b>S7293</b>	60W	15A19/50	120	5000	82	10000	800	4 3/8	2 1/4	Box	48/12
		GU24	<b>S8225</b>	60W	15A19/27/GU24	120	2700	82	10000	800	4 3/4	2 5/8	Box	48/12

## Globe Lamps

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
<b>9</b>	Globe	Med.	<b>S7301</b>	40W	9G25/27	120	2700	82	10000	540	4 5/16	3 1/8	Box	48/12
			<b>S7302</b>	40W	9G25/41	120	4100	82	10000	500	4 5/16	3 1/8	Box	48/12
			<b>S7303</b>	40W	9G25/50	120	5000	82	10000	500	4 5/16	3 1/8	Box	48/12
<b>15</b>	Globe	Med.	<b>S7304</b>	60W	15G25/27	120	2700	82	10000	820	4 3/4	3 3/8	Box	48/12
			<b>S7305</b>	60W	15G25/41	120	4100	82	10000	820	4 3/4	3 7/16	Box	48/12
			<b>S7306</b>	60W	15G25/50	120	5000	82	10000	820	4 3/4	3 7/16	Box	48/12
		GU24	<b>S8221</b>	60W	15G25/27/GU24	120	2700	82	10000	740	4 3/4	3 3/8	Box	48/12




## T10 & Bullet Lamps

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
<b>7</b>	T10	Med.	<b>S7381</b>	40W	7T10/27	120	2700	85	10000	340	4 13/16	1 5/16	Box	48/12
			<b>S7382</b>	40W	7T10/41	120	4100	85	10000	340	4 13/16	1 1/2	Box	48/12
			<b>S7383</b>	40W	7T10/50	120	5000	85	10000	340	4 13/16	1 1/2	Box	48/12
<b>15</b>	Bullet	Med.	<b>S7307</b>	60W	EFT15/27	120	2700	82	10000	800	5 1/2	1 5/16	Box	48/12
			<b>S7308</b>	60W	EFT15/41	120	4100	82	10000	800	5 1/2	1 5/16	Box	48/12
			<b>S7309</b>	60W	EFT15/50	120	5000	82	10000	800	5 1/2	1 5/16	Box	48/12

## Torpedo Lamps

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	M.O.D. Inches	Pkg. Type	Master/Inner Carton
<b>5</b>	Torpedo	Cand.	<b>S7311</b>	25W	5CTCFL/27	120	2700	82	10000	220	4 5/16	1 3/4	Box	48/12
			<b>S7312</b>	25W	5CTCFL/41	120	4100	82	10000	220	4 5/16	1 3/4	Box	48/12
			<b>S7313</b>	25W	5CTCFL/50	120	5000	82	10000	220	4 5/16	1 3/4	Box	48/12
		Med.	<b>S7314</b>	25W	5ETCFL/27	120	2700	82	10000	220	4 7/16	1 3/4	Box	48/12
			<b>S7315</b>	25W	5ETCFL/41	120	4100	82	10000	220	4 7/16	1 3/4	Box	48/12
<b>7</b>	Torpedo	Cand.	<b>S5595</b>	40W	7CTCFL/27	120	2700	82	10000	340	4 11/16	1 3/4	Clamshell	24/6
			<b>S7327</b>	40W	7CTCFL/27	120	2700	82	10000	340	4 11/16	1 3/4	Box	48/12
			<b>S7318</b>	40W	7CTCFL/41	120	4100	82	10000	340	4 11/16	1 3/4	Box	48/12
		Med.	<b>S7319</b>	40W	7CTCFL/50	120	5000	82	10000	340	4 11/16	1 3/4	Box	48/12
			<b>S5596</b>	40W	7ETCFL/27	120	2700	82	10000	340	4 13/16	1 3/4	Clamshell	24/6
			<b>S7328</b>	40W	7ETCFL/27	120	2700	82	10000	340	4 13/16	1 3/4	Box	48/12
			<b>S7322</b>	40W	7ETCFL/41	120	4100	82	10000	340	4 13/16	1 3/4	Box	48/12
			<b>S7323</b>	40W	7ETCFL/50	120	5000	82	10000	340	4 13/16	1 3/4	Box	48/12

# COMPACT FLUORESCENT




## Plug In Lamps

### Twin Tube 2-Pin for Magnetic Ballasts

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Master/Inner Carton
5	T4	G23	<b>S8300</b>	CF55W/827	120	2700	82	12000	230	4 1/2	Hang Box	50
			<b>S6700 ▲</b>	CF5DS/827	120	2700	82	10000	230	4 3/16	Box	50
			<b>S8381</b>	CF55W/835	120	3500	82	12000	230	4 1/2	Hang Box	50
			<b>S8301</b>	CF55W/841	120	4100	82	12000	230	4 1/2	Hang Box	50
			<b>S6701 ▲</b>	CF5DS/841	120	4100	82	10000	230	4 3/16	Box	50
7	T4	G23	<b>S8302</b>	CFS7W/827	120	2700	82	12000	400	5 1/16	Hang Box	50
			<b>S6702 ▲</b>	CF7DS/827	120	2700	82	10000	400	5 3/16	Box	50
			<b>S8303</b>	CFS7W/835	120	3500	82	12000	400	5 1/16	Hang Box	50
			<b>S6703 ▲</b>	CF7DS/835	120	3500	82	10000	400	5 3/16	Box	50
			<b>S8304</b>	CFS7W/841	120	4100	82	12000	400	5 1/16	Hang Box	50
			<b>S6704 ▲</b>	CF7DS/841	120	4100	82	10000	400	5 3/16	Box	50
			<b>S8305</b>	CFS7W/850	120	5000	82	12000	400	5 1/16	Hang Box	50
<b>S6705 ▲</b>	CF7DS/850	120	5000	82	10000	400	5 3/16	Box	50			
9	T4	G23	<b>S8306</b>	CFS9W/827	120	2700	82	12000	580	6 1/16	Hang Box	50
			<b>S6706 ▲</b>	CF9DS/827	120	2700	82	10000	580	6 1/2	Box	50
			<b>S8307</b>	CFS9W/835	120	3500	82	12000	580	6 1/16	Hang Box	50
			<b>S6707 ▲</b>	CF9DS/835	120	3500	82	10000	580	6 1/2	Box	50
			<b>S8308</b>	CFS9W/841	120	4100	82	12000	580	6 1/16	Hang Box	50
			<b>S6708 ▲</b>	CF9DS/841	120	4100	82	10000	580	6 1/2	Box	50
			<b>S8309</b>	CFS9W/850	120	5000	82	12000	580	6 1/16	Hang Box	50
			<b>S6709 ▲</b>	CF9DS/850	120	5000	82	10000	580	6 1/2	Box	50
13	T4	GX23	<b>S8310</b>	CFS13W/827	120	2700	82	12000	800	7 3/8	Hang Box	50
			<b>S6710 ▲</b>	CF13DS/827	120	2700	82	10000	800	7 1/2	Box	50
			<b>S8380</b>	CFS13W/830	120	3000	82	12000	800	7 3/8	Hang Box	50
			<b>S6780 ▲</b>	CF13DS/830	120	3000	82	10000	800	7 3/8	Box	50
			<b>S8311</b>	CFS13W/835	120	3500	82	12000	800	7 3/8	Hang Box	50
			<b>S6711 ▲</b>	CF13DS/835	120	3500	82	10000	800	7 1/2	Box	50
			<b>S8312</b>	CFS13W/841	120	4100	82	12000	800	7 3/8	Hang Box	50
			<b>S6712 ▲</b>	CF13DS/841	120	4100	82	10000	800	7 3/8	Box	50
			<b>S8313</b>	CFS13W/850	120	5000	82	12000	800	7 3/8	Hang Box	50
			<b>S6713 ▲</b>	CF13DS/850	120	5000	82	10000	800	7 1/2	Box	50






### Twin Tube 4-Pin for Electronic & Dimming Ballasts

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Carton
<b>5</b>	T4	2G7	<b>S8360</b>	CF5DS/E/827	120	2700	82	15000	230	4 ½	Box	50
			<b>S8361</b>	CF5DS/E/841	120	4100	82	15000	230	4 ½	Box	50
<b>7</b>	T4	2G7	<b>S8362</b>	CF7DS/E/827	120	2700	82	15000	400	5 1/16	Box	50
			<b>S6413 ▲</b>	CF7DS/E/827	120	2700	82	10000	400	4 ½	Box	50
			<b>S8363</b>	CF7DS/E/841	120	4100	82	15000	400	5 1/16	Box	50
			<b>S6414 ▲</b>	CF7DS/E/841	120	4100	82	10000	400	4 ½	Box	50
			<b>S8364</b>	CF9DS/E/827	120	2700	82	15000	580	6 1/16	Box	50
<b>9</b>	T4	2G7	<b>S6415 ▲</b>	CF9DS/E/827	120	2700	82	10000	580	5 1/16	Box	50
			<b>S8365</b>	CF9DS/E/841	120	4100	82	15000	580	6 1/16	Box	50
			<b>S6416 ▲</b>	CF9DS/E/841	120	4100	82	10000	580	5 1/16	Box	50
			<b>S8366</b>	CF13DS/E/827	120	2700	82	15000	800	7 5/8	Box	50
<b>13</b>	T4	2GX7	<b>S6417 ▲</b>	CF13DS/E/827	120	2700	82	10000	800	6 3/16	Box	50
			<b>S8367</b>	CF13DS/E/830	120	3000	82	15000	800	7 5/8	Box	50
			<b>S6418 ▲</b>	CF13DS/E/830	120	3000	82	10000	800	6 3/16	Box	50
			<b>S8368</b>	CF13DS/E/835	120	3500	82	15000	800	7 5/8	Box	50
			<b>S8369</b>	CF13DS/E/841	120	4100	82	15000	800	7 5/8	Box	50
			<b>S6419 ▲</b>	CF13DS/E/841	120	4100	82	10000	800	6 3/16	Box	50

### Quad Tube 2-Pin for Magnetic Ballasts


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Carton
<b>9</b>	T4	G23-2	<b>S8314</b>	CFD9W/827	120	2700	82	12000	525	4 ½	Hang Box	50
			<b>S6714 ▲</b>	CF9DD/827	120	2700	82	10000	525	4 5/16	Box	50
			<b>S8315</b>	CFD9W/830	120	3000	82	12000	525	4 ½	Hang Box	50
			<b>S8316</b>	CFD9W/835	120	3500	82	12000	525	4 ½	Hang Box	50
			<b>S6716 ▲</b>	CF9DD/835	120	3500	82	10000	525	4 5/16	Box	50

# COMPACT FLUORESCENT



## Quad Tube 2-Pin for Magnetic Ballasts (continued)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Carton
<b>13</b>	T4	GX23-2	<b>S8317</b>	CFD13W/827	120	2700	82	12000	780	5 1/16	Hang Box	50
			<b>S6717 ▲</b>	CF13DD/827	120	2700	82	10000	780	4 3/8	Box	50
			<b>S8318</b>	CFD13W/830	120	3000	82	12000	780	5 1/16	Hang Box	50
			<b>S6718 ▲</b>	CF13DD/830	120	3000	82	10000	780	4 3/8	Box	50
			<b>S8319</b>	CFD13W/835	120	3500	82	12000	780	5 1/16	Hang Box	50
			<b>S6719 ▲</b>	CF13DD/835	120	3500	82	10000	780	4 3/8	Box	50
			<b>S8320</b>	CFD13W/841	120	4100	82	12000	780	5 1/16	Hang Box	50
			<b>S6720 ▲</b>	CF13DD/841	120	4100	82	10000	780	4 3/8	Box	50
<b>18</b>	T4	G24D-2	<b>S8321</b>	CFD18W/827	120	2700	82	12000	1250	6 5/16	Hang Box	50
			<b>S6721 ▲</b>	CF18DD/827	120	2700	82	10000	1250	6	Box	50
			<b>S8322</b>	CFD18W/830	120	3000	82	12000	1250	6 5/16	Hang Box	50
			<b>S6722 ▲</b>	CF18DD/830	120	3000	82	10000	1250	6	Box	50
			<b>S8323</b>	CFD18W/835	120	3500	82	12000	1250	6 5/16	Hang Box	50
			<b>S6723 ▲</b>	CF18DD/835	120	3500	82	10000	1250	6	Box	50
			<b>S8324</b>	CFD18W/841	120	4100	82	12000	1250	6 5/16	Hang Box	50
			<b>S6724 ▲</b>	CF18DD/841	120	4100	82	10000	1250	6	Box	50
<b>22</b>	T5	GX32D-2	<b>S6020</b>	FDL22LE/D/PLC 15mm	120	2700	84	10000	1200	6	Box	40
			<b>S6021</b>	FDL22EX/D/PLC 15mm	120	5000	84	10000	1200	6	Box	50
<b>26</b>	T4	G24D-3	<b>S8325</b>	CFD26W/827	120	2700	82	12000	1825	7 1/8	Hang Box	50
			<b>S6725 ▲</b>	CF26DD/827	120	2700	82	10000	1825	6 13/16	Box	50
			<b>S8326</b>	CFD26W/830	120	3000	82	12000	1825	7 1/8	Hang Box	50
			<b>S6726 ▲</b>	CF26DD/830	120	3000	82	10000	1825	6 13/16	Box	50
			<b>S8327</b>	CFD26W/835	120	3500	82	12000	1825	7 1/8	Hang Box	50
			<b>S6727 ▲</b>	CF26DD/835	120	3500	82	10000	1825	6 13/16	Box	50
			<b>S8328</b>	CFD26W/841	120	4100	82	12000	1825	7 1/8	Hang Box	50
			<b>S6728 ▲</b>	CF26DD/841	120	4100	82	10000	1825	6 13/16	Box	50
<b>28</b>	T5	GX32D-3	<b>S6022</b>	FDL28LE/D/PLC 15mm	120	2800	84	10000	1600	6 13/16	Box	40
			<b>S6023</b>	FDL28EX/D/PLC 15mm	120	5000	84	10000	1600	6 13/16	Box	40




### Quad Tube 4-Pin for Electronic & Dimming Ballasts

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Carton
<b>13</b>	T4	G24q-1	<b>S8329</b>	CFD13W/4P/827	120	2700	82	15000	900	5 1/16	Hang Box	50
			<b>S6729 ▲</b>	CF13DD/E/827	120	2700	82	12000	900	5 3/16	Box	50
			<b>S8330</b>	CFD13W/4P/830	120	3000	82	15000	900	5 11/16	Hang Box	50
			<b>S6730 ▲</b>	CF13DD/E/830	120	3000	82	12000	900	5 3/16	Box	50
			<b>S8331</b>	CFD13W/4P/835	120	3500	82	15000	900	5 11/16	Hang Box	50
			<b>S6731 ▲</b>	CF13DD/E/835	120	3500	82	12000	900	5 3/16	Box	50
			<b>S8332</b>	CFD13W/4P/841	120	4100	82	15000	900	5 11/16	Hang Box	50
			<b>S6732 ▲</b>	CF13DD/E/841	120	4100	82	12000	900	5 3/16	Box	50
<b>18</b>	T4	G24q-2	<b>S8333</b>	CFD18W/4P/827	120	2700	82	15000	1250	6 5/16	Hang Box	50
			<b>S6733 ▲</b>	CF18DD/E/827	120	2700	82	12000	1250	5 13/16	Box	50
			<b>S8334</b>	CFD18W/4P/830	120	3000	82	15000	1250	6 5/16	Hang Box	50
			<b>S6734 ▲</b>	CF18DD/E/830	120	3000	82	12000	1250	5 13/16	Box	50
			<b>S8335</b>	CFD18W/4P/835	120	3500	82	15000	1250	6 5/16	Hang Box	50
			<b>S6735 ▲</b>	CF18DD/E/835	120	3500	82	12000	1250	5 13/16	Box	50
			<b>S8336</b>	CFD18W/4P/841	120	4100	82	15000	1250	6 5/16	Hang Box	50
			<b>S6736 ▲</b>	CF18DD/E/841	120	4100	82	12000	1250	5 13/16	Box	50
<b>26</b>	T4	G24q-3	<b>S8337</b>	CFD26W/4P/827	120	2700	82	15000	1825	6 1/2	Hang Box	50
			<b>S6737 ▲</b>	CF26DD/E/827	120	2700	82	12000	1825	6 1/2	Box	50
			<b>S8338</b>	CFD26W/4P/830	120	3000	82	15000	1825	6 1/2	Hang Box	50
			<b>S6738 ▲</b>	CF26DD/E/830	120	3000	82	12000	1825	6 1/2	Box	50
			<b>S8339</b>	CFD26W/4P/835	120	3500	82	15000	1825	6 1/2	Hang Box	50
			<b>S6739 ▲</b>	CF26DD/E/835	120	3500	82	12000	1825	6 1/2	Box	50
			<b>S8340</b>	CFD26W/4P/841	120	4100	82	15000	1825	6 1/2	Hang Box	50
			<b>S6740 ▲</b>	CF26DD/E/841	120	4100	82	12000	1825	6 1/2	Box	50

### Triple Tube 2-Pin for Magnetic Ballasts


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Carton	Notes
<b>18</b>	T4	GX24d-2	<b>S4367 ▲</b>	CF18DT/827	120	2700	82	12000	1200	4 13/16	Box	50	2
<b>26</b>	T4	GX24d-3	<b>S4368 ▲</b>	CF26DT/827	120	2700	82	12000	1800	5 3/8	Box	50	2

# COMPACT FLUORESCENT




## Triple Tube 4-Pin for Electronic & Dimming Ballasts

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Carton	Notes
13	T4	GX24q-1	<b>S8399</b>	CFT13W/4P/827	120	2700	82	15000	900	4 1/2	Hang Box	50	2
			<b>S4369 ▲</b>	CF13DT/E/827	120	2700	82	12000	900	4 3/16	Box	50	2
			<b>S8396</b>	CFT13W/4P/830	120	3000	82	15000	900	4 1/2	Hang Box	50	2
			<b>S8397</b>	CFT13W/4P/835	120	3500	82	15000	900	4 1/2	Hang Box	50	2
			<b>S4371 ▲</b>	CF13DT/E/835	120	3500	82	12000	900	4 3/16	Box	50	2
			<b>S8398</b>	CFT13W/4P/841	120	4100	82	15000	900	4 1/2	Hang Box	50	2
			<b>S4372 ▲</b>	CF13DT/E/841	120	4100	82	12000	900	4 3/16	Box	50	2
18	T4	GX24q-2	<b>S8341</b>	CFT18W/4P/827	120	2700	82	15000	1200	4 7/8	Hang Box	50	2
			<b>S6741 ▲</b>	CF18DT/E/IN/827	120	2700	82	12000	1200	4 3/8	Box	50	2
			<b>S8342</b>	CFT18W/4P/830	120	3000	82	15000	1200	4 7/8	Hang Box	50	2
			<b>S6742 ▲</b>	CF18DT/E/IN/830	120	3000	82	12000	1200	4 3/8	Box	50	2
			<b>S8343</b>	CFT18W/4P/835	120	3500	82	15000	1200	4 7/8	Hang Box	50	2
			<b>S6743 ▲</b>	CF18DT/E/IN/835	120	3500	82	12000	1200	4 3/8	Box	50	2
			<b>S8344</b>	CFT18W/4P/841	120	4100	82	15000	1200	4 7/8	Hang Box	50	2
<b>S6744 ▲</b>	CF18DT/E/IN/841	120	4100	82	12000	1200	4 3/8	Box	50	2			
26	T4	GX24q-3	<b>S8345</b>	CFT26W/4P/827	120	2700	82	15000	1800	5 11/16	Hang Box	50	2
			<b>S6745 ▲</b>	CF26DT/E/IN/827	120	2700	82	12000	1800	5	Box	50	2
			<b>S8346</b>	CFT26W/4P/830	120	3000	82	15000	1800	5 11/16	Hang Box	50	2
			<b>S6746 ▲</b>	CF26DT/E/IN/830	120	3000	82	12000	1800	5	Box	50	2
			<b>S8347</b>	CFT26W/4P/835	120	3500	82	15000	1800	5 11/16	Hang Box	50	2
			<b>S6747 ▲</b>	CF26DT/E/IN/835	120	3500	82	12000	1800	5	Box	50	2
			<b>S8348</b>	CFT26W/4P/841	120	4100	82	15000	1800	5 11/16	Hang Box	50	2
<b>S6748 ▲</b>	CF26DT/E/IN/841	120	4100	82	12000	1800	5	Box	50	2			
32	T4	GX24q-3	<b>S8349</b>	CFT32W/4P/827	120	2700	82	15000	2400	5 3/16	Hang Box	50	2
			<b>S6749 ▲</b>	CF32DT/E/IN/827	120	2700	82	12000	2400	5 5/8	Box	50	2
			<b>S8350</b>	CFT32W/4P/830	120	3000	82	15000	2400	5 3/16	Hang Box	50	2
			<b>S6750 ▲</b>	CF32DT/E/IN/830	120	3000	82	12000	2400	5 5/8	Box	50	2
			<b>S8351</b>	CFT32W/4P/835	120	3500	82	15000	2400	5 3/16	Hang Box	50	2
			<b>S6751 ▲</b>	CF32DT/E/IN/835	120	3500	82	12000	2400	5 5/8	Box	50	2
			<b>S8352</b>	CFT32W/4P/841	120	4100	82	15000	2400	5 3/16	Hang Box	50	2
<b>S6752 ▲</b>	CF32DT/E/IN/841	120	4100	82	12000	2400	5 5/8	Box	50	2			



Triple Tube  
GX24q-4



Flat Tube  
2G10



Long Twin  
Tube 2G11

### Triple Tube 4-Pin for Electronic & Dimming Ballasts (continued)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Carton	Notes
42	T4	GX24q-4	<b>S8353</b>	CFT42W/4P/827	120	2700	82	15000	3200	6 ¾	Hang Box	50	2
			<b>S6753 ▲</b>	CF42DT/E/IN/827	120	2700	82	12000	3200	6 ½	Box	50	2
			<b>S8354</b>	CFT42W/4P/830	120	3000	82	15000	3200	6 ¾	Hang Box	50	2
			<b>S6754 ▲</b>	CF42DT/E/IN/830	120	3000	82	12000	3200	6 ½	Box	50	2
			<b>S8355</b>	CFT42W/4P/835	120	3500	82	15000	3200	6 ¾	Hang Box	50	2
			<b>S6755 ▲</b>	CF42DT/E/IN/835	120	3500	82	12000	3200	6 ½	Box	50	2
			<b>S8356</b>	CFT42W/4P/841	120	4100	82	15000	3200	6 ¾	Hang Box	50	2
			<b>S6756 ▲</b>	CF42DT/E/IN/841	120	4100	82	12000	3200	6 ½	Box	50	2

### Long Twin Tube 4-Pin for Electronic Ballasts

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Carton	Notes
18	T5	2G11	<b>S8657</b>	FT18HL/830/ENV	120	3000	82	12000	1300	9	Box	10	
			<b>S6757 ▲</b>	FT18DL/830	120	3000	82	12000	1250	9	Box	10	
			<b>S8658</b>	FT18HL/835/ENV	120	3500	82	12000	1300	9	Box	10	
			<b>S6758 ▲</b>	FT18DL/835	120	3500	82	12000	1250	9	Box	10	
			<b>S2965 ▲</b>	FT18DL/835/RS	120	3500	82	20000	1250	10 ½	Box	10	
			<b>S8659</b>	FT18HL/841/ENV	120	4100	82	12000	1300	9	Box	10	
			<b>S6759 ▲</b>	FT18DL/841	120	4100	82	12000	1250	9	Box	10	
			<b>S2966 ▲</b>	FT18DL/841/RS	120	4100	82	20000	1250	10 ½	Box	10	
24	T5	2G11	<b>S8660</b>	FT24HL/830/ENV	120	3000	82	12000	1800	12 1/16	Box	10	
			<b>S6760 ▲</b>	FT24DL/830	120	3000	82	12000	1800	12 7/8	Box	10	1
			<b>S8661</b>	FT24HL/835/ENV	120	3500	82	12000	1800	12 1/16	Box	10	
			<b>S6761 ▲</b>	FT24DL/835	120	3500	82	12000	1800	12 7/8	Box	10	1
			<b>S8662</b>	FT24HL/841/ENV	120	4100	82	12000	1800	12 1/16	Box	10	
			<b>S6762 ▲</b>	FT24DL/841	120	4100	82	12000	1800	12 7/8	Box	10	1
36	T5	2G11	<b>S8663</b>	FT36HL/830/ENV	120	3000	82	12000	2800	16 ½	Box	10	
			<b>S6763 ▲</b>	FT36DL/830	120	3000	82	12000	2900	16 5/8	Box	10	1
			<b>S8664</b>	FT36HL/835/ENV	120	3500	82	12000	2800	16 ½	Box	10	
			<b>S6764 ▲</b>	FT36DL/835	120	3500	82	12000	2900	16 5/8	Box	10	1
			<b>S8665</b>	FT36HL/841/ENV	120	4100	82	12000	2800	16 ½	Box	10	
			<b>S6765 ▲</b>	FT36DL/841	120	4100	82	12000	2900	16 5/8	Box	10	1




# COMPACT FLUORESCENT



Long Twin  
Tube 2G11

## Long Twin Tube 4-Pin for Electronic Ballasts (continued)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Carton	Notes
<b>40</b>	T5	2G11	<b>S8666</b>	FT40HL/830/RS/ENV	120	3000	82	20000	3500	22 ½	Box	10	
			<b>S6766 ▲</b>	FT40DL/830/RS	120	3000	82	20000	3150	22 ½	Box	10	
			<b>S8667</b>	FT40HL/835/RS/ENV	120	3500	82	20000	3500	22 ½	Box	10	
			<b>S6767 ▲</b>	FT40DL/835/RS	120	3500	82	20000	3150	22 ½	Box	10	
			<b>S8668</b>	FT40HL/841/RS/ENV	120	4100	82	20000	3500	22 ½	Box	10	
			<b>S6768 ▲</b>	FT40DL/841/RS	120	4100	82	20000	3150	22 ½	Box	10	
<b>50</b>	T5	2G11	<b>S2967 ▲</b>	PLL50W/30/RS	120	3000	82	14000	4300	22 ½	Box	25	
			<b>S2968 ▲</b>	PLL50W/35/RS	120	3500	82	14000	4300	22 ½	Box	25	
			<b>S2969 ▲</b>	PLL50W/41/RS	120	4100	82	14000	4300	22 ½	Box	25	
<b>55</b>	T5	2G11	<b>S8669</b>	FT55HL/830/ENV	120	3000	82	12000	4700	21 ⅝	Box	10	
			<b>S6769 ▲</b>	FT55DL/830	120	3000	82	12000	4800	21 ⅝	Box	10	
			<b>S8670</b>	FT55HL/835/ENV	120	3500	82	12000	4700	21 ⅝	Box	10	
			<b>S6770 ▲</b>	FT55DL/835	120	3500	82	12000	4800	21 ⅝	Box	10	
			<b>S8671</b>	FT55HL/841/ENV	120	4100	82	12000	4700	21 ⅝	Box	10	
<b>S6771 ▲</b>	FT55DL/841	120	4100	82	12000	4800	21 ⅝	Box	10				



## Spiral 4-Pin for Electronic Ballasts

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Pkg. Type	Carton
13	T3	G24q-1	<b>S4438</b>	60W	PLS13/27K/SPIRAL	120	2700	82	10000	850	3 ¾	Box	24
18	T4	GX24q-2	<b>S4440</b>	75W	PLS18/27K/SPIRAL	120	2700	82	10000	1100	4 ¼	Box	24
26	T4	GX24q-3	<b>S4439</b>	100W	PLS26/27K/SPIRAL	120	2700	82	10000	1700	4 ⅝	Box	24

### General CFL Notes

- = Product by a manufacturer other than Satco
- ▲ = Product by one of the Primary lamp manufacturers
- † = To be discontinued when inventory is depleted due to legislation requirements.

### CFL Notes

- 1 These lamps may also be operated on rapid start circuits. On rapid start circuits the 24 watt lamp operates at 27 watts and the 36 watt lamp operated at 39 watts. Rated lamp life is unchanged.
- 2 This 4-pin CF lamp has an internal end-of-life mechanism (EOL) that shuts down the lamp preventing abnormal end-of life failure modes. This lamp was designed for use with high frequency ballasts that do not have their own end-of-life (lamp) sensing circuits, but it is also compatible with high frequency ballasts that have their own end-of-life.

Rule of thumb for compact fluorescent lamps: divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.

Caution: unless otherwise stated, self ballasted CF lamps cannot be used on dimming circuits, emergency exit fixtures or lights, electronic timers, photocells or lighted switches. In outdoor applications, use only in enclosed fixtures to avoid exposure to weather. Use only on 120V, 60 Hz circuits.

ENV and ECO fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local and state regulations. For more information, please visit [lamprecycle.org](http://lamprecycle.org).

Minimum starting temperature for 2-pin CF lamps: CF5: -22 degrees F; CF7: -4 degrees F; CF9: 14 degrees F; CF13DS: 14

degrees F; CF13DD: -4 degrees F; CF18DD: 5 degrees F; CF18DT: -4 degrees F; CF26: 14 degrees F.

There is a NEMA supported, industry issue where T2, T4, and T5 fluorescent and compact fluorescent lamps operated on high frequency ballasts may experience an abnormal end-of-life phenomenon. This end-of-life phenomenon can result in one or both of the following: 1. Bulb wall cracking near the lamp base. 2. The lamp can overheat in the base area and possibly melt the base and socket. NEMA recommends that high frequency compact fluorescent ballasts have an end-of-life shutdown circuit which will safely and reliably shut down the system in the rare event of an abnormal end-of-life failure mode described above. The final requirements of this system are yet to be defined by ANSI. For additional information refer to NEMA papers on their website at [NEMA.org](http://NEMA.org).

# HALOGEN LAMPS





# Popular for good reason.

Halogen lamps come in more sizes, shapes, and base variations than most other technologies, and with good reason – brilliant white light, great color temperature, and color rendering properties, long life, and superior lumen maintenance combine to make them very popular. Satco stocks virtually every variation there is. Our wide inventory allows you to get the types you need, whether a specialty size or an incandescent A19 replacement, that meets government regulations. When it comes to Halogen lamps, we can confidently say “Yes, we have that.”


## Halogen lamp features:

- Available from 5 to 1500 Watts
- From 6 to 240 Volt variations
- All industry standard sizes and bases
- Fully dimmable
- Environmentally friendly – Mercury free
- Energy efficient
- Our Halogen Excel line saves up to 30% in energy costs over traditional incandescent lamps
- Halogen/Xenon technology for enhanced performance in our Halogen Excel™ line
- Excellent color rendering
- High lumen output



Nuvo Lighting's Lynne five light vanity in Polished Nickel with Frosted Glass. Nuvo item number 60-5178. See the [www.nuvolighting.com](http://www.nuvolighting.com) website.






## Bi Pin Lamps

### Bi Pin Lamps 12 and 24 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
<b>5</b>	T3	G4	<b>S3179</b>	5T3/CL	12	Clear	1 ¼	C-6	50	2000	Box	48	
<b>10</b>	T3	G4	<b>S3171</b>	10T3/CL	12	Clear	1 ¼	C-6	120	2000	Box	48	
			<b>S3459</b>	10T3/CL	12	Clear	1 ¼	C-6	120	2000	CD/1	12	
			<b>S1908</b>	10T3/F	12	Frost	1 ¼	C-6	108	2000	Box	48	
<b>20</b>	T3	G4	<b>S3120</b>	20T3/CL	12	Clear	1 ¼	C-6	300	2000	Box	48	
			<b>S3468</b>	20T3/CL	12	Clear	1 ¼	C-6	300	2000	CD/1	12	
			<b>S3420</b>	20T3/CL/2PK	12	Clear	1 ¼	C-6	300	2000	CD/2	12	
			<b>S1909</b>	20T3/F	12	Frost	1 ¼	C-6	270	2000	Box	48	
			<b>S1986</b>	20T3/CL/24V	24	Clear	1 ¼	CC-6	260	2000	Box	48	
		GY6.35	<b>S4197</b>	20T3/CL	12	Clear	1 ¼	C-6	300	2000	Box	48	
<b>35</b>	T4	GY6.35	<b>S3160</b>	35T4/CL	12	Clear	1 ⅞	C-6	595	2000	Box	48	
			<b>S3469</b>	35T4/CL	12	Clear	1 ⅞	C-6	595	2000	CD/1	12	
			<b>S1910</b>	35T4/F	12	Frost	1 ⅞	C-6	536	2000	Box	48	
<b>50</b>	T4	GY6.35	<b>S3121</b>	50T4/CL	12	Clear	1 ⅞	C-6	900	2000	Box	48	
			<b>S3470</b>	50T4/CL	12	Clear	1 ⅞	C-6	900	2000	CD/1	12	
			<b>S3421</b>	50T4/CL/2PK	12	Clear	1 ⅞	C-6	900	2000	CD/2	12	
			<b>S1911</b>	50T4/F	12	Frost	1 ⅞	C-6	810	2000	Box	48	
			<b>S1987</b>	50T4/CL/24V	24	Clear	1 ⅞	CC-6	900	2000	Box	48	
<b>75</b>	T4	GY6.35	<b>S3156</b>	75T4/CL	12	Clear	1 ⅞	C-6	1350	2000	Box	48	
			<b>S3471</b>	75T4/CL	12	Clear	1 ⅞	C-6	1350	2000	CD/1	12	
			<b>S1912</b>	75T4/F	12	Frost	1 ⅞	C-6	1290	2000	Box	48	

### Enclosed Bi Pin Lamps 12 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
<b>20</b>	G14	GU5.3/GX5.3	<b>S3187</b>	20JCGV-G14/BALL	12	White	2 ¾	C-6	240	2000	Box	250/25	
<b>35</b>	G14	GU5.3/GX5.3	<b>S3188</b>	35JCGV-G14/BALL	12	White	2 ¾	C-6	450	2000	Box	250/25	
<b>50</b>	G14	GU5.3/GX5.3	<b>S3189</b>	50JCGV-G14/BALL	12	White	2 ¾	C-6	720	2000	Box	200/25	



T4 G8  
Wide Pin



T4  
GY6.35



T3.5  
G6.35c


## Bi Pin Lamps 120 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
<b>20</b>	T4	G8	<b>S4610</b>	20T4/CL/G8	120	Clear	1 13/16	CC-2V	180	2000	Box	48	
			<b>S3539</b>	20T4/CL/G8	120	Clear	1 13/16	CC-2V	180	2000	CD/1	240/12	
<b>25</b>	T4	GY6.35	<b>S3197</b>	25T4/CL	120	Clear	1 13/16	CC-2V	210	2000	Box	48	
		G8	<b>S4611</b>	25T4/CL/G8	120	Clear	1 13/16	CC-2V	210	2000	Box	48	
<b>35</b>	T4	GY6.35	<b>S3164</b>	35T4/CL	120	Clear	1 13/16	CC-2V	380	2000	Box	48	
			<b>S3418</b>	35T4/CL	120	Clear	1 13/16	CC-2V	380	2000	CD/1	12	
		G8	<b>S4620</b>	35T4/CL/G8	120	Clear	1 13/16	CC-2V	380	2000	Box	48	
			<b>S3540</b>	35T4/CL/G8	120	Clear	1 13/16	CC-2V	380	2000	CD/1	12	
<b>50</b>	T4	GY6.35	<b>S3167</b>	50T4/CL	120	Clear	1 13/16	CC-2V	750	2000	Box	48	
			<b>S3427</b>	50T4/CL	120	Clear	1 13/16	CC-2V	750	2000	CD/1	12	
		G8	<b>S4612</b>	50T4/CL/G8	120	Clear	1 13/16	CC-2V	750	2000	Box	48	
			<b>S3541</b>	50T4/CL/G8	120	Clear	1 13/16	CC-2V	750	2000	CD/1	12	
<b>75</b>	T4	GY6.35	<b>S3168</b>	75T4/CL	120	Clear	2 3/8	CC-2V	750	2000	Box	48	
			<b>S3428</b>	75T4/CL	120	Clear	2 3/8	CC-2V	1250	2000	CD/1	12	
		G8	<b>S4613</b>	75T4/CL/G8	120	Clear	2 1/4	CC-8	1250	2000	Box	48	
			<b>S3542</b>	75T4/CL/G8	120	Clear	2 1/4	CC-8	1250	2000	CD/1	12	
<b>100</b>	T4	GY6.35	<b>S1924</b>	100T4/CL	120	Clear	2 3/8	CC-2V	1700	2000	Box	48	
			<b>S3419</b>	100T4/CL	120	Clear	2 3/8	CC-2V	1700	2000	CD/1	12	
		G8	<b>S4622</b>	100T4/CL/G8	120	Clear	2 1/4	CC-8	1700	2000	Box	48	
			<b>S3543</b>	100T4/CL/G8	120	Clear	2 1/4	CC-8	1700	2000	CD/1	12	

## Bi Pin Marine Lamps 12 and 24 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
<b>55</b>	T3.5	GY6.35	<b>S7183</b>	JCD/12V/55W/DX	12	Clear	1 3/4	C-6	100	Box	500/10	ACR6001
			<b>S7184</b>	JCD/24V/55W/DX	24	Clear	1 13/16	C-6	100	Box	500/10	ACR6003





## Double Loop G9 120 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton	Notes
20	T4	G9	<b>S4614</b>	20T4/G9/CL	120	Clear	1 9/16	CC-2V	200	2000	Box	48	
			<b>S4639</b>	20T4/G9/FR	120	Frost	1 9/16	CC-2V	200	2000	Box	48	
25	T4	G9	<b>S4615</b>	25T4/G9/CL	120	Clear	1 9/16	CC-2V	260	2000	Box	48	
35	T4	G9	<b>S4621</b>	35T4/G9/CL	120	Clear	1 9/16	CC-2V	400	2000	Box	48	
			<b>S3544</b>	35T4/G9/CL	120	Clear	1 9/16	CC-2V	400	2000	CD/1	12	
40	T4	G9	<b>S4641</b>	40T4/G9/CL	120	Clear	1 9/16	CC-2V	500	2000	Box	48	
			<b>S4647</b>	40T4/G9/FR	120	Frost	1 9/16	CC-2V	450	2000	Box	48	
50	T4	G9	<b>S4616</b>	50T4/G9/CL	120	Clear	1 9/16	CC-2V	750	2000	Box	48	
			<b>S3545</b>	50T4/G9/CL	120	Clear	1 9/16	CC-2V	750	2000	CD/1	12	
60	T4	G9	<b>S4648</b>	60T4/G9/CL	120	Clear	1 5/8	CC-2V	820	2000	Box	48	
			<b>S4649</b>	60T4/G9/FR	120	Frost	1 5/8	CC-2V	738	2000	Box	48	
75	T4	G9	<b>S4617</b>	75T4/G9/CL	120	Clear	1 5/8	CC-8	1250	2000	Box	48	
			<b>S3546</b>	75T4/G9/CL	120	Clear	1 5/8	CC-8	1250	2000	CD/1	12	
100	T4	G9	<b>S4642</b>	100T4/G9/CL	120	Clear	1 11/16	CC-8	1700	2000	Box	48	
			<b>S3547</b>	100T4/G9/CL	120	Clear	1 11/16	CC-8	1700	2000	CD/1	12	

## E11 – DC Bay.

Single Ended - E11 MiniCan - E12 Cand - E14 Euro - BA15d DC Bay.


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton	Notes
20	T3	E11	<b>S4486</b>	KX20CL/3M/MC	120	Clear	2 5/16	CC-8	200	3000	Box	10	1
			<b>S4489</b>	KX20FR/3M/MC	120	Frost	2 5/16	CC-8	200	3000	Box	10	1
		E12	<b>S4480</b>	KX20CL/3M/E12	120	Clear	2 7/16	CC-8	200	3000	Box	10	1
			<b>S4483</b>	KX20FR/3M/E12	120	Frost	2 7/16	CC-8	200	3000	Box	10	1
		DC Bay.	<b>S4492</b>	KX20CL/3M/DC	120	Clear	2 1/4	CC-8	200	3000	Box	10	1
			<b>S4495</b>	KX20FR/3M/DC	120	Clear	2 1/4	CC-8	200	3000	Box	10	1



T4  
E11



T4  
DC Bay.



T3  
E11



T3  
E12




T3  
DC Bay.



T4 Long  
DC Bay.

### Single Ended - E11 MiniCan - E12 Cand - E14 Euro - BA15d DC Bay. (continued)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton	Notes
<b>35</b>	T4	E11	<b>S3165</b>	35Q/CL/MC	120	Clear	2 1/16	CC-2V	380	2000	Box	12	
			<b>S1913</b>	35Q/FR/MC	120	Frost	2 1/16	CC-2V	342	2000	Box	12	
	DC Bay.	<b>S1979</b>	35Q/CL/DC	120	Clear	2 1/16	CC-2V	380	2000	Box	12		
		<b>S1980</b>	35Q/FR/DC	120	Frost	2 1/16	CC-2V	342	2000	Box	12		
<b>40</b>	T3	E11	<b>S4487</b>	KX40CL/3M/MC	120	Clear	2 5/16	CC-8	560	3000	Box	10	1
			<b>S4490</b>	KX40FR/3M/MC	120	Frost	2 5/16	CC-8	560	3000	Box	10	1
	E12	<b>S4481</b>	KX40CL/3M/E12	120	Clear	2 7/16	CC-8	560	3000	Box	10	1	
		<b>S4484</b>	KX40FR/3M/E12	120	Frost	2 7/16	CC-8	560	3000	Box	10	1	
	DC Bay.	<b>S4493</b>	KX40CL/3M/DC	120	Clear	2 1/4	CC-8	560	3000	Box	10	1	
		<b>S4496</b>	KX40FR/3M/DC	120	Frost	2 1/4	CC-8	560	3000	Box	10	1	
<b>50</b>	T4	E11	<b>S3162</b>	50Q/CL/MC	120	Clear	2 1/16	CC-2V	750	2000	Box	12	
			<b>S3198</b>	50Q/CL/MC	130	Clear	2 1/16	CC-2V	750	2000	Box	12	
	DC Bay.	<b>S1914</b>	50Q/F/MC	120	Frost	2 1/16	CC-2V	675	2000	Box	12		
		<b>S1981</b>	50Q/CL/DC	120	Clear	2 1/16	CC-2V	750	2000	Box	12		
	E11	<b>S1982</b>	50Q/F/DC	120	Frost	2 1/16	CC-2V	675	2000	Box	12		
		<b>S4488</b>	KX60CL/3M/MC	120	Clear	2 5/16	CC-8	960	3000	Box	10	1	
<b>60</b>	T3	E11	<b>S4491</b>	KX60FR/3M/MC	120	Frost	2 5/16	CC-8	950	3000	Box	10	1
			<b>S4482</b>	KX60CL/3M/E12	120	Clear	2 7/16	CC-8	960	3000	Box	10	1
	E12	<b>S4485</b>	KX60FR/3M/E12	120	Frost	2 7/16	CC-8	950	3000	Box	10	1	
		<b>S4494</b>	KX60CL/3M/DC	120	Clear	2 1/4	CC-8	960	3000	Box	10	1	
	DC Bay.	<b>S4497</b>	KX60FR/3M/DC	120	Frost	2 1/4	CC-8	950	3000	Box	10	1	
		<b>S3157</b>	75Q/CL/MC	120	Clear	2 11/16	CC-8	1250	2000	Box	12		
<b>75</b>	T4	E11	<b>S3484</b>	75Q/CL/MC	120	Clear	2 11/16	CC-8	1250	2000	CD/1	12	
			<b>S1915</b>	75Q/F/MC	120	Frost	2 11/16	CC-8	1125	2000	Box	12	
	DC Bay.	<b>S3159</b>	75Q/CL/DC	120	Clear	2 3/8	CC-8	1250	2000	Box	12		
		<b>S3432</b>	75Q/CL/DC	120	Clear	2 3/8	CC-8	1250	2000	CD/1	12		
	E11	<b>S1919</b>	75Q/F/DC	120	Frost	2 3/8	CC-8	1125	2000	Box	12		



## Single Ended - E11 MiniCan - E12 Cand - E14 Euro - BA15d DC Bay. (continued)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton	Notes	
<b>100</b>	T4	E11	<b>S3107</b>	100Q/CL/MC	120	Clear	2 1/16	CC-8	1700	2000	Box	12		
			<b>S3485</b>	100Q/CL/MC	120	Clear	2 1/16	CC-8	1700	2000	CD/1	12		
			<b>S1916</b>	100Q/FR/MC	120	Frost	2 1/16	CC-8	1530	2000	Box	12		
	E14	<b>S3132</b>	100Q/CL/E14	120	Clear	2 1/16	CC-8	1700	2000	Box	12			
		<b>S3491</b>	100Q/CL/E14	120	Clear	2 1/16	CC-8	1700	2000	CD/1	12			
		<b>S3147</b>	100Q/CL/DC	120	Clear	2 3/8	CC-8	1700	2000	Box	12			
	DC Bay.	<b>S3488</b>	100Q/CL/DC	120	Clear	2 3/8	CC-8	1700	2000	CD/1	12			
		<b>S1920</b>	100Q/F/DC	120	Frost	2 3/8	CC-8	1530	2000	Box	12			
		<b>S4361</b>	100Q/CL/DC	120	Clear	3 3/8	CC-2V	1600	2000	Box	10	2		
	<b>150</b>	T4.5	E11	<b>S3108</b>	150Q/CL/MC	120	Clear	2 1/16	CC-8	2700	2000	Box	12	
<b>S3486</b>				150Q/CL/MC	120	Clear	2 1/16	CC-8	2700	2000	CD/1	12		
<b>S1917</b>				150Q/F/MC	120	Frost	2 1/16	CC-8	2430	2000	Box	12		
E14		<b>S3133</b>	150Q/CL/E14	120	Clear	3	CC-8	2700	2000	Box	12			
		<b>S3492</b>	150Q/CL/E14	120	Clear	3	CC-8	2700	2000	CD/1	12			
		<b>S3122</b>	150Q/CL/DC	120	Clear	2 1/16	CC-8	2700	2000	Box	12			
DC Bay.		<b>S3489</b>	150Q/CL/DC	120	Clear	2 1/16	CC-8	2700	2000	CD/1	12			
		<b>S1921</b>	150Q/F/DC	120	Frost	2 1/16	CC-8	2430	2000	Box	12			
		<b>250</b>	T4.5	E11	<b>S3109</b>	250Q/CL/MC	120	Clear	3 1/8	CC-8	4200	2000	Box	12
<b>S3487</b>					250Q/CL/MC	120	Clear	3 1/8	CC-8	4200	2000	CD/1	12	
<b>S1918</b>	250Q/F/MC				120	Frost	3 1/8	CC-8	3780	2000	Box	12		
E14	<b>S3134</b>		250Q/CL/E14	120	Clear	3 5/8	CC-8	4200	2000	Box	12			
	<b>S3493</b>		250Q/CL/E14	120	Clear	3 5/8	CC-8	4350	2000	CD/1	12			
	<b>S3123</b>		250Q/CL/DC	120	Clear	2 13/16	CC-8	4200	2000	Box	12			
DC Bay.	<b>S3490</b>	250Q/CL/DC	120	Clear	2 13/16	CC-8	4200	2000	CD/1	12				
	<b>S1922</b>	250Q/F/DC	120	Frost	2 13/16	CC-8	3780	2000	Box	12				
	<b>500</b>	T4	E11	<b>S3181</b>	500Q/CL	120	Clear	3 7/16	CC-8	8500	2000	Box	12	
<b>S3182</b>				500Q/F	120	Frost	3 7/16	CC-8	7650	2000	Box	12		
<b>S4363 ▲</b>				500Q/MC/EYX	120	Frost	3 3/4	CC-8	10100	2000	Box	12	3	
DC Bay.		<b>S1983</b>	500Q/CL	120	Clear	3 3/4	CC-8	8500	2000	Box	12			
		<b>S1984</b>	500Q/F	120	Frost	3 3/4	CC-8	7650	2000	Box	12			



T2 3/4  
Mini Bay.



T2 1/2  
P14.5s



T3  
R7s


## Specialty Single Ended Lamps

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton	Notes
5	T2 3/4	BA9s	<b>VJ020 ▲</b>	64111	12	Clear	1 ¼	C-6	50	240	Sleeve	10	10
55	T2 1/2	P14.5s	<b>S7968</b>	55W/12V H1	120	Clear	2 7/16	C-8	1000	350	Sleeve	10	11

## Linear Double Ended Lamps

### Double Ended J-Style

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/ Inner Carton	Notes
<b>75</b>	T3	R7s	<b>S3199</b>	75T3Q/CL/78MM	120	Clear	3 ½	C-8	1050	1500	Box	12	
			<b>S3183</b>	75T3Q/CL/78MM	130	Clear	3 ½	C-8	1050	1500	Box	12	
<b>100</b>	T3	R7s	<b>S3146</b>	100T3Q/CL/78MM	120	Clear	3 ½	C-8	1650	1500	Box	12	
			<b>S3480</b>	100T3Q/CL/78MM	120	Clear	3 ½	C-8	1650	1500	CD/1	12	
			<b>S3422</b>	100T3Q/CL/78MM/2PK	120	Clear	3 ½	C-8	1650	1500	CD/2	12	
			<b>S3166</b>	100T3Q/CL/118MM	120	Clear	4 11/16	C-8	1650	1500	Box	12	
			<b>S3431</b>	100T3Q/CL/118MM	120	Clear	4 11/16	C-8	1650	1500	CD/1	12	
<b>150</b>	T3	R7s	<b>S3135</b>	150T3Q/CL/S/78MM	120	Clear	3 ½	C-8	2400	1500	Box	12	
			<b>S3481</b>	150T3Q/CL/S/78MM	120	Clear	3 ½	C-8	2400	1500	CD/1	12	2
			<b>S3423</b>	150T3Q/CL/S/78MM/2PK	120	Clear	3 ½	C-8	2400	1500	CD/2	12	
			<b>S3142</b>	150T3Q/CL/L/118MM	120	Clear	4 11/16	C-8	2400	1500	Box	12	
			<b>S3494</b>	150T3Q/CL/L/118MM	120	Clear	4 11/16	C-8	2400	1500	CD/1	12	
<b>200</b>	T3	R7s	<b>S3145</b>	200T3Q/CL/78MM	120	Clear	3 ½	C-8	3400	1500	Box	12	
			<b>S3482</b>	200T3Q/CL/78MM	120	Clear	3 ½	C-8	3400	1500	CD/1	12	
			<b>S3136</b>	200T3Q/CL/78MM	120	Clear	4 11/16	C-8	3400	1500	Box	12	
			<b>S3495</b>	200T3Q/CL/78MM	120	Clear	4 11/16	C-8	3400	1500	CD/1	12	
<b>250</b>	T3	R7s	<b>S3184</b>	250T3Q/CL/78MM	120	Clear	3 ½	C-8	4500	1500	Box	12	
			<b>S3426</b>	250T3Q/CL/78MM	120	Clear	3 ½	C-8	4500	1500	CD/1	12	




## Double Ended J-Style (continued)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
300	T3	R7s	<b>S3104</b>	300T3Q/CL	120	Clear	4 11/16	C-8	5300	1500	Box	12	
			<b>S3496</b>	300T3Q/CL	120	Clear	4 11/16	C-8	5300	1500	CD/1	12	
			<b>S3430</b>	300T3Q/CL/2PK	120	Clear	4 11/16	C-8	5300	1500	CD/2	12	
			<b>S3410</b>	300T3Q/CL/3PK	120	Clear	4 11/16	C-8	5300	1500	CD/3	12	
			<b>S1925</b>	300T3Q/CL	130	Clear	4 11/16	C-8	5300	1500	Box	12	
	Flat Blade	<b>S3180</b>	300T3Q/CL	120	Clear	5 13/16	C-8	5300	1500	Box	12		
		<b>S3429</b>	300T3Q/CL	120	Clear	5 13/16	C-8	5300	1500	CD/1	12		
		<b>S3105</b>	500T3Q/CL	120	Clear	4 11/16	C-8	9500	1500	Box	12		
500	T3	R7s	<b>S3497</b>	500T3Q/CL	120	Clear	4 11/16	C-8	9500	1500	CD/1	12	2
			<b>S3433</b>	500T3Q/CL/2PK	120	Clear	4 11/16	C-8	9500	1500	CD/2	12	
			<b>S3411</b>	500T3Q/CL/3PK	120	Clear	4 11/16	C-8	9500	1500	CD/3	12	
			<b>S1926</b>	500T3Q/CL/130V	130	Clear	4 11/16	C-8	9500	1500	Box	12	
			<b>S2228</b>	500T3Q/CL/RS/130V	130	Clear	4 11/16	C-8	9500	1500	Box	12	
			<b>S3185</b>	500T3Q/CL/240V	240	Clear	4 11/16	C-8	9000	1500	Box	12	
			<b>S1923</b>	500T3Q/CL	120	Clear	5 13/16	C-8	9500	1500	Box	12	
	<b>S2456</b>	Q900T3/CL/HIR/277V	277	Clear	10 1/16	C-8	31000	2000	Box	6			
1000	T3	R7s	<b>S4198</b>	1000T3Q/CL	120	Clear	10 1/16	C-8	18000	1500	Box	480/12	
			<b>S4199</b>	1000T3Q/CL/240V	240	Clear	10 1/16	C-8	18000	1500	Box	480/12	
1500	T3	R7s	<b>S3106</b>	1500T3Q/CL/240V	240	Clear	10 1/16	C-8	30000	1500	Box	480/12	
			<b>S4169</b>	1500T3Q/CL	120	Clear	10 1/16	C-8	32000	1500	Box	480/12	

## MR8, MR11, MR16 Lamps

### MR8 Bi Pin Base 12 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
10	MR8	GU4	<b>S4646</b>	10MR8/NSP	NSP 9	—	12	Y	N	—	2000	C-6	1 1/4	Box	12
			<b>S4645</b>	10MR8/NFL	NFL 23	—	12	Y	N	—	2000	C-6	1 1/4	Box	12




## MR11 Bi Pin Base 6, 12 & 24 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
5	MR11	GZ4	<b>S4628</b>	5MR11/NFL/6V	NFL 30	–	6	Y	N	1000	2000	C-6	1 ¼	Box	12
			<b>S3194</b>	5MR11/NSP	NSP 9	–	12	N	N	130	2000	C-6	1 ¼	Box	12
10	MR11	GZ4	<b>S4629</b>	10MR11/NFL/6V	NFL 30	–	6	Y	N	150	2000	C-6	1 ¼	Box	12
			<b>S3195</b>	10MR11/SP	SP 12	–	12	N	N	380	2000	C-6	1 ¼	Box	12
			<b>S3444</b>	10MR11/FL/30/12V	FL30	–	12	N	N	150	2000	C-6	1 ¼	CD/1	12
20	MR11	GZ4	<b>S3150</b>	20MR11/NSP	NSP 9	FTB	12	N	N	1500	2000	C-6	1 ¼	Box	12
			<b>S3152</b>	20MR11/SP	SP 12	FTC	12	N	N	1000	2000	C-6	1 ¼	Box	12
			<b>S3464</b>	20MR11/SP	SP 12	FTC	12	N	Y	1000	2000	C-6	1 ¼	CD/1	12
			<b>S1990</b>	20MR11/SP/C/24V	SP 12	FTC/C/24	24	Y	Y	1750	2000	C-6	1 ¼	Box	12
			<b>S3154</b>	20MR11/NFL	NFL 24	FTD	12	N	N	500	2000	C-6	1 ¼	Box	12
			<b>S3465</b>	20MR11/NFL	NFL 24	FTD	12	N	Y	500	2000	C-6	1 ¼	CD/1	12
			<b>S3424</b>	20MR11/NFL/2PK	NFL 24	FTD	12	N	Y	700	2000	C-6	1 ¼	CD/2	12
			<b>S1950</b>	20MR11/NFL/C	NFL 24	FTD/C	12	Y	N	450	2000	C-6	1 ¼	Box	12
			<i>SOFT RAY</i> <b>S4124</b>	20MR11/FL/FR/C	FL 36	–	12	Y	Y	450	2000	C-6	1 ¼	Box	12
			35	MR11	GZ4	<b>S3151</b>	35MR11/NSP	NSP 9	FTE	12	N	N	2500	2000	C-6
<b>S1991</b>	35MR11/NSP/C/24V	NSP 9				FTE/C/24	24	Y	Y	4500	2000	C-6	1 ¼	Box	12
<b>S3153</b>	35MR11/SP	SP 12				FTF	12	N	N	2500	2000	C-6	1 ¼	Box	12
<b>S3466</b>	35MR11/SP	SP 12				FTF	12	N	Y	2500	2000	C-6	1 ¼	CD/1	12
<b>S3155</b>	35MR11/NFL	NFL 24				FTH	12	N	N	800	2000	C-6	1 ¼	Box	12
<b>S3467</b>	35MR11/NFL	NFL 24				FTH	12	N	Y	800	2000	C-6	1 ¼	CD/1	12
<b>S3425</b>	35MR11/NFL/2PK	NFL 24				FTH	12	N	Y	1550	2000	C-6	1 ¼	CD/2	12
<b>S1951</b>	35MR11/NFL/C	NFL 24				FTH/C	12	Y	N	720	2000	C-6	1 ¼	Box	12
<b>S1989</b>	35MR11/NFL/C/24V	NFL 24				FTH/C/24	24	Y	Y	1250	2000	C-6	1 ¼	Box	12
<i>SOFT RAY</i> <b>S4125</b>	35MR11/FL/FR/C	FL 36				–	12	Y	Y	720	2000	C-6	1 ¼	Box	12


## MR11 GU10 Base Frosted Back with Lens 120 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
20	MR11	GU10	<b>S4195</b>	20MR11/FL	FL 30	FTD	120	N	N	110	1000	C-6	1 ¼	Box	12
35	MR11	GU10	<b>S4196</b>	35MR11/FL	FL 24	FTH	120	N	N	300	1000	C-6	1 ¼	Box	12





MR11  
DC Bay.





MR16  
GU5.3/  
GX5.3

## MR11 DC Bay. Base 12 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
20	MR11	DC Bay.	<b>S1954</b>	20MR11/SP/DC	SP 12	FST/C	12	Y	Y	1750	2000	C-6	1 3/8	Box	12
			<b>S1952</b>	20MR11/NFL/DC	NFL 24	FSV/C	12	Y	Y	450	2000	C-6	1 3/8	Box	12
35	MR11	DC Bay.	<b>S1955</b>	35MR11/SP/DC	SP 12	GDY/C	12	Y	Y	2550	2000	C-6	1 3/8	Box	12
			<b>S1953</b>	35MR11/NFL/DC	NFL 24	GDZ/C	12	Y	Y	720	2000	C-6	1 3/8	Box	12

## MR16 Bi Pin 12 & 24 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton	Notes
10	MR16	GU5.3/GX5.3	<b>S4185</b>	10MR16/NFL	NFL 38	—	12	N	Y	300	2000	C-8	1 3/8	CD/1	12	
20	MR16	GU5.3/GX5.3	<b>S1957</b>	20MR16/NSP	NSP 9	ESX	12	N	Y	2200	2000	C-8	1 3/8	Box	12	
			<b>S3460</b>	20MR16/NSP	NSP 9	ESX	12	N	Y	2200	2000	C-8	1 3/8	CD/1	12	
			<b>S1967</b>	20MR16/NSP/C	NSP 9	ESX/C	12	Y	Y	2000	2000	C-8	1 3/8	Box	12	
			<b>S1995</b>	20MR16/NSP/C/24V	NSP 9	ESX/C	24	Y	Y	2000	2000	C-8	1 3/8	Box	12	
			<b>S1956</b>	20MR16/FL	FL 36	BAB	12	N	Y	500	2000	C-6	1 3/8	Box	12	
			<b>S3461</b>	20MR16/FL	FL 36	BAB	12	N	Y	500	2000	C-6	1 3/8	CD/1		
			<b>S1966</b>	20MR16/FL/C	FL 36	BAB/C	12	Y	Y	450	2000	C-6	1 3/8	Box	12	
			<b>S1992</b>	20MR16/FL/C/24V	FL 36	BAB/C	24	Y	Y	405	2000	C-8	1 3/8	Box	12	
			<i>SOFT RAY</i> <b>S4120</b>	20MR16/FL/FR/C	FL 36	—	12	Y	Y	450	2000	C-6	1 3/8	Box	12	5
			<b>S4354</b>	20MR16/Frost TFR	—	—	12	N	Y	500	2000	C-6	1 3/8	Box	12	
35	MR16	GU5.3/GX5.3	<b>S1958</b>	35MR16/NSP	NSP 9	FRB	12	N	Y	4000	2000	C-6	1 3/8	Box	12	
			<b>S4364</b>	35MR16/NSP/C	NSP 9	FRB/C	12	Y	Y	4000	2000	C-6	1 3/8	Box	12	
			<b>S1996</b>	35MR16/NSP/C/24V	NSP 9	FRB/C	24	Y	Y	3600	2000	C-6	1 3/8	Box	12	
			<b>S1959</b>	35MR16/FL	FL 36	FMW	12	N	Y	925	2000	C-6	1 3/8	Box	12	
			<b>S3451</b>	35MR16/FL	FL 36	FMW	12	N	Y	925	2000	C-6	1 3/8	CD/1	—	
			<b>S4365</b>	35MR16/FL/C	FL 36	FMW/C	12	Y	Y	810	2000	C-6	1 3/8	Box	12	
			<b>S1993</b>	35MR16/FL/C/24V	FL 36	FMW/C	24	Y	Y	1000	2000	C-6	1 3/8	Box	12	
						<i>SOFT RAY</i> <b>S4121</b>	35MR16/FL/FR/C	FL 36	—	12	Y	Y	810	2000	C-6	1 3/8
			<b>S4355</b>	35MR16/Frost TFR	—	—	12	N	Y	925	2000	C-6	1 3/8	Box	12	




### MR16 Bi Pin 12 & 24 Volt (continued)


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton	Notes
50	MR16	GU5.3/GX5.3	S1961	50MR16/NSP	NSP 9	EXT	12	N	Y	7000	2000	C-6	1 7/8	Box	12	
			S3462	50MR16/NSP	NSP 9	EXT	12	N	Y	7000	2000	C-6	1 7/8	CD/1	12	
			S3170	50MR16/NSP/C	NSP 9	EXT/C	12	Y	Y	6500	2000	C-8	1 7/8	Box	12	
			S1962	50MR16/NFL	NFL 18	EXZ	12	N	Y	4400	2000	C-6	1 7/8	Box	12	
			S3143	50MR16/NFL25/C	NFL 25	EXZ	12	Y	Y	2800	2000	AX	1 7/8	Box	20	
			S1960	50MR16/FL	FL 36	EXN	12	N	Y	1600	2000	C-8	1 7/8	Box	12	
			S3463	50MR16/FL	FL 36	EXN	12	N	Y	1600	2000	C-8	1 7/8	CD/1	12	
			S3169	50MR16/FL/C	FL 36	EXN/C	12	Y	Y	1500	2000	C-8	1 7/8	Box	12	
			S1994	50MR16/FL/C/24V	FL 36	EXN/C	24	Y	Y	1845	2000	C-8	1 7/8	Box	12	
			<i>SOFT RAY</i> S4122	50MR16/FL/FR/C	FL 36	–	12	Y	Y	1500	2000	C-6	1 7/8	Box	12	
S1963	50MR16/WFL	WFL 60	FNV	12	N	Y	600	2000	C-6	1 7/8	Box	12				
S4356	50MR16/Frost TFR	–	–	12	Y	Y	765	2000	C-6	1 7/8	Box	12	5			
65	MR16	GU5.3/GX5.3	S1965	65MR16/NSP	NSP 9	FPA	12	N	Y	7100	2000	C-6	1 7/8	Box	12	
			S1969	65MR16/NSP/C	NSP 9	FPA	12	Y	Y	9500	2000	C-8	1 7/8	Box	12	
			S1964	65MR16/FL	FL 36	FPB	12	N	Y	2000	2000	C-6	1 7/8	Box	12	
			S1968	65MR16/FL/C	FL 36	FPB	12	Y	Y	1800	2000	C-6	1 7/8	Box	12	
			<i>SOFT RAY</i> S4123	65MR16/FL/FR/C	FL 36	–	12	Y	Y	880	2000	C-6	1 7/8	Box	12	
75	MR16	GU5.3/GX5.3	S4187	75MR16/FL/C	FL 38	EYC	12	Y	Y	1650	2000	C-6	1 7/8	Box	12	
			S4188	75MR16/SP/C	SP 9	EYF	12	Y	Y	8700	2000	C-6	1 7/8	Box	12	

### MR11 Bi Pin Coated Lensed Reflector 12 Volt (Black or Silver)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
20	MR11	GZ4	S4170	20MR11/FTD/S/C	NFL 30	FTD	12	Y	700	3000	AX	1 1/4	Box	12
			S4173	20MR11/FTD/B/C	NFL 30	FTD	12	Y	700	3000	AX	1 1/4	Box	12
35	MR11	GZ4	S4172	35MR11/FTH/S/C	NFL 30	FTH	12	Y	1250	3000	AX	1 1/4	Box	12
			S4174	35MR11/FTH/B/C	NFL 30	FTH	12	Y	1250	3000	AX	1 1/4	Box	12



MR16  
GU5.3/  
GX5.3



MR16  
GU10

## MR16 Bi Pin Coated Lensed Reflector 12 Volt (Black or Silver)


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Finish	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
20	MR16	GU5.3/GX5.3	<b>S4175</b>	20MR16/BAB/S/C	FL 38	BAB	12	Silver	Y	700	3000	AX	1 7/8	Box	12
			<b>S4178</b>	20MR16/BAB/B/C	FL 38	BAB	12	Black	Y	700	3000	AX	1 7/8	Box	12
35	MR16	GU5.3/GX5.3	<b>S4176</b>	35MR16/FMW/S/C	FL 38	FMW	12	Silver	Y	1250	3000	AX	1 7/8	Box	12
			<b>S4179</b>	35MR16/FMW/B/C	FL 38	FMW	12	Black	Y	1250	3000	AX	1 7/8	Box	12
50	MR16	GU5.3/GX5.3	<b>S4177</b>	50MR16/EXN/S/C	FL 38	EXN	12	Silver	Y	1250	3000	AX	1 7/8	Box	12
			<b>S4180</b>	50MR16/EXN/B/C	FL 38	EXN	12	Black	Y	1250	3000	AX	1 7/8	Box	12

## MR16 GU10 Coated Lensed Reflector 120 Volt (Black, Silver or Aluminized)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Finish	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
20	MR16	GU10	<b>S4190</b>	20MR16/BAB/ALU/GU10	FL 38	BAB	120	Alu.	Y	700	3000	AX	1 7/8	Box	12
35	MR16	GU10	<b>S4181</b>	35MR16/FMW/S/GU10	FL 38	FMW	120	Silver	Y	1250	3000	CC-8	1 7/8	Box	12
			<b>S4183</b>	35MR16/FMW/B/GU10	FL 38	FMW	120	Black	Y	1250	3000	CC-8	1 7/8	Box	12
			<b>S4192</b>	35MR16/FMW/ALU/GU10	FL 38	BAB	120	Alu.	Y	1250	3000	AX	1 7/8	Box	12
50	MR16	GU10	<b>S4182</b>	50MR16/EXN/S/GU10	FL 38	FMW	120	Silver	Y	1700	3000	CC-8	1 7/8	Box	12
			<b>S4184</b>	50MR16/EXN/B/GU10	FL 38	FMW	120	Black	Y	1700	3000	CC-8	1 7/8	Box	12
			<b>S4194</b>	50MR16/EXN/ALU/GU10	FL 38	BAB	120	Alu.	Y	1700	3000	AX	1 7/8	Box	12

## MR16 Bi Pin Aluminized Reflector 12 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton	Notes
20	MR16	GU5.3/GX5.3	<b>S2603 ▲</b>	20MR16/B/NSP	NSP 10	ESX	12	N	Y	4650	4000	AX	1 3/4	Box	20	6
			<b>S2601 ▲</b>	20MR16/B/FL	FL 35	BAB	12	N	Y	625	4000	AX	1 3/4	Box	20	6
35	MR16	GU5.3/GX5.3	<b>S2605 ▲</b>	35MR16/B/FL	FL 35	FMW	12	N	Y	1300	4000	AX	1 3/4	Box	20	6
50	MR16	GU5.3/GX5.3	<b>S2610 ▲</b>	50MR16/B/SP	SP 11	EXT	12	N	Y	10500	4000	AX	1 3/4	Box	20	6
			<b>S2609 ▲</b>	50MR16/B/NFL	NFL 25	EXZ	12	N	Y	3000	4000	AX	1 3/4	Box	20	6
			<b>S2607 ▲</b>	50MR16/B/FL	FL 35	EXN	12	N	Y	1900	4000	AX	1 3/4	Box	20	6




MR16  
GU5.3/  
GX5.3

## MR16 Bi Pin Hard Coated Dichroic Reflector 12 Volt


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton	Notes
20	MR16	GU5.3/GX5.3	<b>S2616</b> ▲	20MR16/T/SP/C	SP 10	ESX	12	Y	Y	5000	4000	AX	1 ¾	Box	20	7
			<b>S2615</b> ▲	20MR16/T/FL/C	FL 40	BAB	12	Y	Y	700	4000	AX	1 ¾	Box	20	7
			<b>S2617</b> ▲	20MR16/T/WFL/C	WFL 60	–	12	Y	Y	350	4000	AX	1 ¾	Box	20	7
35	MR16	GU5.3/GX5.3	<b>S2620</b> ▲	35MR16/T/SP/C	SP 10	FRB	12	Y	Y	8300	4000	AX	1 ¾	Box	20	7
			<b>S2619</b> ▲	35MR16/T/NFL/C	NFL 25	–	12	Y	Y	3100	4000	AX	1 ¾	Box	20	7
			<b>S2618</b> ▲	35MR16/T/FL/C	FL 40	FMW	12	Y	Y	1250	4000	AX	1 ¾	Box	20	7
			<b>S2621</b> ▲	35MR16/T/WFL/C	WFL 60	–	12	Y	Y	650	4000	AX	1 ¾	Box	20	7
50	MR16	GU5.3/GX5.3	<b>S2624</b> ▲	50MR16/T/SP/C	SP 10	EXT	12	Y	Y	11500	4000	AX	1 ¾	Box	20	7
			<b>S2623</b> ▲	50MR16/T/NFL/C	NFL 25	EXZ	12	Y	Y	3200	4000	AX	1 ¾	Box	20	7
			<b>S2622</b> ▲	50MR16/T/FL/C	FL 40	EXN	12	Y	Y	2000	4000	AX	1 ¾	Box	20	7
			<b>S2625</b> ▲	50MR16/T/WFL/C	WFL 60	FNV	12	Y	Y	1000	4000	AX	1 ¾	Box	20	7

## MR16 Bi Pin Energy Saver 12 Volt with Infrared Reflective Coating


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton	Notes
20	MR16	GU5.3/GX5.3	<b>S2632</b> ▲	20MR16/IR/SP	SP 10	12	Y	Y	6000	4000	AX	1 ¾	Box	20	8
			<b>S2631</b> ▲	20MR16/IR/NFL	NFL 25	12	Y	Y	2300	4000	AX	1 ¾	Box	20	8
			<b>S2630</b> ▲	20MR16/IR/FL	FL 40	12	Y	Y	1000	4000	AX	1 ¾	Box	20	8
			<b>S2633</b> ▲	20MR16/IR/WFL	WFL 60	12	Y	Y	450	4000	AX	1 ¾	Box	20	8
37	MR16	GU5.3/GX5.3	<b>S2636</b> ▲	37MR16/IR/SP	SP 10	12	Y	Y	12500	4000	AX	1 ¾	Box	20	8
			<b>S2635</b> ▲	37MR16/IR/NFL	NFL 25	12	Y	Y	4400	4000	AX	1 ¾	Box	20	8
			<b>S2634</b> ▲	37MR16/IR/FL	FL 40	12	Y	Y	2200	4000	AX	1 ¾	Box	20	8
			<b>S2637</b> ▲	37MR16/IR/WFL	WFL 60	12	Y	Y	1100	4000	AX	1 ¾	Box	20	8
50	MR16	GU5.3/GX5.3	<b>S2640</b> ▲	50MR16/IR/SP	SP 10	12	Y	Y	15000	4000	AX	1 ¾	Box	20	8
			<b>S2639</b> ▲	50MR16/IR/NFL	NFL 25	12	Y	Y	5700	4000	AX	1 ¾	Box	20	8
			<b>S2638</b> ▲	50MR16/IR/FL	FL 40	12	Y	Y	2850	4000	AX	1 ¾	Box	20	8
			<b>S2641</b> ▲	50MR16/IR/WFL	WFL 60	12	Y	Y	1430	4000	AX	1 ¾	Box	20	8



MR16  
DC Bay.



MR16  
GU5.3/  
GX5.3



MR16  
GU10

## MR16 DC Bay. 12 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
20	MR16	DC Bay.	<b>S1971</b>	20MR16/DC/NSP	NSP 9	GEU	12	Y	Y	4100	2000	C-8	1 7/8	Box	12
			<b>S1970</b>	20MR16/DC/FL	FL 36	GES	12	Y	Y	450	2000	C-6	1 7/8	Box	12
50	MR16	DC Bay.	<b>S1973</b>	50MR16/DC/NSP	NSP 9	GBT	12	Y	Y	6500	2000	C-8	1 7/8	Box	12
			<b>S1972</b>	50MR16/DC/FL	FL 36	GBW	12	Y	Y	1500	2000	C-8	1 7/8	Box	12
65	MR16	DC Bay.	<b>S1975</b>	65MR16/DC/NSP	NSP 9	—	12	Y	Y	9500	2000	C-8	1 7/8	Box	12
			<b>S1974</b>	65MR16/DC/FL	FL 36	—	12	Y	Y	10000	2000	C-8	1 7/8	Box	12

## MR16 Bi Pin 120 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
20	MR16	GU5.3/GX5.3	<b>S1976</b>	20MR16/FL/120V	FL 36	120	Y	Y	220	2000	CC-8	1 7/8	Box	12
		G8	<b>S3445</b>	20MR16/FL/120V	FL 36	120	Y	Y	220	2000	CC-8	1 7/8	CD/1	12
			<b>S4626</b>	20MR16/FL/120V	FL 36	120	Y	N	220	2000	CC-8	1 7/8	Box	12
35	MR16	GU5.3/GX5.3	<b>S1977</b>	35MR16/FL/120V	FL 36	120	Y	Y	440	2000	CC-8	1 7/8	Box	12
		G8	<b>S4627</b>	35MR16/FL/120V	FL 36	120	Y	N	440	2000	CC-8	1 7/8	Box	12
50	MR16	GU5.3/GX5.3	<b>S1978</b>	50MR16/FL/120V	FL 36	120	Y	Y	1000	2000	CC-8	1 7/8	Box	12
		G8	<b>S3446</b>	50MR16/FL/120V	FL 36	120	Y	Y	1000	2000	CC-8	1 7/8	CD/1	12
			<b>S4618</b>	50MR16/FL/120V	FL 36	120	Y	N	1000	2000	CC-8	1 7/8	Box	12

## MR16 GU10 (Twist Base) 120 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
20	MR16	GU10	<b>S3515</b>	20MR16/GU10/FL	FL 36	120	Y	Y	200	2000	CC-8	1 7/8	Box	12
			<b>S3500</b>	20MR16/GU10/FL	FL 36	120	Y	Y	200	2000	CC-8	1 7/8	CD/1	12
			<b>S4127</b>	20MR16/GU10/FL/FR	FL 36	120	Y	Y	200	2000	CC-8	1 7/8	Box	12
35	MR16	GU10	<b>S3516</b>	35MR16/GU10/FL	FL 36	120	Y	Y	400	2000	CC-8	1 7/8	Box	12
			<b>S3501</b>	35MR16/GU10/FL	FL 36	120	Y	Y	400	2000	CC-8	1 7/8	CD/1	12
			<b>S4128</b>	35MR16/GU10/FL/FR	FL 36	120	Y	Y	400	2000	CC-8	1 7/8	Box	12
50	MR16	GU10	<b>S3517</b>	50MR16/GU10/FL	FL 36	120	Y	Y	900	2000	CC-8	1 7/8	Box	12
			<b>S3502</b>	50MR16/GU10/FL	FL 36	120	Y	Y	900	2000	CC-8	1 7/8	CD/1	12
			<b>S4129</b>	50MR16/GU10/FL/FR	FL 36	120	Y	Y	900	2000	CC-8	1 7/8	Box	12



### MR16 & JDR Screw Base 120 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
<b>20</b>	MR16	Med.	<b>S4623</b>	20MR16/FL/MED	FL 36	120	Y	Y	700	2000	CC-8	1 7/8	Box	12
<b>35</b>	MR16	Med.	<b>S4624</b>	35MR16/FL/MED	FL 36	120	Y	Y	1250	2000	CC-8	1 7/8	Box	12


### MR16 & JDR Screw Base 120 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
<b>50</b>	MR16	Med.	<b>S4625</b>	50MR16/FL/MED	FL 36	120	Y	Y	1700	2000	CC-8	2	Box	12
	JDR	Med.	<b>S3139</b>	50JDR/FL	FL 36	120	Y	Y	950	2000	CC-8	2 5/8	Box	12
<b>75</b>	JDR	Int.	<b>S3115</b>	75JDR/N/FL	FL 36	120	Y	Y	1200	2000	CC-8	2 3/4	Box	12
			<b>S3434</b>	75JDR/N/FL	FL 36	120	Y	Y	1650	2000	CC-8	2 5/8	CD/1	12
	Med.	<b>S3113</b>	75JDR/FL	FL 36	120	Y	Y	1200	2000	CC-8	2 5/8	Box	12	
		<b>S3438</b>	75JDR/FL	FL 36	120	Y	Y	1200	2000	CC-8	2 5/8	CD/1	12	
<b>100</b>	JDR	Int.	<b>S3116</b>	100JDR/N/FL	FL 36	120	Y	Y	1950	2000	CC-8	2 3/4	Box	12
			<b>S3435</b>	100JDR/N/FL	FL 36	120	Y	Y	1950	2000	CC-8	2 7/8	CD/1	12
	Med.	<b>S3114</b>	100JDR/FL	FL 36	120	Y	Y	2000	2000	CC-8	2 5/8	Box	12	
		<b>S3439</b>	100JDR/FL	FL 36	120	Y	Y	1950	2000	CC-8	2 7/8	CD/1	12	


### MR20 & JDR GU10 (Twist Base) 120 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
<b>50</b>	JDR	GU10	<b>S3519</b>	50JDR-C/GU10/FR	FL 50	120	Y	Y	1600	2000	CC-8	2	Box	12
<b>75</b>	MR20	GU10	<b>S3518</b>	75MR20/GU10/FL	FL 50	120	Y	Y	1600	2000	CC-8	2	Box	12





ALR12  
DC Bay.



ALR18  
DC Bay.



AR70  
DC Bay.



AR111  
G53

## Aluminum Reflector Lamps

### ALR Closed Aluminum Reflector 12 Volt


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	ANSI	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Master/ Inner Carton
20	ALR12	DC Bay.	<b>S2642 ▲</b>	20ALR12/NSP/CLR	NSP 6	GBD	12	Y	Y	6400	2000	C-8	1 3/8	Box	50
			<b>S2643 ▲</b>	20ALR12/SP/FRST	SP 18	GBE	12	Y	Y	1000	2000	C-8	1 3/8	Box	50
			<b>S2644 ▲</b>	20ALR12/FL/FRST	FL 32	GBF	12	Y	Y	350	2000	C-8	1 3/8	Box	50
			<b>Shatter Proof S3937</b>	20ALR12/FL/FRST	FL 32	GBF	12	Y	Y	350	2000	C-8	1 3/8	Box	50
			<b>S4189</b>	20ALR12/FL/FRST	FL 32	GBF	12	Y	Y	350	2000	C-8	1 3/8	Box	200/10
50	ALR18	DC Bay.	<b>S2645 ▲</b>	50ALR18/NFL/FRST	NFL 22	GBK	12	Y	Y	2000	2000	C-8	2 1/4	Box	50

### AR70 Aluminum Reflector 12 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
20	AR70	DC Bay.	<b>S4680 ▲</b>	20AR70/SP8	SP 8	12	N	Y	7700	3000	C-8	1 5/16	Box	10
			<b>S4681 ▲</b>	20AR70/FL25	FL 25	12	N	Y	900	3000	C-8	1 5/16	Box	10
50	AR70	DC Bay.	<b>S4682 ▲</b>	50AR70/SP8	SP 8	12	N	Y	12500	3000	C-8	1 5/16	Box	10
			<b>S4683 ▲</b>	50AR70/FL25	FL 25	12	N	Y	2600	3000	C-8	1 5/16	Box	10

### AR111 Aluminum Reflector 6 & 12 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Lens	UV Block	CBCP	Avg. Rated Hours	Filament	M.O.L. Inches	Pkg. Type	Carton
35	AR111	G53	<b>S4684 ▲</b>	35AR111/SSP4	SSP 4	12	N	Y	40000	3000	C-8	2 3/8	Box	6
			<b>S4686 ▲</b>	35AR111/SP8	SP 8	12	N	Y	14000	3000	C-8	2 5/16	Box	6
			<b>S4687 ▲</b>	35AR111/FL25	NFL 25	12	N	Y	2500	3000	C-8	2 1/2	Box	6
50	AR111	G53	<b>S4688 ▲</b>	50AR111/SSP4	SSP 4	12	N	Y	45000	3000	C-8	2 3/8	Box	6
			<b>S4689 ▲</b>	50AR111/SP8	SP 8	12	N	Y	20000	3000	C-8	2 1/4	Box	6
			<b>S4690 ▲</b>	50AR111/FL25	NFL 25	12	N	Y	4000	3000	C-8	2 1/2	Box	6
75	AR111	G53	<b>S4691 ▲</b>	75AR111/SP8	SP 8	12	N	Y	30000	3000	C-8	2 1/4	Box	6
			<b>S4692 ▲</b>	75AR111/FL25	NFL 25	12	N	Y	5300	3000	C-8	2 5/16	Box	6
100	AR111	G53	<b>S4694 ▲</b>	100AR111/SP8	SP 8	12	N	Y	48000	3000	C-8	2 1/4	Box	6
			<b>S4695 ▲</b>	100AR111/FL25	NFL 25	12	N	Y	8500	3000	C-8	2 5/16	Box	6




## R20, BR25, BR30 & R40 Reflector 120 & 130 Volt – Halogen

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Finish	M.O.L. Inches	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton
<b>45</b>	R20	Med.	<b>S4514</b>	45R20/FL/HAL	FL 70	120	Frost	4	560	2000	Sleeve	48/6
			<b>S4414</b>	45R20/FL/HAL/130V	FL 70	130	Frost	4	540	2000	Sleeve	48/6
	BR25		<b>S2451</b>	45BR25/FL/HAL/120V	FL 70	120	Frost	4 3/4	560	2000	Box	24/12
<b>65</b>	BR30	Med.	<b>S4515</b>	65BR30/FL/HAL	FL 80	120	Frost	5 3/8	920	2000	Sleeve	48/6
			<b>S4415</b>	65BR30/FL/HAL/130V	FL 80	130	Frost	6 1/2	900	2000	Sleeve	48/6
	BR40	Med.	<b>S4516</b>	65BR40/FL/HAL	FL 90	120	Frost	6 1/2	920	2000	Sleeve	24/6
			<b>S4416</b>	65BR40/FL/HAL/130V	FL 90	130	Frost	6 1/2	900	2000	Sleeve	24/6

## Halogen A19

### Halogen/Excel A19 Replacements

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Finish	M.O.L. Inches	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/ Inner Carton
<b>29</b>	A19	Med.	<b>S2401</b>	40W	29A19/HAL/ES/CL/120V/2PK	120	Clear	4 1/2	430	1000	Box	12/2
			<b>S2405</b>	40W	29A19/HAL/ES/SW/120V/2PK	120	White	4 1/2	430	1000	Box	12/2
<b>43</b>	A19	Med.	<b>S2402</b>	60W	43A19/HAL/ES/CL/120V/2PK	120	Clear	4 1/2	750	1000	Box	12/2
			<b>S2406</b>	60W	43A19/HAL/ES/SW/120V/2PK	120	White	4 1/2	750	1000	Box	12/2
			<b>S2448</b>	60W	43A19/HAL/ES/SW/120V/4PK	120	White	4 1/2	750	1000	Box	12/4
<b>53</b>	A19	Med.	<b>S2403</b>	75W	53A19/HAL/ES/CL/120V/2PK	120	Clear	4 1/2	1050	1000	Box	12/2
			<b>S2407</b>	75W	53A19/HAL/ES/SW/120V/2PK	120	White	4 1/2	1050	1000	Box	12/2
			<b>S2449</b>	75W	53A19/HAL/ES/SW/120V/4PK	120	White	4 1/2	1050	1000	Box	12/4
<b>72</b>	A19	Med.	<b>S2404</b>	100W	72A19/HAL/ES/CL/120V/2PK	120	Clear	4 1/2	1490	1000	Box	12/2
			<b>S2408</b>	100W	72A19/HAL/ES/SW/120V/2PK	120	White	4 1/2	1490	1000	Box	12/2
			<b>S2450</b>	100W	72A19/HAL/ES/SW/120V/4PK	120	White	4 1/2	1490	1000	Box	12/4



## Tubular and BT Shape


### Med. Base Tubular and A Style Replacements

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
20	T3	Med.	S4308	KX20CL/3M/E26	120	Clear	2 3/4	200	3000	Box	10	1
			S4309	KX20FR/3M/E26	120	Frost	2 3/4	200	3000	Box	10	1
30/70/100	A21	Med.	S4505	30/100A/HAL	120	White	5 1/6	295/785/1080	4000	Sleeve	36/12	
40	T3	Med.	S4310	KX40CL/3M/E26	120	Clear	2 3/4	560	3000	Box	10	1
			S4311	KX40FR/3M/E26	120	Frost	2 3/4	560	3000	Box	10	1
43	BT15	Med.	S2452	43BT15/CL/120V/CD	120	Clear	4	750	1000	CD/1	24/6	
			S2453	43BT15/WH/120V/CD	120	White	4	750	1000	CD/1	24/6	
50/100/150	A21	Med.	S4506	50/150A/HAL	120	White	5 1/6	585/1400/1985	4000	Sleeve	36/12	
53	BT15	Med.	S2454	53BT15/WH/120V/CD	120	White	4	1050	1000	CD/1	24/6	
60	T3	Med.	S4312	KX60CL/3M/E26	120	Clear	2 3/4	960	3000	Box	10	1
			S4313	KX60FR/3M/E26	120	Frost	2 3/4	960	3000	Box	10	1
72	BT15	Med.	S2455	72BT15/WH/120V/CD	120	White	4	1490	1000	CD/1	24/6	
150	T10	Med.	S3474	150T10Q/CL	120	Clear	4	2600	2000	CD/1	12	
			S3478	150T10Q/F	120	Frost	4	2600	2000	CD/1	12	
			S3620▲	150T10Q/CL	230	Clear	4	2600	2000	CD/1	12	
250	T10	Med.	S3475	250T10Q/CL	120	Clear	4	4000	2000	CD/1	12	
			S3479	250T10Q/F	120	Frost	4	3600	2000	CD/1	12	

## Decorative Halogen Lamps

### Halogen/Excel Globe and Chandelier

Watts	Bulb Type	Base	Satco Prod. #	Incand. Equiv.	Lamp Code	Volts	Finish	M.O.L. Inches	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton
43	G25	Med.	S2437	60W	43G25/CL/120V	120	Clear	4 3/8	750	1000	Box	72/6
			S2438	60W	43G25/WH/120V	120	White	4 3/8	750	1000	Box	72/6
			S2441	60W	43G25/CL/120V/3PK	120	Clear	4 3/8	750	1000	Box	40/3
			S2442	60W	43G25/WH/120V/3PK	120	White	4 3/8	750	1000	Box	40/3
Torpedo	Med.	S2443	60W	43ETC/HAL/120V/E26/CD	120	Clear	3 1/2	750	1000	CD/2	120/12	
		S2444	60W	43ETF/HAL/120V/E26/CD	120	Frost	3 1/2	750	1000	CD/2	120/12	
		S2445	60W	43ETW/HAL/120V/E26/CD	120	White	3 1/2	750	1000	CD/2	120/12	
		S2457	60W	43ETC/HAL/120V/E26 1/BX	120	Clear	3 1/2	750	1000	Box	500/25	
Flame Tip	Med.	S2458	60W	43ETC/HAL/120V/E26 1/BX	120	Frost	3 1/2	750	1000	Box	500/25	
		S2446	60W	43EFC/HAL/120V/E26/CD	120	Clear	4 3/4	750	1000	CD/2	120/12	
			S2447	60W	43EFF/HAL/120V/E26/CD	120	Frost	4 3/4	750	1000	CD/2	120/12



# Halogen PAR Lamps

## PAR14 and PAR16

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Finish	CBCP	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton	Notes
<b>35</b>	PAR14	Med.	<b>S4658</b> ▲	35PAR14/CAP/FL	WFL 50	120	Clear	85	2 1/16	CC-8	300	2000	Box	6	
<b>45</b>	PAR16	Med.	<b>S2200</b>	45PAR16/HAL/NFL	NFL 30	120	Clear	1250	3 3/16	CC-8	360	2500	Box	15	
			<b>S2300</b>	45PAR16/HAL/NFL	NFL 30	130	Clear	1250	3 3/16	CC-8	360	2500	Box	15	
<b>60</b>	PAR16	Med.	<b>S2202</b>	60PAR16/HAL/NSP	NSP 10	120	Clear	4700	3 3/16	CC-8	550	2500	Box	15	
			<b>S4902</b> ▲	60PAR16/CAP/NSP	NSP 10	120	Clear	5000	2 7/8	CC-8	650	2000	Box	15	
			<b>S2302</b>	60PAR16/HAL/NSP	NSP 10	130	Clear	4700	3 3/16	CC-8	550	2500	Box	15	
			<b>S4903</b> ▲	60PAR16/CAP/NSP	NSP 10	130	Clear	5000	2 7/8	CC-8	650	2000	Box	15	
			<b>S2201</b>	60PAR16/HAL/NFL	NFL 30	120	Clear	2000	3 3/16	CC-8	550	2500	Box	15	
			<b>S4900</b> ▲	60PAR16/CAP/NFL	NFL 30	120	Clear	1300	2 7/8	CC-8	650	2000	Box	15	
			<b>S2301</b>	60PAR16/HAL/NFL	NFL 30	130	Clear	2000	3 3/16	CC-8	550	2500	Box	15	
			<b>S4901</b> ▲	60PAR16/CAP/NFL	NFL 30	130	Clear	1300	2 7/8	CC-8	650	2000	Box	15	
			<b>75</b>	PAR16	Med.	<b>S2204</b>	75PAR16/HAL/NSP	NSP 10	120	Clear	7000	3 3/16	CC-8	800	2500
<b>S4906</b> ▲	75PAR16/CAP/NSP	NSP 10				120	Clear	7500	2 7/8	CC-8	900	2000	Box	15	
<b>S4907</b> ▲	75PAR16/CAP/NSP	NSP 10				130	Clear	7500	2 7/8	CC-8	900	2000	Box	15	
<b>S2203</b>	75PAR16/HAL/NFL	NFL 30				120	Clear	2750	3 3/16	CC-8	800	2500	Box	15	
<b>S4904</b> ▲	75PAR16/CAP/NFL	NFL 30				120	Clear	1900	2 7/8	CC-8	900	2000	Box	15	
<b>S2303</b>	75PAR16/HAL/NFL	NFL 30				130	Clear	2750	3 3/16	CC-8	800	2500	Box	15	
<b>S4905</b> ▲	75PAR16/CAP/NFL	NFL 30				130	Clear	1900	2 7/8	CC-8	900	2000	Box	15	
	<i>SOFT RAY</i>	<b>S4109</b>	75PAR16/HAL/FL/Frost	FL 38	120	Frost	1000	3 3/16	CC-8	725	2500	Box	15	5	


## PAR20

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Finish	CBCP	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton	Notes		
<b>39</b>	PAR20	Med.	<b>S2231</b>	39PAR20/HAL/XEN/NSP/120V	NSP 10	120	Clear	4700	3 1/4	CC-8	530	1500	Box	15			
			<b>Y16103</b> ▲	39PAR20/HAL/SP10/120V	SP 10	120	Clear	3700	3 1/4	CC-8	475	1500	Box	10			
			<b>Y16108</b> ▲	39PAR20/HAL/SP10/130V	SP 10	130	Clear	3700	3 1/4	CC-8	475	1500	Box	10			
			<b>S2328</b>	39PAR20/HAL/XEN/NFL/130V	NFL 30	130	Clear	1300	3 1/4	CC-8	530	2000	Box	15			
			<b>S2232</b>	39PAR20/HAL/XEN/NFL/120V	NFL 34	120	Clear	1300	3 1/4	CC-8	530	1500	Box	15			
			<b>S2267</b>	39PAR20/HAL/XEN/NFL/120V 2PK	NFL 34	120	Clear	1300	3 1/4	CC-8	530	1500	Box	8-2pks			
			<b>Y16104</b> ▲	39PAR20/HAL/FL30/120V	FL 30	120	Clear	1000	3 1/4	CC-8	475	1500	Box	10			
			<b>Y16109</b> ▲	39PAR20/HAL/FL30/130V	FL 30	130	Clear	1000	3 1/4	CC-8	475	1500	Box	10			
				<i>SOFT RAY</i>	<b>S4130</b>	39PAR20/HAL/XEN/FL/FR/120V	FL 42	120	Frost	500	3 1/4	CC-8	500	1500	Box	15	5
				<i>SOFT RAY</i>	<b>S4208</b>	39PAR20/HAL/XEN/FL/FR/130V	FL 42	130	Frost	500	3 1/4	CC-8	500	2000	Box	15	5



## PAR30 Short Neck

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Finish	CBCP	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton	Notes
<b>39</b>	PAR30	Med.	<b>S2233</b>	39PAR30/HAL/XEN/NSP/120V	NSP 9	120	Clear	6500	3 5/8	CC-8	530	1500	Box	15	
			<b>Y16117 ▲</b>	39PAR30/HAL/SP10/120V	SP 10	120	Clear	6100	3 5/8	CC-8	550	1500	Box	10	
			<b>Y16121 ▲</b>	39PAR30/HAL/SP10/130V	SP 10	130	Clear	6100	3 5/8	CC-8	550	1500	Box	10	
			<b>S2234</b>	39PAR30/HAL/XEN/NFL/120V	NFL 34	120	Clear	1350	3 5/8	CC-8	530	1500	Box	15	
			<b>Y16118 ▲</b>	39PAR30/HAL/NFL25/120V	NFL 25	120	Clear	1700	3 5/8	CC-8	550	1500	Box	10	
			<b>S2330</b>	39PAR30/HAL/XEN/NFL/130V	NFL 34	130	Clear	1350	3 5/8	CC-8	530	2000	Box	15	
			<b>Y16122 ▲</b>	39PAR30/HAL/NFL25/130V	NFL 25	130	Clear	1700	3 5/8	CC-8	550	1500	Box	10	
			<b>S2335</b>	39PAR30/HAL/XEN/WFL/130V	WFL 34	130	Clear	750	3 5/8	CC-8	530	2000	Box	15	
			<b>Y16119 ▲</b>	39PAR30/HAL/WFL50/120V	WFL 50	120	Clear	600	3 5/8	CC-8	550	1500	Box	10	
			<b>Y16123 ▲</b>	39PAR30/HAL/WFL50/130V	WFL 50	130	Clear	600	3 5/8	CC-8	550	1500	Box	10	
			<i>SOFT RAY</i> <b>S4131</b>	39PAR30/HAL/XEN/FL/FR/120V	FL 42	120	Frost	550	3 5/8	CC-8	500	1500	Box	15	5
			<i>SOFT RAY</i> <b>S4209</b>	39PAR30/HAL/XEN/FL/FR/130V	FL 42	130	Frost	550	3 5/8	CC-8	500	2000	Box	15	5
			<b>S2235</b>	39PAR30/HAL/XEN/WFL/120V	WFL 50	120	Clear	750	3 5/8	CC-8	530	1500	Box	15	
<b>60</b>	PAR30	Med.	<b>S2236</b>	60PAR30/HAL/XEN/NSP/120V	NSP 9	120	Clear	10500	3 5/8	CC-8	1090	1500	Box	15	
			<b>Y16127 ▲</b>	60PAR30/HAL/S/SP10/120V	SP 10	120	Clear	12000	3 5/8	CC-8	1070	1500	Box	10	
			<b>S2237</b>	60PAR30/HAL/XEN/NFL/120V	NFL 34	120	Clear	2300	3 5/8	CC-8	1090	1500	Box	15	
			<b>Y16128 ▲</b>	60PAR30/HAL/S/NFL25/120V	NFL 25	120	Clear	3300	3 5/8	CC-8	1070	1500	Box	10	
			<b>S2268</b>	60PAR30/HAL/XEN/NFL/120V 2PK	NFL 34	120	Clear	2300	3 5/8	CC-8	1090	1500	Box	8-2pks	
			<b>S2238</b>	60PAR30/HAL/XEN/WFL/120V	WFL 50	120	Clear	950	3 5/8	CC-8	1090	1500	Box	15	
			<b>Y16129 ▲</b>	60PAR30/HAL/S/WFL50/120V	WFL 50	120	Clear	1300	3 5/8	CC-8	1070	1500	Box	10	




PAR30L  
Med.


## PAR30 Long Neck

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Finish	CBCP	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton
39	PAR30	Med.	<b>S2239</b>	39PAR30L/HAL/XEN/NSP/120V	NSP 9	120	Clear	6500	4 ½	CC-8	530	1500	Box	15
			<b>Y16153 ▲</b>	39PAR30LN/HAL/SP10/120V	SP 10	120	Clear	6100	4 ⅝	CC-8	550	1500	Box	10
			<b>Y16159 ▲</b>	39PAR30LN/HAL/SP10/130V	SP 10	130	Clear	6100	4 ⅝	CC-8	550	1500	Box	10
			<b>S2240</b>	39PAR30L/HAL/XEN/NFL/120V	NFL 34	120	Clear	1350	4 ½	CC-8	530	1500	Box	15
			<b>Y16154 ▲</b>	39PAR30LN/HAL/NFL25/120V	NFL 25	120	Clear	1700	4 ⅝	CC-8	550	1500	Box	10
			<b>S2332</b>	39PAR30L/HAL/XEN/NFL/130V	NFL 36	130	Clear	1350	4 ½	CC-8	530	2000	Box	15
			<b>Y16160 ▲</b>	39PAR30LN/HAL/NFL25/130V	NFL 25	130	Clear	1700	4 ⅝	CC-8	550	1500	Box	10
			<i>SOFT RAY</i> <b>S4132</b>	39PAR30L/HAL/XEN/FL/FR/120V	FL 42	120	Frost	550	4 ½	CC-8	500	1500	Box	15
			<i>SOFT RAY</i> <b>S4210</b>	39PAR30L/HAL/XEN/FL/FR/130V	FL 42	130	Frost	550	4 ½	CC-8	500	2000	Box	15
			<b>S2241</b>	39PAR30L/HAL/XEN/WFL/120V	WFL 50	120	Clear	750	4 ½	CC-8	530	1500	Box	15
			<b>Y16156 ▲</b>	39PAR30LN/HAL/WFL50/120V	WFL 50	120	Clear	600	4 ⅝	CC-8	550	1500	Box	10
			<b>S2336</b>	39PAR30L/HAL/XEN/WFL/130V	WFL 50	130	Clear	750	4 ½	CC-8	530	2000	Box	15
			<b>Y16161 ▲</b>	39PAR30LN/HAL/WFL50/130V	WFL 50	130	Clear	600	4 ⅝	CC-8	550	1500	Box	10
			60	PAR30	Med.	<b>S2242</b>	60PAR30L/HAL/XEN/NSP/120V	NSP 9	120	Clear	10500	4 ½	CC-8	1090
<b>Y16166 ▲</b>	60PAR30LN/HAL/S/SP10/120V	SP 10				120	Clear	12000	4 ⅝	CC-8	1070	1500	Box	10
<b>S2243</b>	60PAR30L/HAL/XEN/NFL/120V	NFL 34				120	Clear	2300	4 ½	CC-8	1090	1500	Box	15
<b>S2269</b>	60PAR30L/HAL/XEN/NFL/120V 2PK	NFL 34				120	Clear	2300	4 ½	CC-8	1090	1500	Box	8-2pks
<b>Y16167 ▲</b>	60PAR30LN/HAL/S/NFL25/120V	NFL 25				120	Clear	3300	4 ⅝	CC-8	1070	1500	Box	10
<b>S2244</b>	60PAR30L/HAL/XEN/WFL/120V	WFL 50				120	Clear	950	4 ½	CC-8	1090	1500	Box	15
<b>Y16168 ▲</b>	60PAR30LN/HAL/S/WFL50/120V	WFL 50				120	Clear	1300	4 ⅝	CC-8	1070	1500	Box	10






PAR38  
Med. Sk.




PAR38  
Med. Side Prong  
MSPG

## PAR38


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	Finish	CBCP	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton	Notes
39	PAR38	Med. Sk.	<b>S2245</b>	39PAR38/HAL/XEN/NSP/120V	NSP 9	120	Clear	5000	5 5/16	CC-8	530	1500	Box	15	
			<b>Y16728 ▲</b>	39PAR38/HAL/SP10/120V	SP 10	120	Clear	7700	5 5/16	CC-8	550	1500	Box	10	
			<b>Y16732 ▲</b>	39PAR38/HAL/SP10/130V	SP 10	130	Clear	7700	5 5/16	CC-8	550	1500	Box	10	
			<b>S2246</b>	39PAR38/HAL/XEN/FL/120V	FL 30	120	Clear	1100	5 5/16	CC-8	530	1500	Box	15	
			<b>Y16729 ▲</b>	39PAR38/HAL/NFL25/120V	NFL 25	120	Clear	2100	5 5/16	CC-8	550	1500	Box	10	
			<b>S2334</b>	39PAR38/HAL/XEN/NFL/130V	FL 30	130	Clear	1100	5 5/16	CC-8	530	2000	Box	15	
			<b>Y16733 ▲</b>	39PAR38/HAL/NFL25/130V	NFL 25	130	Clear	2100	5 5/16	CC-8	550	1500	Box	10	
			<i>SOFT RAY</i> <b>S4133</b>	39PAR38/HAL/XEN/FL/FR/120V	FL 42	120	Frost	550	5 5/16	CC-8	500	1500	Box	15	5
<i>SOFT RAY</i> <b>S4211</b>	39PAR38/HAL/XEN/FL/FR/130V	FL 42	130	Frost	550	5 5/16	CC-8	500	2000	Box	15	5			
50	PAR38	Med. Sk.	<b>Y16734 ▲</b>	50PAR38/HAL/S/SP10/120V	SP 10	120	Clear	11900	5 5/16	CC-8	850	1500	Box	10	
			<b>Y16735 ▲</b>	50PAR38/HAL/S/NFL25/120V	NFL 25	120	Clear	3300	5 5/16	CC-8	850	1500	Box	10	
60	PAR38	Med. Sk.	<b>S2247</b>	60PAR38/HAL/XEN/NSP/120V	NSP 9	120	Clear	12000	5 5/16	CC-8	1090	1500	Box	15	
			<b>Y16737 ▲</b>	60PAR38/HAL/S/SP10/120V	SP 10	120	Clear	14900	5 5/16	CC-8	1070	1500	Box	10	
			<b>S2248</b>	60PAR38/HAL/XEN/FL/120V	FL 30	120	Clear	2500	5 5/16	CC-8	1090	1500	Box	15	
			<b>Y16738 ▲</b>	60PAR38/HAL/S/NFL25/120V	NFL 25	120	Clear	4100	5 5/16	CC-8	1070	1500	Box	10	
			<b>S2249</b>	60PAR38/HAL/XEN/FL/2PK/120V	FL 30	120	Clear	2500	5 5/16	CC-8	1090	1500	Box	8	
70	PAR38	Med. Sk.	<b>S2256</b>	70PAR38/HAL/XEN/NSP/120V	NSP 9	120	Clear	14000	5 5/16	CC-8	1380	1500	Box	15	
			<b>Y16742 ▲</b>	70PAR38/HAL/S/SP10/120V	SP 10	120	Clear	18200	5 5/16	CC-8	1305	1500	Box	10	
			<b>S2257</b>	70PAR38/HAL/XEN/FL/120V	FL 30	120	Clear	3000	5 5/16	CC-8	1380	1500	Box	15	
			<b>Y16743 ▲</b>	70PAR38/HAL/S/NFL25/120V	NFL 25	120	Clear	5100	5 5/16	CC-8	1305	1500	Box	10	
80	PAR38	Med. Sk.	<b>S2258</b>	80PAR38/HAL/XEN/NSP/120V	NSP 9	120	Clear	20000	5 5/16	CC-8	1600	1500	Box	15	
			<b>Y16747 ▲</b>	80PAR38/HAL/S/SP10/120V	SP 10	120	Clear	21600	5 5/16	CC-8	1545	1500	Box	10	
			<b>S2259</b>	80PAR38/HAL/XEN/FL/120V	FL 30	120	Clear	4500	5 5/16	CC-8	1600	1500	Box	15	
			<b>Y16748 ▲</b>	80PAR38/HAL/S/NFL25/120V	NFL 25	120	Clear	6000	5 5/16	CC-8	1545	1500	Box	10	
			<b>S2260</b>	80PAR38/HAL/XEN/FL/2PK/120V	FL 30	120	Clear	4500	5 5/16	CC-8	1600	1500	Box	8	
			<b>Y16751 ▲</b>	80PAR38/HAL/S/WFL50/120V	WFL 50	120	Clear	2300	5 5/16	CC-8	1545	1500	Box	10	
90	PAR38	MSPG	<b>S4674 ▲</b>	90PAR38/CAP/3WSP	WSP 12	120	Clear	14300	4 5/16	CC-8	1310	2500	Box	15	9
			<b>S4675 ▲</b>	90PAR38/CAP/3FL	FL 30	120	Clear	3500	4 5/16	CC-8	1310	2500	Box	15	9



PAR36  
Screw Term.  
MP2



PAR56  
Mog.  
End Prong



PAR64  
Mog.  
End Prong

## PAR36 12 Volt

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	CBCP	M.O.L. Inches	Filament	Avg. Rated Hours	Pkg. Type	Carton
36	PAR36	MP2	S4807 ▲	36PAR36/CAP/VNSP	VNSP 5	12	17000	2 3/4	CC-8	4000	Box	12
			S4808 ▲	36PAR36/CAP/NSP	NSP 13	12	3500	2 3/4	CC-8	4000	Box	12
			S4809	36PAR36/CAP/WFL	WFL 32	12	1000	2 3/4	CC-8	4000	Box	12
50	PAR36	MP2	S4806 ▲	50PAR36/CAP/NSP	NSP 6	12	25000	2 3/4	CC-8	4000	Box	12
			S4804 ▲	50PAR36/WFL	WFL 30	12	-	2 3/4	C-6	2000	Box	12

## PAR56 and PAR64

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Beam Pattern	Volts	CBCP	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Carton
300	PAR56	Mog. End Pr.	S4810 ▲	300PAR56/MFL	MFL 22	120	24000	5	CC-13	3850	2000	Box	12
			S4811 ▲	300PAR56/WFL	WFL 37	120	11000	5	CC-13	3850	2000	Box	12
500	PAR56	Mog. End Pr.	S4668 ▲	500PAR56Q/NSP	NSP 15	120	78500	5	CC-6	-	4000	Box	12
			S4669 ▲	500PAR56Q/MFL	MFL 30	120	40000	5	CC-6	-	4000	Box	12
			S4670 ▲	500PAR56Q/WFL	WFL 45	120	19500	5	CC-6	-	4000	Box	12
1000	PAR64	Mog. End Pr.	S4671 ▲	1000PAR64Q/NSP	NSP 20	120	135000	6	CC-6	-	4000	Box	6
			S4672 ▲	1000PAR64Q/MFL	MFL 30	120	82000	6	CC-6	-	4000	Box	6
			S4673 ▲	1000PAR64Q/WFL	WFL 60	120	23000	6	CC-6	-	4000	Box	6

### General Halogen Notes

▲ = Product by one of the Primary lamp manufacturers  
 † = To be discontinued when inventory is depleted due to legislation requirements.

CD/1 = Carded or Clamshell – 1 lamp per card  
 CD/2 = Carded or Clamshell – 2 lamps per card  
 CD/4 = Carded or Clamshell – 4 lamps per card

### Open Fixture Warning

Unless otherwise stated, all non-enclosed halogen lamps carry the following warning, A suitable protective shield, screening technique, or both must be used to protect people and surroundings from the possibility of a lamp shattering and from possible ultraviolet radiation. Enclosed halogen lamps include PAR and BR lamps, A, T10 Double Envelope, and BT15 lamps, Lensed MR11 and MR16 lamps, and BallLites.

### Incandescent Notes

- Krypton/Xenon filled lamps provide bright white light similar to Halogen, without a UV hazard. These lamps are fully dimmable without performance loss.
- Extra tall lamp, with a porcelain spacer designed to create distance between the heat of the filament and the fixture socket. These lamps are primarily used in high-end Euro. import fixtures.

- Commercial grade product.
- Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.
- These lamps feature a frosted reflector and frosted integral cover glass, designed for decorative glass pendant fixtures. They provide light in all directions, without the striations of backlight color common to MR16 lamps.
- Features an aluminized reflector, creating consistent color over the life of the lamp. Heat is transmitted out the front of the lamp.
- Features a hard coated dichroic reflector, creating consistent color over the life of the lamp. Heat is transmitted through the back of the reflector.
- Features MR16 IR technology, increasing light output, or saving energy. The hard coated dichroic reflector creates consistent color over the life of the lamp. Heat is transmitted through the back of the reflector.
- High Performance PAR lamps, feature a spiral reflector/lens system providing a smoother uniform beam pattern, with superior beam control and sharp cutoff of light.
- Primarily used in automotive and linear lighting applications.
- Primarily used in automotive applications. Also used in Tizio desk lamps manufactured prior to 1993.

# INCANDESCENT LAMPS



Nuvo Lighting's Laguna two-tier, nine light chandelier in Aged Bronze with white glass. Nuvo item number 60-5929. [www.nuvolighting.com](http://www.nuvolighting.com)

## Enduring solutions.

Incandescent lamps represent the original lighting technology, remaining virtually unchanged since their invention in the mid-19th century, and the lighting technology Satco was founded upon. This is the technology most everyone has become familiar with and the baseline comparison for all other lighting technologies. As the incandescent bulb becomes more and more regulated, Satco remains on the cutting edge of new lighting technologies. Still, we remain well-stocked with incandescent lamps in a multitude of wattages, base sizes, and shapes for every application.


### Incandescent lamp features:

- High lumen output
- Up to 5,000 hour life
- Virtually every size and style imaginable
- Wattages from 3 to 500 Watts
- Durable vibration and rough service products
- Colored and special application types



Nuvo Lighting's Neval five light chandelier in Brushed Nickel with Satin White Glass. Nuvo item number 60-5485. See the [www.nuvolighting.com](http://www.nuvolighting.com) website.


# INCANDESCENT



## Vintage Style Incandescent Lamps

Bulb Type	Watts	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton
<b>A15</b>	40	Med.	<b>S2424</b>	40A15/CL/11S/120V/Vint.	120	Clear	3 5/8	Cage Style	160	3000	Box	50/10
<b>A19</b>	25	Med.	<b>S2411</b>	25A19/CL/120V/Vint.	120	Clear	4 1/2	Quad Loop	100	3000	Box	48/6
	40	Med.	<b>S2412</b>	40A19/CL/120V/Vint.	120	Clear	4 1/2	Quad Loop	160	3000	Box	48/6
	60	Med.	<b>S2419</b>	60A19/CL/120V/Vint.	120	Clear	4 1/2	Quad Loop	240	3000	Box	48/6
<b>CA8</b>	25	Cand.	<b>S2418</b>	25CFC/7S/120V/Vint.	120	Clear	5	Deco Carbon	100	3000	Box	50/10
<b>G25</b>	40	Med.	<b>S2425</b>	40G25/CL/15S/120V/Vint.	120	Clear	4 3/4	Cage Style	160	3000	Box	48/6
<b>ST19</b>	40	Med.	<b>S2413</b>	40ST19/CL/15S/120V/Vint.	120	Clear	5 3/16	Cage Style	160	3000	Box	48/6
			<b>S2414</b>	40ST19/CL/9S/120V/Vint.	120	Clear	5 3/16	Hairpin	160	3000	Box	48/6
	60	Med.	<b>S2423</b>	60ST19/CL/15S/120V/Vint.	120	Clear	5 3/16	Cage Style	240	3000	Box	48/6
<b>T14</b>	40	Med.	<b>S2416</b>	40T14/CL/32S/120V/Vint.	120	Clear	4 1/4	Spiral	160	3000	Box	50/10
			<b>S2417</b>	40T14/CL/15S/120V/Vint.	120	Clear	4 1/4	Cage Style	160	3000	Box	50/10
<b>T9</b>	20	Med.	<b>S2415</b>	20T9/CL/120V/Vint.	120	Clear	5 1/2	Hairpin	80	3000	Box	48/6
	40	Cand.	<b>S2420</b>	40T9/GLD/9S/E12/120V/Vint.	120	Clear Gold	3 1/2	Cage Style	160	3000	Box	50/10
		Med.	<b>S2426</b>	40T9/CL/120V/Vint.	120	Clear	5 1/2	Hairpin	160	3000	Box	50/10
		Med.	<b>S2421</b>	40T9/CL/12S/120V/Vint.	120	Clear	7 5/16	Hairpin	160	3000	Box	50/10
	60	Med.	<b>S2422</b>	60T9/CL/12S/120V/Vint.	120	Clear	7 5/16	Hairpin	240	3000	Box	50/10






## Incandescent Lamps

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton
<b>3</b>	BA9 1/2	Cand.	<b>S3659</b>	3BA9 1/2/Flicker	120	Clear	3 1/2	Neon	—	1000	Box	500/25
			<b>S3759</b>	3BA9 1/2/Flicker	120	Clear	3 1/2	Neon	—	1000	CD/1	120/12
	CA5 1/2	Cand.	<b>S3661</b>	3CA5 1/2/Flicker	120	Clear	3 1/4	Neon	—	1000	Box	500/25
			<b>S3761</b>	3CA5 1/2/Flicker	120	Clear	3 1/4	Neon	—	1000	CD/1	120/12
	CA8	Cand.	<b>S3656</b>	3CA8/Flicker	120	Clear	3 7/8	Neon	—	1000	Box	500/25
			<b>S3756</b>	3CA8/Flicker	120	Clear	3 7/8	Neon	—	1000	CD/1	120/12
	BA9 1/2	Med.	<b>S3660</b>	3BA9 1/2/Flicker	120	Clear	4 1/6	Neon	—	1000	Box	500/25
	CA9	Med.	<b>S3760</b>	3CA9/Flicker	120	Clear	4 1/6	Neon	—	1000	CD/1	120/12
	CA10	Med.	<b>S3657</b>	3CA10/Flicker	120	Clear	4 1/6	Neon	—	1000	Box	500/25
			<b>S3757</b>	3CA10/Flicker	120	Clear	4 1/6	Neon	—	1000	CD/1	120/12
S6	Cand.	<b>S4567</b> ■	356/5	130	Clear	1 7/8	C-6	10	1500	Sleeve/10	10	
<b>4</b>	C7	Cand.	<b>S3680</b>	4C7	120	Clear	2 1/8	C-7A	16	3000	Bulk	2000/50
			<b>S4724</b>	4C7	120	Clear	2 1/8	C-7A	16	3000	CD/4	48/12
			<b>S3681</b>	4C7/W	120	White	2 1/8	C-7A	8	3000	Bulk	2000/50
<b>5</b>	C7	Cand.	<b>S4520</b> ■	5C7	120	Silicone Tail	2 1/2+	C-7A	10	1000	CD/2	144/12
<b>6</b>	S6	Cand.	<b>S4568</b> ■	6S6/6V	6	Clear	1 7/8	C-6	40	1500	Sleeve/10	10
			<b>S4569</b> ■	6S6/12V	12	Clear	1 7/8	C-6	40	1500	Sleeve/10	10
			<b>S4570</b> ■	6S6/24V	24	Clear	1 7/8	C-6	40	1500	Sleeve/10	10
			<b>S4571</b> ■	6S6/48V	48	Clear	1 7/8	C-6	40	1500	Sleeve/10	10
			<b>S3900</b>	6S6	130	Clear	1 7/8	C-7A	30	2500	Sleeve/10	120/10
			<b>S4717</b>	6S6	130	Clear	1 7/8	C-7A	30	2500	CD/2	120/12
	DC Bay.	<b>S3901</b>	6S6/DC	130	Clear	1 7/8	C-7A	30	2500	Sleeve/10	120/10	
Cand.	<b>S4572</b> ■	6S6/230V	230	Clear	1 7/8	C-7A	25	1500	Sleeve/10	10		
<b>7</b>	C7	Cand.	<b>S3691</b>	7C7	120	Clear	2 1/8	C-7A	35	3000	Bulk	2000/25
			<b>S3791</b>	7C7	120	Clear	2 1/8	C-7A	35	3000	CD/2	400/20
			<b>S4725</b>	7C7	120	Clear	2 1/8	C-7A	35	3000	CD/4	48/12
			<b>S3902</b>	7C7	130	Clear	1 7/8	C-7A	35	2500	Sleeve/10	120/10
			<b>S3692</b>	7C7/W	120	White	2 1/8	C-7A	28	3000	Bulk	2000/25
			<b>S3792</b>	7C7/W	120	White	2 1/8	C-7A	28	3000	CD/2	400/20
	<b>S4726</b>	7C7/W	120	White	2 1/8	C-7A	28	3000	CD/4	48/12		
CA10	Cand.	<b>S3866</b>	7CA10/12V	12	Clear	4 1/4	CC-2V	65	1500	Box	500/25	

NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.


# INCANDESCENT



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	
<b>7.5</b>	BA9 1/2	Cand.	<b>S4994</b>	7 1/2BA9 1/2	120	Clear	3 1/2	C-7A	37	3000	Bulk	500/25	
	C-9 1/2	Cand.	<b>S4988</b>	7 1/2C-9 1/2	120	Clear	3 1/2	C-7A	37	3000	Bulk	500/25	
	CA5	Cand.	<b>S3241</b>	7 1/2CA5	120	Clear	2 7/8	C-7A	40	1500	Box	2000/50	
			<b>S3242</b>	7 1/2CA5/F	120	Frost	2 7/8	C-7A	35	1500	Box	2000/50	
			<b>S3243</b>	7 1/2CA5/FY	120	Yellow	2 7/8	C-7A	35	1500	Box	2000/50	
	S11	Med.	<b>S3606</b>	7 1/2S11	120	Clear	2 1/4	C-7A	40	2500	Sleeve	1000/25	
			<b>S3794</b>	7 1/2S11	120	Clear	2 1/4	C-7A	40	2500	CD/1	240/20	
			<b>S3607</b>	7 1/2S11/W	120	Gloss White	2 1/4	C-7A	20	2500	Sleeve	1000/25	
			<b>S3795</b>	7 1/2S11/W	120	Gloss White	2 1/4	C-7A	20	2500	CD/1	240/20	
			<b>S3608</b>	7 1/2S11/B	120	Cer. Blue	2 1/4	C-7A	-	2500	Sleeve	1000/25	
			<b>S4508</b>	7 1/2S11/B	120	Cer. Blue	2 1/4	C-7A	-	2500	CD/1	120/10	
			<b>S3609</b>	7 1/2S11/G	120	Cer. Green	2 1/4	C-7A	-	2500	Sleeve	1000/25	
			<b>S4509</b>	7 1/2S11/G	120	Cer. Green	2 1/4	C-7A	-	2500	CD/1	120/10	
			<b>S3610</b>	7 1/2S11/O	120	Cer. Orange	2 1/4	C-7A	-	2500	Sleeve	1000/25	
			<b>S4510</b>	7 1/2S11/O	120	Cer. Orange	2 1/4	C-7A	-	2500	CD/1	120/10	
			<b>S3611</b>	7 1/2S11/R	120	Cer. Red	2 1/4	C-7A	-	2500	Sleeve	1000/25	
			<b>S4511</b>	7 1/2S11/R	120	Cer. Red	2 1/4	C-7A	-	2500	CD/1	120/10	
	<b>S4512</b>	7 1/2S11/Y	120	Cer. Yellow	2 1/4	C-7A	-	2500	CD/1	120/10			
	<b>10</b>	C7	Cand.	<b>S3903</b>	10C7	130	Clear	2 1/8	C-7A	60	2500	Sleeve/10	120/10
				<b>S3904</b>	10C7/DC	130	Clear	2 1/8	C-7A	60	2500	Sleeve/10	120/10
CA7		Cand.	<b>S3272</b>	10CA7	120	Clear	3	C-7A	80	1500	Box	1000/25	
			<b>S3276</b>	10CA7/F	120	Frost	3	C-7A	70	1500	Box	1000/25	
G8		Cand.	<b>S3864</b>	10G8/W	120	Gloss White	1 7/8	C-7A	50	1500	Box	1000/25	
G12 1/2 Pear		Cand.	<b>S3844</b>	10G12 1/2	120	Clear	2 3/8	C-7A	60	1500	Box	500/25	
			<b>S3830</b>	10G12 1/2/W	120	Satin White	2 3/8	C-7A	50	1500	Box	500/25	
G12 1/2		Cand.	<b>S3836</b>	10G12 1/2/A	120	Trans. Amber	2 3/8	C-7A	-	1500	Box	500/25	
			<b>S3834</b>	10G12 1/2/B	120	Trans. Blue	2 3/8	C-7A	-	1500	Box	500/25	
			<b>S3835</b>	10G12 1/2/G	120	Trans. Green	2 3/8	C-7A	-	1500	Box	500/25	
			<b>S3837</b>	10G12 1/2/PK	120	Trans. Pink	2 3/8	C-7A	-	1500	Box	500/25	
			<b>S3833</b>	10G12 1/2/R	120	Trans. Red	2 3/8	C-7A	-	1500	Box	500/25	
S11		Inter.	<b>S3621</b>	10S11/N	120	Clear	2 3/8	C-7A	80	1500	Box	600/10	
			<b>S3622</b>	10S11/N/F	120	Frost	2 3/8	CC-2V	80	1500	Box	600/10	

NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.






Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton
<b>11</b>	S14	Med.	<b>S3965</b>	11S14	130	Clear	3 ½	CC-9	80	2500	Sleeve/4	120/4
			<b>S4565</b>	11S14	130	Clear	3 ½	CC-9	80	2500	CD/1	120/10
			<b>S3966</b>	11S14/F	130	Frost	3 ½	CC-9	65	2500	Sleeve/4	120/4
			<b>S4566</b>	11S14/F	130	Frost	3 ½	CC-9	65	2500	CD/1	120/10
			<b>S3963</b>	11S14/B	130	Cer. Blue	3 ½	CC-9	–	2500	Sleeve/4	120/4
			<b>S4563</b>	11S14/B	130	Cer. Blue	3 ½	CC-9	–	2500	CD/1	120/10
			<b>S3962</b>	11S14/G	130	Cer. Green	3 ½	CC-9	–	2500	Sleeve/4	120/4
			<b>S4562</b>	11S14/G	130	Cer. Green	3 ½	CC-9	–	2500	CD/1	120/10
			<b>S3964</b>	11S14/O	130	Cer. Orange	3 ½	CC-9	–	2500	Sleeve/4	120/4
			<b>S4564</b>	11S14/O	130	Cer. Orange	3 ½	CC-9	–	2500	CD/1	120/10
			<b>S3961</b>	11S14/R	130	Cer. Red	3 ½	CC-9	–	2500	Sleeve/4	120/4
			<b>S4561</b>	11S14/R	130	Cer. Red	3 ½	CC-9	–	2500	CD/1	120/10
			<b>S3960</b>	11S14/Y	130	Cer. Yellow	3 ½	CC-9	–	2500	Sleeve/4	120/4
			<b>S4560</b>	11S14/Y	130	Cer. Yellow	3 ½	CC-9	–	2500	CD/1	120/10
<b>15</b>	A15	Med.	<b>S3948</b>	15A15	130	Clear	3 ½	C-9	100	2500	Sleeve/2	120/2
			<b>S3949</b>	15A15/F	130	Frost	3 ½	C-9	100	2500	Sleeve/2	120/2
	B8	Cand.	<b>S3345</b>	15B8/Petite	130	Clear	3	C-7A	114	1500	Box	500/25
			<b>S3230</b>	15BA9 1/2	120	Clear	3 ½	C-7A	114	1500	Box	500/25
	BA9 1/2	Cand.	<b>S3291</b>	15BA9 1/2/F	120	Frost	3 ½	C-7A	114	1500	Box	500/25
			<b>A3620</b>	15BA9 1/2	130	Clear	3 ½	C-7A	114	2500	Box	500/25
	CA8	Cand.	<b>S3273</b>	15CA8	120	Clear	3 ⅝	C-7A	100	1500	Box	500/25
			<b>S3773</b>	15CA8	120	Clear	3 ⅝	C-7A	100	1500	CD/2	120/10
			<b>A3673</b>	15CA8	130	Clear	3 ⅝	C-7A	95	2500	Box	500/25
			<b>S3277</b>	15CA8/F	120	Frost	3 ⅝	C-7A	95	1500	Box	500/25
			<b>S3777</b>	15CA8/F	120	Frost	3 ⅝	C-7A	95	1500	CD/2	120/10
			<b>A3677</b>	15CA8/F	130	Frost	3 ⅝	C-7A	90	2500	Box	500/25
	CA10	Cand.	<b>S3867</b>	15CA10/12V	12	Clear	4 ¼	CC-2V	150	1500	Box	500/25
	F10	Cand.	<b>S3360</b>	15F10	120	Clear	3 ⅙	C-7A	110	1500	Box	500/25
			<b>S2760</b>	15F10	120	Clear	3 ⅙	C-7A	110	1500	CD/2	120/12
			<b>S3361</b>	15F10/W	120	White	3 ⅙	C-7A	90	1500	Box	500/25
			<b>S2761</b>	15F10/W	120	White	3 ⅙	C-7A	90	1500	CD/2	120/2
	G12 1/2	Cand.	<b>S3845</b>	15G12 1/2	120	Clear	2 ⅜	C-7A	100	1500	Box	500/25
	G12 1/2 Pear	Cand.	<b>S3879</b>	15G12 1/2/W	120	Satin White	2 ⅜	C-7A	100	1500	Box	500/25
			<b>S3750</b>	15G12 1/2/W	120	Satin White	2 ⅜	C-7A	100	1500	CD/2	120/10


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.

# INCANDESCENT



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
15	G16 1/2	Cand.	<b>S3821</b>	15G16 1/2	120	Clear	3	C-7A	114	1500	Box	500/25	
			<b>S3726</b>	15G16 1/2	120	Clear	3	C-7A	114	1500	CD/2	120/10	
			<b>S3824</b>	15G16 1/2/W	120	Satin White	3	C-7A	94	1500	Box	500/25	
			<b>S3752</b>	15G16 1/2/W	120	Satin White	3	C-7A	94	1500	CD/2	120/10	
			<b>A3921</b>	15G16 1/2	130	Clear	3	C-7A	98	2500	Box	500/25	
			<b>A3924</b>	15G16 1/2/W	130	Satin White	3	C-7A	83	2500	Box	500/25	
	Pygmy	Euro.	<b>S7939</b>	15T8/120V/E14	120	Clear	2 ¼	C-5A	100	1000	Box	25	
			<b>S7941</b>	15T8/220V/E14	220	Clear	2 ¼	C-5A	100	1000	Box	25	
			<b>S7945</b>	15E14/130V/Oven	130	Clear	2	—	—	10000	Box	1000/50	
	S11	Inter.	<b>S3628</b>	15S11/N	120	Clear	2 ¾	C-7A	100	1500	Box	600/10	
	T4 1/2	Cand.	<b>S3913</b>	15T4 1/2/C	130	Clear	1 ½	C-7A	90	1000	Sleeve/10	10	5
	T6	Cand.	<b>S3315</b>	15T6/F	120	Frost	4	C-5A	90	2500	Sleeve	500/25	5
			<b>S3715</b>	15T6/F	120	Frost	4	C-5A	90	2500	CD/2	72/6	5
			<b>S3910</b>	15T6	130	Clear	3 ¼	C-5A	95	2500	Sleeve/10	120/10	
			<b>S3912</b>	15T6/145V	145	Clear	3 ¼	C-5A	90	2000	Sleeve/10	120/10	
			<b>S4727</b>	15T6/145V	145	Clear	3 ¼	C-5A	90	2000	CD/1	120/10	
	T7	Cand.	<b>S3905</b>	15T7C	130	Clear	2 ¼	C-5A	95	2500	Sleeve/10	120/10	
			<b>S4718</b>	15T7C	130	Clear	2 ¼	C-5A	95	2500	CD/1	120/12	
DC Bay.		<b>S3906</b>	15T7/DC	130	Clear	2 ¼	C-5A	95	2500	Sleeve/10	120/10		
		<b>S4719</b>	15T7/DC	130	Clear	2 ¼	C-5A	95	2500	CD/1	120/12		
Inter.		<b>S3911</b>	15T7/N	130	Clear	2 ¼	C-5A	95	2500	Sleeve/10	120/10		
		<b>S4722</b>	15T7/N	130	Clear	2 ¼	C-5A	95	2500	CD/1	120/12		
20	R12	SC Bay.	<b>S1383</b>	1383	13	—	2 ¾	C-6	—	300	Box	10	
	<b>Shatter Proof</b>		<b>S3618</b>	1383/TF	13	—	2 ¾	C-6	—	300	Box	10	
	T6 1/2	DC Bay.	<b>S3297</b>	20T6 1/2DC	130	Clear	5 ¾	C-6	150	1500	Box	500/25	
			<b>S3298</b>	20T6 1/2DC/F	130	Frost	5 ¾	C-6	140	1500	Box	500/25	
	Inter.	<b>S3280</b>	20T6 1/2N	130	Clear	5 ¾	C-6	150	1500	Box	500/25		
		<b>S3281</b>	20T6 1/2N/F	130	Frost	5 ¾	C-6	140	1500	Box	500/25		
	T9	Med.	<b>S2415</b>	20T9/CL/120V/Vint.	120	Clear	5 ½	Hairpin	80	3000	Box	48/6	
	25	A15	Med.	<b>S3814</b>	25A15/CL	130	Clear	3 ½	C-9	150	2500	Box	500/25
<b>S3815</b>				25A15/F	130	Frost	3 ½	C-9	150	2500	Box	500/25	
<b>Shatter Proof</b>		<b>S4880</b>	25A15/TF	130	Frost	3 ½	C-9	120	2500	Box	500/25	4	
A19		Med.	<b>S5010</b>	25A19/F/12V	12	Frost	4 ¾	C-6	250	1500	Box	120/6	
			<b>S5020</b>	25A19/F/34V	34	Frost	4 ¾	C-6	250	1500	Box	120/6	
			<b>S6040</b>	25A19/CL	120	Clear	4 ¾	C-9	185	1500	2pk	120	
<b>S3940</b>	25A19/CL	130	Clear	4 ¾	CC-6	170	2500	2pk	120				


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes	
25	A19	Med.	<b>S3950</b>	25A19/F	130	Frost	4 1/8	CC-6	180	2500	2pk	120		
			<b>S6050</b>	25A19/F	120	Frost	4 1/8	C-9	180	1500	2pk	120		
			<b>S2411</b>	25A19/CL/120V Vint.	120	Clear	4 1/2	Quad Loop	100	3000	Box	48/6		
			<b>S6092</b>	25A/B	130	Cer. Blue	4 1/8	C-9	—	1000	Sleeve	24/12		
			<b>S6091</b>	25A/G	130	Cer. Green	4 1/8	C-9	—	1000	Sleeve	24/12		
			<b>S6090</b>	25A/R	130	Cer. Red	4 1/8	C-9	—	1000	Sleeve	24/12		
			<b>S6093</b>	25A/Y	130	Cer. Yellow	4 1/8	C-9	—	1000	Sleeve	24/12		
			<b>S6082</b>	25A/TB	130	Trans. Blue	4 1/8	C-9	—	2000	Sleeve	24/12		
			<b>S6081</b>	25A/TG	130	Trans. Green	4 1/8	C-9	—	2000	Sleeve	24/12		
			<b>S6080</b>	25A/TR	130	Trans. Red	4 1/8	C-9	—	2000	Sleeve	24/12		
				<b>S6083</b>	25A/TY	130	Trans. Yellow	4 1/8	C-9	—	2000	Sleeve	24/12	
		B8	Cand.	<b>S3346</b>	25B8/Petite	130	Clear	3	CC-2V	212	1500	Box	500/25	
		B10	Cand.	<b>S3386</b>	25B10/220V	220	Clear	3 3/4	CC-2F	200	1000	Box	500/25	
			Euro.	<b>S3393</b>	25B10/220V	220	Clear	3 3/4	CC-2F	200	1000	Box	500/25	
		B11	Med.	<b>S3231</b>	25B11	120	Clear	3 7/8	CC-2V	210	1500	Box	500/25	
				<b>S3731</b>	25B11	120	Clear	3 7/8	CC-2V	210	1500	CD/2	120/10	
				<b>S3234</b>	25B11/F	120	Frost	3 7/8	CC-2V	200	1500	Box	500/25	
				<b>S3734</b>	25B11/F	120	Frost	3 7/8	CC-2V	200	1500	CD/2	120/10	
				<b>S3237</b>	25B11/W	120	White	3 7/8	CC-2V	150	1500	Box	500/25	
				<b>S3737</b>	25B11/W	120	White	3 7/8	CC-2V	150	1500	CD/2	120/10	
	<b>A3631</b>			25B11	130	Clear	3 7/8	CC-2V	210	2500	Box	500/25		
	<b>A3634</b>			25B11/F	130	Frost	3 7/8	CC-2V	200	2500	Box	500/25		
	<b>A3637</b>			25B11/W	130	White	3 7/8	CC-2V	160	2500	Box	500/25		
					<b>S3282</b>	25BA9 1/2	120	Clear	3 1/2	CC-2V	212	1500	Box	500/25
			<b>S3782</b>	25BA9 1/2	120	Clear	3 1/2	CC-2V	212	1500	CD/2	120/10		
			<b>S4995</b>	KR25BA9 1/2	120	Clear	3 7/8	CC-2V	212	2500	Box	500/25	1	
			<b>A3682</b>	25BA9 1/2	130	Clear	3 1/2	CC-2V	193	2500	Box	500/25		
			<b>S3285</b>	25BA9 1/2/F	120	Frost	3 1/2	CC-2V	212	1500	Box	500/25		
			<b>S3785</b>	25BA9 1/2/F	120	Frost	3 1/2	CC-2V	212	1500	CD/2	120/10		
			<b>A3685</b>	25BA9 1/2/F	130	Frost	3 1/2	CC-2V	193	2500	Box	500/25		
			<b>S3288</b>	25BA9 1/2/W	120	Gloss White	3 1/2	CC-2V	180	1500	Box	500/25		
			<b>S3788</b>	25BA9 1/2/W	120	Gloss White	3 1/2	CC-2V	180	1500	CD/2	120/10		
			<b>A3688</b>	25BA9 1/2/W	130	Gloss White	3 1/2	CC-2V	163	2500	Box	500/25		
			<b>S3813</b>	25BA9 1/2/A	120	Trans. Amber	3 1/2	CC-2V	—	1500	Box	500/25		
			<b>S3218</b>	25BA9 1/2/B	120	Trans. Blue	3 1/2	CC-2V	—	1500	Box	500/25		
			<b>S3219</b>	25BA9 1/2/R	120	Trans. Red	3 1/2	CC-2V	—	1500	Box	500/25		


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.

# INCANDESCENT



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
25	BA9 1/2	Euro.	<b>S3390</b>	25BA9 1/2	120	Clear	3 1/2	CC-2V	220	1500	Box	500/25	
			<b>S4711</b>	25BA9 1/2	120	Clear	3 1/2	CC-2V	220	1500	CD/2	120/12	
			<b>S3380</b>	25BA9 1/2/F	120	Frost	3 1/2	CC-2V	220	1500	Box	500/25	
			<b>S4714</b>	25BA9 1/2/F	120	Frost	3 1/2	CC-2V	220	1500	CD/2	120/10	
	C11	Cand.	<b>S3403</b>	25C11	120	Satin Spun	4	C-7A	160	4000	Box	500/25	
			<b>S2703</b>	25C11	120	Satin Spun	4	C-7A	160	4000	CD/1	120/10	
			<b>S3406</b>	25C11/A	120	Amber Spun	4	C-7A	–	4000	Box	500/25	
			<b>S2706</b>	25C11/A	120	Amber Spun	4	C-7A	–	4000	CD/1	120/10	
	C15	Med.	<b>S2713</b>	25C15	120	Satin Spun	4 1/2	C-9	160	4000	CD/1	120/12	
			<b>S3413</b>	25C15	120	Satin Spun	4 1/2	C-9	160	4000	Box	300/25	
	CA8	Cand.	<b>S3274</b>	25CA8	120	Clear	3 3/8	CC-2V	210	1500	Box	500/25	
			<b>S3774</b>	25CA8	120	Clear	3 3/8	CC-2V	210	1500	CD/2	120/10	
			<b>A3674</b>	25CA8	130	Clear	3 3/8	CC-2V	210	2500	Box	500/25	
			<b>S3278</b>	25CA8/F	120	Frost	3 3/8	CC-2V	200	1500	Box	500/25	
			<b>S3778</b>	25CA8/F	120	Frost	3 3/8	CC-2V	200	1500	CD/2	120/10	
			<b>A3678</b>	25CA8/F	130	Frost	3 3/8	CC-2V	200	2500	Box	500/25	
			<b>S2418</b>	25CFC/75/120V/Vint.	120	Clear	5	Deco Carbon	100	3000	Box	50/10	
			CA9 1/2	Cand.	<b>S4465</b>	KR25CA9 1/2	120	Clear	3 15/16	CC-2V	212	2500	Box
	CA10	Cand.	<b>S3868</b>	25CA10/12V	12	Clear	4 1/4	CC-2V	250	1500	Box	500/25	
			<b>S3869</b>	25CA10/12V	12	Clear	4 1/4	CC-2V	250	1500	Box	500/25	
Med.		<b>S3264</b>	25CA10	120	Clear	4 1/4	CC-2V	210	1500	Box	500/25		
		<b>S3764</b>	25CA10	120	Clear	4 1/4	CC-2V	210	1500	CD/2	120/10		
		<b>A3664</b>	25CA10	130	Clear	4 1/4	CC-2V	210	2500	Box	500/25		
		<b>S3267</b>	25CA10/F	120	Frost	4 1/4	CC-2V	200	1500	Box	500/25		
		<b>S3767</b>	25CA10/F	120	Frost	4 1/4	CC-2V	200	1500	CD/2	120/10		
		<b>A3667</b>	25CA10/F	130	Frost	4 1/4	CC-2V	200	2500	Box	500/25		
F10	Cand.	<b>S3371</b>	25F10	120	Clear	3 1/16	C-7A	195	1500	Box	500/25		
		<b>S2771</b>	25F10	120	Clear	3 1/16	C-7A	195	1500	CD/2	120/12		
		<b>S3372</b>	25F10/W	120	White	3 1/16	C-7A	185	1500	Box	500/25		
		<b>S2772</b>	25F10/W	120	White	3 1/16	C-7A	185	1500	CD/2	120/12		
		<b>S3374</b>	25F10/A	120	Amber	3 1/16	C-7A	–	1500	Box	500/25		
		<b>S2774</b>	25F10/A	120	Amber	3 1/16	C-7A	–	1500	CD/2	120/12		
		<b>S3373</b>	25F10/AU	120	Aurora	3 1/16	C-7A	190	1500	Box	500/25		
		<b>S2773</b>	25F10/AU	120	Aurora	3 1/16	C-7A	190	1500	CD/2	120/12		


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes	
<b>25</b>	F15	Med.	<b>S3363</b>	25F15	120	Clear	4 ½	CC-9	180	1500	Box	300/25		
			<b>S2763</b>	25F15	120	Clear	4 ½	CC-9	180	1500	CD/2	120/12		
			<b>S3364</b>	25F15/W	120	White	4 ½	CC-9	160	1500	Box	300/25		
			<b>S2764</b>	25F15/W	120	White	4 ½	CC-9	160	1500	CD/2	120/12		
			<b>S3365</b>	25F15/AU	120	Aurora	4 ½	CC-9	165	1500	Box	300/25		
			<b>S2765</b>	25F15/AU	120	Aurora	4 ½	CC-9	165	1500	CD/2	120/10		
				<b>S3366</b>	25F15/A	120	Amber	4 ½	CC-9	–	1500	Box	300/25	
	G12 1/2	Cand.	<b>S3846</b>	25G12 1/2	120	Clear	2 ¾	C-7A	180	1500	Box	500/25		
	G12 1/2 Pear	Cand.	<b>S3863</b>	25G12 1/2/W	120	Satin White	2 ¾	C-7A	180	1500	Box	500/25		
			<b>S3751</b>	25G12 1/2/W	120	Satin White	2 ¾	C-7A	202	1500	CD/2	120/10		
	G16 1/2	Cand.	<b>S3822</b>	25G16 1/2	120	Clear	3	C-7A	232	1500	Box	500/25		
			<b>S3727</b>	25G16 1/2	120	Clear	3	C-7A	232	1500	CD/2	120/10		
			<b>A3922</b>	25G16 1/2	130	Clear	3	C-7A	186	2500	Box	500/25		
			<b>S3260</b>	25G16 1/2/W	120	Gloss White	3	C-7A	175	1500	Box	500/25		
			<b>S3825</b>	25G16 1/2/W	120	Satin White	3	C-7A	202	1500	Box	500/25		
			<b>S3753</b>	25G16 1/2/W	120	Satin White	3	C-7A	202	1500	CD/2	120/2		
			<b>A3925</b>	25G16 1/2/W	130	Satin White	3	C-7A	162	2500	Box	500/25		
			<b>S3244</b>	25G16 1/2/SL	120	Silver Crown	3	CC-2V	232	1500	Box	500/25		
			Med.	<b>S3838</b>	25G16 1/2	120	Clear	3 ¼	CC-2V	220	1500	Box	500/25	
				<b>S4538</b>	25G16 1/2	120	Clear	3 ¼	CC-2V	220	1500	CD/1	500/25	
		<b>S3841</b>	25G16 1/2/W	120	Gloss White	3 ¼	CC-2V	180	1500	Box	500/25			
		<b>S4541</b>	25G16 1/2/W	120	Gloss White	3 ¼	CC-2V	180	1500	CD/1	500/25			
G18 1/2	Med.	<b>S3887</b>	25G18 1/2	120	Clear	3 ½	C-9	180	1500	Box	250/25			
		<b>S3827</b>	25G18 1/2/W	120	Gloss White	3 ½	C-9	160	1500	Box	250/25			
G25	Med.	<b>S3447</b>	25G25	120	Clear	4 ¾	CC-6	180	3000	Box	72/6			
		<b>A3647</b>	25G25	130	Clear	4 ¾	CC-9	180	3000	Box	72/6			
		<b>S3440</b>	25G25/W	120	Gloss White	4 ¾	CC-6	160	3000	Box	72/6			
		<b>A3640</b>	25G25/W	130	Gloss White	4 ¾	CC-6	160	3000	Box	72/6			
		<b>S3860</b>	25G25/SL	120	Silver Crown	4 ¾	C-9	150	1500	Box	72/6			
G30	Med.	<b>S3651</b>	25G30	120	Clear	5 ½	CC-9	180	2500	Box	72/6			
		<b>S3653</b>	25G30/W	120	Gloss White	5 ½	CC-9	150	2500	Box	72/6			
G40	Med.	<b>S3010</b>	25G40	120	Clear	6 ¾	C-9	120	4000	Box	24/6			
		<b>S3000</b>	25G40/W	120	Gloss White	6 ¾	C-9	110	4000	Box	24/6			
HX10.5	Cand.	<b>S3744</b>	25HX10 1/2	120	Clear	4 15/16	C-7A	175	1500	CD/2	120/12			


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.

# INCANDESCENT



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton
<b>25</b>	Pygmy	Euro.	<b>S7940</b>	25T8/120V/E14	120	Clear	2 ¼	C-5A	180	1000	Box	25
			<b>S7942</b>	25T8/220V/E14	220	Clear	2 ¼	C-5A	200	1000	Box	25
	R14	Inter.	<b>S3205</b>	25R14N	120	Frost	2 ¾	CC-2V	135	1500	Box	500/25
			<b>S4700</b>	25R14N	120	Frost	2 ¾	CC-2V	135	1500	CD/1	120/10
		Med.	<b>S3604</b>	25R14	120	Frost	2 ¾	CC-2V	135	1500	Box	500/25
			<b>S4704</b>	25R14	120	Clear	2 ¾	CC-2V	135	1500	CD/1	120/10
	R14 Stubby		<b>S3601</b>	25R14	120	Clear	2 ¼	CC-2V	135	1500	Box	500/25
	S11	Inter.	<b>S3630</b>	25S11/N	–	Clear	2 ¾	CC-2V	210	1500	Box	600/10
			<b>S3718</b>	25S11/CL/E17/CD	120	Clear	2 ½	CC-2V	220	1500	CD/1	120/10
	T6	Cand.	<b>S3714</b>	25T6/CL/E12/CD	120	Clear	3 ¾	C-5A	180	2000	CD/1	120/10
	T6 1/2	DC Bay.	<b>S3248</b>	25T6 1/2/DC	130	Clear	5 ¾	C-8	180	1500	Box	500/25
			<b>S3711</b>	25T6 1/2/DC	130	Clear	5 ¾	C-8	180	1500	CD/1	120/10
			<b>S3249</b>	25T6 1/2/DC/F	130	Frost	5 ¾	C-8	170	1500	Box	500/25
			<b>S3713</b>	25T6 1/2/DC/F	130	Frost	5 ¾	C-8	170	1500	CD/1	120/10
		Inter.	<b>S3222</b>	25T6 1/2N	130	Clear	5 ¾	C-8	180	1500	Box	500/25
			<b>S3709</b>	25T6 1/2N	130	Clear	5 ¾	C-8	180	1500	CD/1	120/10
			<b>S3223</b>	25T6 1/2N/F	130	Frost	5 ¾	C-8	170	1500	Box	500/25
			<b>S3708</b>	25T6 1/2N/F	130	Frost	5 ¾	C-8	170	1500	CD/1	120/10
	T8	Cand.	<b>S3907</b>	25T8/C	130	Clear	2 ¾	C-5A	190	2500	Sleeve/10	120/10
			<b>S3909</b>	25T8/DC	130	Clear	2 ¾	C-5A	190	2500	Sleeve/10	120/10
DC Bay.		<b>S4721</b>	25T8/DC	130	Clear	2 ¾	C-5A	190	2500	CD/1	120/12	
		Inter.	<b>S3908</b>	25T8/N	130	Clear	2 ¾	C-5A	190	2500	Sleeve/10	120/10
<b>S4720</b>	25T8/N		130	Clear	2 ¾	C-5A	190	2500	CD/1	120/12		
T10	Med.	<b>S3250</b>	25T10	120	Clear	5	C-5V	200	2000	Box	500/25	
		<b>S3700</b>	25T10	120	Clear	5	C-5V	200	2000	CD/1	120/10	
		<b>S3251</b>	25T10/F	120	Frost	5	C-5V	200	2000	Box	500/25	
		<b>S3701</b>	25T10/F	120	Frost	5	C-5V	200	2000	CD/1	120/10	
<b>30</b>	R20	Med.	<b>S3210</b>	30R20	120	Frost	4	CC-9	185	2000	Sleeve	96/12
			<b>S2810</b>	30R20	130	Frost	4	CC-9	185	2000	Sleeve	96/12
<b>30/70/100</b>	A19	Med.	<b>S1824</b>	30/100A19/W Reduced Size	120	White	4 ¾	CC-8	280/680/960	2500	Sleeve	36/12
	A21	Med.	<b>S1820</b>	30/100A21/W	120	White	5 ¼	CC-2V/C-9	280/680/960	2500	Sleeve	36/12

NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes	
<b>40</b>	A15	Cand.	<b>S2740</b>	40A15/CL/E12	120	Clear	3 3/8	C-9	420	1000	CD/2	120/10		
			<b>S4160</b>	40A15/CL/E12	130	Clear	3 3/8	C-9	420	1000	Box	500/25		
			<b>S2741</b>	40A15/F/E12	120	Frost	3 3/8	C-9	420	1000	CD/2	120/10		
		<b>S4161</b>	40A15/F/E12	130	Frost	3 3/8	C-9	420	1000	Box	500/25			
		Inter.	<b>S2744</b>	40A15/CL/E17	120	Clear	3 3/8	C-9	420	1000	CD/2	120/10		
			<b>S4164</b>	40A15/CL/E17	130	Clear	3 3/8	C-9	420	1000	Box	500/25		
			<b>S2745</b>	40A15/F/E17	120	Frost	3 3/8	C-9	420	1000	CD/2	120/10		
		Med.	<b>S4165</b>	40A15/F/E17	130	Frost	3 3/8	C-9	420	1000	Box	500/25		
			<b>S3989</b>	40A15/230V ECONOBRITE	230	White	3 1/2	C-9	280	2500	Box	500/25		
	<b>S3720</b>		40A15/CL	130	Clear	3 1/2	C-9	290	2500	CD/1	240/20			
	<b>S3810</b>		40A15/CL	130	Clear	3 1/2	C-9	290	2500	Box	500/25			
	<b>S3721</b>		40A15/F	130	Frost	3 1/2	C-9	280	2500	CD/1	240/20			
	<b>S3811</b>		40A15/F	130	Frost	3 1/2	C-9	280	2500	Box	500/25			
	<b>S4881</b>		40A15/TF	130	Frost	3 1/2	C-9	265	2500	Box	500/25	4		
	<b>Shatter Proof</b>			<b>S2424</b>	40A15/CL/11S/120V/Vint.	130	Clear	3 3/8	Cage Style	160	3000	Box	50/10	
		A19	Euro. Bay.	<b>S5030</b>	40A19/F	130	Frost	4 1/8	CC-6	330	2500	Box	120	
		<b>S5040</b>		40A19/F/230V	220	Frost	4 1/8	CC-2F	330	2500	Box	120		
		A19	Med.	<b>S4076</b>	40A19/W/230V	230	White	4 1/8	C-9	327	1000	Box	120	
				<b>S3941</b>	40A19/CL/VS	130	Clear	4 1/8	C-9	300	2500	2pk	120	
<b>S2412</b>				40A19/CL/120V/Vint.	120	Clear	4 1/2	Quad Loop	160	3000	Box	48/6		
<b>S3951</b>				40A19/F/VS	130	Frost	4 1/8	C-9	300	2500	2pk	120		
<b>S4981</b>			40A/B	130	Cer. Blue	4 1/8	C-9	-	2000	Sleeve	24/12			
<b>S4982</b>			40A/G	130	Cer. Green	4 1/8	C-9	-	2000	Sleeve	24/12			
<b>S4980</b>			40A/R	130	Cer. Red	4 1/8	C-9	-	2000	Sleeve	24/12			
<b>S4983</b>			40A/Y	130	Cer. Yellow	4 1/8	C-9	-	2000	Sleeve	24/12			
<b>S3859</b>	40A/Bug	130	Yellow	4 1/8	C-9	-	2000	2pk	24					
B8	Cand.	<b>S3347</b>	40B8/Petite	130	Clear	3	CC-2V	384	1500	Box	500/25			
B10	Cand.	<b>S2971</b> ■	40B10/VLX	120	Full Spec.	3 7/8	CC-2V	370	2000	CD/1	50/10	3		
		<b>S3387</b>	40B10/220V	220	Clear	3 3/4	CC-2F	330	1000	Box	500/25			
		<b>S3385</b>	40B10/F/220V	220	Frost	3 3/4	CC-2F	330	1000	Box	500/25			

NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.




# INCANDESCENT



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes	
40	B10	Euro.	<b>S3394</b>	40B10/220V	220	Clear	3 3/4	CC-2F	330	1000	Box	500/25		
	B10/B11	Med.	<b>S3232</b>	40B11	120	Clear	3 7/8	CC-2V	370	1500	Box	500/25		
			<b>S3732</b>	40B11	120	Clear	3 7/8	CC-2V	370	1500	CD/2	120/10		
			<b>A3632</b>	40B11	130	Clear	3 7/8	CC-2V	370	2500	Box	500/25		
			<b>S4740</b>	40B10/FAN	120	Clear	3 7/8	CC-2V	300	2000	CD/2	120/12		
			<b>S4742</b>	40B10/FAN/F	120	Frost	3 7/8	CC-2V	300	2000	CD/2	120/12		
			<b>S3235</b>	40B11/F	120	Frost	3 7/8	CC-2V	360	1500	Box	500/25		
			<b>S3735</b>	40B11/F	120	Frost	3 7/8	CC-2V	360	1500	CD/2	120/10		
			<b>A3635</b>	40B11/F	130	Frost	3 7/8	CC-2V	360	2500	Box	500/25		
			<b>S3238</b>	40B11/W	120	White	3 7/8	CC-2V	330	1500	Box	500/25		
			<b>S3738</b>	40B11/W	120	White	3 7/8	CC-2V	330	1500	CD/2	120/10		
			<b>A3638</b>	40B11/W	130	White	3 7/8	CC-2V	320	2500	Box	500/25		
			<b>S3384</b>	40B11/220V	220	Clear	3 7/8	CC-2F	330	1000	Box	500/25		
		BA9 1/2	Cand.	<b>S3283</b>	40BA9 1/2	120	Clear	3 1/2	CC-2V	384	1500	Box	500/25	
				<b>S3783</b>	40BA9 1/2	120	Clear	3 1/2	CC-2V	384	1500	CD/2	120/10	
				<b>S4996</b>	KR40BA9 1/2	120	Clear	3 7/8	CC-2V	380	2500	Box	500/25	1
				<b>A3683</b>	40BA9 1/2	130	Clear	3 1/2	CC-2V	384	2500	Box	500/25	
				<b>S3286</b>	40BA9 1/2/F	120	Frost	3 1/2	CC-2V	384	1500	Box	500/25	
				<b>S3786</b>	40BA9 1/2/F	120	Frost	3 1/2	CC-2V	384	1500	CD/2	120/10	
				<b>A3686</b>	40BA9 1/2/F	130	Frost	3 1/2	CC-2V	384	2500	Box	500/25	
			<b>S3289</b>	40BA9 1/2/W	120	White	3 1/2	CC-2V	328	1500	Box	500/25		
			<b>S3789</b>	40BA9 1/2/W	120	White	3 1/2	CC-2V	328	1500	CD/2	120/10		
			<b>A3689</b>	40BA9 1/2/W	130	White	3 1/2	CC-2V	328	2500	Box	500/25		
			<b>S3725</b>	40BA9 1/2/DIA	120	Crystal	3 7/8	CC-2V	370	1500	CD/2	120/10		
			<b>S3818</b>	40BA9 1/2/A	120	Trans. Amber	3 1/2	CC-2V	-	1500	Box	500/25		
		Euro.	<b>S3391</b>	40BA9 1/2	120	Clear	3 1/2	CC-2V	370	1500	Box	500/25		
			<b>S4712</b>	40BA9 1/2	120	Clear	3 1/2	CC-2V	370	1500	CD/2	120/10		
			<b>S3381</b>	40BA9 1/2/F	120	Frost	3 1/2	CC-2V	370	1500	Box	500/25		
			<b>S4715</b>	40BA9 1/2/F	120	Frost	3 1/2	CC-2V	370	1500	CD/2	120/10		
	C11	Cand.	<b>S3404</b>	40C11	120	Satin Spun	4	C-7A	316	4000	Box	500/25		
			<b>S2704</b>	40C11	120	Satin Spun	4	C-7A	316	4000	CD/1	120/12		
	C15	Med.	<b>S3414</b>	40C15	120	Satin Spun	4 1/2	C-7A	316	4000	Box	300/25		
			<b>S2714</b>	40C15	120	Satin Spun	4 1/2	C-7A	316	4000	CD/1	120/12		
			<b>S3416</b>	40C15/A	120	Amber Spun	4 1/2	C-7A	-	4000	Box	300/25		
			<b>S2716</b>	40C15/A	120	Amber Spun	4 1/2	C-7A	-	4000	CD/1	120/12		


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes	
40	CA9 1/2	Cand.	<b>S3275</b>	40CA9 1/2	120	Clear	3 7/8	CC-2V	370	1500	Box	500/25		
			<b>S3775</b>	40CA9 1/2	120	Clear	3 7/8	CC-2V	370	1500	CD/2	120/10		
			<b>S4466</b>	KR40CA9 1/2	120	Clear	3 15/16	CC-2V	380	2500	Box	500/25	1	
			<b>A3675</b>	40CA9 1/2	130	Clear	3 15/16	CC-2V	370	2500	Box	500/25		
			<b>S3279</b>	40CA9 1/2/F	120	Frost	3 15/16	CC-2V	384	1500	Box	500/25		
			<b>S3779</b>	40CA9 1/2/F	120	Frost	3 15/16	CC-2V	384	1500	CD/2	120/10		
	CA10	Med.	<b>A3679</b>	40CA9 1/2/F	130	Frost	3 15/16	CC-2V	350	2500	Box	500/25		
			<b>S3265</b>	40CA10	120	Clear	4 1/4	CC-2V	370	1500	Box	500/25		
			<b>S3765†</b>	40CA10	120	Clear	4 1/4	CC-2V	370	1500	CD/2	120/10		
			<b>A3665</b>	40CA10	130	Clear	4 1/4	CC-2V	360	2500	Box	500/25		
			<b>S3268</b>	40CA10/F	120	Frost	4 1/4	CC-2V	360	1500	Box	500/25		
			<b>S3768</b>	40CA10/F	120	Frost	4 1/4	CC-2V	360	1500	CD/2	120/10		
F15	Med.	<b>A3668</b>	40CA10/F	130	Frost	4 1/4	CC-2V	360	2500	Box	500/25			
		<b>S3367</b>	40F15	120	Clear	4 1/2	CC-9	350	1500	Box	300/25			
		<b>S2767</b>	40F15	120	Clear	4 1/2	CC-9	350	1500	CD/2	120/12			
		<b>S2768</b>	40F15/W	120	White	4 1/2	CC-9	320	1500	CD/2	120/12			
		<b>S3368</b>	40F15/W	120	White	4 1/2	CC-9	320	1500	Box	300/25			
		<b>S3369</b>	40F15/AU	120	Aurora	4 1/2	CC-9	335	1500	Box	300/25			
G12 1/2	Cand.	<b>S2769</b>	40F15/AU	120	Aurora	4 1/2	CC-9	335	1500	CD/2	120/12			
		<b>S3370</b>	40F15/A	120	Amber	4 1/2	CC-9	—	1500	Box	300/25			
		<b>S2770</b>	40F15/A	120	Amber	4 1/2	CC-9	—	1500	CD/2	120/12			
		<b>S3847</b>	40G12 1/2	120	Clear	2 3/8	C-7A	370	1500	Box	500/25			
		G14	Euro.	<b>S3397</b>	40G14	130	Clear	3 1/8	CC-9	370	1500	Box	500/25	
				<b>S4707</b>	40G14	130	Clear	3 1/8	CC-9	370	1500	CD/2	120/10	
<b>S3398</b>	40G14/W			130	Gloss White	3 1/8	CC-9	330	1500	Box	500/25			
<b>S4708</b>	40G14/W			130	Gloss White	3 1/8	CC-9	330	1500	CD/2	120/10			
G16 1/2	Cand.	<b>S3823</b>	40G16 1/2	120	Clear	3	CC-2V	384	1500	Box	500/25			
		<b>S3728</b>	40G16 1/2	120	Clear	3	CC-2V	384	1500	CD/2	120/10			
		<b>A3923</b>	40G16 1/2	130	Clear	3	CC-2V	360	2500	Box	500/25			
		<b>S3754</b>	40G16 1/2/W	120	Satin White	3	CC-2V	348	1500	CD/2	120/10			
		<b>S3826</b>	40G16 1/2/W	120	Satin White	3	CC-2V	348	1500	Box	500/25			
		<b>A3926</b>	40G16 1/2/W	130	Satin White	3	CC-2V	325	2500	Box	500/25			
		<b>S3261</b>	40G16 1/2/W	120	Gloss White	3	CC-2V	348	1500	Box	500/25			
		<b>S2974 ■</b>	40G16 1/2/VLX	120	Full Spectrum	3	CC-2V	370	2000	CD/1	50/10	3		
<b>S3245</b>	40G16 1/2/SL	120	Silver Crown	3	CC-2V	384	1500	Box	500/25					


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.

# INCANDESCENT



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
<b>40</b>	G16 1/2	Med.	<b>S3839</b>	40G16 1/2	120	Clear	3 ¼	CC-2V	370	1500	Box	500/25	
			<b>S4539</b>	40G16 1/2	120	Clear	3 ¼	CC-2V	370	1500	CD/1	120/10	
			<b>S3842</b>	40G16 1/2/W	120	Gloss White	3 ¼	CC-2V	330	1500	Box	500/25	
			<b>S4542</b>	40G16 1/2/W	120	Gloss White	3 ¼	CC-2V	330	1500	CD/1	500/25	
G18 1/2	Med.	<b>S3888</b>	40G18 1/2	120	Clear	3 ½	C-9	340	1500	Box	250/25		
		<b>S3828</b>	40G18 1/2/W	120	Gloss White	3 ½	C-9	300	1500	Box	250/25		
G25	Med.	<b>S3448</b>	40G25	120	Clear	4 ¾	CC-9	360	3000	Box	72/6		
		<b>S4048</b>	40G25/3PK	120	Clear	4 ¾	CC-9	360	3000	3pk	40/3		
		<b>A3648</b>	40G25	130	Clear	4 ¾	CC-6	360	3000	Box	72/6		
		<b>A3644</b>	40G25/220V	220	Clear	4 ¾	CC-9	212	2500	Box	72/6		
		<b>S3441</b>	40G25/W	120	Gloss White	4 ¾	CC-6	320	3000	Box	72/6		
		<b>S4041</b>	40G25/W/3PK	120	Gloss White	4 ¾	CC-6	320	3000	3pk	40/3		
		<b>A3641</b>	40G25/W	130	Gloss White	4 ¾	CC-6	320	3000	Box	72/6		
		<b>A3645</b>	40G25/W/220V	220	Gloss White	4 ¾	CC-9	187	2500	Box	72/6		
		<b>S2425</b>	40G25/CL/155/120V/Vint.	120	Clear	4 ¾	Cage Style	160	3000	Box	48/6		
		<b>S3861</b>	40G25/SL	120	Silver Crown	4 ¾	C-9	280	1500	Box	72/6		
G30	Med.	<b>S3652</b>	40G30	120	Clear	5 ½	CC-9	340	2500	Box	72/6		
		<b>S3671</b>	40G30/W	120	Gloss White	5 ½	CC-9	300	2500	Box	72/6		
G40	Med.	<b>S3011</b>	40G40	120	Clear	6 ¾	C-9	300	4000	Box	24/6		
		<b>S3001</b>	40G40/W	120	Gloss White	6 ¾	C-9	280	4000	Box	24/6		
HX10.5	Cand.	<b>S3745</b>	40HX10 1/2	120	Clear	4 ½	C-7A	360	1500	CD/2	120/12		
R14	Euro.	<b>S3396</b>	40R14/E14	130	Clear	2 ¾	CC-2V	280	1500	Box	500/25		
		<b>S4706</b>	40R14/E14	130	Frost	2 ¾	CC-2V	280	1500	CD/1	120/10		
	Inter.	<b>S3215</b>	40R14N	120	Clear	2 ¾	CC-2V	300	1500	Box	500/25		
		<b>S4701</b>	40R14N	120	Clear	2 ¾	CC-2V	280	1500	CD/1	120/10		
	Med.	<b>S3605</b>	40R14	120	Clear	2 ¾	CC-2V	280	1500	Box	500/25		
		<b>S4705</b>	40R14	120	Clear	2 ¾	CC-2V	280	1500	CD/1	120/10		
	R14 Stubby	Med.	<b>S3602</b>	40R14	120	Clear	2 ¼	CC-2V	280	1500	Box	500/25	
	R16	Med.	<b>S3214</b>	40R16	120	Frost	3 ¾	C-9	330	1500	Box	500/25	
<b>S4702</b>			40R16	120	Frost	3 ¾	C-9	330	1500	CD/1	120/10		
R50	Euro.	<b>S3619</b>	40R50/E14	1250	Frost	3 ¾	C-9	300	1000	Box	500/25		


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
<b>40</b>	S11	Inter.	<b>S3629</b>	40S11/N	120	Clear	2 3/8	CC-2V	370	1500	Box	600/10	
			<b>S3729</b>	40S11/N	-	Clear	2 3/8	CC-2V	370	1500	CD/1	240/20	
	ST19	Med.	<b>S2413</b>	40ST19/CL/15S/120V/Vint.	120	Clear	5 1/4	Hairpin	160	3000	Box	48/6	
			<b>S2414</b>	40ST19/CL/9S/120V/Vint.	120	Clear	5 1/4	Hairpin	160	3000	Box	48/6	
	T6 1/2	Inter.	<b>S3224</b>	40T6 1/2/N	130	Clear	5 3/8	C-8	350	1500	Box	500/25	
			<b>S3710</b>	40T6 1/2/N	130	Clear	5 3/8	C-8	350	1500	CD/1	120/10	
			<b>S3225</b>	40T6 1/2/N/F	130	Frost	5 3/8	C-8	340	1500	Box	500/25	
			<b>S3712</b>	40T6 1/2/N/F	130	Frost	5 3/8	C-8	340	1500	CD/1	120/10	
	T8	Inter.	<b>S3917</b>	40T8N	130	Clear	2 3/8	CC-2V	360	2000	CD/1	120/10	
			<b>S2977</b> ■	40T8	130	Clear	12	C-8	265	2000	Box	10	
	T9	Cand.	<b>S2420</b>	40T9/GOLD/9S/E12/120V/Vint.	120	Clear Gold	3 1/2	Cage Style	160	3000	Box	50/10	
			<b>S2421</b>	40T9/CL/12S/120V/Vint.	120	Clear	7 3/8	Hairpin	160	3000	Box	50/10	
			<b>S2426</b>	40T9/CL/120V/Vint.	120	Clear	5 1/2	Hairpin	160	3000	Box	50/10	
	T10	Med.	<b>S3252</b>	40T10	120	Clear	5	C-5V	280	2000	Box	500/25	
			<b>S3702</b>	40T10	120	Clear	5	C-5V	280	2000	CD/1	120/10	
			<b>S3253</b>	40T10/F	120	Frost	5	C-5V	280	2000	Box	500/25	
			<b>S3703</b>	40T10/F	120	Frost	5	C-5V	280	2000	CD/1	120/10	
	T14	Med.	<b>S2417</b>	40T14/CL/15S/120V/Vint.	120	Clear	4 3/8	Cage Style	160	3000	Box	50/10	
			<b>S2416</b>	40T14/CL/32S/120V/Vint.	120	Clear	4 3/8	Spiral	160	3000	Box	50/10	
	<b>45</b>	R20	Med.	<b>S3229</b>	45R20	120	Frost	4	CC-9	330	2000	Sleeve	96/12
<b>S3849</b>				45R20	130	Frost	4	CC-9	330	2000	Sleeve	96/12	
<b>S8519</b>				45R20/5M	130	Frost	4	C-9	280	5000	Sleeve	60/12	
<b>50</b>	A19	Med.	<b>S5011</b>	50A19/F/12V	12	Frost	4 1/8	C-6	540	1500	Box	120/6	
			<b>S5021</b>	50A19/F/34V	34	Frost	4 1/8	C-6	540	1500	Box	120/6	
			<b>S3969</b>	50A/RS	130	Frost	4 1/8	C-11/5	380	2500	2pk	24	
<b>50/100/150</b>	A21	Med.	<b>S1821</b>	50/150A21/W	120	White	5 3/8	CC-2V/C-9	520/1050/1570	2500	Sleeve	36/12	
			<b>S4823</b> ■	50/150A21/VLX	120	Full Spectrum	5 3/8	C-9	350/910/1260	5000	Box	50/10	3
	PS25	Mog.	<b>S1825</b>	50/150PS25/F	120	Frost	6 3/4	CC-2V/C-9	550/1300/1850	2000	Box	36/12	
<b>50/200/250</b>	A21	Med.	<b>S1823</b>	50/250A21/W	120	White	5 3/8	C-9	640/3300/3940	1500	Sleeve	12	


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.

# INCANDESCENT



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes	
<b>50</b>	BR30	Med.	<b>S3259</b>	50BR30/FL	120	Frost	5 3/8	CC-9	360	2000	Sleeve	96/12		
	ER30	Med.	<b>S4956</b>	50ER30	130	Frost	6 1/8	CC-6	310	2000	Sleeve	24		
<b>Shatter Proof</b>	R20	Med.	<b>S4886</b>	50R20/TF	120	Frost	4	CC-9	300	2000	Sleeve	96/12	4	
			<b>S3203</b>	50R20/A	130	Amber	4	CC-9	—	2000	Sleeve	96/12		
			<b>S3202</b>	50R20/B	130	Blue	4	CC-9	—	2000	Sleeve	96/12		
			<b>S3201</b>	50R20/G	130	Green	4	CC-9	—	2000	Sleeve	96/12		
			<b>S3212</b>	50R20/PK	130	Pink	4	CC-9	—	2000	Sleeve	96/12		
			<b>S3200</b>	50R20/R	130	Red	4	CC-9	—	2000	Sleeve	96/12		
			<b>S2850</b>	50R20/GRO	120	Plant	4	C-9	—	2000	Box	96/12		
			<b>60</b>	A15	Cand.	<b>S4162</b>	60A15/CL/E12	130	Clear	3 3/8	C-9	700	1000	Box
<b>S2742</b>	60A15/CL/E12S	120				Clear	3 3/8	C-9	700	1000	CD/2	120/10		
<b>S4163</b>	60A15/F/E12	130				Frost	3 3/8	C-9	700	1000	Box	500/25		
<b>S2743</b>	60A15/F/E12S	120				Frost	3 3/8	C-9	700	1000	CD/2	120/10		
Med.	<b>S3870</b>	60A15/CL				130	Clear	3 1/2	C-9	580	2500	Box	500/25	
	<b>S3739</b>	60A15/CL				130	Clear	3 1/2	C-9	580	2500	CD/1	240/20	
Med.	<b>S3871</b>	60A15/F		130	Frost	3 1/2	C-9	570	2500	Box	500/25			
	<b>S3740</b>	60A15/F		130	Frost	3 1/2	C-9	570	2500	CD/1	240/20			
	<b>S4882</b>	60A15/TF		130	Frost	3 1/2	C-9	570	2500	Box	500/25	4		
	A19	Euro. Bay.		<b>S5031</b>	60A19/F	130	Frost	4 1/8	CC-6	630	2500	Box	120	
				<b>S5041</b>	60A19/F/230V	230	Frost	4 1/8	CC-2F	630	2500	Box	120	
	Med.	<b>S4077</b>		60A19/W/230V	230	White	4 1/8	C-9	570	1000	Box	120		
<b>S3942</b>		60A19/CL/V5	130	Clear	4 1/8	C-9	580	2500	2pk	120				


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes		
60	A19	Med.	<b>S3952</b>	60A19/F/VS	130	Frost	4 1/8	C-9	580	2500	2pk	120			
			<b>S8522</b>	60A19/RS	130	Frost	4 1/8	C-11/5	440	5000	4pk	120			
			<b>Shatter Proof S3927</b>	60A/RS/TF/2PK	130	Frost	4 1/8	C-9	520	5000	2pk	12/2	4		
			<b>Shatter Proof S3930</b>	60A/RS/TF	130	Frost	4 1/8	C-9	520	5000	Box	12	4		
			<b>S4816</b>	60A19/VLX	120	Full Spectrum	4 1/8	C-9	465	5000	Box	50/10	3		
			<b>S3955</b>	60A/SL	130	Silver Crown	4 1/8	C-9	580	1500	Box	24			
			<b>S2419</b>	60A19/CL/120V/Vint.	120	Clear	4 1/2	Quad Loop	240	3000	Box	48/6			
			<b>S4985</b>	60A/B	130	Cer. Blue	4 1/8	C-9	-	2000	Sleeve	24/12			
			<b>S4986</b>	60A/G	130	Cer. Green	4 1/8	C-9	-	2000	Sleeve	24/12			
			<b>S4984</b>	60A/R	130	Cer. Red	4 1/8	C-9	-	2000	Sleeve	24/12			
			<b>S4987</b>	60A/Y	130	Cer. Yellow	4 1/8	C-9	-	2000	Sleeve	24/12			
			<b>S3938</b>	60A/Bug	130	Yellow	4 1/8	C-9	-	2000	2pk	24			
			B10	Cand.	<b>S3284</b>	60B10	120	Clear	3 3/4	CC-2V	672	1500	Box	500/25	
					<b>S3784</b>	60B10	120	Clear	3 3/4	CC-2V	672	1500	CD/2	120/10	
					<b>S4997</b>	KR60B10	120	Clear	3 7/8	CC-2V	720	2500	Box	500/25	1
<b>A3684</b>	60B10	130			Clear	3 3/4	CC-2V	642	2500	Box	500/25				
<b>S3287</b>	60B10/F	120			Frost	3 3/4	CC-2V	672	1500	Box	500/25				
<b>S3787</b>	60B10/F	120			Frost	3 3/4	CC-2V	672	1500	CD/2	120/10				
<b>A3687</b>	60B10/F	130			Frost	3 3/4	CC-2V	642	2500	Box	500/25				
<b>S3290</b>	60B10/W	120			White	3 3/4	CC-2V	630	1500	Box	500/25				
<b>S3790</b>	60B10/W	120			White	3 3/4	CC-2V	630	1500	CD/2	120/10				
<b>A3690</b>	60B10/W	130			White	3 3/4	CC-2V	564	2500	Box	500/25				
<b>S2972</b>	60B10/VLX	120			Full Spectrum	3 7/8	CC-2V	650	2000	CD/1	50/10	3			
<b>S3388</b>	60B10/220V	220			Clear	3 3/4	CC-2F	650	1000	Box	500/25				
Euro.	<b>S3392</b>	60B10			120	Clear	3 3/4	CC-2V	650	1500	Box	500/25			
	<b>S4713</b>	60B10			120	Clear	3 3/4	CC-2V	650	1500	CD/2	120/10			
	<b>S3382</b>	60B10/F			120	Frost	3 3/4	CC-2V	650	1500	Box	500/25			
	<b>S4716</b>	60B10/F	120	Frost	3 3/4	CC-2V	650	1500	CD/2	120/10					

NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.


# INCANDESCENT



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
<b>60</b>	B10/B11	Med.	<b>S7010</b>	60B11/TF <b>Shatter Proof</b>	130	Frost	3 7/8	CC-2V	600	2500	Box	500/25	
	BA9 1/2	Cand.	<b>S3819</b>	60BA9 1/2/A	120	Trans. Amber	3 1/2	CC-2V	—	1500	Box	500/25	
	C11	Cand.	<b>S3405</b>	60C11	120	Satin Spun	4	C-7A	606	1500	Box	500/25	
			<b>S2705</b>	60C11	120	Satin Spun	4	C-7A	606	4000	CD/2	120/12	
	C15	Med.	<b>S2715</b>	60C15	120	Satin Spun	4 1/2	C-9	606	4000	Box	500/25	
			<b>S3415</b>	60C15	120	Satin Spun	4 1/2	C-9	606	4000	CD/2	120/12	
	CA10	Cand.	<b>S3262</b>	60CA10	120	Clear	4 1/4	CC-2V	650	1500	Box	500/25	
			<b>S3762</b>	60CA10	120	Clear	4 1/4	CC-2V	650	1500	CD/2	120/10	
			<b>S4467</b>	KR60CA10	120	Clear	4 1/4	CC-2V	720	2500	Box	500/25	1
			<b>A3662</b>	60CA10	130	Clear	4 1/4	CC-2V	642	2500	Box	500/25	
			<b>S3263</b>	60CA10/F	120	Frost	4 1/4	CC-2V	640	1500	Box	500/25	
			<b>S3763</b>	60CA10/F	120	Frost	4 1/4	CC-2V	640	1500	CD/2	120/10	
	F15	Med.	<b>A3663</b>	60CA10/F	130	Frost	4 1/4	CC-2V	635	2500	Box	500/25	
			<b>S3376</b>	60F15/VS	120	Clear	4 1/2	C-9	620	1500	Box	300/25	
			<b>S3378</b>	60F15/AU	120	Aurora	4 1/2	CC-9	—	1500	Box	300/25	
	G16 1/2	Cand.	<b>S3377</b>	60F15/A	120	Amber	4 1/2	CC-9	—	1500	Box	300/25	
			<b>S3771</b>	60G16 1/2	120	Clear	3	CC-2V	672	1500	CD/2	120/10	
			<b>S3831</b>	60G16 1/2	120	Clear	3	CC-2V	672	1500	Box	500/25	
			<b>A3931</b>	60G16 1/2	130	Clear	3	CC-2V	642	2500	Box	500/25	

NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.






Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes	
<b>60</b>	G16 1/2	Cand.	<b>S3772</b>	60G16 1/2/W	120	Satin White	3	CC-2V	630	1500	CD/2	120/10		
			<b>S3832</b>	60G16 1/2/W	120	Satin White	3	CC-2V	630	1500	Box	500/25		
			<b>A3932</b>	60G16 1/2/W	130	Satin White	3	CC-2V	564	2500	Box	500/25		
			<b>S3271</b>	60G16 1/2/W	120	Gloss White	3	CC-2V	630	1500	Box	500/25		
			<b>S2975</b> ■	25G16 1/2/VLX	120	Full Spec.	3	CC-2V	650	2000	CD/1	50/10	3	
			<b>S3246</b>	60G16 1/2/SL	120	Silver Crown	3	CC-2V	672	1500	Box	500/25		
		G25	Med.	<b>S4543</b> †	60G16 1/2/W	120	Gloss White	3 ¼	CC-2V	550	1500	CD/1	500/25	
	<b>S3862</b>			60G25/SL	120	Silver Crown	4 ¾	C-9	540	1500	Box	72/6		
	<b>S3012</b>			Med.	60G40	120	Clear	6 ¾	C-9	580	4000	Box	24/6	
		<b>S3002</b>	60G40/W		120	Gloss White	6 ¾	C-9	550	4000	Box	24/6		
		ST19	Med.	<b>S2423</b>	60ST19/CL/15S/120V/Vint.	120	Clear	5 ¾	Cage Style	240	3000	Box	48/6	
		T8	Med.	<b>S2978</b>	60T8	130	Clear	12	C-8	425	2000	Box	10	
		T9	Med.	<b>S2422</b>	60T9/CL/12S/120V/Vint.	120	Clear	7 ¾	Hairpin	230	3000	Box	50/10	
		T10	Med.	<b>S3896</b>	60T10	120	Clear	5	C-5V	500	2000	Box	500/25	
	<b>S3704</b>			60T10	120	Clear	5	C-5V	500	2000	CD/1	120/10		
<b>S3899</b>	60T10/F			120	Frost	5	C-5V	500	2000	Box	500/25			
<b>S3705</b>	60T10/F			120	Frost	5	C-5V	500	2000	CD/1	120/10			
<b>65</b>	BR30	Med.	<b>S2808</b>	65BR30/FL	120	Frost	5 ¾	CC-9	685	2000	Box	48/12		
			<b>S2817</b>	65BR30/FL/2PK	120	Frost	5 ¾	CC-9	620	2000	2pk	60/2		
			<b>S3408</b>	65BR30/FL	130	Frost	5 ¾	CC-9	620	2000	Box	48/12		
			<b>S8520</b>	65BR30/FL	130	Frost	5 ¾	C-9	530	5000	Box	60		


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.

# INCANDESCENT



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes	
<b>65</b>	BR30	Med.	<b>S3417</b>	65BR30/FL/2PK	130	Frost	5 3/8	CC-9	620	2000	2pk	60/2		
	<b>Shatter Proof</b>		<b>S4887</b>	65BR30/TF	120	Frost	5 3/8	C-9	685	2000	Sleeve	48/12	4	
	BR40	Med.	<b>S2853</b>	65BR40/FL	120	Frost	6 1/2	CC-6	580	2500	Sleeve	24		
			<b>S4453</b>	65BR40/FL	130	Frost	6 1/2	CC-6	540	2500	Sleeve	24		
			<b>S8521</b>	65BR40/FL	130	Frost	6 1/2	C-9	510	5000	Box	24		
	PAR38	Side Prong	<b>S4800 ▲</b>	65PAR/3FL/MINE	120	Clear	4 5/16	CC-6	765	2000	Box	12		
<b>69</b>	A21	Med.	<b>S2996 ▲</b>	69A21/TS/8M	130	Clear	4 7/16	C-9	640	8000	Sleeve	24	2	
<b>75</b>	A19	Med.	<b>S3970</b>	75A/RS	130	Frost	4 1/8	C-11/5	710	2500	2pk	24		
			<b>S8517</b>	75A/RS	130	Frost	4 1/8	C-11/5	590	5000	4pk	120		
	<b>Shatter Proof</b>		<b>S3928</b>	75A/RS/TF/2PK	130	Frost	4 1/8	C-9	680	5000	2pk	12/2	4	
	<b>Shatter Proof</b>		<b>S3931</b>	75A/RS/TF	130	Frost	4 1/8	C-9	680	5000	Box	12	4	
			<b>S4078</b>	75A19/W/230V	230	White	4 1/8	CC-2F	808	1000	Box	120		
			<b>S3920</b>	75A/BlackLight	120	Black Light	4 1/8	C-9	–	480	Box	96/6		
		A21	Med.	<b>S5012</b>	75A21/F/12V	12	Frost	5 5/16	C-6	720	1500	Box	120/6	
			<b>S5022</b>	75A21/F/34V	34	Frost	5 5/16	C-6	720	1500	Box	120/6		
			<b>S3934</b>	75A21/IF	130	Frost	5 5/16	C-9	680	5000	Sleeve	120/6		
	<b>Shatter Proof</b>		<b>S3972</b>	75A21/TF	130	Frost	5 5/16	C-9	700	2500	Box	24	4	
BR30	Med.	<b>S3239</b>	75BR30/A	130	Amber	5 3/8	C-9	–	2000	Sleeve	96/12			
		<b>S3228</b>	75BR30/B	130	Blue	5 3/8	C-9	–	2000	Sleeve	96/12			
		<b>S3227</b>	75BR30/G	130	Green	5 3/8	C-9	–	2000	Sleeve	96/12			
		<b>S3213</b>	75BR30/PK	130	Pink	5 3/8	C-9	–	2000	Sleeve	96/12			
		<b>S3240</b>	75BR30/R	130	Red	5 3/8	C-9	–	2000	Sleeve	96/12			
BR38	Med.	<b>S5000</b>	75BR38/FL/230V	230	Clear	5 5/16	CC-9	700	2000	Box	12			
R25	Med.	<b>S2851</b>	75R25/GRO	120	Plant	4 3/4	C-9	–	2000	Box	96/12			
T8	Med.	<b>S2979</b>	75T8	130	Clear	12	C-8	584	2000	Box	10			


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes			
<b>100</b>	A19	Med.	<b>S4079</b>	100A19/W/230V	230	White	4 1/8	C-9	1178	1000	Box	120				
				Med. Left Hand Thread (LHT)	<b>S6010</b>	100A/LHT	130	Frost	4 1/8	C-9	1200	2000	Sleeve	120/6		
				Med.	<b>S3971</b>	100A/RS	130	Frost	4 1/8	C-11/5	1100	2500	2pk	24		
					<b>S8518</b>	100A/RS	130	Frost	4 1/8	C-11/5	900	5000	4pk	120		
				<b>Shatter Proof</b>	<b>S3929</b>	100A/RS/TF/2PK	130	Frost	4 1/8	C-9	960	5000	2pk	12/2	4	
				<b>Shatter Proof</b>	<b>S3932</b>	100A/RS/TF	130	Frost	4 1/8	C-9	960	5000	Box	12	4	
					<b>S3956</b>	100A/SL	130	Silver Crown	4 1/8	C-9	960	1500	Box	24		
					<b>S3939</b>	100A/Bug	130	Yellow	4 1/8	C-9	-	2000	2pk	24		
				A21	Med.	<b>S5013</b>	100A21/F/12V	12	Frost	5 3/16	C-6	980	1500	Box	120/6	
				<b>S5023</b>		100A21/F/34V	34	Frost	5 3/16	C-6	980	1500	Box	120/6		
		<b>S3935</b>	100A21/F/VS	130		Frost	5 3/16	C-7A/5	1030	5000	Sleeve	130				
		<b>Shatter Proof</b>	<b>S3973</b>	100A21/TF	130	Frost	5 3/16	C-9	1000	2500	Box	24	4			
		A23	Med.	<b>S3936</b>	100A23/F/VS	130	Frost	6 1/16	C-7A/5	1030	5000	Sleeve	120/6			
		BR38	Med.	<b>S4424</b>	100BR38/R	120	Red	5 3/16	CC-9	-	2000	Box	6			
				<b>S4425</b>	100BR38/A	120	Amber	5 3/16	CC-9	-	2000	Box	6			
				<b>S4426</b>	100BR38/Y	120	Yellow	5 3/16	CC-9	-	2000	Box	6			
				<b>S4427</b>	100BR38/G	120	Green	5 3/16	CC-9	-	2000	Box	6			
				<b>S4428</b>	100BR38/B	120	Blue	5 3/16	CC-9	-	2000	Box	6			
				<b>S4429</b>	100BR38/PK	120	Pink	5 3/16	CC-9	-	2000	Box	6			
				<b>S5002</b>	100BR38/R/230V	230	Red	5 3/16	CC-9	-	2000	Box	6			
	<b>S5003</b>			100BR38/A/230V	230	Amber	5 3/16	CC-9	-	2000	Box	6				
	<b>S5004</b>			100BR38/Y/230V	230	Yellow	5 3/16	CC-9	-	2000	Box	6				
	<b>S5005</b>			100BR38/G/230V	230	Green	5 3/16	CC-9	-	2000	Box	6				
	<b>S5006</b>	100BR38/B/230V	230	Blue	5 3/16	CC-9	-	2000	Box	6						
	<b>S5007</b>	100BR38/PK/230V	230	Pink	5 3/16	CC-9	-	2000	Box	6						
	G40	Med.	<b>S3013</b>	100G40	120	Clear	6 3/4	C-9	1150	4000	Box	24/6				
			<b>S3003</b>	100G40/W	120	Gloss White	6 3/4	C-9	1050	4000	Box	24/6				
<b>100/200/300</b>	PS25	Mog.	<b>S1822</b>	100/300W	120	White	6 3/4	CC-6/C-9	1385/3540/4925	1200	Sleeve	12				
			<b>S1826</b>	100/300PS25/F	120	Frost	6 3/4	CC-6/CC-6	1300/2800/4100	2000	Sleeve	12				
<b>100</b>	R20	Med.	<b>S7002</b>	100R20FL/POOL	12	Frost	3 3/16	CC-6	1000	2000	Box	100/10				
			<b>S7001</b>	100R20FL/POOL	130	Frost	3 3/16	CC-6	970	2000	Box	100/10				


NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.

# INCANDESCENT



Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
120	BR40	Med. Skt.	<b>S7011</b>	120BR40/TF	130	Frost	6 1/2	C-9	1150	5000	Box	24	
	PAR38	Side Prong	<b>S4802 ▲</b>	120PAR/3FL/MINE	120	Clear	4 5/16	CC-6	1740	2000	Box	12	
			<b>S4803 ▲</b>	120PAR/3SP/MINE	120	Clear	4 1/2	CC-6	1740	2000	Box	12	
125	R40	Med.	<b>S4750</b>	125R40/1	120	Clear Heat	6 1/2	C-11	—	6000	Box	12	
			<b>S4756</b>	125R40/1/CL/2PK	120	Clear Heat	6 1/2	C-11	—	6000	Box	12	
135	A21	Med.	<b>S2999 ▲</b>	135A21/TS/8M/SS	120	Clear	4 7/16	C-11V	1750	8000	Sleeve	24	2
150	A21	Med.	<b>S3946</b>	150A21/CL/120V	120	Clear	5 1/16	CC-6	2670	750	Box	24	
			<b>S3945</b>	150A21/FR/120V	120	Frost	5 1/16	CC-6	2670	750	Box	24	
<b>Shatter Proof</b>			<b>S4883</b>	150A21/TF	130	Frost	5 1/16	C-9	1750	2500	Box	24	4
	BR38	Med.	<b>S5001</b>	150BR38/FL/230V	230	Clear	5 5/16	CC-9	1550	2000	Box	12	
	G40	Med.	<b>S3014</b>	150G40	120	Clear	6 3/4	C-9	1700	4000	Box	24/6	
			<b>S3004</b>	150G40/W	120	Gloss White	6 3/4	C-9	1550	4000	Box	24/6	
<b>Shatter Proof</b>	PS25	Med.	<b>S3017</b>	150PS25/TF	130	Frost	6 15/16	C-9	2200	5000	Box	24	4
	R30	Med.	<b>S2852</b>	150R30/GRO	120	Plant	5 15/16	C-9	—	2000	Box	96/12	
175	BR38	Med.	<b>S4751</b>	175BR38/HR	120	Red Heat	5 15/16	C-9	—	5000	Box	12	
			<b>S4752</b>	175BR38/HC	120	Clear	5 5/16	C-9	—	5000	Box	12	
200	A23	Med.	<b>S3958</b>	200A23/CL/120V	120	Clear	6 1/16	CC-6	2900	2500	Box	24	
			<b>S3957</b>	200A23/FR/120V	120	Frost	6 1/16	CC-6	2780	2500	Box	24	
250	R40	Med.	<b>S4999</b>	250R40/1	120	Clear Heat	6 1/2	C-9	—	6000	Sleeve	12	
			<b>S4755</b>	250R40/1/CL/2PK	120	Clear Heat	6 1/2	C-9	—	6000	Box	12	
<b>Shatter Proof</b>			<b>S4885</b>	250R40/1/TF	120	Clear Heat	6 7/8	C-9	—	6000	Sleeve	12	4
	BR40	Med.	<b>S4757</b>	250BR40/1/CL/3PK	120	Clear Heat	6 1/2	CC-9	—	6000	Box	24/3	
<b>Shatter Proof</b>			<b>S4758</b>	250BR40/1/CL/TF/3PK	120	Clear Heat	6 1/2	CC-9	—	6000	Box	24/3	
			<b>S4998</b>	250R40/HR	120	Red Heat	6 1/2	C-9	—	6000	Sleeve	12	
			<b>S4754</b>	250R40/HR/2PK	120	Red Heat	6 1/2	C-9	—	6000	Box	12	
			<b>S4884</b>	250R40/HR/TF	120	Red Heat	6 7/8	C-9	—	6000	Sleeve	12	4
300	BR40	Med.	<b>S7004</b>	300BR40FL/POOL	12	Frost	6 1/2	CC-9/1	2960	2000	Box	24/12	
			<b>S4353 ▲</b>	300BR/FL	120	Flood	6 1/2	CC-2V	3030	2000	Sleeve	24	
			<b>S7003</b>	300BR40FL/POOL	130	Frost	6 1/2	CC-9/1	2485	2000	Box	24/12	
	PS25	Med.	<b>S4959</b>	300M/CL	130	Clear	6 15/16	C-9	3600	5000	Box	24	
			<b>S4960</b>	300M/IF	130	Frost	6 15/16	C-9	3600	5000	Box	24	
	PS35	Mog.	<b>S4961</b>	300PS35/CL	130	Clear	9 3/8	C-9	3600	2500	Box	12	
			<b>S4962</b>	300PS35/IF	130	Frost	9 3/8	C-9	3600	2500	Box	12	
			<b>S7982</b>	300PS35/SB/IF	130	Silver Bowl Inside Frost	9 3/8	C-9	—	1000	Box	24	

NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.



Watts		Bulb Type	Base	Satco Prod. #	Lamp Code	Volts	Finish	M.O.L. Inches	Filament	Initial Lumens	Avg. Rated Hours	Pkg. Type	Master/Inner Carton	Notes
<b>375</b>	<b>Shatter Proof</b>	R40	Med.	<b>S7012</b>	375R40/TF	120	Clear Heat	7 5/8	C-11	—	5000	Box	12	4
		R40	Med.	<b>S4366</b>	375R40/1	120	Clear Heat	7 5/8	C-11	—	5000	Box	12	
<b>400</b>		BR40	Med.	<b>S7006</b>	400BR40FL/POOL	120	Frost	6 1/2	CC-9/1	4000	2000	Box	24/12	
		G30	Med.	<b>S7005</b>	400G30/CL/POOL	120	Clear	5	CC-9/1	6000	2000	Box	100/10	
<b>500</b>		BR40	Med.	<b>S7007</b>	500BR40FL/POOL	130	Frost	6 1/2	CC-9/1	5500	2000	Box	24/12	
		PS35	Mog.	<b>S3015</b>	500PS35/CL	130	Clear	9 3/8	CC-8	8000	5000	Box	24	
	<b>Shatter Proof</b>			<b>S3016</b>	500PS35/TF	130	Clear	9 3/8	CC-8	8000	5000	Box	24	4

**General Incandescent Notes**

- = Product by a manufacturer other than Satco
- ▲ = Product by one of the Primary lamp manufacturers
- † = To be discontinued when inventory is depleted.
- CD/1** = Carded or Clamshell – 1 lamp per card
- CD/2** = Carded or Clamshell – 2 lamps per card
- CD/4** = Carded or Clamshell – 4 lamps per card

**Incandescent Notes**

- 1 Krypton decorative bulbs create a brilliant sparkle, similar to the look of halogen. Additionally, Krypton bulbs last longer than conventional incandescent bulbs, maintaining their lumen output for the full course of their life.
- 2 While these very long life lamps were originally designed for traffic signals, we offer them primarily as an extraordinarily long life product. Per Title 20 Section 1605.3(m) of the California code of regulations, these lamps may not be sold or offered for sale in the state of California for use in traffic signals.

- 3 These Natural Spectrum light bulbs contain Neodymium, a rare earth element that filters out the excessive yellow part of the spectrum to which our eY are most sensitive. Made of hand blown glass, these incredible bulbs are the closest replication of natural sunlight available in an incandescent. These bulbs last up to five times longer than ordinary bulbs, show colors more accurately, increase the contrast between black and white, and reduce glare, eYtrain, and fatigue. While other manufacturers use a film that can degrade from the heat of the incandescent filament, the Neodymium in these lamps are integral to the glass, and therefore will last for the life of the bulb.
- 4 **Shatter Proof** lamps are designed for any application where the bulbs are at risk of being broken. The rubber coating will contain the glass particles should the lamp break, keeping it from falling into food, or anywhere else. Many jurisdictions now require the use of coated lamps in all food preparation, and service areas.
- 5 Designed primarily for picture light applications.

NOTE: When using a 130 Volt lamp on a 120 Volt line, life is extended approximately 2.5 times and lumens are reduced approximately 20%.

# HID LAMPS





# The largest lighting problems, solved.


High Intensity Discharge, or HID lamps, as they are commonly called, are a lighting mainstay for commercial applications, indoors or out. Our Hygrade™ brand covers all the HID technologies; mercury vapor, metal halide, and high pressure sodium. Manufactured to the highest quality standards, our HID lamps are in-service in virtually every state, in every type of business. Satco Hygrade high intensity discharge lamps are perfect for large indoor or outdoor open areas such as parking lots, street lighting, warehouses, anywhere high lumen output is critical.

## HID lamp features:

- Energy saving pulse start
- Protected MH for open rated fixtures
- Available from 50 to 1500 Watts
- High quality, rugged Arc tubes and frames
- Hydroponic line including Metal Halide to High Pressure Sodium conversion lamps
- Long life – up to 24,000 hours
- Full range of color temperatures from 1800K to 12000K







## Metal Halide Lamps – Protected/Pulse Start\* (Med. Base)


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	Pulse Start	Open Rated	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
50	ED17	Med.	<b>S5854</b>	MP50/ED17/U/PS	Clear	Y	Y	M110/O	4000	65	6000	3800	Univ.	5 7/16	12
			<b>S4847</b>	MP50/C/ED17/U/PS	Coated	Y	Y	M110/O	3000	70	10000	3300	Univ.	5 7/16	12
70	ED17	Med.	<b>S5856</b>	MP70/ED17/U/PS	Clear	Y	Y	M98/O	4000	65	10000	6000	Univ.	5 7/16	12
			<b>S4849</b>	MP70/C/ED17/U/PS	Coated	Y	Y	M98/O	3700	70	15000	5300	Univ.	5 7/16	12
100	ED17	Med.	<b>S5858</b>	MP100/ED17/U/PS	Clear	Y	Y	M90/O	4000	65	10000	9500	Univ.	5 7/16	12
			<b>S4851</b>	MP100/C/ED17/U/PS	Coated	Y	Y	M90/O	3700	70	15000	8100	Univ.	5 7/16	12
150	ED17	Med.	<b>S5860</b>	MP150/ED17/U/PS	Clear	Y	Y	M102/O	4000	65	10000	14000	Univ.	5 7/16	12
			<b>S4853</b>	MP150/C/ED17/U/PS	Coated	Y	Y	M102/O	3700	70	10000	13500	Univ.	5 7/16	12
175	ED17	Med.	<b>S5863</b>	MP175/ED17/U/PS	Clear	Y	Y	M152/O	4200	65	15000	10800	Univ.	5 7/16	12

\* High Output lamps for use in open or enclosed fixtures.

## Metal Halide Lamps – Protected/Pulse Start\* (Mog. Base)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	Pulse Start	Open Rated	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
200	ED28	Mog.	<b>S5881</b>	MP200/ED28/PS/BU/4K	Clear	Y	Y	M136/O	4200	65	15000	20000	BU+/- 15	8 5/16	12
250	ED28	Mog.	<b>S5882</b>	MP250/ED28/PS/BU/4K	Clear	Y	Y	M153/O	4200	65	15000	23500	BU+/- 15	8 5/16	12
320	ED28	Mog.	<b>S5883</b>	MP320/ED28/PS/BU/4K	Clear	Y	Y	M154/O	4200	65	20000	31000	BU+/- 15	8 5/16	12
			<b>S4254</b>	MP320/C/ED28/PS/BU	Coated	Y	Y	M154/O	3700	70	20000	29000	BU+/- 15	8 5/16	12
350	ED37	Mog.	<b>S4256</b>	MP350/ED37/V/UVS/UPS/4K/EX39	Clear	Y	Y	M131/O	4000	65	20000	33000	Vert+/- 15	11 1/2	12
			<b>S4257</b>	MP350/ED37/C/V/UVS/UPS/4K/EX39	Coated	Y	Y	M131/O	3700	70	20000	33000	Vert+/- 15	11 1/2	12
400	ED37	Mog.	<b>S4259</b>	MP400/ED37/C/BU/UVS/UPS/4K/EX39	Coated	Y	Y	M155/O	3700	70	20000	40000	BU+/- 15	11 1/2	12
			<b>S5884</b>	MP400/ED37/PS/BU/4K	Clear	Y	Y	M155/O	4200	65	20000	42000	BU+/- 15	11 1/2	12
			Mog. Ext. <b>S5888</b>	MP400/ED28/PS/BU/4K	Clear	Y	Y	M155/O	4200	65	20000	42000	BU+/- 15	8 5/16	12
1000	BT56	Mog.	<b>S7882</b>	MP1000/BT56/PS/BU/4K/EX39	Clear	Y	Y	M141/O	4200	68	12000	105000	BU+/- 15	15 3/8	12


\* High Output lamps for use in open or enclosed fixtures.



## Metal Halide Lamps – Pulse Start\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	Pulse Start	Open Rated	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
<b>70</b>	ED28	Mog.	<b>S5830</b>	MH70/ED28/U/4K	Clear	Y	N	M98/E	4200	65	15000	5600	Univ.	8 5/16	12
	T6 DE	RSC	<b>S4864</b> ■	MH-DE70/42K	Clear	Y	N	M85/E	4200	65	10000	5500	HOR+/-15	13	25
<b>100</b>	ED28	Mog.	<b>S5832</b>	MH100/ED28/PS	Clear	Y	N	M90/E	4200	65	15000	8500	Univ.	8 5/16	12
<b>125</b>	ED28	Mog.	<b>S5822</b>	MH125/ED28/PS/HBU/4K	Clear	Y	N	M150/E	4200	65	15000	12000	Univ.	8 5/16	12
<b>150</b>	ED28	Mog.	<b>S5834</b>	MH150/ED28/U/4K	Clear	Y	N	M102/E	4200	65	15000	12000	Univ.	8 1/2	12
	T8 DE	RSC	<b>S4866</b> ■	MH-DE150/3K	Clear	Y	N	M81/E	3000	70	10000	12500	HOR+/-15	5 3/8	12
			<b>S4867</b> ■	MH-DE150/42K	Clear	Y	N	M81/E	4200	65	10000	12000	HOR+/-15	5 7/16	25
<b>175</b>	ED17	Med.	<b>S4235</b>	MS175/C/BU/UPS/ED17/4K/E26	Coated	Y	N	M152/E	3700	70	15000	16600	BU+/-15	5 7/16	12
	ED28	Mog.	<b>S5824</b>	MS175/ED28/PS/BU/4K	Clear	Y	N	M152/E	4200	65	16000	17000	Univ.	8 5/16	12
			<b>S4237</b>	MS175/C/BU/UPS/ED28/4K/E39	Coated	Y	N	M152/E	3700	70	16000	16600	BU+/-15	8 5/16	12
<b>200</b>	ED28	Mog.	<b>S5838</b>	MS200/ED28/PS/U/4K	Clear	Y	N	M136/E	4200	65	15000	19000	Univ.	8 5/16	12
<b>250</b>	ED28	Mog.	<b>S5839</b>	MS250/ED28/PS/U/4K	Clear	Y	N	M153/E	4000	65	15000	25000	Univ.	8 5/16	12
<b>320</b>	ED28	Mog.	<b>S5841</b>	MS320/ED28/PS/U/4K	Clear	Y	N	M154/E	4200	65	20000	33000	Univ.	8 5/16	12
			<b>S4242</b>	MS320W/ED28/C/UPS/V/4K/E39	Coated	Y	N	M154/E	3700	70	20000	32000	Vert+/-15	8 5/16	12
<b>350</b>	ED28	Mog.	<b>S5825</b>	MS350/ED28/PS/U/4K	Clear	Y	N	M131/E	4200	65	20000	37000	Univ.	8 5/16	12
	ED37	Mog.	<b>S4244</b>	MS350W/ED37/C/UPS/V/4K/E39	Coated	Y	N	M131/E	3700	70	20000	35000	Vert+/-15	11 1/2	12
<b>400</b>	ED37	Mog.	<b>S4246</b>	MS400W/ED37/C/UPS/V/4K/E39	Coated	Y	N	M155/E	3700	70	20000	42000	Vert+/-15	11 1/2	12
	ED28	Mog.	<b>S5878</b>	MS400/ED28/PS/U/4K	Clear	Y	N	M155/E	4200	65	20000	44000	Univ.	8 5/16	12
			<b>S4248</b>	MS400W/ED28/C/UPS/V/4K/E39	Coated	Y	N	M155/E	3700	70	20000	42000	Vert+/-15	8 5/16	12
<b>750</b>	BT37	Mog.	<b>S4390</b> ▲	MS750/PS/BU-HOR/BT37	Clear	Y	N	M149/E	4000	65	16000	80000	BU+/-90	11 1/2	6
<b>1000</b>	BT37	Mog.	<b>S4391</b>	MS1000/BU/BT37/PS/4K/E39	Clear	Y	N	M141/E	4000	65	12000	115000	BU+/-15	11 1/2	12

\* High Output lamps for use in enclosed fixtures only.



## Metal Halide Lamps – Protected\*


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	Pulse Start	Open Rated	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
<b>175</b>	ED17	Med.	<b>S5862</b>	MP175/ED17/U	Clear	N	Y	M57/O	4000	65	12000	14000	Univ.	5 7/16	12
	BT28	Mog.	<b>S4384 ▲</b>	MP175/BU-ONLY	Clear	N	Y	M57/O	4000	65	10000	14400	BU+/-15	8 5/16	6
	ED28	Mog.	<b>S5885</b>	MP175/ED28/BU/4K	Clear	N	Y	M57/O	4200	65	10000	14400	BU+/-15	8 5/16	12
<b>250</b>	BT28	Mog.	<b>S4386 ▲</b>	MP250/BU-ONLY	Clear	N	Y	M58/O	4000	65	10000	23000	BU+/-15	8 1/2	6
			<b>S5886</b>	MP250/ED28/BU/4K	Clear	N	Y	M58/O	4200	65	10000	23000	BU+/-15	8 1/2	12
<b>400</b>	ED37	Mog.	<b>S5887</b>	MP400/ED37/BU/4K	Clear	N	Y	M59/O	3600	65	20000	40000	BU+/-15	11 1/2	12
			<b>S4388 ■</b>	MP400/BU-ONLY	Clear	N	Y	M59/O	3600	65	20000	40000	BU+/-15	11 1/2	6
<b>1000</b>	BT56	Mog.	<b>S7921</b>	MP1000/BT56/BU/4K/EX39	Clear	N	Y	M47/O	4000	65	12000	100000	BU+/-15	15 3/8	6

\* Probe start lamps for use in open or enclosed fixtures.

## Metal Halide Lamps – Standard\*

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	Pulse Start	Open Rated	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
<b>70</b>	ED17	Med.	<b>S4857</b>	MH70/C/U/ED17/4K/E26	Coated	Y	N	M98/E	3700	70	15000	5300	Univ.	5 7/16	12
<b>100</b>	ED28	Mog.	<b>S5832</b>	MH100/ED28/U/4K	Clear	N	N	M90/E	4200	65	15000	8500	Univ.	8 5/16	12
<b>150</b>	ED17	Med.	<b>S4379</b>	MH150/U/ED17/4K/E26/EM	Clear	N	N	M107/E	4000	65	10000	13500	Univ.	5 9/16	12
			<b>S4861</b>	MH150/C/U/ED17/4K/E26	Coated	Y	N	M102/E	3700	70	10000	12500	Univ.	5 7/16	12
<b>175</b>	BT28	Mog.	<b>S4829 ▲</b>	MH175/U	Clear	N	N	M57/E	4000	65	10000	14000	Univ.	8 5/16	6
	ED17	Med.	<b>S4862 ▲</b>	MH175/U/MED	Clear	N	N	M57/E	4000	65	10000	16000	Univ.	5 7/16	12
			<b>S4863</b>	MH175/C/U/ED17/4K/E26	Coated	N	N	M57/E	3700	70	10000	13300	Univ.	5 7/16	12
	ED28	Mog.	<b>S5829</b>	MH175/ED28/U/4K	Clear	N	N	M57/E	4200	65	10000	13600	Univ.	8 5/16	12
			<b>S4830</b>	MH175/ED28/C/U/4K/E39	Coated	N	N	M57/E	3700	70	10000	13300	Univ.	8 5/16	12
	T15	Mog.	<b>S4840</b>	MH175/HOR/T15/4K/E39	Clear	N	N	M57/E	4000	65	10000	14000	HOR+/-15	9 3/4	12
	R40	Med.	<b>S4261 ■</b>	MH175W/U/R40/FL70	Frosted	N	N	M57/E	4000	65	10000	6500	Univ.	6 1/2	6
<b>250</b>	ED28	Mog.	<b>S5831</b>	MH250/ED28/U/4K	Clear	N	N	M58/E	4000	65	12000	20000	Univ.	8 5/16	12
			<b>S4832</b>	MH250/C/U/ED28/E39	Coated	N	N	M58/E	3700	70	10000	21500	Univ.	8 1/2	12
	BT28	Mog.	<b>S4831</b>	MH250/U	Clear	N	N	M58/E	4000	65	10000	21000	Univ.	8 1/2	6
	T15	Mog.	<b>S4841</b>	MH250/HOR/T15/4K/E39	Clear	N	N	M58/E	4200	65	10000	20000	HOR+/-15	9 3/4	12

\* Probe start lamps for use in open or enclosed fixtures.




## Metal Halide Lamps – Standard\* (continued)

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	Pulse Start	Open Rated	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
<b>250</b>	ET18	Mog.	<b>S4385 ▲</b>	M250/U/ET18	Clear	N	N	M58/E	4000	65	10000	22000	Univ.	9 ¾	10
	T8 DE	Fc2	<b>S4262 ■</b>	MH-DE250W/3K/Fc2	Clear	N	N	M80/E	3000	70	10000	20000	HOR+/-45	6 7/16	25
			<b>S4263 ■</b>	MH-DE250W/42K/Fc2	Clear	N	N	M80/E	4200	70	10000	20000	HOR+/-45	6 7/16	25
<b>400</b>	ED37	Mog.	<b>S5833</b>	MH400/ED37/U/4K	Clear	N	N	M59/E	4000	65	15000	36000	Univ.	11 ½	12
			<b>S4834</b>	MH400/C/U/ED37/4K/E39	Coated	N	N	M59/E	3700	70	20000	34000	Univ.	11 ½	12
	ED28	Mog.	<b>S5843</b>	MH400/ED28/U/4K/E39	Clear	N	N	M59/E	4200	65	20000	36000	Univ.	8 5/16	12
			<b>S4844</b>	MH400/C/U/ED28/E39	Coated	N	N	M59/E	3700	65	20000	33900	Univ.	8 5/16	12
	ET18	Mog.	<b>S4389 ▲</b>	M400/U/ET18	Clear	N	N	M59/E	4000	65	20000	36000	Univ.	9 ¾	10
	T15	Mog.	<b>S4842</b>	MH400/HOR/T15/4K/E39	Clear	N	N	M59/E	4200	65	15000	36000	HOR+/-15	9 ¾	12
<b>1000</b>	BT56	Mog.	<b>S5835</b>	MH1000/BT56/U/4K	Clear	N	N	M47/E	4000	65	10000	105000	Univ.	15 ¾	6
			<b>S4836 ■</b>	MH1000/C/U/BT56/4K/E39	Coated	N	N	M47/E	3700	70	12000	105000	Univ.	15 ¾	6
	BT37	Mog.	<b>S5845</b>	MH1000/BT37/U/4K	Clear	N	N	M47/E	4200	65	15000	110000	Univ.	11 ½	12
	BT56	Mog.	<b>S4835</b>	MH1000/U	Clear	N	N	M47/S	4000	65	18000	110000	Univ.	15 ¾	6
<b>1500</b>	BT56	Mog.	<b>S5837</b>	MH1500/BT56/U/4K	Clear	N	N	M48/E	4200	65	3000	167000	Univ.	15 ¾	6
			<b>S4839 ■</b>	MH1500/U/XL	Clear	N	N	M48/E	4000	65	6000	170000	Univ.	15 ¾	6

\* Probe start lamps for use in open or enclosed fixtures.

## Metal Halide Lamps – Ceramic

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	Pulse Start	Open Rated	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
<b>39</b>	T4 SE	G8.5	<b>S4286 ▲</b>	CDM35/TC/830	Clear	Y	N	M130/E	3000	81	9000	3300	Univ.	3 5/16	12
	T6 SE	G12	<b>S4288 ▲</b>	CDM35/T6/830	Clear	Y	N	M130/E	3000	81	12000	3400	Univ.	3 5/16	12
	PAR20	Med.	<b>S4284 ▲</b>	CDM35PAR20/M/SP	Clear	Y	Y	M130/O	3000	81	9000	23000	Univ.	3 ¾	12
			<b>S4285 ▲</b>	CDM35PAR20/M/FL	Clear	Y	Y	M130/O	3000	81	9000	5000	Univ.	3 ¾	12
	PAR30	Med.	<b>S4876 ▲</b>	CDM35PAR30L/M/SP	Clear	Y	Y	M130/O	3000	81	9000	44000	Univ.	4 ¾	6
		<b>S4877 ▲</b>	CDM35PAR30L/M/FL	Clear	Y	Y	M130/O	3000	81	9000	7400	Univ.	4 ¾	6	
<b>70</b>	T4 SE	G8.5	<b>S4287 ▲</b>	CDM70/TC/830	Clear	Y	N	M139/E	3000	83	6000	6400	Univ.	3 5/16	12
	T6 SE	G12	<b>S4289 ▲</b>	CDM70/T6/830	Clear	Y	N	M139/E	3000	81	12000	6600	Univ.	3 5/8	12
			<b>S4264 ▲</b>	CDM70T6/942	Clear	Y	N	M139/E	4200	92	12000	6600	Univ.	3 5/16	12
	T6 DE	RSC	<b>S4292 ▲</b>	CDM70/TD/830	Clear	Y	N	M85/M139/E	3000	82	15000	6500	HOR+/-15	4 3/8	12



## Metal Halide Lamps – Ceramic (continued)


Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	Pulse Start	Open Rated	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
70	PAR30	Med.	<b>S4878 ▲</b>	CDM70/PAR30L/M/SP	Clear	Y	Y	M143/M96/O	3000	83	9000	68000 <sup>†</sup>	Univ.	4 ¾	12
			<b>S4879 ▲</b>	CDM70/PAR30L/M/FL	Clear	Y	Y	M143/M96/O	3000	83	9000	10000 <sup>†</sup>	Univ.	4 ¾	12
	PAR38	Med.	<b>S4897 ▲</b>	CDM70/PAR38/SP/3K	Clear	Y	Y	M143/M96/O	3000	82	10000	50000 <sup>†</sup>	Univ.	5 ½	12
			<b>S4812 ▲</b>	CDM70/PAR38/SP/4K	Clear	Y	Y	M143/M96/O	4000	92	10000	42000 <sup>†</sup>	Univ.	5 ¾	12
			<b>S4898 ▲</b>	CDM70/PAR38/FL/3K	Clear	Y	Y	M143/M96/O	3000	82	10000	18000 <sup>†</sup>	Univ.	5 ¾	12
			<b>S4813 ▲</b>	CDM70/PAR38/FL/4K	Clear	Y	Y	M143/M96/O	4000	92	10000	16000 <sup>†</sup>	Univ.	5 ¾	12
100	PAR38	Med.	<b>S4888 ▲</b>	CDM100/PAR38/SP/3K	Clear	Y	Y	M140/M90/O	3000	85	12500	70000 <sup>†</sup>	Univ.	5 ½	12
			<b>S4814 ▲</b>	CDM100/PAR38/SP/4K	Clear	Y	Y	M140/M90/O	4000	93	10000	25000 <sup>†</sup>	Univ.	5 ¾	12
			<b>S4889 ▲</b>	CDM100/PAR38/FL/3K	Clear	Y	Y	M140/M90/O	3000	86	12500	54000 <sup>†</sup>	Univ.	5 ¾	12
			<b>S4869 ▲</b>	CDM100/PAR38/FL/4K	Clear	Y	Y	M140/M90/O	4000	93	10000	54000 <sup>†</sup>	Univ.	5 ¾	12
150	T6 SE	G12	<b>S4290 ▲</b>	CDM150T6/830	Clear	Y	N	M142/E	3000	85	12000	14000	Univ.	4 ½	12
			<b>S4266 ▲</b>	CDM150T6/942	Clear	Y	N	M142/E	4200	96	9000	12700	Univ.	4 ¾	25
	T8 DE	RSC	<b>S4293 ▲</b>	CDM150/TD/830	Clear	Y	N	M142/M81/M102/E	3000	88	15000	13250	HOR+/-15	5 ¾	12

## Metal Halide Lamps – Double Ended

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	Pulse Start	Open Rated	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
70	T6 DE	RSC	<b>S4865 ■</b>	MH-DE70/3K	Clear	Y	N	M85/E	3000	70	10000	5200	HOR+/-15	4 ¾	12


## Metal Halide Lamps – Retrofit for High Pressure Sodium (HPS) Fixtures

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	Pulse Start	Open Rated	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
250	ED28	Mog.	<b>S4268</b>	MH250W/BU/LU/ED28/4K/E39 <b>Retrofit for LU250</b>	Clear	N	N	S50/E	4000	65	10000	18500	BU+/-15	8 ¾	12
400	ED37	Mog.	<b>S4269</b>	MH400W/BU/LU/ED37/4K/E39 <b>Retrofit for LU400</b>	Clear	N	N	S51/E	4000	65	20000	36000	BU+/-15	11 ½	12
			<b>S4270</b>	MH400W/C/BU/LU/ED37/4K/E39 <b>Retrofit for LU400/D</b>	Coated	N	N	S51/E	3700	70	20000	34000	BU+/-15	11 ½	12



## High Pressure Sodium (HPS) Lamps

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Burning Position	M.O.L. Inches	Carton
<b>35</b>	ED17	Med.	<b>S3130</b>	LU35/MED	Clear	S76	2100	22	2250	16000	Univ.	5 7/8	12
<b>50</b>	ED17	Med.	<b>S3131</b>	LU50/MED	Clear	S68	2100	22	4000	24000	Univ.	5 7/8	12
	ET23.5	Mog.	<b>S1929</b>	LU50	Clear	S68	2100	22	3700	24000	Univ.	7 3/4	12
<b>70</b>	ED17	Med.	<b>S3127</b>	LU70/MED	Clear	S62	2100	22	6300	24000	Univ.	5 7/8	12
			<b>S5123 ▲</b>	LU70/D/MED	Coated	S62	2100	22	5800	24000	–	5 7/8	20
	ET23.5	Mog.	<b>S1930</b>	LU70	Clear	S62	2100	22	6300	24000	Univ.	7 3/4	12
<b>100</b>	ED17	Med.	<b>S3128</b>	LU100/MED	Clear	S54	2100	22	9500	24000	Univ.	5 7/8	12
	ET23.5	Mog.	<b>S1931</b>	LU100	Clear	S54	2100	22	9500	24000	Univ.	7 3/4	12
			<b>S5126 ▲</b>	LU100/D	Coated	S54	2100	22	8800	24000	–	7 3/4	20
<b>150</b>	ED17	Med.	<b>S3129</b>	LU150/55/MED	Clear	S55	2100	22	24000	16000	Univ.	5 7/8	12
			<b>S5127 ▲</b>	LU150/55/D/MED	Coated	S55	2100	22	24000	14500	–	5 11/8	20
	ET23.5	Mog.	<b>S1932</b>	LU150/55	Clear	S55	2100	22	24000	16000	–	7 3/4	12
			<b>S5128 ▲</b>	LU150/55/D	Coated	S55	2100	22	24000	14000	–	7 3/4	–
<b>200</b>	ET18	Mog.	<b>S1927</b>	LU200/ET18	Clear	S66	2100	22	24000	22000	Univ.	9 11/8	12
<b>250</b>	ET18	Mog.	<b>S1940</b>	LU250	Clear	S50	2100	22	24000	28000	–	9 3/8	12
	BT28	Mog.	<b>S5130 ▲</b>	LU250/D	Coated	S50	2100	22	24000	26000	–	8 15/8	10
<b>310</b>	ET18	Mog.	<b>S5131 ▲</b>	LU310/ECO	Clear	S67	2100	22	24000	37000	–	9 3/8	20
<b>400</b>	ET18	Mog.	<b>S1941</b>	LU400	Clear	S51	2100	22	24000	51000	–	9 3/8	12
<b>750</b>	BT37	Mog.	<b>S5133 ▲</b>	LU750	Clear	S111	2100	22	24000	105000	–	11 1/2	6
<b>1000</b>	E25	Mog.	<b>S5124 ▲</b>	LU1000	Clear	S52	2100	22	24000	130000	–	15 5/8	6
	ET25	Mog.	<b>S1928</b>	LU1000/ET25	Clear	S52	2100	22	24000	130000	Univ.	15 5/8	12




## Mercury Vapor Lamps

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Carton
<b>75</b>	ED17	Med.	<b>S4475</b>	H43AV-75DX	Coated	H43	3900	50	24000	2700	5 7/16	12
<b>100</b>	A23	Med.	<b>S1933</b>	H38MP-100DX	Coated	H38	3900	50	24000	4000	5 7/16	12
	ED17	Med.	<b>S4377</b>	H38AV-100DX	Coated	H38	3900	50	24000	4000	5 7/16	20
	ET23.5	Mog.	<b>S1935</b>	H38JA-100DX	Coated	H38	3900	50	24000	4000	7 1/2	12
<b>175</b>	ED28	Mog.	<b>S1934</b>	H39KC-175DX	Coated	H39	3900	50	24000	7800	8 1/4	12
			<b>S1936</b>	H39KB-175	Clear	H39	4500	20	24000	7800	8 1/4	12
	R40	Med.	<b>S4394</b>	H39BP-175DX	Coated	H39	3900	50	24000	5700	7 1/2	12
<b>250</b>	ED28	Mog.	<b>S1937</b>	H37KC-250DX	Coated	H37	3900	50	24000	11200	8 1/4	12
<b>400</b>	ED37	Mog.	<b>S1938</b>	H33GL-400DX	Coated	H33	3900	50	24000	22600	11 5/16	12
	ED28	Mog.	<b>S1939</b>	MV400/DX/ED28/H33/E39	Coated	H33	3900	50	24000	22600	8 5/16	12
<b>1000</b>	BT56	Mog.	<b>S4396</b> ■	H36GW-1000DX	Coated	H36	3900	50	24000	58000	15 3/8	6
			<b>S1998</b>	H36GW-1000DX	Coated	H36	3900	50	24000	58000	15 3/8	6

## SOX Low Pressure Sodium Lamps

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Carton
<b>18</b>	T17	BY22D	<b>S4870</b> ▲	SOX18	Clear	L69	1800	16000	1800	BU +/- 110	8 1/2	12
<b>35</b>	T17	BY22D	<b>S4871</b> ▲	SOX35	Clear	L70	1800	16000	4500	BU +/- 110	12 1/4	12
<b>55</b>	T17	BY22D	<b>S4872</b> ▲	SOX55	Clear	L71	1800	16000	7300	BU +/- 110	16 3/4	12
<b>90</b>	T21	BY22D	<b>S4873</b> ▲	SOX90	Clear	L72	1800	16000	13500	HOR +/- 20	20 13/16	12
<b>135</b>	T21	BY22D	<b>S4874</b> ▲	SOX135	Clear	L73	1800	16000	22000	HOR +/- 20	30 1/2	12
<b>180</b>	T21	BY22D	<b>S4875</b> ▲	SOX180	Clear	L74RF	1800	16000	30000	HOR +/- 20	44 15/16	6





**NOTE:** Compatible ballasts are on pages 115-117.

## Hydroponic Lamps – High Pressure Sodium

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Carton
<b>150</b>	ED23.5	Mog.	<b>S5901</b>	LU150/ED23.5/HO	Clear	S55	2000	20	24000	16000	7 ¾	12
<b>250</b>	ET18	Mog.	<b>S5902</b>	LU250/ET18/HO	Clear	S50	2000	20	32000	32000	9 ⅝	12
<b>400</b>	ET18	Mog.	<b>S5903</b>	LU400/ET18/HO	Clear	S51	2000	20	32000	54500	9 ⅝	12
<b>600</b>	T15	Mog.	<b>S5904</b>	LU600/T15/HO	Clear	S106	2000	20	32000	85000	11 ⅙	24
<b>1000</b>	ET25	Mog.	<b>S5905</b>	LU1000/ET25/HO	Clear	S52	2000	20	32000	140000	15	12
<b>1500</b>	ET25	Mog.	<b>S5906</b>	LU1500/ET25/HO	Clear	Electric Ballast	2000	20	32000	200000	15 ⅙	12

## Hydroponic Lamps – High Pressure Sodium/Dual Arctube

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Carton
<b>1000</b>	ET25	Mog.	<b>S5913</b>	LU1000MH/DA	Clear	S52/Electric Ballast	3000	60	10000	90000	15 ⅙	12

## Hydroponic Lamps – Metal Halide

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Carton
<b>400</b>	T15	Mog.	<b>S5907</b>	MS400/7500	Clear	M59/E	7500	65	10000	32000	9 ¾	24
			<b>S5908</b>	MS400/10000	Clear	M59/E	10000	85	10000	23000	9 ¾	24
<b>1000</b>	T120	Mog.	<b>S5909</b>	MS1000/7500	Clear	M47/E	7500	65	10000	92000	15 ⅝	12
			<b>S5910</b>	MS1000/10000	Clear	M47/E	10000	85	10000	68000	15 ⅝	12

## Hydroponic Lamps – Metal Halide/Conversion

Watts	Bulb Type	Base	Satco Prod. #	Lamp Code	Finish	ANSI	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	M.O.L. Inches	Carton
<b>600</b>	T25	Mog.	<b>S5911</b>	MH600/LU	Clear	S106	6500	65	10000	45000	11 ½	24
<b>1000</b>	T120	Mog.	<b>S5912</b>	MH1000/LU	Clear	S52	6500	65	10000	92000	15 ⅝	12

## HID Notes

- = Product by a manufacturer other than Satco
- ▲ = Product by one of the Primary lamp manufacturers

## Steps to choosing the correct Metal Halide lamp:

- 1 Determine the correct wattage.
- 2 Determine the base.
- 3 Choose the shape. ED and BT style lamps are generally interchangeable.
- 4 Determine the correct size, some wattages come in multiple sizes. For example, 400w lamps are standard ED37, but are also commonly available in an ED28 compact envelope.
- 5 Determine burning position, BU, BD, Vertical, Horizontal, or Universal.
- 6 Determine Pulse Start, or Probe Start. Pulse Start is standard on lower wattage lamps, (39 through 150 watts). Probe Start is standard on higher wattage lamps, (175 through 1500 watts), however Pulse Start technology is being used more and more on the higher wattages.
- 7 Determine whether the project is calling for the newer Ceramic Arc tube lamps. These lamps offer higher color rendering, and Lumen Output than the more traditional Quartz Arc tube lamps.
- 8 Determine whether fixture requires an Open Rated (Protected) lamp, or an Enclose Rated lamp.
- 9 All Metal Halide lamps and ballasts are identified with an ANSI code. It is best to make sure that the ANSI code matches between the ballast and lamp.

## ANSI Codes

All HID lamps and ballasts are identified by an ANSI code. The purpose of these codes are to make sure that the lamp from one manufacturer is properly matched to any other manufacturers ballast, therefore resulting in safe operation, and produce the designed light output. Especially with the increasing complexities of metal halide product offerings, it is very important that the ballast and lamp ANSI codes are matched before use. The most recent changes to the ANSI lamp codes have added the E, S, and O letter designations. For example, a 400 watt probe start metal halide lamp will have an ANSI code of M59/E, M59/S, or M59/O. This should be used only on a ballast with an ANSI code of M59.

- E – Lamps must be used in enclosed luminaires which meet the requirements of UL1598.
- S – Lamps are considered “suitable” for open luminaire operation, only if operated in the vertical  $\pm 15^\circ$  position. Lamps do not meet ANSI criteria for containment and must be turned off at least once per week for a minimum of 15 minutes if operated continuously. In addition these lamps must be group relamped before reaching rated lamp life.
- O – Lamps can be operated in open or enclosed luminaires within the manufacturer’s specified operating position limits. This type meets the ANSI criteria for containment rated operation. Special exclusionary sockets are available for these lamps to ensure that the wrong lamp type is not used.

## Rated Life

The rated life of metal halide lamps is based on the point when 50% of the lamps have burned out, based on a burn cycle of 10 hours per start. Various operating conditions affect lamp life. One key factor is operating position. Lamps designated universal can be operated in any position. However, life expectancy and lumen output are sacrificed in certain positions. Published “rated life” for universal lamps is based on operation in the vertical position. “Rated life” for universal lamps operated horizontally is 75% of

the published rating. Shorter operating cycles also severely reduce life. At operating cycles shorter than 10 hours per start, life will shorten as follows:

- 5 hrs per start: Life is approx. 75% of rating
- 2.5 hrs per start: Life is approx. 55% of rating

## Initial Lumen Listings

Rated initial lumens are based on measurements at 100 hours of use, and are based on specified burning position. The measures listed for universal position lamps are based on a vertical burning position; horizontal usage decreases the output by 25 to 30%. For specifics on any particular lamp, call Satco customer service (800-43-SATCO).

## ▲WARNING:

It is the responsibility of the purchaser to read all safety warnings on the lamp package before use. For more information, call Satco customer service (800-43-SATCO).

## Measured vs Perceived Light Levels of HID Lamp

Studies on nighttime visibility demonstrate experimentally that the human eyes is sensitive to different colors of light based on various lighting levels, thus impacting the “true” or “effective” lumen output of a lamp. Recent research shows that the color of a light source has a significant effect on nighttime visibility, which is important since most road accidents happen at night. It is also well known that the eye responds to color differently based on the amount of light available.

While lumens are the standard measurement of light output, light is actually defined as energy evaluated by the eye. Standard lumen measurements are based on the light output response of a person only during high light levels (photopic light), typical of daylight and interior lighting. Light meters measure photopic light as seen by the central region of the eye. When light levels are very low, like starlight, the viewing conditions are referred to as scotopic. Under these conditions, the eyes visual response changes dramatically. Sensitivity to yellow and red light is greatly reduced, while response to blue light is vastly increased. Since lamp lumen measurements have been determined using photopic measurements, the lumen values do not accurately measure the effective light output as perceived by the human eye.

Since the value of a lamp’s lumen output is different when considering the shifting color sensitivity of the eye at low levels, the effective lumens will be different from the measurable photopic lumens. As light diminishes from photopic to scotopic conditions, the effective lumens of yellow sodium light sources are reduced, and the effective lumens of the whiter metal halide sources increase. This effect is most dramatic for low pressure sodium (SOX) lamps. Almost all energy output from SOX lamps is yellow, resulting in an artificially high photopic lumen output, yet a very low perceived light output in low light level applications.

Typical metal halide lamps have strong light output in the blue, green and yellow areas, resulting in high lumen output at all light levels. The blue light output of metal halide is in the high sensitivity region of the eye for low light levels. This means that the effective lumens actually increase for a metal halide lamp as the light level reduces and the eye shifts to a blue/green peak sensitivity. The ability to detect fine contrast is also significantly better under metal halide sources than sodium, making it a more effective light source in warehouse and retail applications. Studies have shown that metal halide lighting, in some circumstances, can be up to six times as effective as HPS. This can make a difference in peripheral viewing and dark areas where hidden hazards may be present.

## Metal Halide 2005 NEC Changes

The 2005 update to the National Electrical Code (NEC) includes two changes that affect the manufacture and installation of metal halide luminaires. Both changes address methods for preventing risk when metal halide lamps are used.

The purpose of these changes is to prevent possible injury and property damage. Metal halide lamps can explode, shooting hot glass out of the luminaire, or fixture. In an open luminaire - one that does not have a lens - this can result in a fire, personal injury, and property damage. Although violent failure is a rare occurrence (about three incidents per year), the NEC has included these changes to help eliminate the hazard.

In sports facilities, particularly in schools, athletic activity can break the outer jacket of a metal halide lamp used in an open luminaire. When this happens, the arc tube can continue to operate with a damaged or missing outer jacket. This leads to reports of UV over-exposure, including sunburn and a burning sensation around the eyes. The NEC change requires complete lamp enclosure in these facilities, which will provide mechanical protection to reduce the possibility of damage to the outer lamp jacket.

### NEC changes for open luminaires

The NEC change regarding open luminaires is the new section 410.73(F)(5) that states, "Metal Halide Lamp Containment. Luminaires (fixtures) that use a metal halide lamp other than a thick-glass parabolic reflector lamp (PAR) shall be provided with a containment barrier that encloses the lamp, or shall be provided with a physical means that only allows the use of a lamp that is Type O."

Therefore, to meet the 2005 NEC requirements, luminaires that use metal halide lamps must either:

- Be enclosed to provide a containment barrier.
- Use a special lampholder that will only accept an ANSI Type O rated metal halide lamp.

### NEC 2005 changes for sporting facilities

The NEC change regarding open luminaires is the new section 410.4(E) that states, "Luminaires (fixtures) subject to physical damage, using a mercury vapor or metal halide lamp, installed in playing and spectator seating areas of indoor sports, mixed-use, or all-purpose facilities shall be of the type that protects the lamp with a glass or plastic lens. Such luminaires (fixtures) shall be permitted to have an additional guard."

# MINIATURES & SEALED BEAMS




## Many sizes, many applications.

### Accent and indicator lighting

Satco miniatures are perfectly suited for those applications requiring specific sizes and a long lifespan. Miniature bulbs are, by definition, generally small in size and find their way into many applications and are available in a wide variety of filament constructions, bases, and wire terminal leads. Most are designed for operation with low voltage power sources such as battery/generator systems, dry cell or storage batteries, or transformers. Most common uses include flashlights, indicator lights, landscape lights, and appliances.






## Mini Lamps

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	MSCP	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
S6929	10	G3 1/2	Mini Bi Pin	G5	2.5	0.5	0.5	1.25	C-6	1 <sup>5</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	3000	Box	10
S6930	12	G3 1/2	Mini Bi Pin	G5	6.3	0.15	0.35	0.95	C-6	1 <sup>5</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	5000	Box	10
S6931	14	G3 1/2	Mini Screw	E10	2.47	0.3	0.5	0.074	C-2R	1 <sup>5</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	15	Box	10
S6932	19	G3 1/2	Mini Bi Pin	G5	14.4	0.1	0.9	1.44	C-6	1 <sup>5</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	1000	Box	10
S7019	24	T2 3/4	Euro Sub Mini Wedge	W2x4.6d	14	0.24	0.5	3.4	C-2V	1 <sup>3</sup> / <sub>16</sub>	3 <sup>8</sup> / <sub>16</sub>	1500	Box	10
S7020	27	G4 1/2	Mini Screw	E10	4.9	0.3	1.4	1.47	C-2R	1 <sup>5</sup> / <sub>8</sub>	9 <sup>1</sup> / <sub>16</sub>	30	Box	10
S7021	31	G4 1/2	Mini Screw	E10	6.15	0.3	2	1.85	C-2R	1 <sup>5</sup> / <sub>8</sub>	9 <sup>1</sup> / <sub>16</sub>	15	Box	10
S7022	37	T1 3/4	Sub Mini Wedge	W2.1x4.9d	14	0.1	—	1.4	C-2F	1 <sup>3</sup> / <sub>16</sub>	1 <sup>4</sup> / <sub>16</sub>	500	Box	10
S6908	40	T3 1/4	Mini Screw	E10	6.3	0.15	0.52	0.95	C-2R	1 <sup>3</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	3000	Box	10
S6909	41	T3 1/4	Mini Screw	E10	2.5	0.5	0.5	1.25	C-2R	1 <sup>3</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	3000	Box	10
S7023	43	T3 1/4	Mini Bay.	BA9s	2.5	0.5	—	1.25	C-2R	1 <sup>3</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	3000	Box	10
S6910	44	T3 1/4	Mini Bay.	BA9s	6.3	0.25	0.9	1.58	C-2R	1 <sup>3</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	3000	Box	10
S7024	45	T3 1/4	Mini Bay.	BA9s	3.2	0.35	—	1.12	C-2R	1 <sup>1</sup> / <sub>4</sub>	7 <sup>1</sup> / <sub>16</sub>	3000	Box	10
S6911	46	T3 1/4	Mini Screw	E10	6.3	0.25	0.9	1.58	C-2R	1 <sup>3</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	3000	Box	10
S6912	47	T3 1/4	Mini Bay.	BA9s	6.3	0.15	0.5	0.95	C-2R	1 <sup>3</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	3000	Box	10
S6913	48	T3 1/4	Mini Screw	E10	2	0.06	0.04	0.12	C-6	1 <sup>3</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	1000	Box	10
S7025	49	T3 1/4	Mini Bay.	BA9s	2	0.06	—	2	S2R	1 <sup>1</sup> / <sub>4</sub>	7 <sup>1</sup> / <sub>16</sub>	1000	Box	10
S6933	51	G3 1/2	Mini Bay.	BA9s	7.5	0.22	1	1.65	C-2R	1 <sup>3</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	1000	Box	10
S7026	52	G3 1/2	Midget Screw	E5.5	14.4	0.1	—	1.44	C-2V	1 <sup>5</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	1000	Box	10
S6934	53	G3 1/2	Mini Bay.	BA9s	14.4	0.12	1	1.73	C-2V	1 <sup>5</sup> / <sub>16</sub>	7 <sup>1</sup> / <sub>16</sub>	1000	Box	10
S7835	55	G4 1/2	Mini Bay.	BA9s	7	0.41	2	2.87	C-2R	1 <sup>5</sup> / <sub>8</sub>	9 <sup>1</sup> / <sub>16</sub>	200	Box	10
S6935	57	G4 1/2	Mini Bay.	BA9s	14	0.24	2	3.36	C-2V	1 <sup>5</sup> / <sub>8</sub>	9 <sup>1</sup> / <sub>16</sub>	500	Box	10
S6946	63	G6	Bi Pin G6	G6	7	0.63	3	4.41	C-6	1 <sup>7</sup> / <sub>16</sub>	3 <sup>4</sup> / <sub>16</sub>	1000	Box	10
S7865	64	G6	Bi Pin G6	G6	7	0.63	3	4.41	C-6	1 <sup>7</sup> / <sub>16</sub>	3 <sup>4</sup> / <sub>16</sub>	1000	Box	10
S6947	67	G6	Bi Pin G6	G6	13.5	0.59	4	7.97	C-6	1 <sup>7</sup> / <sub>16</sub>	3 <sup>4</sup> / <sub>16</sub>	5000	Box	10
S7029	68	G6	Bi Pin G6	G6	13.5	0.59	4	7.97	C-6	1 <sup>7</sup> / <sub>16</sub>	3 <sup>4</sup> / <sub>16</sub>	5000	Box	10
S7030	72	G5 3/4	Double Contact	BA15d	22	0.182	—	4	C-2V	1 <sup>5</sup> / <sub>8</sub>	3 <sup>4</sup> / <sub>16</sub>	200	Box	10
S6900	73	T1 3/4	Sub Mini Wedge	W2.1x4.9d	14	0.8	0.3	1.12	C-2F	1 <sup>3</sup> / <sub>16</sub>	1 <sup>4</sup> / <sub>16</sub>	15000	Box	10
S7031	74	T1 3/4	Sub Mini Wedge	W2.1x4.9d	14	0.1	—	1.4	C-2F	1 <sup>4</sup> / <sub>16</sub>	1 <sup>4</sup> / <sub>16</sub>	500	Box	10
S7032	81	G6	Single Contact	BA15s	6.5	1.02	—	6.63	C-2R	1 <sup>7</sup> / <sub>16</sub>	3 <sup>4</sup> / <sub>16</sub>	500	Box	10
S7033	82	G6	DC Bay.	BA15d	6.5	1.02	6	6.63	C-6	1 <sup>7</sup> / <sub>16</sub>	3 <sup>4</sup> / <sub>16</sub>	500	Box	10
S6901	85	T1 3/4	Sub Mini Wedge	W2.1x4.9d	28	0.04	0.3	1.12	C-2F	1 <sup>3</sup> / <sub>16</sub>	1 <sup>4</sup> / <sub>16</sub>	7000	Box	10
S6902	86	T1 3/4	Sub Mini Wedge	W2.1x4.9d	6.3	0.2	0.4	1.26	C-2F	1 <sup>3</sup> / <sub>16</sub>	1 <sup>4</sup> / <sub>16</sub>	20000	Box	10
S7034	87	S8	Double Contact	BA15d	6	2.17	—	13	C-6	—	1	200	Box	10
S6953	88	S8	DC Bay.	BA15d	6.8	1.91	15	12.99	C-6	2	1	300	Box	10




# MINIATURES & SEALED BEAMS



## Mini Lamps (continued)

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	MSCP	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S6948</b>	89	G6	SC Bay.	BA15s	13	0.58	6	7.54	C-6	1 7/16	3/4	750	Box	10
<b>S6949</b>	90	G6	DC Bay.	BA15d	13	0.58	6	7.54	C-6	1 7/16	3/4	750	Box	10
<b>S3623</b>	93	S8	SC Bay.	BA15s	12.8	1.04	15	13.31	C-6	1 7/16	1	700	Box	10
<b>S3723</b>	93	S8	SC Bay.	BA15s	12.8	1.04	15	13.31	C-6	1 7/16	1	700	CD/2	10
<b>S7782</b>	94	S8	DC Bay.	BA15d	12.8	1.04	15	13.3	C-2R	2	1	700	Box	10
<b>S6950</b>	97	G6	SC Bay.	BA15s	13.5	0.69	4	9.32	C-6	1 7/16	3/4	5000	Box	10
<b>S7036</b>	105	B6	Single Contact	BA15s	12.8	1	—	12.8	C-6	1 3/4	3/4	500	Box	10
<b>S7037</b>	112	TL3	Mini Screw	E10	1.2	0.22	—	0.26	S2R	1 5/16	3/8	5	Box	10
<b>S7054</b>	123	G3 1/2	Mini Screw	E10	1.25	0.3	—	0.37	S2R	1 5/16	7/16	10	Box	10
<b>S7055</b>	124	T3 1/4	Mini Wedge	W2.1x9.5d	14	0.27	1.5	3.78	C-2F	1 5/8	7/16	5000	Box	10
<b>S7059</b>	130	G3 1/2	Mini Bay.	BA9s	6.3	0.159	—	1	C-2R	1 5/16	7/16	5000	Box	10
<b>S7060</b>	131	G3 1/2	Mini Screw	E10	1.3	0.1	—	0.13	S2R	1 5/16	7/16	50	Box	10
<b>S7817</b>	147	T3 1/4	Mini Wedge	W2.1x9.5d	7	0.43	2	3.01	C-2R	1 5/8	7/16	1500	Box	10
<b>S7068</b>	158	T3 1/4	Mini Wedge	W2.1x9.5d	14	0.24	2	3.36	C-2V	1 5/8	7/16	500	Box	10
<b>S7069</b>	159	T3 1/4	Mini Wedge	W2.1x9.5d	6.3	0.15	0.34	9.45	C-2R	1 5/8	7/16	5000	Box	10
<b>S6914</b>	161	T3 1/4	Mini Wedge	W2.1x9.5d	14	0.19	9.45	2.66	C-2F	1 5/8	7/16	4000	Box	10
<b>S6915</b>	168	T3 1/4	Mini Wedge	W2.1x9.5d	14	0.35	4.9	4.9	C-2F	1 5/8	7/16	1500	Box	10
<b>S7838</b>	182	G3 1/2	Mini Bay.	BA9s	14.4	—	—	2.59	C-2F	1 5/16	7/16	2000	Box	10
<b>S7089</b>	192	T3 1/4	Mini Wedge	W2.1x9.5d	13	0.33	3	4.29	C-2V	1 5/8	7/16	1000	Box	10
<b>S7962</b>	193	T3 1/4	Mini Wedge	W2.1x9.5d	14	0.33	4.62	4.62	C-2F	1 5/8	7/16	15000	Box	10
<b>S6916</b>	194	T3 1/4	Mini Wedge	W2.1x9.5d	14	0.27	3.78	3.78	C-2F	1 5/8	7/16	2500	Box	10
<b>S7090</b>	198	S8	DC Indexed Bay.	Bay.15d	12.8	2.25	32	28.8	C-6	2	1	1200	Box	10
<b>S7091</b>	209	B6	Single Contact	BA15s	6.5	1.78	—	11.6	C-6	1 3/4	3/4	100	Box	10
<b>S7092</b>	210	B6	Double Contact	BA15d	6.5	1.77	—	11.5	C-6	1 1/2	3/4	100	Box	10
<b>S6907*</b>	222	TL-3	Mini Screw	E10	2.25	0.25	—	0.56	C-2R	1 5/16	3/8	5	Box	10
<b>S7096</b>	233	G3 1/2	Mini Screw	E10	2.33	0.27	—	0.63	C-2R	1 5/16	7/16	10	Box	10
<b>S7098</b>	243	TL-3	Mini Screw	E10	2.33	0.27	—	0.63	C-2R	1 5/16	3/8	10	Box	10
<b>S7099</b>	245	G3 1/2	Mini Screw	E10	2.46	0.5	—	1.23	C-2R	1 5/16	7/16	15	Box	10
<b>S7169</b>	251	T1 3/4	Midget Flange	SX6s	2.47	0.3	—	0.74	C-2R	5/8	1/4	30	Box	10
<b>S7170</b>	256	T3 1/4	Mini Bay.	BA9s	14	0.27	—	3.78	C-2R	1 1/4	7/16	500	Box	10
<b>S7171</b>	257	G4 1/2	Mini Bay.	BA9s	14	0.27	—	3.78	C-2R	1 1/16	5/16	500	Box	10
<b>S7172</b>	258	T4 1/2	Mini Screw	E10	14	0.27	—	3.78	C-2R	1 1/16	5/16	500	Box	10
<b>S7827</b>	259	T3 1/4	Mini Wedge	W2.1x9.5d	6.3	0.25	0.66	1.58	C-2R	1 5/8	7/16	5000	Box	10
<b>S7173</b>	265	G3 1/2	Mini Bay.	BA9s	28	0.08	—	2.24	C2F	1 5/16		5000	Box	10
<b>S7174</b>	268	T1 3/4	Midget Flange	SX6s	2.5	0.35	—	0.88	C-2R	5/8	1/4	10000	Box	10
<b>S7175</b>	301	G5 3/4	Single Contact	BA15s	28	0.179	—	5	C-2F	1 5/8	3/4	500	Box	10
<b>S7107</b>	304	G6	Double Contact	BA15d	28	0.3	—	8.4	C-2F	1 7/16	3/4	500	Box	10

\* 2 "AA" Cells




## Mini Lamps (continued)

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	MSCP	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S7109</b>	306	S8	DC Bay.	BA15d	28	0.51	15	14.28	C-6	2	1	300	Box	10
<b>S7110</b>	307	S8	Single Contact	BA15s	28	0.67	—	18.8	C-2V	2	1	300	Box	10
<b>S7111</b>	308	S8	Double Contact	BA15d	28	0.67	—	18.8	C-2V	2	1	300	Box	10
<b>S6917</b>	313	T3 1/4	Mini Bay.	BA9s	28	0.17	3.5	4.76	C-2F	1 3/16	7/16	500	Box	10
<b>S7112</b>	315	S8	SC Bay.	BA15s	28	0.9	—	25.2	C-2V	2	1	300	Box	10
<b>S6903</b>	327	T1 3/4	Midget Flange	SX6s	28	0.04	0.34	1.12	C-2F	5/8	1/4	4000	Box	10
<b>S7113</b>	328	T1 3/4	Midget Flange	SX6s	6	0.2	0.6	1.2	C-2R	5/8	1/4	1000	Box	10
<b>S7114</b>	330	T1 3/4	Midget Flange	SX6s	14	0.08	—	1.12	C-2F	5/8	1/4	2500	Box	10
<b>S7115</b>	331	T1 3/4	Midget Flange	SX6s	1.4	0.06	—	0.08	C-6	5/8	1/4	3000	Box	10
<b>S7116</b>	334	T1 3/4	Midget Grooved	S5.7s	28	0.04	—	1.12	C-2F	5/8	1/4	4000	Box	10
<b>S7117</b>	335	T1 3/4	Midget Screw	E5.5	28	0.04	0.34	1.12	C-2F	3/4	1/4	4000	Box	10
<b>S7119</b>	337	T1 3/4	Midget Grooved	S5.7s	6	0.2	—	1.2	C-2R	5/8	1/4	1000	Box	10
<b>S7120</b>	356	G3 1/2	Mini Bay.	BA9s	28	0.17	3.5	4.76	C-2V	1 5/16	1/4	500	Box	10
<b>S7121</b>	370	T1 3/4	Midget Flange	SX6s	18	0.04	—	0.72	C-2F	5/8	1/4	10000	Box	10
<b>S7122</b>	373	T1 3/4	Midget Screw	E5.5	14	0.08	—	1.12	C-2F	3/4	1/4	2500	Box	10
<b>S7123</b>	376	T1 3/4	Midget Flange	SX6s	28	0.06	—	1.68	C-2F	5/8	1/4	25000	Box	10
<b>S7124</b>	378	T1 3/4	Midget Screw	E5.5	6.3	0.2	—	1.26	C-2F	3/4	1/4	50000	Box	10
<b>S7125</b>	381	T1 3/4	Midget Flange	SX6s	6.3	0.2	—	1.26	C-2F	5/8	1/4	50000	Box	10
<b>S7126</b>	382	T1 3/4	Midget Flange	SX6s	14	0.08	—	1.12	C-2F	5/8	1/4	50000	Box	10
<b>S7127</b>	385	T1 3/4	Midget Flange	SX6s	28	0.04	—	1.12	C-2F	5/8	1/4	50000	Box	10
<b>S7128</b>	386	T1 3/4	Midget Grooved	S5.7s	14	0.08	—	1.12	C-2F	5/8	1/4	50000	Box	10
<b>S7829</b>	387	T1 3/4	Midget Flange	SX6s	28	0.04	0.3	1.12	C-2F	5/8	1/4	10000	Box	10
<b>S7830</b>	388	T1 3/4	Midget Grooved	S5.7s	28	—	—	1.12	C-2F	5/8	1/4	7000	Box	10
<b>S7129</b>	394	T1 3/4	Midget Flange	SX6s	12	0.04	0.12	0.48	C-2F	5/8	1/4	20000	Box	10
<b>S7130</b>	399	T1 3/4	Midget Screw	E5.5	28	0.04	—	1.12	C-2F	5/8	1/4	7000	Box	10
<b>S7131</b>	400	T3 1/4	Mini Wedge	W2.1x9.5d	28	0.1	—	2.8	C-2F	1 1/16	7/16	1000	Box	10
<b>S7132</b>	407	G4 1/2	Mini Screw	E10	4.9	0.3	—	1.47	C-2R	1 1/16	5/16	50	Box	10
<b>S6936</b>	425	G4 1/2	Mini Screw	E10	5	0.5	2.3	2.5	C-2R	1 3/8	5/16	15	Box	10
<b>S7133</b>	428	G4 1/2	Mini Screw	E10	12.5	0.25	2.04	3.13	C-2V	1 3/8	5/16	250	Box	10
<b>S7134</b>	432	G4 1/2	Mini Screw	E10	18	0.25	—	4.5	C-2V	1 1/16	5/16	250	Box	10
<b>S7135</b>	464	T3 1/4	Mini Wedge	W2.1x9.5d	28	0.179	—	5	C2F	1 1/16	7/16	1500	Box	10
<b>S6937</b>	502	G4 1/2	Mini Screw	E10	5.1	0.15	0.6	0.77	C-2R	1 3/8	5/16	100	Box	10
<b>S7136</b>	503	G4 1/2	Mini Bay.	BA9s	5.1	0.15	—	0.77	C-2R	1 1/16	5/16	100	Box	10
<b>S7137</b>	555	T3 1/4	Mini Wedge	W2.1x9.5d	6.3	0.25	—	1.58	C-2R	1 1/16	7/16	3000	Box	10
<b>S7138</b>	558	TL3	Mini Wedge	W2.1x9.5d	13	0.33	—	4.29	C-2V	1 1/16	3/8	500	Box	10
<b>S7139</b>	562	T3	Rigid Loop	Rigid Loop	13.5	0.741	—	10	C-8	1 3/4	3/8	2000	Box	10




# MINIATURES & SEALED BEAMS



## Mini Lamps (continued)

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	MSCP	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S7140</b>	563	T3	Rigid Loop	Rigid Loop	13.5	0.519	—	7	C-8	1 13/16	3/8	1000	Box	10
<b>S7141</b>	577	T4 3/4	EC11-5	EC11-5	12.8	1.4	—	17.9	C-6	1 11/16	5/8	1000	Box	10
<b>S7142</b>	585	T3 1/4	Mini Wedge	W2.1x9.5d	28	0.04	—	1.12	C-2F	1 1/4	7/16	7000	Box	10
<b>S7143</b>	590	T3 1/4	Mini Wedge	W2.1x9.5d	13.5	0.37	—	5	C2F	1 1/4	7/16	200	Box	10
<b>S7144</b>	605	G4 1/2	Mini Screw	E10	6.15	0.5	3.4	3.08	C-2R	1 5/8	9/16	15	Box	10
<b>S7145</b>	623	G6	Single Contact	BA15s	28	0.37	—	10.4	CC-2V	1 7/16	3/4	1000	Box	10
<b>S7146</b>	624	G6	DC Bay.	BA15d	28	0.37	—	10.4	CC-2V	1 7/16	3/4	1000	Box	10
<b>S7147</b>	631	G5 3/4	Single Contact	BA15s	14	0.629	—	8.8	2C2R	1 7/16	3/4	1000	Box	10
<b>S7837</b>	656	T3 1/4	Mini Wedge	W2.1x9.5d	28	0.06	0.62	1.68	C-2F	1 5/8	7/16	2500	Box	10
<b>S7702</b>	657	T3 1/4	Mini Wedge	W2.1x9.5d	28	0.08	—	2.24	C-2F	1 1/4	7/16	15000	Box	10
<b>S7148</b>	658	T3 1/4	Mini Wedge	W2.1x9.5d	14	0.08	—	1.12	C-2F	1 1/4	7/16	15000	Box	10
<b>S6918</b>	755	T3 1/4	Mini Bay.	BA9s	6.3	0.15	0.33	0.95	C-2R	1 3/16	7/16	20000	Box	10
<b>S6919</b>	756	T3 1/4	Mini Bay.	BA9s	14	0.08	0.31	1.12	C-2F	1 3/16	7/16	15000	Box	10
<b>S6920</b>	757	T3 1/4	Mini Bay.	BA9s	28	0.08	0.62	2.24	C-2F	1 3/16	7/16	15000	Box	10
<b>S7153</b>	787	T3	G4	G4	6	1.67	—	10	C-6	1 3/16	3/8	100	Box	10
<b>S7154</b>	789	T2 3/4	G4	G4	12	1.17	—	14	C-6	1 1/4	3/8	200	Box	10
<b>S7156</b>	880	T3 1/4	PG12	PG12	12.8	2.11	—	27	C-6	2 11/16	7/16	300	Box	10
<b>S7157*</b>	891	T2 1/2	Bi Pin G4	G4	12.8	0.625	11.5	8	C-6	1 3/16	9/16	500	Box	10
<b>S7158</b>	894	T3 1/4	PGJ13	PGJ13	12.8	2.93	—	37.5	C-6	2 11/16	7/16	200	Box	10
<b>S6938</b>	901	T5	Mini Wedge	W2.1x9.5d	12.8	0.31	2.9	3.97	C-2R	1 1/2	5/8	500	Box	10
<b>S6939</b>	904	T5	Mini Wedge	W2.1x9.5d	13.5	0.69	4	9.32	C-2F	1 1/2	5/8	5000	Box	10
<b>S6940</b>	906	T5	Mini Wedge	W2.1x9.5d	13	0.69	6	8.97	C-2F	1 1/2	5/8	1000	Box	10
<b>S6941</b>	908	T5	Mini Wedge	W2.1x9.5d	6	1.5	12	9	C-2R	1 1/2	5/8	50	Box	10
<b>S6942</b>	909	T5	Mini Wedge	W2.1x9.5d	6	0.62	3	3.72	C-2R	1 1/2	5/8	50	Box	10
<b>S6943</b>	912	T5	Mini Wedge	W2.1x9.5d	12.8	1	12	12.8	C-2R	1 1/2	5/8	1000	Box	10
<b>S7839</b>	914	T5	Mini Wedge	W2.1x9.5d	4	0.9	3.5	3.6	C-2R	1 1/2	5/8	50	Box	10
<b>S7866</b>	915	T5	Mini Wedge	W2.1x9.5d	12	0.75	11	9	C-2R	1 1/2	5/8	50	Box	10
<b>S7159</b>	916	T5	Mini Wedge	W2.1x9.5d	13.5	0.54	2	7.29	C-2F	1 1/2	5/8	10000	Box	10
<b>S7160</b>	917	T5	Mini Wedge	W2.1x9.5d	12.8	1.2	10	15.36	C-2F	1 1/2	5/8	1200	Box	10
<b>S6944</b>	918	T5	Mini Wedge	W2.1x9.5d	12.8	0.56	6.5	7.17	C-2R	1 1/2	5/8	500	Box	10
<b>S6945</b>	921	T5	Mini Wedge	W2.1x9.5d	12.8	1.4	21	17.92	C-2R	1 1/2	5/8	1000	Box	10
<b>S7161</b>	922	T5	Mini Wedge	W2.1x9.5d	12.8	0.98	15	12.54	C-2R	1 1/2	5/8	200	Box	10
<b>S7162</b>	923	T5	Mini Wedge	W2.1x9.5d	12.8	0.906	—	11.6	C-2R	1 1/2	5/8	200	Box	10
<b>S7163</b>	928	T5	Mini Wedge	W2.1x9.5d	28	0.3	—	8.4	C-2F	1 1/2	5/8	500	Box	10
<b>S7101</b>	939	T5	Mini Wedge	W2.1x9.5d	6	0.9	—	5.4	C-2R	1 1/2	5/8	50	Box	10
<b>S7165</b>	957	T4 1/2	Mini Bay.	BA9s	9.84	0.508	—	5	C-2R	1 3/8	9/16	200	Box	10

\* 2 "AA" Cells




## Mini Lamps (continued)

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	MSCP	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S6951</b>	1003	B6	SC Bay.	BA15s	12.8	0.94	15	12.03	C-6	1 3/4	3/4	200	Box	10
<b>S6952</b>	1004	B6	DC Bay.	BA15d	12.8	0.94	15	12.03	C-6	1 3/4	3/4	200	Box	10
<b>S6955</b>	1073	S8	SC Bay.	BA15s	12.8	1.8	32	23.04	C-6	2	1	200	Box	10
<b>S7861</b>	1076	S8	DC Bay.	BA15d	12.8	1.8	32	23.04	C-6	2	1	200	Box	10
<b>S7039</b>	1129	S8	SC Bay.	BA15s	6.4	2.63	21	16.83	C-6	2	1	200	Box	10
<b>S7040</b>	1130	S8	Double Contact	BA15d	6.4	2.69	-	17.2	C-6	2	1	200	Box	10
<b>S3624</b>	1133	RP11	SC Bay.	BA15s	6.2	3.91	32	24.24	C-6	2 1/4	1 3/8	200	Box	10
<b>S3724</b>	1133	RP11	SC Bay.	BA15s	6.2	3.91	32	24.24	C-6	2 1/4	1 3/8	200	Box	20
<b>S7041</b>	1134	RP11	DC Bay.	BA15d	6.2	3.87	-	24	C-2R	2 1/4	1 3/8	200	Box	10
<b>S6966</b>	1141	S8	SC Bay.	BA15s	12.8	1.6	21	18.43	C-6	2	1	1500	Box	10
<b>S7042</b>	1142	S8	DC Bay.	BA15d	12.8	1.6	21	18.43	C-6	2	1	1500	Box	10
<b>S7043</b>	1143	RP11	Single Contact	BA15s	12	2.07	-	24.8	C-2R	2 1/4	1 3/8	400	Box	10
<b>S7044</b>	1144	RP11	Double Contact	BA15d	12.5	1.98	-	24.8	C-2R	2 1/4	1 3/8	400	Box	10
<b>S7045</b>	1152	S8	Double Contact	BA15d	12.8	1.34	-	17.2	C-2R	2	1	500	Box	10
<b>S6956</b>	1154	S8	DC Indexed Bay.	Bay.15d	6.4	2.63	21	16.83	C-6	2	1	200	Box	10
<b>S7047</b>	1155	G6	Double Contact	BA15d	13.5	0.59	-	7.97	C-2R	1 7/16	3/4	5000	Box	10
<b>S6895</b>	1156	S8	SC Bay.	BA15s	12.8	2.1	32	26.88	C-6	2	1	1200	Box	10
<b>S6957</b>	1157	S8	DC Bay.	BA15d	12.8	2.1	32	26.88	C-6	2	1	1200	Box	10
<b>S7048</b>	1158	S8	Double Contact	BA15d	6.4	2.63	-	16.8	C-6	2	1	200	Box	10
<b>S7049</b>	1176	S8	Double Contact	BA15d	12.8	1.33	-	17 / 8.3	C-6	2	1	200	Box	10
<b>S7050</b>	1178	G5 3/4	DC Bay.	BY22d	13	-	-	9	C-2V	1 7/16	3/4	5000	Box	10
<b>S7051</b>	1195	RP11	Single Contact	BA15s	12.5	3	-	37	C-2V	2 1/4	1 3/8	300	Box	10
<b>S7052</b>	1196	RP11	Double Contact	BA15d	12.5	3	-	37	C-2V	2 1/4	1 3/8	300	Box	10
<b>S7053</b>	1224	G6	Double Contact	BA15d	34	0.16	-	5.44	C-2F	1 7/16	3/4	500	Box	10
<b>S7057</b>	1251	G6	Single Contact	BA15s	28	0.23	-	6.4	C-2R	1 3/8	3/4	2000	Box	10
<b>S7058*</b>	1252	G6	DC Bay.	BA15d	28	0.23	3	6.44	C-6	1 7/16	3/4	2000	Box	10
<b>S7061</b>	1385	R12	Single Contact	BA15s	28	0.72	-	20.2	CC-8	2 5/8	1 1/2	300	Box	10
<b>S7062</b>	1408	T3 1/4	Mini Bay.	BA9s	10	0.13	0.85	1.3	C-2V	1 3/16	7/16	250	Box	10
<b>S7063</b>	1447	G3 1/2	Mini Screw	E10	18	0.15	-	2.7	C-2V	1 5/16	7/16	250	Box	10
<b>S7064</b>	1449	G3 1/2	Mini Screw	E10	14	0.2	2	2.8	C-2V	1 5/16	7/16	250	Box	10
<b>S7065</b>	1477	T3 1/4	Mini Screw	E10	24	0.167	-	4	C-2V	1 3/16	7/16	250	Box	10
<b>S7961</b>	1487	T3 1/4	Mini Screw	E10	14	0.2	-	2.8	C-2V	1 3/16	7/16	3000	Box	10
<b>S7066</b>	1493	S8	Double Contact	BA15d	6.5	2.75	-	17.9	C-6	2	1	100	Box	10
<b>S7067</b>	1495	T4 1/2	Mini Bay.	BA9s	28	0.3	-	8.4	C-2F	1 3/8	9/16	500	Box	10


\* Series Filament

# MINIATURES & SEALED BEAMS



## Mini Lamps (continued)


Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	MSCP	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S7070</b>	1630	S8	Dbl. Cont. Prefocused Flanged	P15d30A	6.5	2.75	—	17.9	C-6	2	1	500	Box	10
<b>S7071</b>	1651	S8	SC Bay.	BA15s	5	0.6	3	3	C-6	2	1	20	Box	10
<b>S7072</b>	1810	T3 1/4	Mini Bay.	BA9s	6.3	0.4	—	2.52	C-2R	1 1/4	7/16	3000	Box	10
<b>S7862</b>	1813	T3 1/4	Mini Bay.	BA9s	14.4	0.1	—	1.44	C-2V	1 3/16	7/16	1000	Box	10
<b>S7073</b>	1815	T3 1/4	Mini Bay.	BA9s	14	0.2	1.4	2.8	C-2V	1 3/16	7/16	3000	Box	10
<b>S7074</b>	1816	T3 1/4	Mini Bay.	BA9s	13	0.33	3	4.29	C-2V	1 3/16	7/16	1000	Box	10
<b>S7075</b>	1818	T3 1/4	Mini Bay.	BA9s	24	0.17	—	4.08	C-2R	1 1/4	7/16	250	Box	10
<b>S7820</b>	1819	T3 1/4	Mini Bay.	BA9s	28	0.04	—	1.12	C-2F	1 1/2	7/16	2500	Box	10
<b>S7821</b>	1820	T3 1/4	Mini Bay.	BA9s	28	0.1	1.6	2.8	C-2F	1 3/16	7/16	1000	Box	10
<b>S7076</b>	1821	T3 1/4	Mini Screw	E10	28	0.179	—	5	C-2F	1 3/16	7/16	500	Box	10
<b>S7747</b>	1822	T3 1/4	Mini Bay.	BA9s	36	0.1	—	3.6	C-2F	1 1/4	7/16	1000	Box	10
<b>S7077</b>	1826	T3 1/4	Mini Bay.	BA9s	18	0.17	—	3.06	C-2V	1 1/4	7/16	250	Box	10
<b>S7078</b>	1828	T3 1/4	Mini Bay.	BA9s	37.5	0.05	—	1.88	C2F	1 1/4	7/16	3000	Box	10
<b>S7822</b>	1829	T3 1/4	Mini Bay.	BA9s	28	0.07	1	1.96	C-2F	1 3/16	7/16	1000	Box	10
<b>S7823</b>	1835	T3 1/4	Mini Bay.	BA9s	55	—	—	2.8	C-5	1 1/4	7/16	5000	Box	10
<b>S7824</b>	1847	T3 1/4	Mini Bay.	BA9s	6.3	0.15	0.38	0.95	C-2R	1 3/16	7/16	5000	Box	10
<b>S7079</b>	1850	T3 1/4	Mini Bay.	BA9s	5	0.09	—	0.45	C-2R	1 1/4	7/16	1500	Box	10
<b>S7080</b>	1864	T3 1/4	Mini Bay.	BA9s	28	0.17	3	4.76	C-2F	1 3/16	7/16	1500	Box	10
<b>S7825</b>	1866	T3 1/4	Mini Bay.	BA9s	6.3	—	—	1.58	C-2R	1 1/4	7/16	5000	Box	10
<b>S7081</b>	1873	T3 1/4	Mini Bay.	BA9s	28	0.2	—	5.6	C-2F	1 1/4	7/16	7000	Box	10
<b>S7082</b>	1888	T3 1/4	Mini Bay.	BA9s	7	0.5	—	3.5	C-2R	1 1/4	7/16	3000	Box	10
<b>S7083</b>	1889	T3 1/4	Mini Bay.	BA9s	14	0.27	—	14	C-2F	1 1/4	7/16	1500	Box	10
<b>S7084</b>	1891	T3 1/4	Mini Bay.	BA9s	14	0.24	—	3.36	C2F	1 1/4	7/16	500	Box	10
<b>S7085</b>	1892	T3 1/4	Mini Bay.	BA9s	14.4	0.12	0.75	1.73	C-2F	1 1/2	7/16	1000	Box	10
<b>S7086</b>	1893	T3 1/4	Mini Bay.	BA9s	14	0.33	2	4.62	C-2V	1 1/2	7/16	1000	Box	10
<b>S7087</b>	1895	G4 1/2	Mini Bay.	BA9s	14	0.27	—	3.75	C-2F	1 1/16	9/16	1500	Box	10
<b>S7088</b>	1906	T3 1/4	Mini Bay.	BA9s	5	0.07	—	0.35	C-6	1 1/4	7/16	1000	Box	10
<b>S6959</b>	2057	S8	DC Indexed Bay.	Bay.15d	12.8	2.1	32	26.88	C-6	2	1	1200	Box	10
<b>S7094</b>	2232	S8	Single Contact	BA15s	28	0.643	—	18	CC-8	2	1	2000	Box	10
<b>S7095</b>	2233	S8	Single Contact	BA15s	28	0.766	—	21.4	CC-8	2	1	2000	Box	10
<b>S6961</b>	2357	S8	DC Indexed Bay.	Bay.15d	12.8	2.23	—	28.54	C-6	2	1	400	Box	10
<b>S7097</b>	2396	S8	Single Contact	BA15s	12.8	2.23	—	28.5	C-6	2	1	400	Box	10
<b>S7108</b>	3057	S8	Plastic Wedge	W3x16q	12.8	2.1	32	26.88	C-6	2 15/16	1	1200	Box	10
<b>S6963</b>	3155	S8	Plastic Wedge	W3x16q	12.8	1.6	21	18.43	C-6	2 15/16	1	1500	Box	10
<b>S6964</b>	3156	S8	Plastic Wedge	W3x16q	12.8	2.1	32	26.88	C-6	2 15/16	1	1200	Box	10
<b>S6965</b>	3157	S8	Plastic Wedge	W3x16q	12.8	2.1	32	26.88	C-6	2 15/16	1	1200	Box	10
<b>S7118</b>	3357	S8	Plastic Wedge	W3x16q	12.8	2.23	40	28.54	C-6	2 15/16	1	800	Box	10



## Mini Lamps (continued)

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	MSCP	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S7149</b>	7327	T1 3/4	G3.17	G3.17	28	0.04	—	1.12	C-2F	5/8	1/4	4000	Box	10
<b>S7150</b>	7376	T1 3/4	G3.17	G3.17	28	0.065	—	1.82	C-2F	5/8	1/4	5000	Box	10
<b>S7151</b>	7382	T1 3/4	G3.17	G3.17	14	0.08	—	1.12	C-2F	5/8	1/4	50000	Box	10
<b>S7883</b>	7387	T1 3/4	G3.17	G3.17	28	0.04	—	1.12	C-2F	5/8	1/4	7000	Box	10
<b>S7152</b>	7839	T1	G1.27	G1.27	28	0.024	—	0.67	C-2R	3/8	1/8	16000	Box	10
<b>S7155</b>	8610	T1 3/4	Wire Leads	—	6.3	0.2	—	1.26	C-2R	7/16	1/4	5000	Box	10
<b>VJ020</b>	64111	T2 3/4	Mini Bay.	BA9s	12	—	—	5	C-6	1 3/16	3/8	240	Box	10
<b>S7038</b>	112/BP	TL3	Mini Screw	E10	1.2	0.22	—	0.26	S2R	1 5/16	—	5	Box	10
<b>S6896</b>	1156NA	S8	SC Bay.	BA15s	12.8	2.1	24	26.88	C-6	2	1	1200	Box	10
<b>S6958</b>	1157NA	S8	DC Bay.	BA15d	12.8	2.1	—	26.88	C-6	2	1	1200	Box	10
<b>S6905</b>	120MB	T2 1/2	Mini Bay.	BA9s	120	0.025	—	3	C-2F	1 3/16	5/16	10000	Box	10
<b>S7816</b>	120PSB5	T2	Telephone Slide	T55	120	0.025	—	3	C-2F	1 1/8	1/4	10000	Box	10
<b>S7056</b>	124/BP	T3 1/4	Mini Wedge	W2.1x9.5d	14	0.27	—	3.78	C2F	1 1/16	—	5000	Box	10
<b>S7815</b>	12PSB	T2	Telephone Slide	T55	12	0.17	—	2.04	C-2F	1 1/8	1/4	12000	Box	10
<b>S7762</b>	130MB	T2 1/2	Mini Bay.	BA9s	130	0.025	—	0.33	CC-7A	1 3/16	5/16	10000	Box	10
<b>S6960</b>	2057NA	S8	DC Indexed Bay.	Bay.15d	12.8	2.1	—	26.88	C-6	2	1	1200	Box	10
<b>S6906</b>	211-2	Festoon	DE Cap	SF6	12.8	0.97	—	12.42	C-8	1 3/4	0	1000	Box	10
<b>S7093</b>	214-2	T3	DE Cap	SF6	13.5	0.52	—	7.02	C-8	1 3/4	3/8	2000	Box	10
<b>S6962</b>	2357NA	S8	DC Indexed Bay.	Bay.15d	12.8	2.23	—	28.54	C-6	2	1	400	Box	10
<b>S7863</b>	24MB	T2 1/2	Mini Bay.	BA9s	24	0.073	—	1.68	C-2F	1 1/8	5/16	10000	Box	10
<b>S6904</b>	24PSB5	T2	Telephone Slide	T55	24	0.073	—	1.75	C-2F	1 1/8	1/4	10000	Box	10
<b>S7864</b>	28MB	T2 1/2	Mini Bay.	BA9s	28	0.04	—	1.4	C-2F	1 1/8	5/16	5000	Box	10
<b>S7828</b>	28PSB5	T2	Telephone Slide	T55	28	—	—	2.04	C-2F	1 1/8	1/4	6000	Box	10
<b>S7832</b>	509K	G6	Candelabra	E12	24	0.18	2.8	4.32	C-2F	1 3/8	3/8	1000	Box	10
<b>S7968</b>	55W/12VH1	T2 1/2	P14.5s	P14.5s	120	—	—	55	C-8	2 7/16	5/16	350	Box	10
<b>S7836</b>	6PSB	T2	Telephone Slide	T55	6	0.14	—	0.84	C-2F	1 1/8	1/4	15000	Box	10
<b>S7801</b>	NE51H	T3 1/4	Mini Bay.	BA9s	105	—	—	0.14	Neon	1 3/16	7/16	25000	Box	10
<b>S6926</b>	PR12	B3 1/2	Flange	P13.5s	5.95	0.5	—	2.98	C-2R	1 1/4	7/16	15	Box	10
<b>S6927</b>	PR13	B3 1/2	Flange	P13.5s	4.75	0.5	—	2.38	C-2R	1 1/4	7/16	15	Box	10
<b>S7970</b>	PR15	B3 1/2	Single Cont. Mini Flange	P13.5s	4.8	0.5	—	2.4	C-2R	1 1/4	7/16	30	Box	10
<b>S7166</b>	PR16	B3 1/2	Single Cont. Mini Flange	P13.5s	12.5	0.25	—	3.13	C-2R	1 1/4	7/16	50	Box	10
<b>S7167</b>	PR18	B3 1/2	Flange	P13.5s	7.2	0.55	5.5	3.96	C-2R	1 1/4	7/16	3	Box	10
<b>S7168</b>	PR20	B3 1/2	Flange	P13.5s	8.63	0.5	—	4.32	C-2R	1 1/4	7/16	15	Box	10
<b>S6921</b>	PR2	B3 1/2	Flange	P13.5s	2.38	0.5	—	1.19	C-2R	1 1/4	7/16	15	Box	10
<b>S6922</b>	PR3	B3 1/2	Flange	P13.5s	3.57	0.5	—	1.79	C-2R	1 1/4	7/16	15	Box	10
<b>S6928</b>	PR30	B3 1/2	Flange	P13.5s	3.75	0.86	—	3.23	C-2R	1 1/4	7/16	40	Box	10
<b>S6923</b>	PR4	B3 1/2	Flange	P13.5s	2.33	0.27	—	0.63	C-2R	1 1/4	7/16	10	Box	10
<b>S6924</b>	PR6	B3 1/2	Flange	P13.5s	2.47	0.3	—	0.74	C-2R	1 1/4	7/16	30	Box	10

# MINIATURES & SEALED BEAMS



## Mini Lamps (continued)

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	MSCP	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Master/Inner Carton
<b>S6925</b>	PR7	B3 1/2	Flange	P13.5s	3.7	0.3	—	1.11	C-2R	1 ¼	7/16	30	Box	10
<b>S6101</b>	1210 X	T3 1/4	Mini Wedge	W2.1x9.5d	12	0.833	—	10	C-2R	1 15/16	7/16	3000	Box	1000/10
<b>S6102</b>	1210 XF	T3 1/4	Mini Wedge	W2.1x9.5d	12	0.833	—	10	C-2R	1 15/16	7/16	3000	Box	1000/10


## Festoon Incandescent Lamps

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	MSCP	Approx. Watts	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Master/Inner Carton
<b>VG020</b>	6411	T3 1/4	Festoon	SV8.5-8	12	0.83	100*	10	1 ¾	7/16	18-Jul	Box	200/10
<b>VG040</b>	6413	T3 1/4	Festoon	SV8.5-8	12	0.4	45*	5	1 ¾	7/16	18-Jul	Box	200/10
<b>S2399</b>	6421	T3 1/4	Festoon	SV8.5-8	24	0.125	18*	3	1 ¾	7/16	26-Sep	Box	200/10
<b>VG100</b>	6424	T3 1/4	Festoon	SV8.5-8	24	0.2	62*	5	1 ¾	7/16	18-Jul	Box	200/10
<b>VG130</b>	6429	T3 1/4	Festoon	SV8.5-8	24	0.42	105*	10	1 ¾	7/16	18-Jul	Box	200/10

\* Lumens

## Festoon & Rigid Xenon Lamps

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	Approx. Watts	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Master/Inner Carton
<b>S6985</b>	XST3 1/4 12V Festoon	T3 1/4	Festoon	SV8.5-8	12	0.37	5	1 ¾	7/16	20000	Box	500/10
<b>S6987</b>	XST3 1/4 24V Festoon	T3 1/4	Festoon	SV8.5-8	24	0.19	5	1 ¾	7/16	15000	Box	500/10
<b>S6989</b>	XST3 1/4 F Festoon	T3 1/4	Festoon	SV8.5-8	12	0.37	5	1 ¾	7/16	20000	Box	500/10
<b>S6991</b>	XST3 1/4 F 24V Festoon	T3 1/4	Festoon	SV8.5-8	24	0.19	5	1 ¾	7/16	15000	Box	500/10
<b>S6993</b>	5RLX 12V Rigid Loop	T3	Rigid Loop	Rigid Loop	12	0.417	5	1 11/16	3/8	20000	Box	500/10
<b>S6995</b>	5RLX 24V Rigid Loop	T3	Rigid Loop	Rigid Loop	24	0.208	5	1 11/16	3/8	20000	Box	500/10
<b>S6997</b>	5RLX F 12V Rigid Loop	T3	Rigid Loop	Rigid Loop	12	0.417	5	1 11/16	3/8	20000	Box	500/10
<b>S6999</b>	5RLX F 24V Rigid Loop	T3	Rigid Loop	Rigid Loop	24	0.208	5	1 11/16	3/8	20000	Box	500/10
<b>S6986</b>	X10T3 1/4 12V Festoon	T3 1/4	Festoon	SV8.5-8	12	0.74	10	1 ¾	7/16	20000	Box	500/10
<b>S6988</b>	X10T3 1/4 24V Festoon	T3 1/4	Festoon	SV8.5-8	24	0.39	10	1 ¾	7/16	10000	Box	500/10
<b>S6990</b>	X10T3 1/4 F Festoon	T3 1/4	Festoon	SV8.5-8	12	0.74	10	1 ¾	7/16	20000	Box	500/10
<b>S6992</b>	X10T3 1/4 F Festoon	T3 1/4	Festoon	SV8.5-8	24	0.39	10	1 ¾	7/16	10000	Box	500/10
<b>S6994</b>	10RLX 12V Rigid Loop	T3	Rigid Loop	Rigid Loop	12	0.833	10	1 11/16	3/8	20000	Box	500/10
<b>S6996</b>	10RLX 24V Rigid Loop	T3	Rigid Loop	Rigid Loop	24	0.417	10	1 11/16	3/8	20000	Box	500/10
<b>S6998</b>	10RLX F 12V Rigid Loop	T3	Rigid Loop	Rigid Loop	12	0.833	10	1 11/16	3/8	20000	Box	500/10
<b>S6850</b>	10RLX/F 10W 24V Rigid Loop	T3	Rigid Loop	Rigid Loop	24	0.417	10	1 11/16	3/8	20000	Box	500/10




## Wedge Base Xenon Lamps

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Amps	Approx. Watts	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S6968</b>	X3T3 1/4 12V Wedge	T3 1/4	Mini Wedge	W2.1x9.5d	12	0.41	3	1 5/8	7/16	20000	Box	1000
<b>S6969</b>	X5T3 1/4 12V Wedge	T3 1/4	Mini Wedge	W2.1x9.5d	12	0.37	5	1 5/8	7/16	8000	Box	1000
<b>S6974</b>	X5T3 1/4 24V Wedge	T3 1/4	Mini Wedge	W2.1x9.5d	24	0.21	5	1 5/8	7/16	10000	Box	1000
<b>S6972</b>	X5T3 1/4 F 12V Wedge	T3 1/4	Mini Wedge	W2.1x9.5d	12	0.37	5	1 5/8	7/16	8000	Box	1000
<b>S6976</b>	X5T3 1/4 F 24V Wedge	T3 1/4	Mini Wedge	W2.1x9.5d	24	0.21	5	1 5/8	7/16	10000	Box	1000
<b>S6975</b>	X7.5T3 1/4 24V Wedge	T3 1/4	Mini Wedge	W2.1x9.5d	24	0.31	7.5	1 5/8	7/16	10000	Box	1000
<b>S6977</b>	X7.5T3 1/4 F 24V Wedge	T3 1/4	Mini Wedge	W2.1x9.5d	24	0.31	7.5	1 5/8	7/16	10000	Box	1000
<b>S6979</b>	X7.2T5 24V Wedge	T5	Mini Wedge	W2.1x9.5d	24	0.3	7.2	1 1/2	5/8	2500	Box	1000
<b>S6982</b>	X7.2T5 F 24V Wedge	T5	Mini Wedge	W2.1x9.5d	24	0.3	7.2	1 1/2	5/8	2500	Box	1000
<b>S6980</b>	X10T5 24V Wedge	T5	Mini Wedge	W2.1x9.5d	24	0.42	10	1 1/2	5/8	2000	Box	1000
<b>S6983</b>	X10T5 F 24V Wedge	T5	Mini Wedge	W2.1x9.5d	24	0.42	10	1 1/2	5/8	2000	Box	1000
<b>S6978</b>	X18T5 12V Wedge	T5	Mini Wedge	W2.1x9.5d	12	1.5	18	1 1/2	5/8	10000	Box	1000
<b>S6981</b>	X18T5 12V Wedge	T5	Mini Wedge	W2.1x9.5d	12	1.5	18	1 1/2	5/8	10000	Box	1000

## Halogen Sealed Beam Lamps for General & Display

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S4807</b>	36PAR36/CAP/VNSP	PAR36	Screw Terminal	MP2	12	36	CC-8	2 3/4	4 1/2	4000	Box	12
<b>S4808</b>	36PAR36/CAP/NSP	PAR36	Screw Terminal	MP2	12	36	CC-8	2 3/4	4 1/2	4000	Box	12
<b>S4809</b>	36PAR36/CAP/WFL	PAR38	Screw Terminal	MP2	12	36	CC-8	2 3/4	4 3/4	4000	Box	12
<b>S4806</b>	50PAR36CAPNSP	PAR36	Screw Terminal	MP2	12	50	CC-8	2 3/4	4 1/2	4000	Box	12
<b>S4668</b>	500PAR56Q/NSP	PAR56	Mogul End Prong	GX16d	120	500	CC-6	5	7	4000	Box	12
<b>S4669</b>	500PAR56Q/MFL	PAR56	Mogul End Prong	GX16d	120	500	CC-6	5	7	4000	Box	12
<b>S4670</b>	500PAR56Q/WFL	PAR56	Mogul End Prong	GX16d	120	500	CC-6	5	7	4000	Box	12
<b>S4671</b>	1000PAR64Q/NSP	PAR64	Mogul End Prong	GX16d	120	1000	CC-6	6	8	4000	Box	6
<b>S4672</b>	1000PAR64Q/MFL	PAR64	Mogul End Prong	GX16d	120	1000	CC-6	6	8	4000	Box	6
<b>S4673</b>	1000PAR64Q/WFL	PAR64	Mogul End Prong	GX16d	120	1000	CC-6	6	8	4000	Box	6

# MINIATURES & SEALED BEAMS



## Landscape Lamps 12V – 4PK Card

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S4551</b>	4T5	T5	Mini Wedge	W2.1x9.5d	12	4	C-2R	5/8	5/8	1000	CD/4	20
<b>S4552</b>	7T5	T6	Mini Wedge	W2.1x9.5d	12	7	C-2R	5/8	3/4	1000	CD/4	20
<b>S4553</b>	11T5	T7	Mini Wedge	W2.1x9.5d	12	11	C-2R	5/8	7/8	1000	CD/4	20
<b>S4554</b>	18T5	T8	Mini Wedge	W2.1x9.5d	12	18	C-2R	5/8	1	1000	CD/4	20

## Incandescent Sealed Beam Lamps for General & Display

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Approx. Watts	Filament	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S4804 ▲</b>	50PAR36/WFL	PAR36	Screw Terminal	MP2	12	50	C-6	2 3/4	4 1/2	2000	Box	12
<b>S4342 ▲</b>	200PAR46/3NSP	PAR46	Side Prong	MSPG	120	200	CC-13	4	5 3/4	2000	Box	12
<b>S4340 ▲</b>	200PAR46/3MFL	PAR46	Side Prong	MSPG	120	200	CC-13	4	5 3/4	2000	Box	12
<b>S4344 ▲</b>	200PAR56/MFL	PAR56	Mogul End Prong	GX16d	120	200	CC-13	5	7	2000	Box	12
<b>S4963 ▲</b>	300PAR56/NSP	PAR56	Mogul End Prong	GX16d	120	300	CC-13	5	7	2000	Box	12
<b>S4810 ▲</b>	300PAR56/MFL	PAR56	Mogul End Prong	GX16d	120	300	CC-13	5	7	2000	Box	12
<b>S4346 ▲</b>	300PAR56/MFL	PAR56	Mogul End Prong	GX16d	130	300	CC-13	5	7	2000	Box	12
<b>S4811 ▲</b>	300PAR56/WFL	PAR56	Mogul End Prong	GX16d	120	300	CC-13	5	7	2000	Box	12
<b>S4348 ▲</b>	500PAR64/NSP	PAR64	Mogul End Prong	GX16d	120	500	CC-13	6	8	2000	Box	6
<b>S4349 ▲</b>	500PAR64/MFL	PAR64	Mogul End Prong	GX16d	120	500	CC-13	6	8	2000	Box	6
<b>S4351 ▲</b>	500PAR64/WFL	PAR64	Mogul End Prong	GX16d	120	500	CC-13	6	8	2000	Box	6

▲ Product by one of the Primary lamp manufacturers.





PAR 36  
Screw  
Term.



PAR 46  
Screw  
Term.



PAR 36  
Slip On  
Term.

## Sealed Beam Lamps for Equipment

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Approx. Watts	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S4300</b>	4014	PAR36	Screw Terminal	MP2	6.4	18	2 3/4	4 1/2	200	Box	12
<b>S4301</b>	4042	PAR36	Screw Terminal	MP2	6.4	12	2 3/4	4 1/2	150	Box	12
<b>S4302</b>	4044	PAR36	Screw Terminal	MP2	12	12	2 3/4	4 1/2	150	Box	12
<b>S4303</b>	4405	PAR36	Screw Terminal	MP2	12.8	30	2 3/4	4 1/2	100	Box	12
<b>S4304</b>	4406	PAR36	Screw Terminal	MP2	12.8	35	2 3/4	4 1/2	300	Box	12
<b>S4305</b>	4411	PAR36	Screw Terminal	MP2	12.8	35	2 3/4	4 1/2	300	Box	12
<b>S4306</b>	4414	PAR36	Screw Terminal	MP2	12.8	18	2 3/4	4 1/2	300	Box	12
<b>S4307</b>	4415	PAR36	Screw Terminal	MP2	12.8	35	2 3/4	4 1/2	300	Box	12
<b>S4316</b>	4416	PAR36	Screw Terminal	MP2	12.8	30	2 3/4	4 1/2	100	Box	12
<b>S4335</b>	4435	PAR46	Screw Terminal	MP2	12.8	30	2 3/4	5 3/4	100	Box	12
<b>S4317</b>	4446	PAR36	Screw Terminal	MP2	12.8	25	2 3/4	4 1/2	300	Box	12
<b>S4318</b>	4502	PAR36	Screw Terminal	MP2	28	50	2 3/4	4 1/2	400	Box	12
<b>S4319</b>	4505	PAR36	Screw Terminal	MP2	28	50	2 3/4	4 1/2	400	Box	12
<b>S4320</b>	4509	PAR36	Screw Terminal	MP2	13	100	2 3/4	4 1/2	25	Box	12
<b>S4321</b>	4510	PAR36	Screw Terminal	MP2	6.4	25	2 3/4	4 1/2	300	Box	12
<b>S4322</b>	4515	PAR36	Screw Terminal	MP2	6.4	30	2 3/4	4 1/2	100	Box	12
<b>S4323</b>	4516	PAR36	Screw Terminal	MP2	6.2	30	2 3/4	4 1/2	300	Box	12
<b>S4324</b>	4535	PAR46	Screw Terminal	MP2	6.4	30	2 3/4	5 3/4	100	Box	12
<b>S4336</b>	4546	PAR36	Screw Terminal	MP2	4.7	2.35	2 3/4	4 1/2	100	Box	12
<b>S4333</b>	7613	PAR36	Screw Terminal	MP2	6	8	2 3/4	4 1/2	50	Box	12
<b>S4334</b>	7672-1	PAR36	Slip On Terminal	SOT2	6	7.2	2 3/4	4 1/2	50	Box	12

## Sealed Beam Lamps for Equipment

Satco Prod. #	Lamp Code	Lamp Shape	Base	ANSI Base	Volts	Approx. Watts	M.O.L. Inches	M.O.D. Inches	Avg. Rated Hours	Pkg. Type	Carton
<b>S4325</b>	H7550	PAR36	Screw Terminal	MP2	6	8	2 3/4	4 1/2	50	Box	12
<b>S4326</b>	H7551	PAR36	Screw Terminal	MP2	6	8	2 3/4	4 1/2	50	Box	12
<b>S4327</b>	H7552	PAR36	Screw Terminal	MP2	6	10	2 3/4	4 1/2	50	Box	12
<b>S4328</b>	H7553	PAR36	Screw Terminal	MP2	6	12	2 3/4	4 1/2	50	Box	12
<b>S4329</b>	H7554	PAR36	Screw Terminal	MP2	6	20	2 3/4	4 1/2	50	Box	12
<b>S4330</b>	H7555	PAR36	Screw Terminal	MP2	12	8	2 3/4	4 1/2	50	Box	12
<b>S4331</b>	H7556	PAR36	Screw Terminal	MP2	6	6	2 3/4	4 1/2	50	Box	12
<b>S4332</b>	H7557	PAR36	Screw Terminal	MP2	12	12	2 3/4	4 1/2	50	Box	12

# HID BALLASTS



## The right power for the job.

### **Operates a variety of lamps.**

Satco has a wide variety of HID ballasts to operate the wide variety of metal halide, high pressure sodium, and low pressure sodium available in today's marketplace.

### **Purpose of a ballast.**

Like fluorescent lamps, HID are gas discharge lamps. Light is produced by an arc discharge between two electrodes located at opposite ends of an arc tube within the lamp's outer glass envelope. The ballast is the lamp's power supply, providing the proper starting and operating current and voltage to start and sustain this arc.

## MH Magnetic Ballasts – Pulse Start (5 Tap is a SKU reducer)

Primary Lamp Type	Tap	Satco Product #	Ballast Code	Circuit Type	ANSI	Start Method	Title 20	Carton
<b>50W PS</b>	5	<b>LPT83602</b>	P50ML5AC3 PULSE MH50	CWA	M110	PULSE	N	1
<b>70W PS</b>	5	<b>LPT88603</b>	P70ML5AA3 PULSE MH70	HX-HPF	M98, M85	PULSE	N	1
<b>100W PS</b>	5	<b>LPT88604</b>	P100ML5AA3 PULSE MH100	HX-HPF	M90	PULSE	N	1
<b>150W PS</b>	5	<b>LPT88605</b>	P150ML5AA3 PULSE MH150	CWA	M102, M81	PULSE	N	1
<b>250W PS</b>	5	<b>LPT88608</b>	P250ML5AA4 PULSE MH250	CWA	M138, M153	PULSE	N	1
<b>320W PS</b>	5	<b>LPT88609</b>	P320ML5AA4 PULSE MH320	CWA	M132, M154	PULSE	N	1
<b>350W PS</b>	5	<b>LPT88610</b>	P350ML5AA4 PULSE MH350	CWA	M131	PULSE	N	1
<b>400W PS</b>	5	<b>LPT88611</b>	P400ML5AA4 PULSE MH400	CWA	M135, M155	PULSE	N	1
<b>750W PS</b>	5	<b>LPT88613</b>	P750ML5AA5 PULSE MH750	CWA	M149	PULSE	N	1
<b>1000W PS</b>	5	<b>LPT84614</b>	P1000ML5AB5 PULSE MH1000	CWA	M141	PULSE	N	1
<b>175W PS</b>	4	<b>LPT85506</b>	P175MLTEC4 PULSE MH175	CWA	M137, M152	PULSE	Y	1
<b>200W PS</b>	4	<b>LPT85507</b>	P200MLTEC4 PULSE MH200	CWA	M136	PULSE	Y	1
<b>250W PS</b>	4	<b>LPT85508</b>	P250MLTEC4 PULSE MH250	CWA	M138, M153	PULSE	Y	1
<b>320W PS</b>	4	<b>LPT85509</b>	P320MLTEC4 PULSE MH320	CWA	M132, M154	PULSE	Y	1
<b>350W PS</b>	4	<b>LPT85510</b>	P350MLTEC4 PULSE MH350	CWA	M131	PULSE	Y	1
<b>400W PS</b>	4	<b>LPT85511</b>	P400MLTEC4 PULSE MH400	CWA	M135, M155	PULSE	Y	1
<b>70W PS</b>	3	<b>LPT83703</b>	P70TRILC3 PULSE MH70	HX-HPF	M98, M85	PULSE	N	1
<b>100W PS</b>	3	<b>LPT83704</b>	P100TRILC3 PULSE MH100	HX-HPF	M90, M140	PULSE	N	1
<b>150W PS</b>	3	<b>LPT83705</b>	P150TRILC3 PULSE MH150	HX-HPF	M102, M142	PULSE	N	1
<b>175W PS</b>	3	<b>LPT83706</b>	P175TRILC3 PULSE MH175	CWA	M137, M152	PULSE	–	1
<b>200W PS</b>	3	<b>LPT83707</b>	P200TRIAC3 PULSE MH200	CWA	M136	PULSE	–	1
<b>250W PS</b>	3	<b>LPT83708</b>	P250TRIAC4 PULSE MH250	CWA	M138, M153	PULSE	–	1
<b>320W PS</b>	3	<b>LPT83709</b>	P320TRIAC4 PULSE MH320	CWA	M132, M154	PULSE	–	1
<b>350W PS</b>	3	<b>LPT83710</b>	P350TRIAC4 PULSE MH350	CWA	M131	PULSE	–	1
<b>400W PS</b>	3	<b>LPT83711</b>	P400TRIAC4 PULSE MH400	CWA	M135, M155	PULSE	–	1
<b>750W PS</b>	3	<b>LPT83713</b>	P750TRIAC5 PULSE MH750	CWA	M149	PULSE	–	1
<b>1000W PS</b>	3	<b>LPT83714</b>	P1000TRIAC5 PULSE MH1000	CWA	M141	PULSE	–	1
<b>750W PS</b>	480/120	<b>LPT83413</b>	P75048TAC5 PULSE MH750	CWA	M149	PULSE	N	1

# HID BALLASTS

## MH Magnetic Ballasts – Probe Start (5 Tap is a SKU reducer)

Primary Lamp Type	Tap	Satco Product #	Ballast Code	Circuit Type	ANSI	Start Method	Title 20	Carton
<b>MH175</b>	5	<b>LPT87606</b>	M175ML5AA3 PROBE MH175	CWA	M57	PROBE	N	1
<b>MH250</b>	5	<b>LPT87608</b>	M250ML5AA4 PROBE MH250	CWA	M58	PROBE	N	1
<b>MH400</b>	5	<b>LPT87611</b>	M400ML5AA4 PROBE MH400	CWA	M59	PROBE	N	1
<b>MH1000</b>	5	<b>LPT87614</b>	M1000ML5AA5 PROBE MH1000	CWA	M47	PROBE	N	1
<b>MH1500</b>	5	<b>LPT81615</b>	M1500ML5AC5 PROBE MH1500	CWA	M48	PROBE	N	1
<b>MH175</b>	4	<b>LPT81506</b>	M175MLTAC3 PROBE MH175	CWA	M57	PROBE	N	1
<b>MH400</b>	4	<b>LPT81511</b>	M400MLTAC4 PROBE MH400	CWA	M59	PROBE	N	1
<b>MH1000</b>	4	<b>LPT81514</b>	M1000MLTAC5 PROBE MH1000	CWA	M47	PROBE	N	1
<b>MH1500</b>	4	<b>LPT89515</b>	M1500MLTAB5 PROBE MH1500	CWA	M48	PROBE	N	1
<b>MH400</b>	480/120	<b>LPT81411</b>	M40048TAC4 PROBE MH400	CWA	M59	PROBE	N	1
<b>MH1000</b>	480/120	<b>LPT81414</b>	M100048TAC5 PROBE MH1000	CWA	M47	PROBE	N	1
<b>MH175</b>	3	<b>LPT81706</b>	M175TRIAC3 PROBE MH175	CWA	M57	PROBE	N	1
<b>MH250</b>	3	<b>LPT81708</b>	M250TRIAC4 PROBE MH250	CWA	M58	PROBE	N	1
<b>MH2400</b>	3	<b>LPT81711</b>	M400TRIAC4 PROBE MH400	CWA	M59	PROBE	N	1
<b>MH1000</b>	3	<b>LPT81714</b>	M1000TRIAC5 PROBE MH1000	CWA	M47	PROBE	N	1

## HPS Magnetic Ballasts – 5 & 4 Tap

Primary Lamp Type	Tap	Satco Product #	Ballast Code	Circuit Type	ANSI	Start Method	Title 20	Carton
<b>250W HPS</b>	5	<b>LPT86608</b>	S250ML5AA4 HPS250	CWA	S50	–	N	1
<b>400W HPS</b>	5	<b>LPT86611</b>	S400ML5AA4 HPS400	CWA	S51	–	N	1
<b>600W HPS</b>	5	<b>LPT86612</b>	S600ML5AA4 HPS600	CWA	S106	–	N	1
<b>1000W HPS</b>	5	<b>LPT86614</b>	S1000ML5AA5 HPS1000	CWA	S52	–	N	1
<b>50W HPS</b>	4	<b>LPT82502</b>	S50MLTLC3 HPS50	HX-HPF	S68	–	N	1
<b>70W HPS</b>	4	<b>LPT82503</b>	S70MLTLC3 HPS70	HX-HPF	S62	–	N	1
<b>100W HPS</b>	4	<b>LPT82504</b>	S100MLTLC3 HPS100	HX-HPF	S54	–	N	1
<b>150W HPS</b>	4	<b>LPT82505</b>	S150MLTLC3 HPS150	HX-HPF	S55	–	N	1
<b>200W HPS</b>	4	<b>LPT86507</b>	S200MLTAA4 HPS200	CWA	S66	–	N	1

## HPS Magnetic Ballasts – 3 Tap

Primary Lamp Type	Tap	Satco Product #	Ballast Code	Circuit Type	ANSI	Input Voltage	Title 20	Carton
<b>50W HPS</b>	3	<b>LPT82702</b>	S50TRILC3 HPS50	HX-HPF	S68	120/277/347	N	1
<b>70W HPS</b>	3	<b>LPT82703</b>	S70TRILC3 HPS70	HX-HPF	S62	120/277/347	N	1
<b>100W HPS</b>	3	<b>LPT82704</b>	S100TRILC3 HPS100	HX-HPF	S54	120/277/347	N	1
<b>150W HPS</b>	3	<b>LPT82705</b>	S150TRILC3 HPS150	HX-HPF	S55	120/277/347	N	1
<b>250W HPS</b>	3	<b>LPT82708</b>	S250TRIAC4 HPS250	CWA	S50	120/277/347	N	1
<b>400W HPS</b>	3	<b>LPT82711</b>	S400TRILC4 HPS400	CWA	S51	120/277/347	N	1
<b>1000W HPS</b>	3	<b>LPT82714</b>	S1000TRIAC5 HPS1000	CWA	S52	120/277/347	N	1

## MH Electronic Ballasts – Ceramic Type

Primary Lamp Type	# of Lamps	Input Voltage	Satco Product #	Ballast Code	Mounting	L x W x H (Inches)	Carton
<b>CDM20</b>	1	120	<b>S6792</b>	HQEB/MH20/120LA2F 120V SQUARE	FCAN	3½ x 3 x 1¼	40
<b>CDM70</b>	1	120	<b>S6793</b>	HQEB/MH39/120LA2F 120V SQUARE	FCAN	3½ x 3 x 1¼	40
<b>CDM100</b>	1	120	<b>S6794</b>	HQEB/MH50/120LA2F 120V SQUARE	FCAN	3½ x 3 x 1¼	40
<b>CDM35, 39</b>	1	UNV	<b>S6795*</b>	HQEB/MH35/123L2AF UNV RECTANGLE	JCAN	5 ½ x 3¾ x 1½	20
<b>CDM70</b>	1	UNV	<b>S6796*</b>	HQEB/MH70/123L2AF UNV RECTANGLE	JCAN	5 ½ x 3¾ x 1½	20
<b>CDM100</b>	1	UNV	<b>S6797*</b>	HQEB/MH100/123L2AF UNV RECTANGLE	JCAN	5 ½ x 3¾ x 1½	20
<b>CDM70</b>	1	UNV	<b>S6799</b>	HQEB/MH70/123L1AF UNV RECTANGLE	FCAN	5 ½ x 3¾ x 1½	20
<b>CDM100</b>	1	UNV	<b>S6800</b>	HQEB/MH100/123L1AF UNV RECTANGLE	FCAN	5 ½ x 3¾ x 1½	20
<b>CDM150</b>	1	UNV	<b>S6801</b>	HQEB/MH150/123L1AF UNV RECTANGLE	FCAN	6 ½ x 3¾ x 1½	20
<b>CDM150</b>	1	UNV	<b>S6804*</b>	HQEB/MH150/123L2AF UNV RECTANGLE	JCAN	6 ½ x 3¾ x 1½	20

\* Bottom Feed Studs

## Hydroponic/Horticulture Ballasts – Fan Cooled

Primary Lamp Type	Tap	Satco Product #	Ballast Code	Dimming Options	L x W x H (Inches)	Carton
<b>400W HPS MH</b>	120-240V	<b>S2791</b>	400W DIMM 120/240V MH/HPS W/120V 8FT PLUG	150W/250W/400W	9 13/16 x 4 ½ x 2 13/16	4
<b>600W HPS MH</b>	120-240V	<b>S2792</b>	600W DIMM 120/240V MH/HPS W/120V 8FT PLUG	250W/400W/600W	12 x 4 ½ x 2 13/16	4
<b>1000W HPS MH</b>	120-240V	<b>S2793</b>	1000W DIMM 120/240V MH/HPS W/120V 8FT PLUG	600W/750W/1000W	14 7/16 x 4 ½ x 2 13/16	4
<b>CORD FOR 240V</b>	240V	<b>S2794</b>	8FT 240V POWER CORD FOR S2791 S2792 S2793	–	–	1

### NOTES – Taps Defined:

5 Tap: 120/208/240/277/480V      3 Tap: 120/208/347V  
 4 Tap: 120/208/240/277V      UNV: 120 – 277V

# FLUORESCENT BALLASTS



## Reliable, steady power.

### A necessary function.

In a fluorescent lighting system, the ballast regulates the current to the lamps and provides sufficient voltage to start them.

### Types of ballasts.

Ballasts consume electricity while providing the necessary circuit conditions; voltage, current, and wave form, to start and operate fluorescent lamps. There are three types of ballasts for commercial applications: magnetic, hybrid, and electronic.

Modern ballast designs use advanced electronics to more precisely regulate the current flowing through the electrical circuit. Since they use a higher cycle rate, you don't generally notice a flicker or a humming noise coming from an electronic ballast. Different lamps require specialized ballasts designed to maintain the specific voltage and current levels needed for varying tube designs.



## T8 Instant Start, Program Start, Universal Voltage Ballasts

Primary Lamp Type	# of Lamps	Input Voltage	Satco Product #	Ballast Code	NAED Code	Wiring Method	Carton
<b>F32T8</b>	1	120/277	<b>S5207</b>	QTP1X32T8/UNIV/ISN/SC	49941	Leads	10
	2	120/277	<b>S5208</b>	QTP2X32T8/UNIV/ISN/SC	49943	Leads	10
	3	120/277	<b>S5209</b>	QTP3X32T8/UNIV/ISN/SC	49945	Leads	10
	4	120/277	<b>S5210</b>	QTP4X32T8/UNIV/ISN/SC	49947	Leads	10
	1,2	120/277	<b>LPT80210*</b>	DB232N-MV-TP-HE	80210	Leads	10
	3	120/277	<b>LPT80213*</b>	DB332N-MV-TP-HE	80213	Leads	10
	4	120/277	<b>LPT80215*</b>	DB432N-MV-TP-HE	80215	Leads	10
<b>F32T8</b>	1	120/277	<b>S5286</b>	QHE1X32T8/UNV/PSN/TC	51397	Leads	10
	2	120/277	<b>S5287</b>	QHE2X32T8/UNV/PSN/TC	51408	Leads	10
	3	120/277	<b>S5288</b>	QHE3X32T8/UNV/PSN/TC	51413	Leads	10
	4	120/277	<b>S5289</b>	QHE4X32T8/UNV/PSN/TC	51418	Leads	10
<ul style="list-style-type: none"> <li>• Listed for: FBO16, F017, FBO24, F025, FB031, F032, F040 &amp; SS Equivalents</li> <li>• Can operate 1 lamp on 2 lamp ballast, 2 lamps on 3 lamp ballast, 3 lamps on 4 lamp ballast</li> <li>• For 40T8 operation use 1 lamp on 2 lamp ballast, 2 lamps on 3 lamp ballast, 3 lamps on 4 lamp ballast</li> </ul>							
<b>F96T8</b>	1, 2	120/277	<b>S5213</b>	QTP2X59T8/UNIV/ISN/SC	49598	Leads	10
	1, 2	120/277	<b>LPT80219</b>	DB259-MV-TP-PIC-SL	80219	Leads	10
<ul style="list-style-type: none"> <li>• Listed for: F096T8 &amp; SS Equivalents</li> <li>• Can operate 1 lamp on 2 lamp ballast</li> </ul>							

\* Shrink wrapped for retail.

## T12 Instant Start / Rapid Start Electronic Ballasts

Primary Lamp Type	# of Lamps	Input Voltage	Satco Product #	Ballast Code	NAED Code	Wiring Method	Carton
<b>F40T12</b>	1, 2	120/277	<b>S5260*</b>	DB240-MV-RSN BALLAST UNV	80205	Leads	20
<ul style="list-style-type: none"> <li>• Listed for: F40T12, F30T12, F25T12 Lamp(s)</li> </ul>							
<b>F96T12</b>	1, 2	120/277	<b>S6697*</b>	DB275ISMV	80206	Leads	20

\* Shrink wrapped for retail.

## T12 T8 HO Instant Start / Rapid Start / Program Start

Primary Lamp Type	# of Lamps	Input Voltage	Satco Product #	Ballast Code	NAED Code	Wiring Method	Carton
<b>T12/RS/HO</b>	1, 2	120/277	<b>Y75303</b>	QTP2X96T12/HO/UNV	50319	Leads	4
	1, 2	120/277	<b>LPT80224</b>	DB-2110-RS-MV	80224	Leads	20
<b>T8/PS/HO</b>	1, 2	120/277	<b>Y50304</b>	QHE2X86T8/HO/UNV/PSN/HT-B	50304	Leads	10
<b>T8/IS/HO</b>	1, 2	120/277	<b>LPT80237</b>	DB-286HO-MV-TP-IS	80237	Leads	10



# FLUORESCENT BALLASTS

## T5 Programmed Start, Universal Voltage Ballasts

Primary Lamp Type	# of Lamps	Input Voltage	Satco Product #	Ballast Code	NAED Code	Wiring Method	Carton
<b>FP28T5</b>	1	120/277	<b>S5221</b>	QTP1X28T5/UNIV/PSN/NL	49171	Wiretap Connections	20
	2	120/277	<b>S5222</b>	QTP2X28T5/UNIV/PSN/NL	49181	Wiretap Connections	20
• Listed for: FP14, FP21, FP28, FP35 Lamp(s)							

## T5 HO Programmed Start, Universal Voltage Ballasts

Primary Lamp Type	# of Lamps	Input Voltage	Satco Product #	Ballast Code	NAED Code	Wiring Method	Carton
<b>FP24T5</b>	2	120/277	<b>S5215</b>	QHE2X3924T5HO/UNV/NL	51479	Wiretap Connections	20
<b>FP24T5 &amp; F39T5</b>	1,2	120/277	<b>LPT80239</b>	DB2S39PS-MV	80239	Leads	10
• Listed for: FPC22T5, FPC24T5HO, FT24DL, CF24DF, FT36DL, FP39T5HO, FPC40T5 Lamp(s)							
<b>FP54T5</b>	1	120/277	<b>S5218</b>	QTP1X54T5HO/UNV/PSN/NL	49121	Wiretap Connections	20
	2	120/277	<b>S5219</b>	QHE2X54T5HO/UNV/PSN/NL	51471	Wiretap Connections	20
	1,2	120/277	<b>LPT80218</b>	DB-254HO-MV-TP-PS-SL	80218	Leads	10
	1,2	347/480	<b>LPT80230</b>	DB254HO-480-TP-PS-SL	80230	Leads	10
	3,4	120/277	<b>LPT80236</b>	DB4M54-PS-MV-90	80236	Leads	10
• Listed for: FP54T5/HO, FT55DL, FPC55 Lamp(s)							
<b>FP80T5</b>	1	120/277	<b>S5220</b>	QTP1X80T5HO/UNV/PSN/NL	49150	Wiretap Connections	20
• Listed for: FP54T5/HO, FP80, FT80DL Lamp(s)							

## FT40DL Instant Start, Universal Voltage Ballasts

Primary Lamp Type	# of Lamps	Input Voltage	Satco Product #	Ballast Code	NAED Code	Wiring Method	Carton
<b>FT40</b>	1	120/277	<b>Y49428</b>	QHE1X40DL/UNIV ISN-SC	49428	Leads	10
	2	120/277	<b>Y49429</b>	QHE2X40DL/UNIV ISN-SC	49429	Leads	10
	3	120/277	<b>Y49430</b>	QHE3X40DL/UNIV ISN-SC	49430	Leads	10
• Listed for: FT40DL/28W/SS/IS							

## Circline Instant Start, Dedicated Voltage Ballasts

Primary Lamp Type	# of Lamps	Input Voltage	Satco Product #	Ballast Code	NAED Code	Wiring Method	Carton
<b>FC6, FC8</b>	1	120	<b>S5296</b>	DB1S26RS120N W/SOCKET	80225	Leads & Socket	60
<b>FC12, 16, 30</b>	1	120	<b>S5297</b>	DB1S40RS120N W/SOCKET	80226	Leads & Socket	60
<b>FC8 &amp; 12</b>	2	120	<b>S5298</b>	DB2S2232RS120N W/SOCKET	80227	Leads & Socket	60
<b>FC12 &amp; 16</b>	2	120	<b>S5299</b>	DB2S3240RS120N W/SOCKET	80228	Leads & Socket	60

## Compact Fluorescent Programmed Start, Universal Voltage Ballasts

Primary Lamp Type	# of Lamps	Input Voltage	Satco Product #	Ballast Code	NAED Code	Wiring Method	Carton
<b>CF13</b>	1, 2	120/277	<b>S5225</b>	QTP1/2X13CF/UNV/DM	51818	Wiretap Connections	20
• Listed for: 1 or 2 CF13DD/E or CF13DT/E Lamp(s)							
<b>CF18</b>	1, 2	120/277	<b>S5226</b>	QTP1/2X18CF/UNV/DM	51823	Wiretap Connections	20
<b>CF13 &amp; CF18</b>	1, 2	120/277	<b>LPT80207</b>	DBC218MVRN/KIT	80207	Wiretap Connections	20
• Listed for: 1 or 2 CF18DD/E or CF18DT/E Lamp(s)							
<b>CF26</b>	1, 2	120/277	<b>S5229</b>	QTP1/2X26CF/UNV/Dual Entry	51833	Wiretap Connections	20
<b>CF26</b>	2	120/277	<b>LPT80208</b>	DBC226MVRN/KIT	80208	Wiretap Connections	20
• Listed for: 1 or 2 CF26DD/E or CF26DT/E Lamp(s) • Also Listed for: 1 ea. CF32DT/E, CF42DT/E, F28/2D, F38/2D, FPC40T5, FT40DL Lamp • Also Listed for: 2 ea. CF13DS/E, FT18DL/RS, CF18DF, F21/2D Lamps							
<b>CF26</b>	1, 2	120/277	<b>S5233</b>	QTP2X26CF/UNV DM PEM	51898	Wiretap Connections	16
<b>CF32, 42</b>	1	120/277					
• Listed for: 1 or 2 CF26DD/E or CF26DT/E Lamp(s) • Also Listed for: 1 ea. CF32DT/E or CF42DT/E Lamp							
<b>CF26, 32, 42</b>	1, 2	120/277	<b>S5235</b>	QTP2X26/32/42CF/UNV DM	51843	Wiretap Connections	20
<b>CF57, 70</b>	1	120/277					
<b>CF26, 32, 42</b>	1, 2	120/277	<b>LPT80204</b>	DBC242MVRN/KIT	80204	Wiretap Connections	20
<b>CF57, 70</b>	1	120/277					
• Listed for: 1 or 2 CF26DD/E or CF26DT/E Lamp(s) • Also Listed for: 1 ea. CF32DT/E or CF42DT/E Lamp							

## T12 (800mA) Electronic Sign Ballasts

Primary Lamp Type	# of Lamps	Input Voltage	Satco Product #	Ballast Code	Total Lamp Length	Carton
<b>T12/RS/HO</b>	1 – 2	120/277	<b>LPT80239</b>	DB-0216-12-MV-TP	2 ft. – 16 ft.	1
	1 – 4	120/277	<b>LPT80240</b>	DB-1040-14-MV-TP	10 ft. – 40 ft.	1
	1 – 4	120/277	<b>LPT80241</b>	DB-0432-14-MV-TP	4 ft. – 32 ft.	1
	4 – 6	120/277	<b>LPT80242</b>	DB-0848-46-MV-TP	8 ft. – 48 ft.	1
• Listed for all T12 HO lamps 18" thru 96": F18T12, F24T12, F30T12, F42T12, F48T12/SS, F48T12, F60T12, F64T12, F72T12, F84T12, F96T12/SS, F96T12/CT, F96T12						

# INDEX

PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE		
4BAKPAK	26	LPT80242	127	S1821	87	S1967	58	S2301	67	S2452	66	S2771	80	S3003	93	S3183	55	S3274	80
4SBAKPAK	26	LPT81411	122	S1822	93	S1968	59	S2302	67	S2453	66	S2772	80	S3004	94	S3184	55	S3275	85
8BAKPAK	26	LPT81414	122	S1823	87	S1969	59	S2303	67	S2454	66	S2773	80	S3010	81	S3185	56	S3276	76
A3620	77	LPT81506	122	S1824	82	S1970	62	S2328	67	S2455	66	S2774	80	S3011	86	S3187	50	S3277	77
A3631	79	LPT81511	122	S1825	87	S1971	62	S2330	68	S2456	56	S2791	123	S3012	91	S3188	50	S3278	80
A3632	84	LPT81514	122	S1826	93	S1972	62	S2332	69	S2457	66	S2792	123	S3013	93	S3189	50	S3279	85
A3634	79	LPT81615	122	S1900	18	S1973	62	S2334	70	S2458	66	S2793	123	S3014	94	S3194	57	S3280	78
A3635	84	LPT81706	122	S1902	18	S1974	62	S2335	68	S2601	60	S2794	123	S3015	95	S3195	57	S3281	78
A3637	79	LPT81708	122	S1904	18	S1975	62	S2336	69	S2603	60	S2808	91	S3016	95	S3197	51	S3282	79
A3638	84	LPT81711	122	S1905	18	S1976	62	S2399	116	S2605	60	S2810	82	S3017	94	S3198	53	S3283	84
A3640	81	LPT81714	122	S1906	18	S1977	62	S2401	65	S2607	60	S2817	91	S3104	56	S3199	55	S3284	89
A3641	86	LPT82502	122	S1907	18	S1978	62	S2402	65	S2609	60	S2850	88	S3105	56	S3200	88	S3285	79
A3644	86	LPT82503	122	S1908	50	S1979	53	S2403	65	S2610	60	S2851	92	S3106	56	S3201	88	S3286	84
A3645	86	LPT82504	122	S1909	50	S1980	53	S2404	65	S2615	61	S2852	94	S3107	54	S3202	88	S3287	89
A3647	81	LPT82505	122	S1910	50	S1981	53	S2405	65	S2616	61	S2853	92	S3108	54	S3203	88	S3288	79
A3648	86	LPT82702	123	S1911	50	S1982	53	S2406	65	S2617	61	S2903	17	S3109	54	S3205	82	S3289	84
A3662	90	LPT82703	123	S1912	50	S1983	54	S2407	65	S2618	61	S2904	25	S3113	63	S3210	82	S3290	89
A3663	90	LPT82704	123	S1913	53	S1984	54	S2408	65	S2619	61	S2905	25	S3114	63	S3212	88	S3291	77
A3664	80	LPT82705	123	S1914	53	S1986	50	S2411	74	S2620	61	S2907	25	S3115	63	S3213	92	S3297	78
A3665	85	LPT82708	123	S1915	53	S1987	50	S2411	79	S2621	61	S2908	18	S3116	63	S3214	86	S3298	78
A3667	80	LPT82711	123	S1916	54	S1989	57	S2412	74	S2622	61	S2909	18	S3120	50	S3215	86	S3315	78
A3668	85	LPT82714	123	S1917	54	S1990	57	S2412	83	S2623	61	S2910	18	S3121	50	S3218	79	S3345	77
A3673	77	LPT83413	121	S1918	54	S1991	57	S2413	74	S2624	61	S2911	18	S3122	54	S3219	79	S3346	79
A3674	80	LPT83602	121	S1919	53	S1992	58	S2413	87	S2625	61	S2913	12	S3123	54	S3222	82	S3347	83
A3675	85	LPT83703	121	S1920	54	S1993	58	S2414	74	S2630	61	S2915	13	S3127	103	S3223	82	S3360	77
A3677	77	LPT83704	121	S1921	54	S1994	59	S2414	87	S2631	61	S2916	13	S3128	103	S3224	87	S3361	77
A3678	80	LPT83705	121	S1922	54	S1995	58	S2415	74	S2632	61	S2917	13	S3129	103	S3225	87	S3363	81
A3679	85	LPT83706	121	S1923	56	S1996	58	S2415	78	S2633	61	S2919	13	S3130	103	S3227	92	S3364	81
A3682	79	LPT83707	121	S1924	51	S1998	104	S2416	74	S2634	61	S2920	13	S3131	103	S3228	92	S3365	81
A3683	84	LPT83708	121	S1925	56	S2200	67	S2416	87	S2635	61	S2922	13	S3132	54	S3229	87	S3366	81
A3684	89	LPT83709	121	S1926	56	S2201	67	S2417	74	S2636	61	S2924	14	S3133	54	S3230	77	S3367	85
A3685	79	LPT83710	121	S1927	103	S2202	67	S2417	87	S2637	61	S2925	25	S3134	54	S3231	79	S3368	85
A3686	84	LPT83711	121	S1928	103	S2203	67	S2418	74	S2638	61	S2926	25	S3135	55	S3232	84	S3369	85
A3687	89	LPT83713	121	S1929	103	S2204	67	S2418	80	S2639	61	S2927	21	S3136	55	S3234	79	S3370	85
A3688	79	LPT83714	121	S1930	103	S2228	56	S2419	74	S2640	61	S2933	23	S3139	63	S3235	84	S3371	80
A3689	84	LPT84614	121	S1931	103	S2231	67	S2419	89	S2641	61	S2937	23	S3142	55	S3237	79	S3372	80
A3690	89	LPT85506	121	S1932	103	S2232	67	S2420	74	S2642	64	S2940	23	S3143	59	S3238	84	S3373	80
A3921	78	LPT85507	121	S1933	104	S2233	68	S2420	87	S2643	64	S2944	24	S3145	55	S3239	92	S3374	80
A3922	81	LPT85508	121	S1934	104	S2234	68	S2421	74	S2644	64	S2946	24	S3146	55	S3240	92	S3376	90
A3923	85	LPT85509	121	S1935	104	S2235	68	S2421	87	S2645	64	S2950	21	S3147	54	S3241	76	S3377	90
A3924	78	LPT85510	121	S1936	104	S2236	68	S2422	74	S2703	80	S2954	22	S3150	57	S3242	76	S3378	90
A3925	81	LPT85511	121	S1937	104	S2237	68	S2422	91	S2704	84	S2955	17	S3151	57	S3243	76	S3380	80
A3926	85	LPT86507	122	S1938	104	S2238	68	S2423	74	S2705	90	S2956	17	S3152	57	S3244	81	S3381	84
A3931	90	LPT86608	122	S1939	104	S2239	69	S2423	91	S2706	80	S2959	17	S3153	57	S3245	85	S3382	89
A3932	91	LPT86611	122	S1940	103	S2240	69	S2424	74	S2713	80	S2961	17	S3154	57	S3246	91	S3384	84
BALBAKPAK	26	LPT86612	122	S1941	103	S2241	69	S2424	83	S2714	84	S2962	17	S3155	57	S3248	82	S3385	83
COMBAKPAK	26	LPT86614	122	S1950	57	S2242	69	S2425	74	S2715	90	S2965	45	S3156	50	S3249	82	S3386	79
LPT80204	127	LPT87606	122	S1951	57	S2243	69	S2425	86	S2716	84	S2966	45	S3157	53	S3250	82	S3387	83
LPT80207	127	LPT87608	122	S1952	58	S2244	69	S2426	74	S2740	83	S2967	46	S3159	53	S3251	82	S3388	89
LPT80208	127	LPT87611	122	S1953	58	S2245	70	S2426	87	S2741	83	S2968	46	S3160	50	S3252	87	S3390	80
LPT80210	125	LPT87614	122	S1954	58	S2246	70	S2437	66	S2742	88	S2969	46	S3162	53	S3253	87	S3391	84
LPT80213	125	LPT88603	121	S1955	58	S2247	70	S2438	66	S2743	88	S2971	83	S3164	51	S3259	88	S3392	89
LPT80215	125	LPT88604	121	S1956	58	S2248	70	S2441	66	S2744	83	S2972	89	S3165	53	S3260	81	S3393	79
LPT80218	126	LPT88605	121	S1957	58	S2249	70	S2442	66	S2745	83	S2974	85	S3166	55	S3261	85	S3394	84
LPT80219	125	LPT88608	121	S1958	58	S2256	70	S2443	66	S2760	77	S2975	91	S3167	51	S3262	90	S3396	86
LPT80224	125	LPT88609	121	S1959	58	S2257	70	S2444	66	S2761	77	S2977	87	S3168	51	S3263	90	S3397	85
LPT80230	126	LPT88610	121	S1960	59	S2258	70	S2445	66	S2763	81	S2978	91	S3169	59	S3264	80	S3398	85
LPT80236	126	LPT88611	121	S1961	59	S2259	70	S2446	66	S2764	81	S2979	92	S3170	59	S3265	85	S3403	80
LPT80237	125	LPT88613	121	S1962	59	S2260	70	S2447	66	S2765	81	S2996	92	S3171	50	S3267	80	S3404	84
LPT80239	126	LPT89515	122	S1963	59	S2267	67	S2448	65	S2767	85	S2999	94	S3179	50	S3268	85	S3405	90
LPT80239	127	MULTIBAKPAK	26	S1964	59	S2268	68	S2449	65	S2768	85	S3000	81	S3180	56	S3271	91	S3406	80
LPT80240	127	S1383	78	S1965	59	S2269	69	S2450	65	S2769	85	S3001	86	S3181	54	S3272	76	S3408	91
LPT80241	127	S1820	82	S1966	58	S2300	67	S2451	65	S2770	85	S3002	91	S3182	54	S3273	77	S3410	56

PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE		
S3411	56	S3493	54	S3710	87	S3810	83	S3917	87	S4162	88	S4301	119	S4391	99	S4565	77	S4694	64
S3413	80	S3494	55	S3711	82	S3811	83	S3920	92	S4163	88	S4302	119	S4394	104	S4566	77	S4695	64
S3414	84	S3495	55	S3712	87	S3813	79	S3927	89	S4164	83	S4303	119	S4396	104	S4567	75	S4700	82
S3415	90	S3496	56	S3713	82	S3814	78	S3928	92	S4165	83	S4304	119	S4414	65	S4568	75	S4701	86
S3416	84	S3497	56	S3714	82	S3815	78	S3929	93	S4169	56	S4305	119	S4415	65	S4569	75	S4702	86
S3417	92	S3500	62	S3715	78	S3818	84	S3930	89	S4170	59	S4306	119	S4416	65	S4570	75	S4704	82
S3418	51	S3501	62	S3718	82	S3819	90	S3931	92	S4172	59	S4307	119	S4424	93	S4571	75	S4705	86
S3419	51	S3502	62	S3720	83	S3821	78	S3932	93	S4173	59	S4308	66	S4425	93	S4572	75	S4706	86
S3420	50	S3515	62	S3721	83	S3822	81	S3934	92	S4174	59	S4309	66	S4426	93	S4574	25	S4707	85
S3421	50	S3516	62	S3723	110	S3823	85	S3935	93	S4175	60	S4310	66	S4427	93	S4610	51	S4708	85
S3422	55	S3517	62	S3724	113	S3824	78	S3936	93	S4176	60	S4311	66	S4428	93	S4611	51	S4711	80
S3423	55	S3518	63	S3725	84	S3825	81	S3937	64	S4177	60	S4312	66	S4429	93	S4612	51	S4712	84
S3424	57	S3519	63	S3726	78	S3826	85	S3938	89	S4178	60	S4313	66	S4438	47	S4613	51	S4713	89
S3425	57	S3539	51	S3727	81	S3827	81	S3939	93	S4179	60	S4316	119	S4439	47	S4614	52	S4714	80
S3426	55	S3540	51	S3728	85	S3828	86	S3940	78	S4180	60	S4317	119	S4440	47	S4615	52	S4715	84
S3427	51	S3541	51	S3729	87	S3830	76	S3941	83	S4181	60	S4318	119	S4453	92	S4616	52	S4716	89
S3428	51	S3542	51	S3731	79	S3831	90	S3942	88	S4182	60	S4319	119	S4465	80	S4617	52	S4717	75
S3429	56	S3543	51	S3732	84	S3832	91	S3945	94	S4183	60	S4320	119	S4466	85	S4618	62	S4718	78
S3430	56	S3544	52	S3734	79	S3833	76	S3946	94	S4184	60	S4321	119	S4467	90	S4620	51	S4719	78
S3431	55	S3545	52	S3735	84	S3834	76	S3948	77	S4185	58	S4322	119	S4475	104	S4621	52	S4720	82
S3432	53	S3546	52	S3737	79	S3835	76	S3949	77	S4187	59	S4323	119	S4480	52	S4622	51	S4721	82
S3433	56	S3547	52	S3738	84	S3836	76	S3950	79	S4188	59	S4324	119	S4481	53	S4623	63	S4722	78
S3434	63	S3601	82	S3739	88	S3837	76	S3951	83	S4189	64	S4325	119	S4482	53	S4624	63	S4724	75
S3435	63	S3602	86	S3740	88	S3838	81	S3952	89	S4190	60	S4326	119	S4483	52	S4625	63	S4725	75
S3438	63	S3604	82	S3744	81	S3839	86	S3955	89	S4192	60	S4327	119	S4484	53	S4626	62	S4726	75
S3439	63	S3605	86	S3745	86	S3841	81	S3956	93	S4194	60	S4328	119	S4485	53	S4627	62	S4727	78
S3440	81	S3606	76	S3750	77	S3842	86	S3957	94	S4195	57	S4329	119	S4486	52	S4628	57	S4740	84
S3441	86	S3607	76	S3751	81	S3844	76	S3958	94	S4196	57	S4330	119	S4487	53	S4629	57	S4742	84
S3444	57	S3608	76	S3752	78	S3845	77	S3960	77	S4197	50	S4331	119	S4488	53	S4639	52	S4750	94
S3445	62	S3609	76	S3753	81	S3846	81	S3961	77	S4198	56	S4332	119	S4489	52	S4641	52	S4751	94
S3446	62	S3610	76	S3754	85	S3847	85	S3962	77	S4199	56	S4333	119	S4490	53	S4642	52	S4752	94
S3447	81	S3611	76	S3756	75	S3849	87	S3963	77	S4208	67	S4334	119	S4491	53	S4645	56	S4754	94
S3448	86	S3618	78	S3757	75	S3859	83	S3964	77	S4209	68	S4335	119	S4492	52	S4646	56	S4755	94
S3451	58	S3619	86	S3759	75	S3860	81	S3965	77	S4210	69	S4336	119	S4493	53	S4647	52	S4756	94
S3459	50	S3620	66	S3760	75	S3861	86	S3966	77	S4211	70	S4340	118	S4494	53	S4648	52	S4757	94
S3460	58	S3621	76	S3761	75	S3862	91	S3969	87	S4235	99	S4342	118	S4495	52	S4649	52	S4758	94
S3461	58	S3622	76	S3762	90	S3863	81	S3970	92	S4237	99	S4344	118	S4496	53	S4658	67	S4800	92
S3462	59	S3623	110	S3763	90	S3864	76	S3971	93	S4242	99	S4346	118	S4497	53	S4668	117	S4802	94
S3463	59	S3624	113	S3764	80	S3866	75	S3972	92	S4244	99	S4348	118	S4505	66	S4668	71	S4803	94
S3464	57	S3628	78	S3765	85	S3867	77	S3973	93	S4246	99	S4349	118	S4506	66	S4669	117	S4804	71
S3465	57	S3629	87	S3767	80	S3868	80	S3989	83	S4248	99	S4351	118	S4508	76	S4669	71	S4804	118
S3466	57	S3630	82	S3768	85	S3869	80	S4041	86	S4254	98	S4353	94	S4509	76	S4670	117	S4806	117
S3467	57	S3651	81	S3771	90	S3870	88	S4048	86	S4256	98	S4354	58	S4510	76	S4670	71	S4806	71
S3468	50	S3652	86	S3772	91	S3871	88	S4076	83	S4257	98	S4355	58	S4511	76	S4671	117	S4807	117
S3469	50	S3653	81	S3773	77	S3879	77	S4077	88	S4259	98	S4356	59	S4512	76	S4671	71	S4807	71
S3470	50	S3656	75	S3774	80	S3887	81	S4078	92	S4261	100	S4361	54	S4514	65	S4672	117	S4808	117
S3471	50	S3657	75	S3775	85	S3888	86	S4079	93	S4262	101	S4363	54	S4515	65	S4672	71	S4808	71
S3474	66	S3659	75	S3777	77	S3896	91	S4109	67	S4263	101	S4364	58	S4516	65	S4673	117	S4809	71
S3475	66	S3660	75	S3778	80	S3899	91	S4120	58	S4264	101	S4365	58	S4520	75	S4673	71	S4809	117
S3478	66	S3661	75	S3779	85	S3900	75	S4121	58	S4266	102	S4366	95	S4538	81	S4674	70	S4810	71
S3479	66	S3671	86	S3782	79	S3901	75	S4122	59	S4268	102	S4367	43	S4539	86	S4675	70	S4810	118
S3480	55	S3680	75	S3783	84	S3902	75	S4123	59	S4269	102	S4368	43	S4541	81	S4680	64	S4811	71
S3481	55	S3681	75	S3784	89	S3903	76	S4124	57	S4270	102	S4369	44	S4542	86	S4681	64	S4811	118
S3482	55	S3691	75	S3785	79	S3904	76	S4125	57	S4284	101	S4371	44	S4543	91	S4682	64	S4812	102
S3484	53	S3692	75	S3786	84	S3905	78	S4127	62	S4285	101	S4372	44	S4551	118	S4683	64	S4813	102
S3485	54	S3700	82	S3787	89	S3906	78	S4128	62	S4286	101	S4377	104	S4552	118	S4684	64	S4814	102
S3486	54	S3701	82	S3788	79	S3907	82	S4129	62	S4287	101	S4379	100	S4553	118	S4686	64	S4816	89
S3487	54	S3702	87	S3789	84	S3908	82	S4130	67	S4288	101	S4384	100	S4554	118	S4687	64	S4823	87
S3488	54	S3703	87	S3790	89	S3909	82	S4131	68	S4289	101	S4385	101	S4560	77	S4688	64	S4829	100
S3489	54	S3704	91	S3791	75	S3910	78	S4132	69	S4290	102	S4386	100	S4561	77	S4689	64	S4830	100
S3490	54	S3705	91	S3792	75	S3911	78	S4133	70	S4292	101	S4388	100	S4562	77	S4690	64	S4831	100
S3491	54	S3708	82	S3794	76	S3912	78	S4160	83	S4293	102	S4389	101	S4563	77	S4691	64	S4832	100
S3492	54	S3709	82	S3795	76	S3913	78	S4161	83	S4300	119	S4390	99	S4564	77	S4692	64	S4834	101

# INDEX

PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE		
S4835	101	S4987	89	S5297	126	S5882	98	S6425	15	S6513	19	S6590	24	S6727	42	S6887	26	S6957	113
S4836	101	S4988	76	S5298	126	S5883	98	S6426	15	S6514	19	S6591	18	S6728	42	S6888	25	S6958	115
S4839	101	S4994	76	S5299	126	S5884	98	S6427	15	S6515	19	S6592	18	S6729	43	S6889	25	S6959	114
S4840	100	S4995	79	S5301	35	S5885	100	S6428	15	S6516	19	S6593	21	S6730	43	S6892	25	S6960	115
S4841	100	S4996	84	S5302	35	S5886	100	S6429	15	S6517	19	S6594	14	S6731	43	S6893	25	S6961	114
S4842	101	S4997	89	S5401	32	S5887	100	S6430	15	S6518	19	S6595	24	S6732	43	S6895	113	S6962	115
S4844	101	S4998	94	S5454	24	S5888	98	S6431	15	S6519	19	S6596	22	S6733	43	S6896	115	S6963	114
S4847	98	S4999	94	S5501	31	S5901	105	S6432	15	S6520	13	S6608	21	S6734	43	S6900	109	S6964	114
S4849	98	S5000	92	S5503	31	S5902	105	S6433	15	S6521	12	S6610	21	S6735	43	S6901	109	S6965	114
S4851	98	S5001	94	S5504	31	S5903	105	S6434	15	S6522	12	S6630	22	S6736	43	S6902	109	S6966	113
S4853	98	S5002	93	S5506	31	S5904	105	S6435	15	S6523	12	S6631	22	S6737	43	S6903	111	S6968	117
S4857	100	S5003	93	S5507	31	S5905	105	S6436	15	S6524	12	S6632	22	S6738	43	S6904	115	S6969	117
S4861	100	S5004	93	S5509	31	S5906	105	S6437	16	S6525	12	S6637	21	S6739	43	S6905	115	S6972	117
S4862	100	S5005	93	S5511	33	S5907	105	S6438	16	S6526	12	S6638	21	S6740	43	S6906	115	S6974	117
S4863	100	S5006	93	S5512	33	S5908	105	S6439	16	S6527	12	S6650	23	S6741	44	S6907	110	S6975	117
S4864	99	S5007	93	S5513	33	S5909	105	S6440	16	S6528	12	S6651	23	S6742	44	S6908	109	S6976	117
S4865	102	S5010	78	S5514	33	S5910	105	S6441	16	S6529	12	S6660	22	S6743	44	S6909	109	S6977	117
S4866	99	S5011	87	S5515	33	S5911	105	S6442	16	S6530	12	S6661	22	S6744	44	S6910	109	S6978	117
S4867	99	S5012	92	S5516	31	S5912	105	S6443	16	S6531	12	S6662	22	S6745	44	S6911	109	S6979	117
S4869	102	S5013	93	S5518	31	S5913	105	S6444	16	S6535	13	S6663	22	S6746	44	S6912	109	S6980	117
S4870	104	S5020	78	S5519	32	S6010	93	S6445	16	S6536	13	S6665	19	S6747	44	S6913	109	S6981	117
S4871	104	S5021	87	S5523	32	S6020	42	S6446	16	S6537	13	S6666	20	S6748	44	S6914	110	S6982	117
S4872	104	S5022	92	S5525	32	S6021	42	S6447	16	S6541	20	S6667	20	S6749	44	S6915	110	S6983	117
S4873	104	S5023	93	S5526	32	S6022	42	S6448	16	S6542	20	S6668	21	S6750	44	S6916	110	S6985	116
S4874	104	S5030	83	S5528	32	S6023	42	S6449	23	S6543	20	S6670	23	S6751	44	S6917	111	S6986	116
S4875	104	S5031	88	S5529	32	S6040	78	S6450	23	S6544	19	S6671	23	S6752	44	S6918	112	S6987	116
S4876	101	S5040	83	S5532	32	S6050	79	S6451	23	S6545	19	S6672	23	S6753	45	S6919	112	S6988	116
S4877	101	S5041	88	S5541	30	S6080	79	S6452	23	S6546	19	S6673	24	S6754	45	S6920	112	S6989	116
S4878	102	S5123	103	S5543	30	S6081	79	S6453	23	S6547	19	S6674	24	S6755	45	S6921	115	S6990	116
S4879	102	S5124	103	S5544	30	S6082	79	S6454	23	S6548	19	S6676	24	S6756	45	S6922	115	S6991	116
S4880	78	S5126	103	S5546	30	S6083	79	S6457	23	S6549	19	S6677	24	S6757	45	S6923	115	S6992	116
S4881	83	S5127	103	S5547	30	S6090	79	S6458	23	S6550	14	S6686	21	S6758	45	S6924	115	S6993	116
S4882	88	S5128	103	S5549	30	S6091	79	S6460	24	S6551	14	S6691	13	S6759	45	S6925	116	S6994	116
S4883	94	S5130	103	S5568	38	S6092	79	S6461	24	S6552	14	S6692	12	S6760	45	S6926	115	S6995	116
S4884	94	S5131	103	S5572	38	S6093	79	S6462	24	S6553	14	S6693	12	S6761	45	S6927	115	S6996	116
S4885	94	S5133	103	S5575	38	S6101	116	S6463	24	S6554	14	S6697	125	S6762	45	S6928	115	S6997	116
S4886	88	S5207	125	S5595	39	S6102	116	S6466	24	S6555	14	S6699	14	S6763	45	S6929	109	S6998	116
S4887	92	S5208	125	S5596	39	S6235	30	S6467	24	S6556	14	S6700	40	S6764	45	S6930	109	S6999	116
S4888	102	S5209	125	S5822	99	S6236	30	S6470	18	S6557	14	S6701	40	S6765	45	S6931	109	S7001	93
S4889	102	S5210	125	S5824	99	S6237	30	S6471	18	S6558	14	S6702	40	S6766	46	S6932	109	S7002	93
S4897	102	S5213	125	S5825	99	S6238	30	S6472	22	S6559	20	S6703	40	S6767	46	S6933	109	S7003	94
S4898	102	S5215	126	S5829	100	S6271	30	S6475	18	S6561	20	S6704	40	S6768	46	S6934	109	S7004	94
S4900	67	S5218	126	S5830	99	S6272	30	S6476	18	S6562	20	S6705	40	S6769	46	S6935	109	S7005	95
S4901	67	S5219	126	S5831	100	S6273	30	S6483	22	S6563	20	S6706	40	S6770	46	S6936	111	S7006	95
S4902	67	S5220	126	S5832	99	S6274	30	S6485	22	S6564	20	S6707	40	S6771	46	S6937	111	S7007	95
S4903	67	S5221	126	S5832	100	S6275	30	S6490	17	S6565	20	S6708	40	S6780	40	S6938	112	S7010	90
S4904	67	S5222	126	S5833	101	S6276	30	S6491	17	S6566	20	S6709	40	S6792	123	S6939	112	S7011	94
S4905	67	S5224	24	S5834	99	S6277	30	S6492	17	S6567	20	S6710	40	S6793	123	S6940	112	S7012	95
S4906	67	S5225	127	S5835	101	S6278	30	S6493	17	S6568	20	S6711	40	S6794	123	S6941	112	S7019	109
S4907	67	S5226	127	S5837	101	S6279	30	S6494	17	S6569	20	S6712	40	S6795	123	S6942	112	S7020	109
S4956	88	S5227	24	S5838	99	S6284	30	S6500	21	S6570	20	S6713	40	S6796	123	S6943	112	S7021	109
S4959	94	S5229	127	S5839	99	S6405	25	S6501	21	S6571	20	S6714	41	S6797	123	S6944	112	S7022	109
S4960	94	S5233	127	S5841	99	S6406	25	S6502	21	S6572	20	S6716	41	S6799	123	S6945	112	S7023	109
S4961	94	S5235	127	S5843	101	S6407	25	S6503	22	S6573	20	S6717	42	S6800	123	S6946	109	S7024	109
S4962	94	S5255	24	S5845	101	S6408	25	S6504	22	S6575	20	S6718	42	S6801	123	S6947	109	S7025	109
S4963	118	S5256	24	S5854	98	S6409	25	S6505	22	S6577	20	S6719	42	S6804	123	S6948	110	S7026	109
S4980	83	S5257	24	S5856	98	S6413	41	S6506	22	S6579	20	S6720	42	S6850	116	S6949	110	S7029	109
S4981	83	S5260	125	S5858	98	S6414	41	S6507	21	S6580	20	S6721	42	S6874	25	S6950	110	S7030	109
S4982	83	S5286	125	S5860	98	S6415	41	S6508	22	S6583	12	S6722	42	S6875	25	S6951	113	S7031	109
S4983	83	S5287	125	S5862	100	S6416	41	S6509	21	S6584	12	S6723	42	S6876	25	S6952	113	S7032	109
S4984	89	S5288	125	S5863	98	S6417	41	S6510	19	S6586	22	S6724	42	S6877	25	S6953	109	S7033	109
S4985	89	S5289	125	S5878	99	S6418	41	S6511	19	S6587	23	S6725	42	S6885	26	S6955	113	S7034	109
S4986	89	S5296	126	S5881	98	S6419	41	S6512	19	S6589	24	S6726	42	S6886	26	S6956	113	S7036	110

PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE	PRODUCT	PAGE		
S7037	110	S7107	110	S7171	110	S7272	33	S7381	39	S7836	115	S8140	16	S8327	42	S8429	11	VG130	116
S7038	115	S7108	114	S7172	110	S7273	33	S7382	39	S7837	112	S8141	16	S8328	42	S8430	11	VJ020	115
S7039	113	S7109	111	S7173	110	S7274	37	S7383	39	S7838	110	S8142	16	S8329	43	S8432	12	VJ020	55
S7040	113	S7110	111	S7174	110	S7275	37	S7384	34	S7839	112	S8143	16	S8330	43	S8433	12	Y16103	67
S7041	113	S7111	111	S7175	110	S7276	37	S7385	34	S7861	113	S8144	16	S8331	43	S8434	12	Y16104	67
S7042	113	S7112	111	S7183	51	S7277	33	S7386	34	S7862	114	S8145	16	S8332	43	S8435	12	Y16108	67
S7043	113	S7113	111	S7184	51	S7278	36	S7387	34	S7863	115	S8155	17	S8333	43	S8436	13	Y16109	67
S7044	113	S7114	111	S7201	37	S7279	37	S7388	34	S7864	115	S8156	17	S8334	43	S8437	11	Y16117	68
S7045	113	S7115	111	S7202	37	S7281	37	S7389	34	S7865	109	S8157	17	S8335	43	S8438	11	Y16118	68
S7047	113	S7116	111	S7203	37	S7282	37	S7391	34	S7866	112	S8158	17	S8336	43	S8439	11	Y16119	68
S7048	113	S7117	111	S7204	37	S7283	37	S7392	34	S7870	26	S8159	17	S8337	43	S8440	11	Y16121	68
S7049	113	S7118	114	S7205	37	S7284	38	S7393	34	S7882	98	S8160	17	S8338	43	S8441	11	Y16122	68
S7050	113	S7119	111	S7206	37	S7285	38	S7394	34	S7883	115	S8161	17	S8339	43	S8442	11	Y16123	68
S7051	113	S7120	111	S7207	37	S7286	38	S7395	34	S7921	100	S8162	17	S8340	43	S8443	11	Y16127	68
S7052	113	S7121	111	S7208	37	S7287	38	S7396	34	S7925	19	S8163	17	S8341	44	S8444	11	Y16128	68
S7053	113	S7122	111	S7209	37	S7288	38	S7397	34	S7928	20	S8164	17	S8342	44	S8445	11	Y16129	68
S7054	110	S7123	111	S7211	31	S7289	38	S7398	34	S7929	20	S8166	17	S8343	44	S8446	11	Y16153	69
S7055	110	S7124	111	S7212	31	S7291	38	S7399	34	S7939	78	S8201	35	S8344	44	S8447	11	Y16154	69
S7056	115	S7125	111	S7213	31	S7292	38	S7401	36	S7940	82	S8202	35	S8345	44	S8450	14	Y16156	69
S7057	113	S7126	111	S7214	31	S7293	38	S7402	36	S7941	78	S8203	35	S8346	44	S8451	14	Y16159	69
S7058	113	S7127	111	S7215	31	S7294	37	S7403	36	S7942	82	S8204	35	S8347	44	S8452	14	Y16160	69
S7059	110	S7128	111	S7216	31	S7301	38	S7411	31	S7945	78	S8205	35	S8348	44	S8453	14	Y16161	69
S7060	110	S7129	111	S7217	31	S7302	38	S7412	31	S7949	19	S8206	35	S8349	44	S8454	14	Y16166	69
S7061	113	S7130	111	S7218	31	S7303	38	S7413	32	S7950	19	S8207	35	S8350	44	S8455	14	Y16167	69
S7062	113	S7131	111	S7219	31	S7304	38	S7414	32	S7961	113	S8208	35	S8351	44	S8456	14	Y16168	69
S7063	113	S7132	111	S7221	32	S7305	38	S7415	34	S7962	110	S8209	35	S8352	44	S8457	14	Y16728	70
S7064	113	S7133	111	S7222	32	S7306	38	S7416	34	S7966	26	S8210	35	S8353	45	S8458	14	Y16729	70
S7065	113	S7134	111	S7223	32	S7307	39	S7417	32	S7967	26	S8221	38	S8354	45	S8459	14	Y16732	70
S7066	113	S7135	111	S7224	32	S7308	39	S7418	32	S7968	115	S8224	36	S8355	45	S8460	14	Y16733	70
S7067	113	S7136	111	S7225	32	S7309	39	S7421	37	S7968	55	S8225	38	S8356	45	S8461	14	Y16734	70
S7068	110	S7137	111	S7226	32	S7311	39	S7422	37	S7970	115	S8226	35	S8360	41	S8462	14	Y16735	70
S7069	110	S7138	111	S7227	32	S7312	39	S7423	33	S7982	94	S8227	35	S8361	41	S8463	14	Y16737	70
S7070	114	S7139	111	S7228	32	S7313	39	S7424	33	S7994	26	S8228	35	S8362	41	S8471	14	Y16738	70
S7071	114	S7140	112	S7229	32	S7314	39	S7425	33	S7997	26	S8229	35	S8363	41	S8472	14	Y16742	70
S7072	114	S7141	112	S7231	32	S7315	39	S7426	33	S8110	15	S8232	35	S8364	41	S8473	14	Y16743	70
S7073	114	S7142	112	S7232	32	S7318	39	S7427	34	S8111	15	S8233	35	S8365	41	S8474	14	Y16747	70
S7074	114	S7143	112	S7233	32	S7319	39	S7428	34	S8112	15	S8300	40	S8366	41	S8475	14	Y16748	70
S7075	114	S7144	112	S7234	32	S7322	39	S7429	34	S8113	15	S8301	40	S8367	41	S8478	13	Y16751	70
S7076	114	S7145	112	S7235	32	S7323	39	S7430	34	S8114	15	S8302	40	S8368	41	S8479	13	Y21376	21
S7077	114	S7146	112	S7236	32	S7327	39	S7432	37	S8115	15	S8303	40	S8369	41	S8517	92	Y23504	23
S7078	114	S7147	112	S7237	37	S7328	39	S7436	33	S8116	15	S8304	40	S8380	40	S8518	93	Y24004	21
S7079	114	S7148	112	S7238	37	S7331	33	S7437	33	S8117	15	S8305	40	S8381	40	S8519	87	Y24965	21
S7080	114	S7149	115	S7241	36	S7332	33	S7438	33	S8118	16	S8306	40	S8396	44	S8520	91	Y29478	23
S7081	114	S7150	115	S7242	36	S7333	33	S7702	112	S8119	16	S8307	40	S8397	44	S8521	92	Y49428	126
S7082	114	S7151	115	S7243	36	S7334	34	S7747	114	S8120	16	S8308	40	S8398	44	S8522	89	Y49429	126
S7083	114	S7152	115	S7247	36	S7335	34	S7762	115	S8121	16	S8309	40	S8399	44	S8657	45	Y49430	126
S7084	114	S7153	112	S7248	36	S7336	34	S7782	110	S8122	16	S8310	40	S8404	12	S8658	45	Y50304	125
S7085	114	S7154	112	S7249	36	S7337	34	S7801	115	S8123	16	S8311	40	S8405	12	S8659	45	Y75303	125
S7086	114	S7155	115	S7254	36	S7338	34	S7815	115	S8125	15	S8312	40	S8406	12	S8660	45		
S7087	114	S7156	112	S7255	36	S7339	34	S7816	115	S8126	15	S8313	40	S8410	12	S8661	45		
S7088	114	S7157	112	S7256	36	S7341	35	S7817	110	S8127	15	S8314	41	S8411	12	S8662	45		
S7089	110	S7158	112	S7257	36	S7342	35	S7820	114	S8128	15	S8315	41	S8412	12	S8663	45		
S7090	110	S7159	112	S7258	36	S7343	35	S7821	114	S8129	15	S8316	41	S8418	13	S8664	45		
S7091	110	S7160	112	S7259	36	S7361	31	S7822	114	S8130	15	S8317	42	S8419	13	S8665	45		
S7092	110	S7161	112	S7261	31	S7362	31	S7823	114	S8131	15	S8318	42	S8420	13	S8666	46		
S7093	115	S7162	112	S7262	31	S7363	31	S7824	114	S8132	15	S8319	42	S8421	13	S8667	46		
S7094	114	S7163	112	S7263	31	S7364	31	S7825	114	S8133	15	S8320	42	S8422	11	S8668	46		
S7095	114	S7165	112	S7264	31	S7365	31	S7827	110	S8134	15	S8321	42	S8423	11	S8669	46		
S7096	110	S7166	115	S7265	31	S7366	31	S7828	115	S8135	15	S8322	42	S8424	11	S8670	46		
S7097	114	S7167	115	S7266	31	S7375	34	S7829	111	S8136	15	S8323	42	S8425	11	S8671	46		
S7098	110	S7168	115	S7267	33	S7376	34	S7830	111	S8137	16	S8324	42	S8426	11	VG020	116		
S7099	110	S7169	110	S7268	31	S7377	34	S7832	115	S8138	16	S8325	42	S8427	11	VG040	116		
S7101	112	S7170	110	S7271	33	S7379	34	S7835	109	S8139	16	S8326	42	S8428	11	VG100	116		



National Toll-Free:  
800-43-SATCO  
(800-437-2826)  
[www.satco.com](http://www.satco.com)

Copyright © 2017  
Satco Products, Inc  
All Rights Reserved.  
3/17 SA1039-2



**Distribution Centers:**

FLORIDA  
900 N.W. 159th Dr.  
Miami, FL 33169  
PH 305-624-2044  
FX 305-623-0286

CALIFORNIA  
31288 San Benito St.  
Hayward, CA 94544  
PH 510-487-4822  
FX 510-487-8955

WASHINGTON  
4710 116th St. S.W.  
Mukilteo, WA 98275  
PH 425-789-3300  
FX 425-789-3310

TEXAS  
2000 Valwood Pkwy.  
Farmers Branch, TX  
75234  
PH 972-247-2437  
FX 972-247-5408

PUERTO RICO  
Campeche St. 23  
Julio N. Matos  
Industrial Park,  
Carolina, PR 00984  
PH 787-757-3510  
FX 787-757-3540

**Corporate Offices and  
Distribution Center:**

NEW YORK  
110 Heartland Blvd.  
Brentwood, NY 11717  
PH 631-243-2022  
FX 631-243-2027