



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3804 South Street
75964-7263, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



SS206CPBG Mom R&L, C Off Switch

Selecta Products

Catalog Number	SS206CPBG
Manufacturer	Selecta Products
Description	Toggle Switch, Bat Handle; 125/250 Vac; 15 Ampere At 125 Vac, 10 Ampere At 250 Vac; Operation Type Momentary On/Maintained Off/Momentary On; Contact Configuration SPDT; Brass/Nickel Toggle Material; 0.687 Inch Toggle Length
Weight per unit	N/A
Product Category	Miniature/Appliance WRG Dev
Additional Information	POWER RATING 3/4 HP AT 125 TO 250 VAC
Brand	SELECTA
Commodity Description	Wiring Dev & Data Telecom Eq - Miniature/Appliance Wrg Dev
Contact Configuration	SPDT
Current Rating	15 AMPERE AT 125 VAC, 10 AMPERE AT 250 VAC
Long Description	TOGGLE SWITCH, BAT HANDLE; 125/250 VAC; 15 AMPERE AT 125 VAC, 10 AMPERE AT 250 VAC; OPERATION TYPE MOMENTARY ON/MAINTAINED OFF/MOMENTARY ON; CONTACT CONFIGURATION SPDT; BRASS/NICKEL TOGGLE MATERIAL; 0.687 INCH TOGGLE LENGTH
Manufacturers Part Number	SS206CP-BG
Model	SS
Mounting	0.47 INCH-32 TPI X 0.465 INCH L BUSHING
Operation Type	MOMENTARY ON/MAINTAINED OFF/MOMENTARY ON
Product Type	Toggle Switch
Size	1.003 INCH D X 1.315 INCH H
Terminal Type	0.25 INCH QUICK DISCONNECT
Toggle Length	0.64 INCH
Type	BAT HANDLE
Voltage Rating	125/250 VAC

TOGGLE SWITCHES • UTILITY & HEAVY DUTY

.50" MOUNTING HOLE DIAMETER













POLES & THROWS	CIRCUIT FUNCTIONS	NOMINAL RATING			ACTUATOR STYLE	ACTUATOR MATERIAL	LIGHTED TOGGLE/TOGGLE COLOR	TERMINATION TYPE	CATALOG NUMBER	FIG. NO.
		AMPS	AMPS	H.P.						
		125 VAC	250 VAC	125-250 VAC						

MOMENTARY CONTACT

SPST	OFF-(ON)	6	3		BAT	BRASS/NICKEL	NO/NICKEL	SCREW	SS277S-BG	1
SPST	OFF-(ON)	15	10	3/4	BAT	BRASS/NICKEL	NO/NICKEL	SCREW	SS206A-BG	2
SPST	OFF-(ON)	20	10Δ	3/4	BAT	BRASS/NICKEL	NO/NICKEL	.250" SPADE	SS206AP-BG	3
SPDT	ON-OFF-(ON)	15	10	3/4	BAT	BRASS/NICKEL	NO/NICKEL	SCREW	SS206B-BG	4
SPDT	ON-OFF-(ON)	20	10Δ	3/4	BAT	BRASS/NICKEL	NO/NICKEL	.250" SPADE	SS206BP-BG	5
SPDT	(ON)-OFF-(ON)	15	10	3/4	BAT	BRASS/NICKEL	NO/NICKEL	SCREW	SS206C-BG	4
SPDT	(ON)-OFF-(ON)	15	10	3/4	FLAT	NYLON	NO/BLACK	.250" SPADE	SS504-BG	6
SPDT	(ON)-OFF-(ON)	20	10Δ	3/4	BAT	BRASS/NICKEL	NO/NICKEL	.250" SPADE	SS206CP-BG	5
DPST	OFF-(ON)	20	10Δ	1 1/2	BAT	BRASS/NICKEL	NO/NICKEL	SCREW	SS208A-BG	7
DPST	ON-(OFF)	15	10	3/4	BAT	BRASS/NICKEL	NO/NICKEL	SCREW	SS208D-BG	8
DPDT	ON-(ON)	20	10Δ	1 1/2	BAT	BRASS/NICKEL	NO/NICKEL	SCREW	SS208E-BG	9
DPDT	ON-OFF-(ON)	15	10	3/4	BAT	BRASS/NICKEL	NO/NICKEL	SCREW	SS208B-BG	10
DPDT	(ON)-OFF-(ON)	15	10	3/4	BAT	BRASS/NICKEL	NO/NICKEL	SCREW	SS208C-BG	10
DPDT	(ON)-OFF-(ON)	20	10Δ	1 1/2	BAT	BRASS/NICKEL	NO/NICKEL	.250" SPADE	SS208CP-BG	11
3PDT	(ON)-OFF-(ON)	15	10	3/4	BAT	BRASS/NICKEL	NO/NICKEL	SCREW	SS212C-BG ²	12

Δ Rated 10 Amps 277 VAC

²Also rated 1, 2, or 3 phase



★ Switch height measurement in Figures above, includes body and terminals combined



All specifications and dimensions are for reference only. If specific information is needed and/or of critical nature, contact Selecta Products headquarters for specific information before ordering.