

Product Information Sheet



HI TECH ENGINE ENAMELS

This is a heat resistant spray paint that restores engines to their original factory color. Protects engines, transmissions, and other O.E.M. Equipment. This paint dries fast, has superior durability, and is resistant to gasoline and oil.

Suggested Uses:

Oil pans Transmissions Engine blocks Intake manifold

Packaging:

Cans per case 6
Shipping weight per case 7 lbs.

Container 16 fluid ounce can
Label weight 12 ounces (340 grams)
Shipping Classification Consumer Commodity ORM-D

UN 1950 Hazard Class 2.1

Properties:

Coverage Up to 15 square feet
Cleanup Paint or lacquer thinner
Flash point -40 F
Specific Gravity 0.82
Solids Content 18%

MIR value 0.86, cannot exceed 0.95 HAPs content 10% Storage Temperature Application Temperature 50-90F

Gasoline Resistance Yes
Heat Resistance 300F
Pagin System Chain

Resin System Chain Stopped alkyd Shelf life Guaranteed for 2 years

Dry Time*:

To touch 5 minutes
Tack free 30 minutes
To recoat Before 1 hour or
after 48 hours

*At 72F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*: High Gloss, >80

*as measured on a 60 degree gloss meter

Available Colors:

Part #	<u>Description</u>	UPC Code	Part #	<u>Description</u>	UPC Code
EN-42	Universal Black	043281003735	EN-60	Alpine Green	043281003834
EN-43	Ford Gray	043281003742	EN-63	Chrysler Blue	043281003841
EN-44	Ford/Chrysler Red	043281003759	EN-66	AMC Blue Metallic	04328100
EN-46	Ford Blue	043281003773	EN-67	GM Blue	043281003889
EN-48	Chevy Orange	043281003780	EN-70	Clear Engine Coating	043281003896
EN-56	Ford/Mustang Blue	043281003803	EN-71	Dull Aluminum	043281003902
EN-59	GM Red	043281003827	EN-76	Hemi Orange	043281008860

Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 Phone: 815-895-9101 or 800-435-4482 Fax: 815-895-8475 or 800-343-4258 www.seymourpaint.com