



Family

Location: Evansville

CED Evansville Supply

Catalog Number: CHS116-1.500
Product ID: 7TAA017980R0000
UPC Number: 78621093679
Status: A

Thin Wall Heat Shrink Tubing, Heat Shrink, Clear, Shrink Ratio 2 to 1, Flexible PVC. 1/16 inch x 1/5 inch long, Total of 1000 foot. Highly flame retardant. UL standard UL224. 110 degree C heat shrink temperature.

North American Specifications (UNSPSC)

UNSPSC	39121723 Heat shrinkable tube
IGCC	5073 Heat shrinkable tube
Brand Name	Shrink-Kon
Type	Thin-Wall Heat Shrinkable Tubing
Shrink Ratio	2:1
Voltage Rating	600 V
Thickness	Thin
Length	1.5 in ; 38.1 mm
Dielectric Strength	600 V/Mil (24kV/mm)
Volume Resistivity	1016 ohm-cm
Minimum Shrink Temperature	230 F ; 110 C
Flammability	Self Extinguishing
Water Absorption	0.30%
Color	Clear

European Specifications (ETIM)

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	2:1
Inner diameter before heat-shrink	1.6mm
Inner diameter after heat-shrink	0.8mm
Nominal diameter inch	1/16 inch
Wall thickness after shrinking	0.45mm
Length	7.62m
Operation temperature	-30-+105°C
Colour	Transparent
Material	PVC
Halogen free	N
With inner glue	N
Printable	N
UL approval	N

Packaging

Outer Quantity	8000
Outer Dimensions (inches)	16x16x6.75
Weight Uom	4.7 lbs. per 1000

For further technical assistance, please contact us...

Memphis, TN 38120
www.tnb.com

860 Ridge Lake Blvd.
Memphis, TN 38120

Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com