



Family

Catalog Number: CHS18-1.500
Product ID: 7TAA017980R0003
UPC Number: 78621093681
Status: Active

Thin Wall Heat Shrink Tubing, Heat Shrink, Clear, Shrink Ratio 2 to 1, Flexible PVC. 1/8 inch X 1.5 inch. 1000 foot. Highly flame retardant. UL standard UL224. 110 degree C heat shrink temperature.

North American Specifications (UNSPSC)

UNSPSC	39121723 Heat shrinkable tube
IGCC	5073 Heat shrinkable tube
Brand Name	Shrink-Kon
Type	Thin-Wall Heat-Shrinkable Tubing
Shrink Ratio	2:1
Voltage Rating	600V
Thickness	Thin
Length	1.5 in ; 38.1 mm
Dielectric Strength	600 V/Mil (24kV/mm)
Volume Resistivity	1016 ohm-cm
Minimum Shrink Temperature	230 Degrees F (110 C)
Flammability	Self Extinguishing
Water Absorption	0.30%
Color	Clear

European Specifications (ETIM)

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	2:1
Inner diameter before heat-shrink	3.175mm
Inner diameter after heat-shrink	1.524mm
Nominal diameter inch	1/8 inch
Wall thickness after shrinking	0.508mm
Length	304.8m
Operation temperature	-30-+105°C
Colour	Transparent
Material	PVC
Halogen free	N
With inner glue	N
Printable	N
UL approval	N

Packaging

Outer Quantity	8000
Outer Dimensions (inches)	16x16x6.75
Weight Uom	4.7 lbs. per 1000

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com