

Location: TIMONIUM

UNITED ELECTRIC SUPPLY

9480 DEERECO ROAD

Catalog Number: HS6-1-3.000R
Product ID: 7TAA017110R0016
UPC Number: 78621076099
Status: A

Heavy wall Heat Shrink Tubing, Red, Cross-linked Polyolefin. Install with WT1400 Heat gun or SIT-1 torch. .750 inch

Actual

North American Specifications (UNSPSC)

UNSPSC	39121723 Heat shrinkable tube
IGCC	5073 Heat shrinkable tube
Type	Heavy-Wall Heat Shrinkable Tubing
Shrink Ratio	3:1
Voltage Rating	600 V
Length	0.75 in ; 19.05 mm
Dielectric Strength	500 V/Mil (20kV/mm)
Volume Resistivity	1016 ohm-cm
Continuous Operating Temperature	-67 to +230 F ; -55 to +110 C
Minimum Shrink Temperature	248 F ; 120 C
Water Absorption	0.10%
Color	Red

European Specifications (ETIM)

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thick-walled
Shrink rate	3:1
Inner diameter before heat-shrink	19.05mm
Inner diameter after heat-shrink	3.096mm
Nominal diameter inch	3/4 inch
Wall thickness after shrinking	2.286mm
Length	0.0762m
Operation temperature	-55-+110°C
Colour	Red
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	Y
Printable	N
UL approval	Y

Packaging

Outer Quantity	100
Outer Dimensions (inches)	6x6x6
Weight Uom	6.25 lbs. per 100

Documents / Support Tools

Safety Data Sheet (SDS) Global	SDS-00046-TB2
--------------------------------	---------------

For further technical assistance, please contact us...

860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com