

Catalog Number: HS6-1-4-4
Product ID: 7TAA017110R0017
UPC Number: 78620992389
Status: Active



Representative

Heat Shrink Tubing, Cable Range #6-#1 AWG, Black, Cut 4 Inches, 4 Piece Kit

North American Specifications (UNSPSC)

UNSPSC	39121723 Heat shrinkable tube
IGCC	5073 Heat shrinkable tube
Brand Name	Shrink-Kon
Shrink Ratio	3:1
Voltage Rating	600V
Length	4 Inches/101.6mm
Dielectric Strength	500 V/Mil (20kV/mm)
Volume Resistivity	1016 ohm-cm
Continuous Operating Temperature	-67 Degrees F (-55C) to 230 Degrees F (110 C)
Minimum Shrink Temperature	248 Degrees F (120 C)
Water Absorption	0.10%
Color	Black

European Specifications (ETIM)

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thick-walled
Shrink rate	3:1
Inner diameter before heat-shrink	19.05mm
Inner diameter after heat-shrink	6.096mm
Nominal diameter inch	3/4 inch
Wall thickness after shrinking	3.048mm
Length	0.1016m
Operation temperature	-55-+110°C
Colour	Black
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	N

Packaging

Outer Quantity	1
Outer Dimensions (inches)	6x6x6
Weight Uom	32 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com