


Flag Terminals

Non-Insulated Flags



Cat. No.	Pkg. Qty.	Wire Range	Bolt Hole	Rec. Tool	Dimensions (in.)				Stock Thick. (in.)	
					A	B	C	M		
AB14-6A	100	22-14	#6	ERG4004	0.55	0.31	0.22	0.39	0.03	
AB51	1,000		#6							
AB14-8A	100		#8							
AB52	1,000		#8							
AB14-10A	100		#10							
AB53	1,000	12-10	#10		0.66	0.25	0.48	0.04		
C51	500		#6							
C10-8A	50		#8							
C52-TB	500		#8							
C10-10A	50		#10							
C53	500	8	#10	WT129	0.83	0.50	0.59	0.06		
D236	200		#10		0.90		0.64			
D226			1/4 in.		0.92		0.68			
D271			#10		0.93		0.69			
E226		6	1/4 in.		0.99		0.73			
E271			5/16 in.		1.05		0.81			
E272			#10		1.07	0.80				
F226		4	1/4 in.		1.10	0.63	0.33	0.80	0.07	
F271			5/16 in.		1.18		0.41	0.88		
F272			3/8 in.		1.20		0.43	0.90		
F273			1/4 in.	1.20	0.33		0.89			
G671	100	2	5/16 in.	1.28	0.46	1.02	0.97	0.08		
G672			3/8 in.	1.32					0.41	1.01
G673			5/16 in.	1.31					0.41	1.06
H672			3/8 in.	1.36					0.46	1.10
H673	50	1/0	5/16 in.	1.46	0.75	0.41	1.15	0.10		
J672			2/0	3/8 in.		1.51	1.24			
J673				1/2 in.		1.67	1.19			
J675		3/0		5/16 in.	1.59	0.41	1.24			
K672			3/8 in.	1.64	0.46	1.34	0.11			
K673			1/2 in.	1.76	0.55	1.43				
K675		250kcmil	3/8 in.	1.89	1.0	0.46		1.52	0.13	
M673			1/2 in.	1.99		0.55				
M675										