

3AA PROPOLYMER® DUALIE® INTRINSICALLY SAFE MULTI-FUNCTION FLASHLIGHT



- Material/Lens** Impact and chemical resistant engineering polymer resin; o-ring sealed and vented. Available in high visibility yellow, black. Unbreakable polycarbonate facecap and side lens with scratch resistant coating
- Dims/Weight** Length: 7.00 in. (17.78 cm) Body thickness: 1.06 in. (2.69 cm) Body Width: 1.52 in. (3.86 cm) Face cap diameter: 1.86 in. (4.72 cm)
6.8 oz. (193 grams) with AA alkaline batteries (included in purchase). 5.9 oz. (167g) with AA lithium batteries
- Light Source** Two White C4® LEDs, impervious to shock with a 50,000 hour lifetime. Spot function uses a smooth parabolic reflector that produces a tight beam with optimum peripheral illumination
- Output** Three output modes: Spot, flood, both (spot and flood simultaneously):
 - Spot: 140 lumens; 7,300 candela; 171m beam distance; runs 18 hours
 - Flood: 140 lumens; 80 candela; 18m beam distance; runs 18 hours
 - Simultaneous spot beam and flood beam: 245 lumens; runs 9 hours
 Spot beam utilizes smooth parabolic reflector for tight beam with optimum peripheral illumination
 Flood beam produces a soft, wide beam to illuminate your work area
 Spot and flood beams intersect for an uninterrupted light pattern to eliminate blind spots
- Switch** Dual, independently operating push-button switches for spot beam, flood beam, or both beams simultaneously. Easy to use with gloves
- Battery** • Three "AA" alkaline (included) or lithium primary batteries
• Mechanical polarity protection ensures correct installation of batteries
- Features** • Operating temperature: -20°F to 130°F. (To maintain hazardous locations rating: -20°C to 40°C)
• Durable, non-conductive, corrosion-proof polymer resin
• Rocky stipple texture for a sure grip
• Rugged, integrated, snag-free clip conforms to body of light
• IPX7 rated; waterproof to 1 meter for 30 minutes.
• 2 meter impact resistance tested
• Ergonomically designed for maximum hand comfort

Approvals Class I, II, Division 1, Groups A, B, C, D, E, F, G; Class III; CL I, ZN 0, IIC; Exia; T-Code: T4

Warranty Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Part #
3AA ProPolymer Dualie with 3 "AA" alkaline batteries. Clam - Yellow	080926-68750-9	68750
3AA ProPolymer Dualie with 3 "AA" alkaline batteries. Clam - Black	080926-68752-3	68752
3AA ProPolymer Dualie without batteries. Mailer - Yellow	080926-68751-6	68751
3AA ProPolymer Dualie without batteries. Mailer - Black	080926-68753-0	68753

#68085



#99075

Helmet Strap.
Helmet and light not included.

Adheres to side of hard hat



#68089 - Poly Mount Kit universal mounting
via slot attachment or self-adhesive mount



Clips onto hard hats

Item	UPC	Part #
4AA/3AA helmet mount	080926-68085-2	68085
Poly Mount Kit	080926-68089-0	68089
Rubber Helmet Strap	080926-99075-3	99075



STREAMLIGHT



30 Eagleville Road • Eagleville, PA 19403 • 610-631-0600/800-523-7488 Phone • 610-631-0712/800-220-7007 Fax
www.streamlight.com ©Streamlight, Inc. 3AA ProPolymer Dualie 9/15