

Catalog Number: 5354-8PT
Product ID: 7TAD012980R0113
UPC Number: 78621026415
Status: Active

1 Inch Liquidtight Flexible Metal Conduit Connector, 90 Degree Angle, Insulated. UL Listed Liquidtight, UL Listed Grounding Means Under NEC 351-9, In Wet Locations Use #5264 Sealing Ring Between Box and Fitting for Knockout Applications. UL Listed for Type 3, 3r, 3sa, 4, 5, 12 and 12k When Used With Sealing Ring 5264. 5 Pieces.

North American Specifications (UNSPSC)

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	T&B
Type	Liquidtight Fittings
Standard	UL Listed
Size	1 Inch
Connection	90 Degree

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	1 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	NPT
Thread connection size	Other
One-piece	N
Material housing	Steel

Packaging

Inner Quantity	5
Inner Dimensions (inches)	4.5x4x6
Outer Quantity	25
Outer Dimensions (inches)	4.81x6.31x21.43
Weight Uom	68.81 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com