


T&B Conduit Fittings

Rigid and Intermediate Metal Conduit Fittings

Tite-Bite® Combination Couplings Armoured Cable for Threaded Rigid



A one-piece fitting that couples armoured cable or flexible conduit to threaded rigid conduit. Tite-Bite wedge holds conduit securely with a double grip. With a Chase® nipple, this fitting will connect flexible conduit to outlet boxes, allowing more wiring space in the box than the usual fitting. Malleable iron.

| Cat. No. | Size | Dimensions (in.) | |
|----------|------|------------------|---------|
| | | A | B |
| 440-C | 1/2" | 1-5/8 | 1-27/32 |
| 441 | 3/4" | 1-3/4 | 2-1/8 |
| 442 | 1" | 2 | 2-17/32 |



Includes bolts. Steel.

Beam Clamps Adjustable



| Cat. No. | Description |
|----------|---------------------------|
| 700TB | Fits Flange 2-3/4"-7-3/8" |
| 703* | Special Bolt and 3 Nuts |

* Not CSA Certified



These supports will fit any flange, tapered or straight up to 5/8" thick. The broad hook holds the conduit at any desired angle. Holds standard rigid conduit, E.M.T., or I.M.C. Malleable iron.

Conduit Supports



| Cat. No. | Size |
|----------|--------|
| 690TB | 1/2" |
| 691TB | 3/4" |
| 692TB | 1" |
| 693TB | 1-1/4" |