



Representative

**Catalog Number:** 5234GRX  
**Product ID:** 7TAD012420R0005  
**UPC Number:** 78621075935  
**Status:** Active

1 Inch Steel External Bonding Liquidtight Connector With Lay-in-lug, Non-insulated

- Ability to install quickly with low torque effort

### UNSPSC Specifications

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	T&B
Type	Grounding Connectors-Straight
Application	To positively bond conduit to box or enclosure
Standard	E 3060
Size	1 Inch
Material	Steel
Finish	Electro Zinc Plated/Chromate Coating

### ETIM Specifications

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	1 inch
Model	Straight
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	NPT
Thread connection size	Other
One-piece	N
Material housing	Steel
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UL	Y

### Packaging

Inner Quantity	10
Inner Dimensions (inches)	6x5x4
Outer Quantity	50
Outer Dimensions (inches)	26.4x6.3x4.5
Weight Uom	48 lbs. per 100

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com