

Overwatch®

Extreme Style In Safety Eyewear



Black Frame

Part	Lens
VGSB718T ●●●●	Bronze H2X Anti-Fog
VGSB722T ●●●●	Forest Gray H2X Anti-Fog
VGSB770T ●●●●	Silver Mirror Anti-Fog

OD Green Frame

Part	Lens
VGS6718T ●●●●	Bronze H2X Anti-Fog
VGS6722T ●●●●	Forest Gray H2X Anti-Fog

- Sunglasses style with metal hinge.
- Soft nosepiece and rubber temple tips provide comfort for all-day use.
- Anti-fog, scratch resistant polycarbonate lens provides 99% UVA/B/C protection.
- Passes MIL-PRF 32432 High Velocity Impact Standards.






GENERAL SPECIFICATION
Bridge: 12.6mm
Closest Point Between Lens: 15.1mm
Closest Point Between Temple Tips: 93mm
Lens Base: 8 Curve
Lens Size Diagonal: 66.7mm
Lens Size Vertical: 42.3mm
Lens Thickness: 2.2mm
Overall Length (Lens-Tip): 160mm
Overall Width (Hinge-Hinge): 131.5mm
Weight: 35.5gm
PD: 64mm

PACKAGING

Sold individually in a Venture Gear Tactical branded box

Case: 60 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve
Frame	PCB	Wrap around design with side temples
Temple	Polycarbonate	Soft tips for comfort
Temple tip	TPE	
Nose Piece	TPR	Glued on nose bridge
Hinge	Nickle Silver	5 barrel type
Screw	Stainless Steel	Standard Hinge Screw

PART	LENS	LENS MARKING	FRAME MARKING
VGSB718T	 Bronze H2X Anti-Fog	P + S	P Z87 +
VGSB722T	 Forest Gray H2X Anti-Fog	P + S	P Z87 +
VGSB770T	 Silver Mirror Anti-Fog	P + S	P Z87 +
VGS6718T	 Bronze H2X Anti-Fog	P + S	P Z87 +
VGS6722T	 Forest Gray H2X Anti-Fog	P + S	P Z87 +

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices