



KITCHEN | BATH

LATEX ULTRA

Siliconized
Acrylic
Latex Sealant



White Lightning® Latex Ultra is a high-performance Siliconized Acrylic Latex Sealant formulated to seal and waterproof around bathtubs, basins, sinks, showers, toilets, countertops and splashboards. This unique formula delivers a high gloss finish similar to silicone. White Lightning® Latex Ultra seals cracks between ceramic tile, marble, granite, porcelain, vinyl, wood, metal and glass.

- HIGH GLOSS FINISH
- Permanently Flexible
- Cured Sealant is Mold and Mildew Resistant



**WATER
PROOF**



PAINTABLE



**WATER
CLEANUP**

PART #	UPC	Color	SIZE
W21000010	0-23275-12861-3	White	10 fl oz
W21000005	0-23275-12862-0	White	5.5 fl oz
W21001010	0-23275-12863-7	Clear	10 fl oz
W21001005	0-23275-12864-4	Clear	5.5 fl oz
W21002510	0-23275-12865-1	Bisque	10 fl oz
W21002505	0-23275-12866-8	Bisque	5.5 fl oz

WHITE



KITCHEN | BATH

LATEX ULTRA

*Scrubable
High Gloss
Finish*

- Durable and crack resistant
- Cured Sealant is Mold and Mildew Resistant

**SILICONIZED
ACRYLIC
LATEX SEALANT**



WATERPROOF



PAINTABLE



WATER CLEANUP



10 FL OZ (295 mL)

Product Description:

White Lightning® Latex Ultra is a high-performance Siliconized Acrylic Latex Sealant formulated to seal and waterproof around bathtubs, basins, sinks, showers, toilets, countertops and splashboards. This unique formula delivers a high gloss finish similar to silicone. White Lightning® Latex Ultra seals cracks between ceramic tile, marble, granite, porcelain, vinyl, wood, metal and glass.

Physical Properties:

Type: Styrene Acrylic

Colors: White, Clear, Bisque

Shelf Life: 24 Months

Flash Point: n/a (water based)

Flammability: n/a (water based)

Full Cure Time: 3 to 4 days for White and Bisque; 5 to 7 days for Clear

Tack Free Time: 45 Minutes at 75° F

Application Temperature: 40° F to 140° F

Service Temperature: -30° F to 180° F

Vehicle: Styrene Acrylic

Solids by Weight: 69+/-2% for White and Bisque; 62.02+/-1% for Clear

Weight/Gallon: 10.78+/-0.15 for White and Bisque; 8.81+/-0.2 for Clear

Painting: Paintable

Primers: Not required

Mildew Resistance: Excellent

Water Resistance: Excellent

Odor: Low

Shrinkage: Low

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/2"

Freeze-Thaw Stability: Passes Through 5 Cycles

Shelf Life: 24 Months

Clean Up: Water, promptly clean tools and excess caulk with water or a damp cloth.

Flexibility: Excellent

Linear Coverage 10oz cartridge 24ft at 1/4" wide by 1/4" deep bead; 5.5oz squeeze tube 12ft at 1/4" wide by 1/4" deep bead

Painting: A minimum of 4 hours dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

NOTE: Acrylic Clear will apply appearing milky white and dry clear when fully cured.

Application:

1. Remove all existing caulk
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

• 10oz cartridge

- Cut cartridge tip 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

• 5.5oz squeeze tube

- Remove cap, cut tube tip 45° angle.
- Squeeze tube to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

Clean Up:

Water; promptly clean tools and excess caulk with water or a damp cloth.

Cautions:

See MSDS

Limitations:

For best results, apply at temperatures above 40° F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line

LIMITED WARRANTY:

For 50 years from date of purchase, if when applied according to label directions within one year from date of purchase, if this product fails to perform in accordance with the specifications set forth on this label, as your sole remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. Applies to single family house only. This warranty is made to the original residential consumer purchaser and is not transferable. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER

For more information please call or write:

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com