



HUBBELL
Advantage

- Recessed Receptacle Design
Minimizes Plug Protrusion
Allowing Furniture to be
Located Over the Plug
- Pre-Assembled Flange, Cover
and Leveling Ring for
Quick Installation
- Cut Box After Pour for
Height Adjustment
- RoHS Compliant



Specifications



- UL Listed for scrub water
- Single ordered service when used with
low voltage divider
- 4" minimum concrete pour
- Parallel PVC hubs for 1" and 3/4" conduit

Floor Box For Structural Concrete Floors

Description	Material	Color	Catalog No.
Flange and hinged door cover assembly; includes tamper-resistant duplex receptacle 15A 125V; gasket; floor leveling PVC ring; high impact and chemically resistant nylon; factory pre-assembled for easy drop-in installation	Solid Brass	–	RF406BR
	Thermoplastic	Almond	RF406AL
	Thermoplastic	Black	RF406BK
	Thermoplastic	Chestnut Brown	RF406BN
	Thermoplastic	Gray	RF406GY
Flush fit assembly, same as above	Solid Brass	–	RF409BR
Floor box with concrete protective cover; accepts 3/4 in. and 1 in. schedule 40 and schedule 80 PVC conduit; includes round box (4 7/8 in. dia. x 6.0 in. deep); four reducers; closure plugs; and concrete cover with locator flag	PVC	Gray	RF400
Hinged nylon replacement door cover; includes neoprene gasket to seal plug openings; replacement cover for RF406 series	Solid Brass	–	RF407BR
	Thermoplastic	Almond	RF407AL
	Thermoplastic	Black	RF407BK
	Thermoplastic	Chestnut Brown	RF407BN
	Thermoplastic	Gray	RF407GY
Low voltage divider; for use in PVC box RF400; when JLOAD® multimedia outlet is used	Thermoplastic	Gray	RF408



RF406BK



RF400



RF407BK



RF408