



ScrubShield Complies with UL514 A & C

3-Inch Core Hole, Two-Piece Unit	2-Inch Core Hole Two-Piece Unit		
Description	Catalog No.	Description	Catalog No.
Large Capacity Multi-Service Pedestal Through-Floor Fitting with (1) 1 ¹ / ₄ in. E.M.T. stem for low voltage and (1) ¹ / ₂ in. E.M.T. stem for power applications.	РТ7ХС	Multi-Service Pedestal Through-Floor Fitting with (1) 1¼ in. E.M.T. stem for low voltage and (1) ½ in. E.M.T. stem for power applications.	PT27A
 Specifications: 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design) For 2¼ in. to 7 in. floor thickness Approved for use in the City of Chicago 		 Specifications: 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design) For 2¹/₄ in. to 7 in. floor thickness Approved for use in the City of Chicago 	

Note: *Includes pre-wired 20A isolated ground duplex receptacle.

Pedestal Service Fittings (Order 1 plate per gang)								
Description	Color/Material	Catalog No.	Description	Color	Catalog No.	Description	Color	Catalog No.
2-Gang	Alum. Finish Black Gray	FR280ALA FR280BKA FR280GYA	4-Gang	Black Gray	FR480BKA FR480GYA	6-Gang	Black Gray	FR680BKA FR680GYA
Use with PT2:				27A or PT7XC.		Use with PT2	7A or PT7XC.	

- Painted aluminum housing with low voltage barrier(s); plates and devices sold separately
- For additional barriers, use Catalog No. FRBR1 (see page Q28)
- UL Listed and CSA Certified

Description	Color/Material	Catalog No.	Description	Color/Material	Catalog No.	
Duplex	Black Gray	SS2309DBKA SS2309DGYA	Furniture Feed (¾ in. KO)	Alum. Finish Black Gray	SS2309FALA SS2309FBKA SS2309FGYA	. 0
Style Line®/ GFCI	Black Gray	SS2309SLBKA SS2309SLGYA	Furniture Feed (1 in. KO)	Black Gray	SS2309F1BKA SS2309F1GYA	. 0
Single Rec. (1.39 in. OD)	Black Gray	SS2309SBKA SS2309SGYA	Bushed Data Opening (1 in. ID)	Black Gray	SS2309TBKA SS2309TGYA	. *
Blank	Alum. Finish Black Gray	SS2309BALA SS2309BBKA SS2309BGYA		uminum plates and CSA Certifi	ed	

