

WATER WELL PUMPS - 4" Submersible Pumps



EFSUB10-203

4" Submersible Pump, 3-Wire

1 HP - 20 GPM

APPLICATIONS

- Provides Smooth Water Passages for Maximum Efficiency

FEATURES

- 1-1/4" FNPT Discharge Connection, includes Built-in Check Valve,
- Stainless Steel Pump Shaft is Precision Ground for Exact Bearing Fit and Straightness
- Precision Molded Impellers and Diffusers
- Stainless Steel Pump Housing for Maximum Protection Against Corrosion
- Stainless Steel Splined Shaft
- Self-healing Resin System
- Hermetically-sealed Windings
- Filter Check Valve
- Kingsbury-type Thrust Bearing
- Pressure Equalizing Diaphragm
- Removable Water-bloc Lead Connector
- NEMA Mounting Dimensions

SPECIFICATIONS

UPC	WARRANTY	WEIGHT	DIMENSIONS (L x W x H)	PALLET QUANTITY
856594003787	3 Year	27.56 Lbs.	25.8" x 3.5"	50



PERFORMANCE CHART

MODEL	HP	GPM	VOLT	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER										
				20	40	60	80	100	125	150	175	200	250	300
EFSUB10-203	1	20	230	-	-	22.7	20	19	12.7	-	-	-	-	-

PERFORMANCE SHOWN IN GPM AT 40 PSI DISCHARGE PRESSURE

ECO-FLO PRODUCTS

1899 Cottage Street, Ashland, Ohio 44805 • Customer Service: 1-877 326-3561 • Fax: 1-877 326-1994 • www.ecofloproducts.com