

WATER WELL PUMPS - 4" Submersible Pumps



EFSUB5-102

4" Submersible Pump, 2-Wire

1/2 HP - 10 GPM

APPLICATIONS

- Provides Smooth Water Passages for Maximum Efficiency

FEATURES

- 1-1/4" FNPT Discharge Connection, includes Built-in Check Valve
- Stainless Steel Pump Shaft is Precision Ground for Exact Bearing Fit and Straightness
- Precision Molded Impellers and Diffusers
- Stainless Steel Pump Housing for Maximum Protection Against Corrosion
- Stainless Steel Splined Shaft
- Self-healing Resin System
- Hermetically-sealed Windings
- Filter Check Valve
- Kingsbury-type Thrust Bearing
- Pressure Equalizing Diaphragm
- Removable Water-bloc Lead Connector
- NEMA Mounting Dimensions

SPECIFICATIONS

UPC	WARRANTY	WEIGHT	DIMENSIONS (L x D)	PALLET QUANTITY
856594003718	3 Year	23.8 Lbs.	23.4" x 3.5"	50



PERFORMANCE CHART

MODEL	HP	GPM	VOLT	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER										
				20	40	60	80	100	150	200	250	300	350	400
EFSUB5-102	1/2	10	230	-	-	11	9.8	8.7	-	-	-	-	-	-

PERFORMANCE SHOWN IN GPM AT 40 PSI DISCHARGE PRESSURE

ECO-FLO PRODUCTS

1899 Cottage Street, Ashland, Ohio 44805 • Customer Service: 1-877 326-3561 • Fax: 1-877 326-1994 • www.ecofloproducts.com