



**PRODUCT FEATURES:**

- **Flexible Selectronic Platform** with programmable, multi-function sensor.
- **Hygienic, touch-free operation**
- **Easy & Flexible Installation:** Single post mounting with optional 4" & 8" deck plate. Water resistant solenoid enclosure mounts to wall.
- **Durable Vandal-Resistant Cast Body:** Ideal for high-use commercial applications.
- **Self-Cleaning Solenoid Valve:** Wiper spring prevents clogging
- **Easy to Service Integrated Strainer:** Patented integrated strainer protects solenoid from debris. Strainer is enclosed in removable debris cup for easy service.
- **Optional Auto Purge Feature:** Faucet can be programmed to open at a pre-determined time after last use to purge the faucet and water lines of stagnant water.
- **Safety Timer:** Helps prevent vandalism by turning off the faucet if the sensor is covered for 55 seconds or more. Timing is adjustable with optional remote control.
- **Adjustable Range:** Detection zone can be adjusted manually or with optional remote control.
- **Fail-Safe:** Faucet automatically shuts off upon loss of power or dead battery. Prevents costly excess water usage and potential flooding.
- **Lead-Free:** Faucet contains ≤ 0.25% total lead content by weighted average.

**GENERAL DESCRIPTION:**

Electronic faucet with proximity operation. Vandal-resistant cast spout with single post mounting. Water pressure range from 20 to 125 psi. Single inlet. 18" flexible inlet hose with 3/8" compression fitting for connection to control box.

**PWR MODEL NUMBER:**



■ **PWRX™ 10 YEAR BATTERY POWERED**

- ❑ **6053.105** 0.5 gpm/1.9 L/min pressure compensating, vandal-resistant multi-laminar spray.
- ❑ **6053.104** 0.35 gpm/1.3 L/min pressure compensating, vandal-resistant multi-laminar spray. Faucet is factory set for 7.5 second running time to deliver 0.044 gpc/0.17 L per cycle.
- ❑ **6053.102** 1.5 gpm/5.7 L/min pressure compensating, vandal-resistant aerator.



■ **DC (CR-P2 LITHIUM BATTERY) POWERED**

- ❑ **6055.105** 0.5 gpm/1.9 L/min pressure compensating, vandal-resistant multi-laminar spray.
- ❑ **6055.104** 0.35 gpm/1.3 L/min pressure compensating, vandal-resistant multi-laminar spray. Faucet is factory set for 7.5 second running time to deliver 0.044 g/0.17 L per cycle.
- ❑ **6055.102** 1.5 gpm/5.7 L/min pressure compensating, vandal-resistant aerator.



■ **OPTIONAL 4" or 8" Deck plates**

- ❑ **605P.400** 4" brass deck plate with 1/4" fixation studs and quick spin nuts. (6-1/8" x 2-1/8" x 1/2")
- ❑ **605P.800** 8" brass deck plate with 1/4" fixation studs and quick spin nuts. (10-1/8" x 2-3/8" x 1/2")

■ **OPTIONAL Mixing Valve**

- ❑ **605XTMV1070** Thermostatic mixing valve. 20" flexible inlet hoses with 3/8" compression fittings. ASSE 1070 certified down to 0.35 gpm/1.3 L/min.

■ **OPTIONAL Remote Control**

- ❑ **605XRT** Adjusts setup parameters and allows for customization of functions. Can be used to program all Selectronic faucets and flush valves.

**POWER OPTIONS:**

- **PWRX 10 Year Battery System:** Battery Life - 480,000 cycles (10 years @ 4,000 cycles per month). Advanced battery & electronics reduce the downtime and maintenance costs associated with changing batteries. Safety Circuitry prevents overheating in case of short circuit and protects the electronics from damage.
- **DC (Battery):** Includes CR-P2 lithium battery. Battery Life - 192,000 cycles (4 years @ 4,000 cycles per month).

**RECOMMENDED SPECIFICATION:**

Electronic, sensor-operated lavatory faucet shall feature a programmable, multi-function sensor and an electronically operated self-cleaning solenoid valve. Shall also feature a vandal resistant cast body with single inlet and in-line strainer. Shall meet ANSI A112.18.1 and ANSI 117.1 codes. Fitting shall be American Standard Model # 605\_10\_.

**CODES AND STANDARDS**

These products meet or exceed the following codes and standards:

- ANSI A117. 1**
- ASME A112.18.1**
- CSA B125.1**
- NSF 61/Section 9**
- NSF 372**

<b>Other Aerators Available:</b>	
<b>Part Suffix</b>	<b>Description</b>
V035*	0.35 gpm/1.3 L/min PCA Vandal-Resistant Multi-Laminar Spray

PCA - PRESSURE COMPENSATING  
 \*MEETS CAL GREEN CODE

