



**PVC SDR 35 D-3034 SEWER PIPE
SOLVENT WELD**

CNWPVC-353034SW

MARCH, 2012

PLEASE ORDER BY PART NUMBER.

10' BELLED END	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PERCENT OF TL	MIN. BELL LENGTH	PART NO.
SOLVENT WELD PVC-SEWER SDR 35 ASTM D-3034 SOLID & PERFORATED GREEN	4" SOLID	4.215	3.975	.120	106.51	900	4.2	3.5	53115
	4" PERF	4.215	3.975	.120	106.51	900	4.2	3.5	53120
	6" SOLID	6.275	5.915	.180	238.40	350	4.1	4.0	53180
	6" PERF	6.275	5.915	.180	238.40	350	4.1	4.0	53195

20' BELLED END	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PERCENT OF TL	MIN. BELL LENGTH	PART NO.
SOLVENT WELD PVC-SEWER SDR 35 ASTM D-3034 SOLID & PERFORATED GREEN	4" SOLID	4.215	3.975	.120	106.51	1200	6.6	3.5	53118
	4" PERF	4.215	3.975	.120	106.51	1200	6.6	3.5	53122
	6" SOLID	6.275	5.915	.180	238.40	700	9.7	4.0	53183
	6" PERF	6.275	5.915	.180	238.40	700	9.7	4.0	53197

10' BELLED END	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PERCENT OF TL	MIN. BELL LENGTH	PART NO.
SOLVENT WELD PVC-SEWER SDR 35 ASTM D-3034 SOLID & PERFORATED WHITE	4" SOLID	4.215	3.975	.120	106.51	900	4.2	3.5	53112
	4" PERF	4.215	3.975	.120	106.51	900	4.2	3.5	53119
	6" SOLID	6.275	5.915	.180	238.40	350	4.1	4.0	53179
	6" PERF	6.275	5.915	.180	238.40	350	4.1	4.0	53196

20' BELLED END	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PERCENT OF TL	MIN. BELL LENGTH	PART NO.
SOLVENT WELD PVC-SEWER SDR 35 ASTM D-3034 SOLID & PERFORATED WHITE	4" SOLID	4.215	3.975	.120	106.51	1200	6.6	3.5	53113
	4" PERF	4.215	3.975	.120	106.51	1200	6.6	3.5	53121
	6" SOLID	6.275	5.915	.180	238.40	700	9.7	4.0	53184
	6" PERF	6.275	5.915	.180	238.40	700	9.7	4.0	53198

REFER TO ASTM D-2321 FOR PROPER INSTALLATION PROCEDURES OF SDR-35 SEWER PIPE.

INSTALL AS DIRECTED BY ASTM D-2321.

PERFORATIONS ARE 2 ROWS OF ½" HOLES ON 5" CENTERS 120° APART.

CRESLINE-NORTHWEST, LLC.

CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD · EVANSVILLE, IN 47715 · TELEPHONE (812) 428-9300

PLANT: 223 MAURIN ROAD · CHEHALIS, WA 98532 · TELEPHONE (360) 740-0708 · FAX (360) 740-0721