

MODEL NUMBER RXL12WMVJU9, 12 KBTU HP OUTDOOR MODEL



[Specifications](#) | [Dimensions](#) | [Features](#) | [System Efficiency Metrics](#) | [Benefits](#)

Specifications

Power Supply	208-230 V/ 60 Hz / 1 Phase
Amount of Additional Charge of Refrigerant	0.21 oz/ft 20 g/m
Casing Color	Ivory White
Heat Exchanger	Waffle Fin (PE) / φ 7 Hi-XSL Tube
Compressor Type	Hermetically Sealed Swing Type
Compressor Model	2YC36PXD
Refrigerant Oil Type	FVC50K
Refrigerant Oil Charge	0.65 L 21.98 oz
Refrigerant Type	R-410A
Refrigerant Charge	2.09 lb
Airflow Rate (H) - Cooling	1144 ft ³ /min 32.4 m ³ /min
Airflow Rate (H) - Heating	1031 ft ³ /min 29.2 m ³ /min
Fan Type	Propeller

Sound Pressure Level - Cooling	50 dBA
--------------------------------	--------

Sound Pressure Level - Heating	50 dBA
--------------------------------	--------

Fan Motor Output	27 W 0.04 hp
------------------	-----------------

Weight	73 lb 33 kg
--------	----------------

Gross Weight	78 lb 35 kg
--------------	----------------

Dimensions

Depth	11-3/16 in 284 mm
-------	----------------------

Width	26-9/16 in 675 mm
-------	----------------------

Height	21-5/8 in 550 mm
--------	---------------------

Packaged Depth	14-11/16 in 373 mm
----------------	-----------------------

Packaged Width	31-7/16 in 798 mm
----------------	----------------------

Packaged Height	23-13/16 in 605 mm
-----------------	-----------------------

Pipe Connections - Liquid	1/4 in 6.4 mm
---------------------------	------------------

Pipe Connections - Gas	3/8 in 9.5 mm
------------------------	------------------

Pipe Connections - Drain	5/8 in 16.0 mm
--------------------------	-------------------

Max. Interunit Height Difference	49-1/4 ft 15 m
----------------------------------	-------------------

Max. Interunit Piping Length	65-5/8 ft 20 m
------------------------------	-------------------

Chargeless32-3/4 ft
10 m

Features

- High-efficiency inverter driven swing compressor
- Low ambient cooling capable
- Powerful (turbo) and Econo mode settings
- Heating operation down to -13°F WB (-25°C WB) ambient temperature

System Efficiency Metrics

Min. Circuit Ampacity	12.2 A
Max. Fuse Ampacity	15 A
Rated Loads Ampacity	12.0 A
Full Load Ampacity	0.21 A

Benefits

- 12-year parts limited warranty with online registration for residential applications
- 5-year parts limited warranty with online registration for commercial applications
- High efficiency cooling operation provides utility bill savings
- May qualify for regional utility rebates and incentives