



see what Delta can doSM

SHOWER HEAD

■ 5-Spray Setting Shower Head

FEATURES:

- Touch-Clean[®] Spray Holes

STANDARD SPECIFICATIONS:

- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Shower head with five spray settings - pause is a non-positive shut-off
- Change spray settings with easy-turn lever
- Fits standard 1/2"-14 NPT pipe fitting
- Ball connector swivel angle is 17° (8.5° per side)
- 5 Spray settings include: Full Body spray, Full Spray with Massage, Massaging spray, Drenching spray and Pause

WARRANTY:

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



Certified by
ICBC Group
SHOWER HEADS
POMMES DE DOUCHE
CABEZALES DE RESERENA

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense[®]

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-75564C Rev. C

Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2025 Delta Faucet Company