SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Clear Glass Coat
Part Number:	DeVilbiss Automotive Refinishing Part No. 803669
Product Description:	Clear Peelable Glass Coating.
SDS #:	SDS-173 REVISION #: 2015-Aug-29
Chemical Formula:	Proprietary polymers and compounds.
CAS Number:	Not Applicable.
Article Code:	Not Applicable.
General Use:	DeVilbiss CLEAN [™] 803669 Clear Glass Coat is clear sprayable liquid which protects indoor glass surfaces from paint overspray. The product forms a tough, peelable film that is easily removed from glass surfaces.

Relevant identified uses of the substance or mixture and uses advised against:

Do not consume. Do not freeze product. Do not use on non-glass surfaces such as walls and doors.

Company Information:

DeVilbiss Automotive Refinishing 11360 S. Airfield Rd. Swanton, Ohio 43558 Customer Service Phone: 1-800-445-3988

Emergency telephone number - CHEMTREC (24 HOURS): 1-800-424-9300

2. HAZARDS IDENTIFICATION

According to OSHA 29 CFR 1910.1200 HCS Skin Sensitizer: Category 3 Eye Irritation: Category 2B Carcinogenicity: Category 2
WARNING
Causes mild skin irritation – H316 Causes eye irritation – H320 Suspected of causing cancer – H351
ents
Avoid breathing dust/fume/gas/mist/vapors/spray. – P261 Wear protective gloves/protective clothing/eye protection/face protection P280
IF ON SKIN: Wash with plenty of soap and water. – P302 + P352 If skin irritation occurs: Get medical advice/attention. – P332 + P313 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. – P305 + P351 + P338 If eye irritation persists: Get medical advice/attention. – P337 + P313 Wash contaminated clothing before reuse. – P363

Finishing Brands. A CARLISLE COMPANY

Page 1 of 8



Storage/Disposal:	Keep container tightly closed. – P233 Store locked up. – P405 Dispose of contents/container in accordance with applicable local/regional/national regulations. – P501
Canada	According to WHMIS
WHMIS	This product is regulated as a hazardous material by the Canadian Controlled Product Regulations and is a controlled product under the Workplace Hazardous Materials Information System.
Classification:	D2A: Very Toxic Material (due to presence of residual vinyl acetate)
Other Information	
Vinyl acetate	Product contains residual vinyl acetate, an IARC 2B possible human carcinogen based on limited animal data.
HMIS Ratings: (Hazard Scale: 0 = Mir	Health: 1, Fire: 0, Physical Hazard: 0 nimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe; * = Chronic hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances: Material does not meet the criteria of a substance.

Mixtures

CAS #	Chemical Name	% by weight
7732-18-5	Water	55 – 65
Not available	Proprietary polymers and compounds	30 – 35
57-55-6	Propylene glycol	1 – 5
108-05-4	Vinyl acetate (residual)	0.2 - 0.4

The exact percentage of this composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Description of first aid measures

Inhalation:Remove person to fresh air. If you feel unwell, get medical attention.Skin Contact:Wash with soap and water. If signs/symptoms develop, get medical attention.Eye Contact:Rinse cautiously with water for several minutes. Remove contact lenses, if present and
easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.Ingestion:Not an expected route of exposure. If swallowed, get medical attention immediately. If
conscious, drink plenty of water. Do not induce vomiting.Most important symptoms and effects, both acute and delayed
See section 11 – Toxicological Information.

Indication of any immediate medical attention and special treatment required Not applicable.



Page 2 of 8



5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

In case of fire: Use a fire-fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Dried film of coating will burn when free from the substrate.

Hazardous decomposition or by-products

Carbon monoxide	During combustion
Carbon dioxide	During combustion
Acetaldehyde	During combustion
Formaldehyde	During combustion

Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

NFPA Ratings:	Health: 1	Flammability: 0	Instability: 0	Special Hazards = None

(Hazard Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Suitable extinguishing media

In case of fire: Use a fire-fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Dried film of coating will burn when free from the substrate.

Hazardous decomposition or by-products

Carbon monoxide	During combustion
Carbon dioxide	During combustion
Acetaldehyde	During combustion
Formaldehyde	During combustion

Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

NFPA Ratings: Health: 1 Flammability: 0 Instability: 0 Special Hazards = None

(Hazard Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For a large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.



Page 3 of 8



Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

Methods and material for containment and cleaning up

Contain spill. Work from around the edges of the spill inward and cover with commercially available inorganic absorbent material. Mix in sufficient absorbent material until it appears dry. Shovel as much of the material as possible into a suitable container. Seal the container and dispose of as soon as possible. Clean up residue with detergent and water.

7. HANDLING AND STORAGE

Precautions for safe handling

For industrial use only. Avoid contact with skin and eyes. Wash thoroughly after handling. Use with adequate ventilation and avoid breathing vapors or mists of this product. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Keep containers closed and in a cool, well-ventilated area. Protect from sunlight. Store away from heat. Store away from acids and oxidizers. Material is freeze-thaw stable, but best practice for any water-borne coating is to protect from freezing whenever possible.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits: If a component is disclosed in section 3 but does not appear here, an occupational exposure limit is not available for the component.

CAS #	Chemical Name	Agency	Limit Type
108-05-4	Vinyl acetate	ACGIH	TWA: 10 ppm; STEL: 15 ppm
108-05-4	Vinyl acetate	OSHA	TWA: 30mg/m3; STEL: 60mg/m3
57-55-6	Propylene glycol	AIHA	TWA: 10mg/m3

Key to abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists; AIHA = American Industrial Hygiene Association; OSHA = Occupational Safety and Health Administration; STEL = Short Term Exposure Limit; TWA = Time-Weighted Average based on 8hr/day and 40hr/week exposures

Exposure controls

Engineering controls

Provide adequate ventilation as needed to control concentrations of airborne contaminants below applicable exposure limits. If ventilation is not adequate, use respiratory protection equipment.

Personal protective equipment

Finishing Brands

Respiratory An exposure assessment may be needed to decide if a respirator is required. If needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, use either a half-facepiece or full-facepiece air-purifying respirator suitable for particulates. Consult respirator manufacturer for suitability for a specific application.

Eye/face protection

Safety glasses with eye shields are recommended.

Page 4 of 8



PRODUCT NAME: Clear Glass Coat

Skin/hand protectionWear protective gloves with cuffs. Normal work clothing (long sleeves and pants) is
recommended.General industrial hygieneHandle in accordance with good industrial hygiene and safety practice. Wash
thoroughly with soap and water after handling and before eating, drinking, or using
tobacco.Environmental exposureFollow best practice for site management and disposal of waste. Avoid release to
the environment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Basic physical and chemical properties

Physical form: Color: Odor: pH: Boiling point: Flash point: Density: Specific gravity: Weight per gallon: Viscosity: Solubility (H20): Solubility (H20): Sol	Liquid White Mild 4 - 7 $212^{\circ} F (100^{\circ} C)$ >=200° F [Test method: Closed Cup] 1.06 g/ml 1.06 [Water = 1] 8.8 lbs 400 - 800 cps [Brookfield] Emulsion No data available 62% 0.10% weight; 1/l [calculated] 3 g/l [calculated] No data available Not applicable No data available
Flammable Limits (LEL): Flammable Limits (UEL): Vapor pressure:	No data available No data available No data available
Vapor density:	No data available

10. STABILITY AND REACTIVITY

Reactivity:	No dangerous reaction known under conditions of normal use.		
Chemical stability:	Stable		
Possibility of hazardous reaction	ns: Hazardous polymerization will not occur.		
Conditions to avoid:	Freezing temperatures; Heat		
Incompatible materials:	Strong oxidizing agents		
Hazardous decomposition prod	ucts: None known. Refer to section 5 for hazardous decomposition products during combustion.		

Finishing Brands. A CARLISLE COMPANY

Page 5 of 8



11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Signs and symptoms: Based on component information, this material may produce the following health effects:

Inhalation:	Respiratory tract irritation: signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.	
Skin contact:	Contact with skin during product use is not expected to result in significant irritation.	
Allergic skin reaction (n	on-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.	
Eye contact:	Sprayed material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.	
Ingestion:	Gastro-intestinal irritation: signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.	

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Chemical Name	Route	Species	Value
Vinyl acetate	Inhalation	Rat	LC50: 11400 mg/m3 (4 hours)
Vinyl acetate	Inhalation	Mouse	LC50: 1550 mg/kg (4 hours)
Vinyl acetate	Oral	Rat	LD50: 2920 mg/kg
Vinyl acetate	Oral	Mouse	LD50: 1613 mg/kg
Vinyl acetate	Dermal	Rabbit	LD50: 2335 mg/kg
Propylene glycol	Ingestion	Rat	LD50: >20,000 mg/kg
Propylene glycol	Dermal	Rabbit	LD50: >2,000 mg/kg
Propylene glycol	Inhalation	Rabbit	LC50: 317.042 mg/l (2 hours, aerosol)

Skin Corrosion / Irritation:Either no data are currently available or the data are not sufficient for classification.Serious Eye Damage/Irritation:Either no data are currently available or the data are not sufficient for classification.Skin Sensitization:Either no data are currently available or the data are not sufficient for classification.Photosensitization:Either no data are currently available or the data are not sufficient for classification.Respiratory sensitization:Either no data are currently available or the data are not sufficient for classification.Germ cell mutagenicity:Either no data are currently available or the data are not sufficient for classification.Carcinogenicity:Either no data are currently available or the data are not sufficient for classification.

Chemical Name	Agency	Classification	
Vinul acotata	ACGIH	A3 – confirmed animal carcinogen with unknown	
Vinyl acetate	ACGIN	relevance to humans	
Vinul acatata		Monograph 63, 1995 (Group 2B (possibly carcinogenic to	
Vinyl acetate	IARC	humans))	

Reproductive and/or developmental effects

Reproductive Toxicity: Either no data are currently available or the data are not sufficient for classification.

Target Organ(s)

Specific Target Organ Toxicity - single exposure: Either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity – repeated exposure: Either no data are currently available or the data are not sufficient for classification.



Page 6 of 8



Aspiration hazard:

Either no data are currently available or the data are not sufficient for classification.

12. ECOLOGICAL INFORMATION

Toxicity – Aquatic toxicity of components

Chemical Name	Species	Test
Vinyl acetate	Fathead minnow	96 hr LC50: 31.0 mg/l
Vinyl acetate	Bluegill	96 hr LC50: 31.0 mg/l
Vinyl acetate	Goldfish	96 hr LC50: 31.0 mg/l
Vinyl acetate	Water flea	24 hr EC50: 52.0 mg/l
Propylene glycol	Rainbow trout	96 hr LC50: 40,613 mg/l
Propylene glycol	Water flee	48 hr LC50: 18,340 mg/l

Persistence and degradability

Product is an aqueous polymer emulsion that is expected to rapidly disperse in the aquatic environment. Polymers are not readily biodegradable.

Bioaccumulative potential:	No data available
Mobility in soil:	No data available

Other adverse effects: No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Avoid disposal. Completely utilize product, if possible. Dispose unused product and container in accordance with local, regional, national, and international regulations. Incinerate unused product in a permitted waste incineration facility. As a disposal alternative, dispose of waste product in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): Not regulated

14. TRANSPORT INFORMATION

US DOT information: TDG information: IMDG information: IATA information: Not regulated as a hazardous material. Not regulated as a dangerous good. Not regulated as a dangerous good. Not regulated as a dangerous good.

Transportation during cold weather

This product is freeze-thaw stable and will function properly if it is frozen and then thawed. However, whenever possible, minimize the number of freeze cycles to which the product is exposed during transportation.

15. REGULATORY INFORMATION

Page 7 of 8

U.S. Federal Regulations

Chemical inventory:

All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical Inventory.

General information:

No additional information available.



DEVILBISS AUTOMOTIVE REFINISHING Component analysis:

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

Vinyl acetate	SARA 302	1000 lb. Threshold Planning Quantities	
Vinyl acetate	SARA 313	0.1% de minimis concentration	
Vinyl acetate	CERCLA	5000 lb. final Reportable Quantity; 2270 kg final RQ	

State Regulations General information:

Other state regulations may apply. Check individual state requirements.

Component analysis:

The following components appear on one or more of the following state hazardous substances lists:

CAS #	Chemical Name	CA	MA	MN	NJ	PA	RI
108-05-4	Vinyl acetate	Yes	Yes	Yes	Yes	Yes	Yes
57-55-6	Propylene glycol	No	No	No	No	Yes	No

Canadian WHMIS information

Chemical inventory:	All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.			
General information:	This product is regulated Product Regulations and	This product is regulated as a hazardous material by the Canadian Controlled Product Regulations and is a controlled product under the Workplace Hazardous Materials Information System. See Section 2 for more information.		
Component analysis:	The following componen Disclosure List:	The following components are identified under the Canada WHMIS Ingredient Disclosure List:		
CAS #	Chemical Name	Minimum Concentration for Disclosure		

CAS #	Chemical Name	Minimum Concentration for Disclosure	
108-05-4	Vinyl acetate	0.1%	

16. OTHER INFORMATION

Date Revised:08/29/2015Date Prepared:06/19/2015Other information06/19/2015

DISCLAIMER: For industrial use only. Reasonable care has been taken in the preparation of this information and is believed to be accurate as of the date issued. Manufacturer does not suggest or guarantee that any hazards listed herein are the only ones which exist and makes no warranty of any kind, express or implied, concerning the safe use of this material in user's process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials.

Manufacturer makes no warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or course of performance or usage of trade. User is responsible for determining whether this product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.

*** END OF SDS ***

©2015 Carlisle Fluid Technologies, Inc., dba Finishing Brands. All rights reserved. DeVilbiss is part of Finishing Brands, a global leader of innovative spray finishing technologies.

Finishing Brands.	Page 8 of 8	DEVILBISS. AUTOMOTIVE REFINISHING
A CARLISLE COMPANY		