


R74 Standard Regulators



Features:


- pressure range 5-150 PSI
- inlet pressure: **300 PSI**
- maximum temperature: **150°F (66°C)**
- in-line or modular installation
- relieving type
- two full flow 1/4" NPT gauge ports
- RG models supplied with GC230 gauge
- To order 0-60 PSI range consult Dixon®.

| Port Size | Flow (SCFM) | with Gauge Part # | without Gauge Part # |
|-----------|-------------|-------------------|----------------------|
| 3/8" | 208 | R74G-3RG | R74G-3R |
| 1/2" | 220 | R74G-4RG | R74G-4R |
| 3/4" | 220 | R74G-6RG | R74G-6R |



Pneumatic Accessories

R17, R18 Jumbo Regulators




Features:

- pressure range 5-125 PSI
- inlet pressure: **300 PSI**
- maximum temperature: **175°F (79°C)**
- in-line or modular installation
- relieving type
- two full-flow 1/4" NPT gauge ports
- RG models supplied with GC230 gauge

| Port Size | Flow (SCFM) | with Gauge Part # | without Gauge Part # |
|-----------|-------------|-------------------|----------------------|
| 3/4" | 440 | R17-600RG | R17-600R |
| 1" | 480 | R17-800RG | R17-800R |
| 1 1/4" | 400 | R17-A00RG | R17-A00R |
| 1 1/2" | 440 | R17-B00RG | R17-B00R |

SCFM ratings given at 150 PSIG inlet pressure



Features:

- 5-125 PSI range
- inlet pressure: **450 PSI**
- maximum temperature: **175°F (79°C)**
- relieving type
- two full flow 1/4" NPT gauge ports
- RG model supplied with GC230 gauge

| Port Size | Flow (SCFM) | with Gauge Part # | without Gauge Part # |
|-----------|-------------|-------------------|----------------------|
| 2" | 2000 | R18-C05RG | R18-C05R |

SCFM ratings given at 100 PSIG inlet pressure




R11 General T-Handle Regulators

Floating valve pin provides positive seating and dependability. Large diaphragm provides quick response to flow demands and line pressure changes. Balanced valve reduces inlet pressure variations on outlet pressure.

Features:

- pressure range 5-125 PSI
- inlet pressure: **400 PSI**
- maximum temperature: **175°F (79°)**
- T-handle adjustment
- supplied with GC620 gauge



| Port Size | Flow (SCFM) | with Gauge Part # |
|-----------|-------------|-------------------|
| 1/4" | 110 | R11-013RG |
| 3/8" | 110 | R11-037RG |
| 1/2" | 260 | R11-061RG |

SCFM ratings at 150 PSIG.



See pages 422 to 427 for accessories.

FRL's are designed for air service only, unless otherwise indicated.