



Materials/Finishes:	Electro-Galvanized (150G)	T-304 Stainless Steel (150SS)
	T-316 Stainless Steel (150SX)	
Variants:	N/A	
Service:	Designed for attaching hanger rods from the center of an I-beam. Normally used with figure 26, 26W eyerods, or figure 13 weldless eye nut.	
Approvals:	Complies with Federal Specifications WW-H-171-E (Type# 21) and MSS SP-58 (Type# 21).	
Ordering:	Specify figure number, finish, clamp size, flange width, beam thickness.	
Notes:	Not available for beams greater than 12" wide. Recommended rod size based on maximum load. Maximum rod size based on dimension "C" and FIG. 13 Weldless Eye Nut.	

FLANGE		WGT. EACH, LBS.	
WIDTH	MAX THK	SIZE 1	SIZE 2
4	1/2	1.1	3.8
5	5/8	1.2	4.1
5-1/2	5/8	1.3	4.4
6	5/8	1.3	4.4
6-1/2	5/8	1.4	4.7
7	7/8	1.4	4.7
8	7/8	3.3	5.0
9	1	3.7	7.0
10	1	4.1	7.5
12	1	4.9	10.1

CLAMP SIZE	FLANGE	MATERIAL SIZE	BOLT	B	C	D	E	REC ROD	MAX ROD	MAX REC LOAD (lbs)
1	4 TO 7	1/4 x 1-1/4	1/2	1-1/8	5/8	5/8	0.840	1/2	3/4	1000
	8 TO 12	3/8 x 2		1-3/8						
2	4 TO 10	1/2 x 2	3/4	2	7/8	1	1.050	3/4	1	3000
	12	1/2 x 3								

PROJECT INFORMATION			APPROVAL STAMP	
Project:			Notes:	
Address:				
Contractor:				
Engineer:				
Date:				
Approved	Approved as Noted	Not Approved		