

Features

- Single lever handle is simple to use and makes adjusting water temperature easy
- Unique three-function sprayhead with Sweep® spray, Boost technology and aerated stream
- Professional-style faucet with an easy-to-clean coated hose and removable coil
- 1.5 gpm (5.7 lpm) maximum flow rate at 60 psi (4.14 bar)
- Sweep® spray creates a wide, forceful blade of water for superior cleaning
- Boost technology increases the flow rate by 30% with the press of a button
- MasterClean™ sprayface features an easy-to-clean surface that withstands mineral buildup and maximizes spray performance
- DockNetik® secure docking system locks sprayhead into place when not in use

Material

- Premium metal construction for durability and reliability
- Select KOHLER finishes feature ScratchShield® technology which withstands even the toughest daily use

Installation

- Flexible supply lines and quick-connect fittings simplify installation
- Installs with 1-, 2-, 3-, or 4- hole sink (escutcheon plate included)
- Longer shank works with countertops up to 2-1/2" (63.5 mm) thick and is easy to install
- Required for installation: Adjustable wrench, Phillips screwdriver



ADA **CSA B651**

Codes/Standards

ASME A112.18.1/CSA B125.1
 NSF/ANSI/CAN 61
 NSF/ANSI/CAN 372
 DOE - Energy Policy Act 1992
 California Energy Commission (CEC)
 ADA
 ICC/ANSI A117.1
 CSA B651

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	BL	Matte Black
	2MB	Vibrant® Brushed Moderne Brass
	LVS	Lacquer Vibrant Stainless

