



# KWH Mirka Ltd 66850 Jeppo

Date printed 30.10.2015, Revision 17.06.2015

Version 02. Supersedes version: 01

Page 1 / 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### **Polarshine Polishing Compound VF5**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1 Relevant uses

Polishing agent

### 1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

#### 1.3 Details of the supplier of the safety data sheet

Company KWH Mirka Ltd

Pensalavägen 210 66850 Jeppo / FINLAND Phone +358 20 760 2111 Fax +358 20 760 2290 Homepage www.mirka.com E-mail sales@mirka.com

Address enquiries to

Technical information sales@mirka.com
Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Company +358 20 760 2111 (8:00 - 16:00)

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

No classification.

#### 2.2 Label elements

The product does not require a hazard in accordance to OSHA Standard 29 CFR 1910.1200

(HCS 2012)

Hazard pictogramsnoneSignal wordnoneHazard statementsnonePrecautionary statementsnone

**Special labelling** Repeated exposure may cause skin dryness or cracking.

#### 2.3 Other hazards

**Human health dangers** Has a degreasing effect on the skin.





# KWH Mirka Ltd 66850 Jeppo

Date printed 30.10.2015, Revision 17.06.2015 Version 02. Supersedes version: 01 Page 2 / 9

## **SECTION 3: Composition / Information on ingredients**

#### Product-type:

The product is a mixture.

Range [%]	Substance			
10 - < 25	10 - < 25 Naphtha (petroleum), hydrotreated heavy			
	CAS: 64742-48-9, EINECS/ELINCS: 927-241-2, EU-INDEX: 649-327-00-6			
GHS/CLP: Asp. Tox. 1: H304 - Flam. Liq. 4: H227				
10 - < 25	10 - < 25 Aluminium oxide			
	CAS: 1344-28-1, EINECS/ELINCS: 215-691-6			
10 - < 25 White mineral oil (petroleum)				
	CAS: 8042-47-5, EINECS/ELINCS: 232-455-8			
	GHS/CLP: Asp. Tox. 1: H304			
< 2,5	Glycerol			
	CAS: 56-81-5, EINECS/ELINCS: 200-289-5			

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0,1%.

For full text of H-statements: see SECTION 16.

#### SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General information** Change soaked clothing.

**Inhalation** Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

**Skin contact** When in contact with the skin, clean with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

**Ingestion** Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Seek medical advice.

# 4.2 Most important symptoms and effects, both acute and delayed

No information available.

# 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to the doctor.

#### SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

be used

Full water jet

## 5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.

Risk of formation of toxic pyrolysis products.

Nitrogen oxides (NOx).

## **Polarshine Polishing Compound VF5**



# KWH Mirka Ltd 66850 Jeppo

Date printed 30.10.2015, Revision 17.06.2015

Version 02. Supersedes version: 01

Page 3 / 9

#### 5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

High risk of slipping due to leakage/spillage of product.

#### 6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater.

# 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.

#### 6.4 Reference to other sections

See SECTION 8+13

## SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Use only in well-ventilated areas.

Avoid spilling in enclosed areas.

During mechanical processing vacuuming at processing machines is necessary.

Do not eat, drink or smoke when using this product.

Wash hands before breaks and after work.

Use barrier skin cream.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

## 7.2 Conditions for safe storage, including any incompatibilities

Provide solvent-resistant and impermeable floor.

Prevent penetration into the ground. Keep only in original container.

Do not store together with oxidizing agents.

Protect from heat/overheating.

Keep container in a well-ventilated place.

Keep container tightly closed.

Recommended storage temperature: 15-25 °C.

## 7.3 Specific end use(s)

See product use, SECTION 1.2





# KWH Mirka Ltd 66850 Jeppo

Date printed 30.10.2015, Revision 17.06.2015

Version 02. Supersedes version: 01

Page 4 / 9

## SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (US)

	Range [%]	Substance
	10 - < 25	Aluminium oxide
		CAS: 1344-28-1, EINECS/ELINCS: 215-691-6
		Long-term exposure: 10 mg/m³, (E,N)

## 8.2 Exposure controls

Additional advice on system design 
Ensure adequate ventilation on workstation.

Eye protection safety glasses

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information. In full contact:

> 0,4 mm: Butyl rubber, >480 min (EN 374).

In splash contact

> 0,4 mm: Nitrile rubber, >480 min (EN 374).

**Skin protection** light protective clothing

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

**Respiratory protection** Breathing apparatus in the event of high concentrations.

Short term: filter apparatus, combination filter A-P1.

Thermal hazards not applicable

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

#### Polarshine Polishing Compound VF5



# **KWH Mirka Ltd** 66850 Jeppo

Form

Date printed 30.10.2015, Revision 17.06.2015

Version 02. Supersedes version: 01

Page 5 / 9

## SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

liquid viscous

Color grey

Odor characteristic Odour threshold not determined

pH-value 7-9

not determined pH-value [1%] Boiling point [°C] > 100 (> 212°F) Flash point [°C] > 100 (> 212 °F) Flammability [°C] not determined Lower explosion limit not determined Upper explosion limit not determined

**Oxidizing properties** no

Vapour pressure/gas pressure [kPa] not determined

Density [g/ml]

not applicable Bulk density [kg/m³] Solubility in water miscible Partition coefficient [n-octanol/water] not determined

Viscosity > 20,5 mm<sup>2</sup>/s (40°C/ 104°F)

Relative vapour density determined

in air

not determined

**Evaporation speed** not determined Melting point [°C] not determined Autoignition temperature [°C] not determined Decomposition temperature [°C] not determined

#### 9.2 Other information

No information available.

#### SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reactions known if used as directed.

## 10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

#### 10.3 Possibility of hazardous reactions

Reactions with oxidizing agents.

### 10.4 Conditions to avoid

Strong heating.

#### 10.5 Incompatible materials

Oxidizing agent

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.





# KWH Mirka Ltd 66850 Jeppo

Date printed 30.10.2015, Revision 17.06.2015 Version 02. Supersedes version: 01 Page 6 / 9

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

## **Acute toxicity**

Range [%]	Substance			
10 - < 25	10 - < 25 White mineral oil (petroleum), CAS: 8042-47-5			
LD50, dermal, Rabbit: > 2000 mg/kg.				
LD50, oral, Rat: > 5000 mg/kg.				
	LC50, inhalative, Rat: > 5 mg/l/4h.			
< 2,5	< 2,5 Glycerol, CAS: 56-81-5			
	LD50, oral, Rat: 12 600 mg/kg.			
10 - < 25 Naphtha (petroleum), hydrotreated heavy, CAS: 64742-48-9				
	LD50, dermal, Rabbit: > 3000 mg/kg bw (OECD 402).			
	LD50, oral, Rat: > 5000 mg/kg bw (OECD 401).			

Serious eye damage/irritation not determined
Skin corrosion/irritation not determined
Respiratory or skin sensitisation not determined
Specific target organ toxicity — not determined
single exposure

Specific target organ toxicity —

repeated exposure

not determined

 Mutagenicity
 not determined

 Reproduction toxicity
 not determined

 Carcinogenicity
 not determined

**General remarks** Frequent persistent contact with the skin can cause skin irritation.

Has a degreasing effect on the skin.

Toxicological data of complete product are not available.

No classification on the basis of the calculation procedure of the preparation directive.

## SECTION 12: Ecological information

### 12.1 Toxicity

Range [%]	Substance			
10 - < 25	10 - < 25 White mineral oil (petroleum), CAS: 8042-47-5			
LC50, (72h), Pseudokirchneriella subcapitata: >= 100 mg/l.				
LC50, (96h), Oncorhynchus mykiss: > 100 mg/l.				
< 2,5	< 2,5 Glycerol, CAS: 56-81-5			
LC50, (96h), fish: > 1000 mg/l.				
10 - < 25 Naphtha (petroleum), hydrotreated heavy, CAS: 64742-48-9				
EL0, (72h), Pseudokirchneriella subcapitata: 1000 mg/l (Lit.).				
EL0, (48h), Daphnia magna: 1000 mg/l (Lit.).				
LL0, (96h), Oncorhynchus mykiss: 1000 mg/l (Lit.).				

#### 12.2 Persistence and degradability

Behaviour in environment not determined

compartments

Behaviour in sewage plant not determined Biological degradability not determined

#### 12.3 Bioaccumulative potential

No information available.





# **KWH Mirka Ltd** 66850 Jeppo

Date printed 30.10.2015, Revision 17.06.2015

Version 02. Supersedes version: 01

Page 7 / 9

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

No information available.

#### 12.6 Other adverse effects

Ecological data of complete product are not available. Do not discharge product unmonitored into the environment.

#### SECTION 13: Disposal considerations

## 13.1 Waste treatment methods

Product Dispose of as hazardous waste.

Contaminated packaging Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

RCRA Hazard Class (40CFR 261) Waste must be disposed of in accordance with federal, state and local environmental control

regulations. Consult your local or regional authorities.

# SECTION 14: Transport

#### 14.1 UN number

See SECTION 14.2 in accordance with UN shipping name

### 14.2 UN proper shipping name

Transport by land according to

NO DANGEROUS GOODS

ADR/RID

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

**IMDG** 

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS" **DOT Road Shipment Information (49 CFR)** NOT CLASSIFIED AS "DANGEROUS GOODS"

## 14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

# 14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name

## 14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name





## KWH Mirka Ltd 66850 Jeppo

Date printed 30.10.2015, Revision 17.06.2015

Version 02. Supersedes version: 01

Page 8 / 9

#### 14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

#### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

No information available.

## SECTION 15: Regulatory information

#### **US Regulations**

National regulations 29 CFR 1910.1200-HCS 2012, OSHA-PEL, ACGIH-TLV, NTP, IARC, SARA Title III, NFPA,

TSCA, California - Prop. 65

SARA, 302 This product is not classified as hazardous under SARA 302.
 SARA, 311 This product is not classified as hazardous under SARA 311.

- SARA, 313 This product contain one ingredient regulated under this list(40 CFR part 372.65): Aluminum

oxide (fume or dust) (CAS 1344-28-1).

- CA Proposition 65 No chemical substances in this material are named on the California P65 list.

- TSCA All chemical substances in this material are included on or exempted from listing on the

TSCA Inventory.

- FDA not determined

American Conference of Governmental

Industrial Hygienists - ACGIH

International Agency for Research on

**Cancer IARC** 

National Toxicology Program - NTP

HAP-VOC

Ingredients not listed as carcinogens.

Ingredients not listed as carcinogens.

This product is named NTP - National Toxicology Program (contains glycerol).

12,4%

Transport-regulations DOT-Classification, ADR (2015); IMDG-Code (2015, 37. Amdt.); IATA-DGR (2015).

### **SECTION 16: Other information**

#### 16.1 Hazard statements (SECTION 3)

H319 Causes serious eye irritation. H318 Causes serious eye damage. H302 Harmful if swallowed. H227 Combustible Liquid.

H304 May be fatal if swallowed and enters airways.





## KWH Mirka Ltd 66850 Jeppo

Date printed 30.10.2015, Revision 17.06.2015

Version 02. Supersedes version: 01

Page 9 / 9

#### 16.2 Abbreviations and acronyms:

ACGIH = American Conference of Governmental Industrial Hygienists;

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route:

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses;

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure;

CAS = Chemical Abstracts Service;

CERCLA = Comprehensive Environmental Response, Compensation and Liability Act;

CFR = Code of Federal Regulations;

CPR = Controlled Products Regulations;

DMEL = Derived Minimum Effect Level;

DNEL = Derived No Effect Level;

DOT = Department of Transportation;

EC50 = Median effective concentration;

EPA = Environmental Protection Agency;

GHS = Globally Harmonized System of Classification and Labelling of Chemicals;

IATA = International Air Transport Association;

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk;

IC50 = Inhibition concentration, 50%;

IMDG = International Maritime Code for Dangerous Goods;

IARC = International Agency of Research on Cancer;

IATA = International Air Transport Association;

TSCA = Toxic Substance Control Act;

HMIS = Hazardous Materials Identification System;

NFPA = National Fire Protection Association;

NIOSH = National Institute for Occupational Safety and Health;

OSHA = Occupational Safety and Health Administration;

LC50 = Lethal concentration, 50%;

LD50 = Median lethal dose, 50%;

MARPOL = International Convention for the Prevention of Marine Pollution from Ships;

PBT = Persistent, Bioaccumulative and Toxic substance;

PNEC = Predicted No-Effect Concentration;

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals;

SARA = Superfund Amendments and Reauthorization Act;

TLV®/TWA = Threshold limit value – time-weighted average;

TLV®STEL = Threshold limit value – short-time exposure limit;

VOC = Volatile Organic Compounds;

vPvB = very Persistent and very Bioaccumulative;

#### 16.3 Ratings

## **HMIS Ratings**

Timio Rauligs					
HEALTH	1	1 - Slight Hazard			
FLAMMABILITY	1	1 - Slight Hazard			
REACTIVITY	0	0 - Minimal Hazard			
PERSONAL PROTECTION	Х	X - Personal protection rating to be supplied by user depending on use conditions			

## NFPA Ratings



TOP, FLAMMABILITY: 1 - Slight Hazard

LEFT, HEALTH: 1 - Slight Hazard RIGHT, REACTIVITY: 0 - Minimal Hazard

BOTTOM, SPECIAL NOTICE: -