

**18V LXT® LITHIUM-ION BRUSHLESS
CORDLESS 4-1/2" / 5" PADDLE
SWITCH X-LOCK ANGLE GRINDER,
WITH AFT®, TOOL ONLY**



**3
YEAR
WARRANTY
LITHIUM-ION
TOOL & BATTERY**

PRODUCT HIGHLIGHTS



POWER
Brushless Motor eliminates carbon brushes, enabling the motor to run cooler and more efficiently



CONTROL
AFT® turns the motor off if rotation of the wheel is suddenly forced to stop



INNOVATION
X-LOCK quick change system allows for easy tool-free wheel changes



CONVENIENCE
3-stage L.E.D. gauge indicates battery charge level

RELATED PRODUCTS

1. X-LOCK 5" x 1/4" x 7/8" Metal & Stainless Grinding Wheel, 36 Grit (E-00468)
2. X-LOCK 5" x .045" x 7/8" Metal & Stainless Thin Cut-Off Wheel, 60 Grit (E-00474)
3. X-LOCK 5" Segmented Diamond Blade (E-07238)
4. LXT® and LXT® X2 (36V) Portable Backpack Power Supply (PDC01)
5. 18V LXT® Brushless 4-1/2" / 5" X-LOCK Angle Grinder, with AFT® (XAG25Z)



**NEW TOOL OVERVIEW
XAG26Z**

LXT® BRUSHLESS

FEATURES

- Electric Brake stops the grinding or cut-off wheel in 2 seconds or less for maximum productivity
- Automatic Speed Change™ technology adjusts speed and torque during operation for optimum performance
- Soft start suppresses start-up reaction for smooth start-ups and longer gear life
- Anti-restart protection engineered to prevent motor start up when battery is inserted with switch in the on position
- No lock-on power switch; Features a two stage power lock-off switch to start the grinder

SPECIFICATIONS

Battery	18V LXT® Lithium-Ion
Wheel Diameter	5"
No Load Speed	8,500 RPM
Spindle Type	X-LOCK
Lock-On Switch	No
Lock-Off Switch	Yes
Switch Type	Body grip/paddle
Electric Brake	Yes
Variable speed dial	No
Overall Length	14-3/4"
Net Weight (with battery)	5.99 lbs.
Shipping Weight	7.72 lbs.
UPC Code	088381-728874
Bind-Up Control	Yes

STANDARD EQUIPMENT

- Side Handle (158237-4)
- X-LOCK 5" X 1/4" X 7/8" Metal & Stainless Grinding Wheel, 36 Grit (E-00468)
- X-LOCK 5" X .045" X 7/8" Metal & Stainless Thin Cut-Off Wheel, 60 Grit (E-00474)
- 5" Tool-less Wheel Guard (140T26-1)
- 5" Tool-less Cut-Off Guard (140U29-1)