

Stainless Steel PTFE Thread Tape



Merit Part #	Container Size	Sleeve Qty	Sleeves/Case Qty	List Price/Roll
SSNCTAPE-08	1/2" x 260"	10 Rolls	4 Sleeves/40 Rolls	\$10.00
SSNCTAPE-12	3/4" x 260"	10 Rolls	4 Sleeves/40 Rolls	\$13.50

General Product Information: Designed for use in difficult service conditions associated with stainless steel, aluminum & brass threaded connections. Helps prevent thread seizing and galling. UL® Listed thread sealant 561R. Meets Mill Spec MIL-T-27730A. *NOT FOR OXYGEN.*

Product Features: Nickel coated. Only requires 2 wraps to achieve seal. Fittings may be disassembled and reinstalled without additional tape.



Density Type	HIGH	Elongation (%)	75
Thickness (mils)	4.3	Testing Lab.	UL561R
Tensile (min psi)	1000	Temp. Range (°F)	-450 to +550
MIL SPEC	T-2773	Toxicity	Non-Toxic
MIL SPEC	27730A	Shelf Life	Indefinite
Density (g/cm3)	1.25 - 1.55	Pressure Range (psi)	Up to 10,000

CONTACT A MERIT ASSOCIATE TODAY!

CLEVELAND HEADQUARTERS

One Merit Drive/PO Box 43127
Cleveland, OH 44143
TEL: 800.726.9800
FAX: 855.MBFAXIT (623.2948)
EMAIL: mbsales@meritbrass.com

DALLAS DISTRIBUTION CENTER

10614 King William Drive
Dallas, TX 75220
TEL: 877.259.2591
FAX: 877.259.2596
EMAIL: mbsalesTX@meritbrass.com

SPARKS DISTRIBUTION CENTER

200 Vista Blvd., Suite #106
Sparks, NV 89434
TEL: 877.711.RENO (7366)
FAX: 877.376.0093
EMAIL: mbsalesNV@meritbrass.com

BIRMINGHAM DISTRIBUTION CENTER

220 Oxmoor Court
Birmingham, AL 35209
TEL: 855.912.0409
FAX: 866.668.9168
EMAIL: mbsalesAL@meritbrass.com

MERIT BRASS CLEVELAND HEADQUARTERS HAS AN ISO 9001:2015 REGISTERED QUALITY MANAGEMENT SYSTEM

WWW.MERITBRASS.COM • WWW.MBWEBXPRESS.COM

