

HOSE BIBB • 125 PSI

BRASS



- Meets NSF approved low lead standards
- 3/4" hose thread outlet
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Available in Handy Carton (HC) bin box packaging

Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
103-003 ◇	030039	1/2"	12/72	27
103-004	030046	3/4"	12/72	31
103-003HC ◇	030039	1/2"	25/NA	15
103-004HC	030046	3/4"	25/NA	17

◇ = 1/2" Male external threads and 1/2" internal solder connection

HOSE BIBB • QUARTER TURN • 125 PSI

FORGED BRASS



- Easy quarter turn operation
- Maximum 125 PSI working pressure
- Meets NSF approved low lead standards
- CSA Certified – Canadian Standards Association
- UPC approved, complies to ASME A112.18.1 standards
- Chrome plated brass ball
- P.T.F.E. seats
- Rust resistant handle
- 3/4" hose thread outlet
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Solder ends comply with ANSI-16.18
- Patent no. D472962 valve handle
- Patent no. D5166785 valve body

Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
103-053HC ◇	000391	1/2"	25/NA	10
103-054HC §	000407	3/4"	25/NA	12

◇ = 1/2" Male external threads and 1/2" internal solder connection

§ = Tapped 1/2" female thread

HOSE BIBB • BALL VALVE DESIGN • 200 PSI

FORGED BRASS



- Rated for 200 PSI WOG
- Quarter turn operation
- Chrome plated brass ball
- 3/4" hose thread outlet
- Large flow rate
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Available in Handy Carton (HC) bin box packaging

Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
103-023 ◇	030237	1/2"	10/100	43
103-024	030244	3/4"	10/100	56
103-023HC ◇	030237	1/2"	20/NA	8
103-024HC	030244	3/4"	20/NA	11

◇ = 1/2" Male external threads and 1/2" internal solder connection

