


NIBCO

 1516 Middlebury Street
 Elkhart, IN 46516-4740

Phone: 574.295.3000 • **Fax:** 800.234.0557

Email: info@nibco.com • **Web site:** www.nibco.com
Material Number NLK680K, GD-4765 - Butterfly Valve - Ductile Iron, Grooved, 300 PSI, Handle

The NIBCO® ductile iron butterfly valve provides ease of operation with quarter-turn (90 degrees) open to close. The valve features an EPDM encapsulated ductile iron disc. The internal stem/disc splined drive design eliminates the need for pins or bolts that may create leak paths or turbulence in the waterway. An extended neck allows for insulation up to 2 inches. Please refer to NIBCO technical data sheets, chemical resistance guides and catalogs for engineering and installation information.

[+ more](#)

Specifications

UPC Code	039923767271
Type	Butterfly Valve
Connection Type	Grooved
Seat Material	Polymid
Valve Size	6
Material	DI Ductile Iron
Disc Material	EPDM Coated Ductile Iron
Valve Operator	Lever-Lock Handle
Description	GD47653 6 GRV BFV L/LK HNDL DUCT IRON
eClass Classification	Ductile Iron Butterfly Valves
All Type of Item	Valve
Turns/Operation	Quarter-Turn
Weight	27.359 lb