



# SAFETY DATA SHEET

Revision Date 14-May-2020

Version 11

## 1. IDENTIFICATION

### Product identifier

**Product Name** 81844 REARVIEW MIRROR ADHESIVE KIT PART 2

### Other means of identification

**Product Code** PTX394319X

### Recommended use of the chemical and restrictions on use

**Recommended Use** Activator

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

ITW Permatex  
6875 Parkland Blvd.  
Solon, Ohio 44139 USA  
Telephone: 1-87-Permatex  
(866) 732-9502

#### 24-hour emergency phone number

Chem-Tel: 800-255-3924  
International Emergency:  
00+1+ 813-248-0585  
Contract Number: MIS0003453

#### May Also Be Distributed by:

ITW Permatex Canada  
101-2360 Bristol Circle  
Oakville, ON Canada L6H 6M5  
Telephone: (800) 924-6994

**E-mail address:** mail@permatex.com

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

### Label elements

#### **Emergency Overview**

#### Signal word

**Danger**

Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
May cause respiratory irritation  
May cause drowsiness or dizziness

Highly flammable liquid and vapor



**Appearance** Apple

**Physical state** Liquid

**Odor** Alcoholic

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Wear eye/face protection  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ ventilating/ lighting/ equipment  
Use non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam to extinguish.

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

Not applicable.

Unknown acute toxicity

2.2 % of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%
2-PROPANOL	67-63-0	60 - 100
MINERAL SPIRITS	8052-41-3	0.1 - 1

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
<b>Eye contact</b>	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
<b>Skin contact</b>	Wash skin with soap and water.
<b>Inhalation</b>	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
<b>Ingestion</b>	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

##### Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

##### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Keep victim warm and quiet. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam, Water spray, fog or alcohol-resistant foam

##### Unsuitable extinguishing media

Do not use straight streams CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient Do not use dry chemical extinguishers to control fires involving nitromethane or nitroethane

##### Specific hazards arising from the chemical

Vapors may travel to source of ignition and flash back. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard.

##### Explosion data

**Sensitivity to Mechanical Impact** None.  
**Sensitivity to Static Discharge** None.

##### Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

**Other Information** Water spray may reduce vapor; but may not prevent ignition in closed spaces.

**Environmental precautions**

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas.

**Methods and material for containment and cleaning up**

**Methods for containment** A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

**Methods for cleaning up** Use clean non-sparking tools to collect absorbed material.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong oxidizing agents

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-PROPANOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
MINERAL SPIRITS 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>

*NIOSH IDLH Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

<b>Skin and body protection</b>	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
<b>Respiratory protection</b>	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
<b>General Hygiene Considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid
<b>Appearance</b>	Apple
<b>Odor</b>	Alcoholic
<b>Odor threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
<b>Melting point / freezing point</b>	No information available	
<b>Boiling point / boiling range</b>	82 °C / 180 °F	
<b>Flash point</b>	12 °C / 54 °F	Tag Closed Cup
<b>Evaporation rate</b>	7.7	Butyl acetate = 1
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	12.0%	
<b>Lower flammability limit:</b>	2.0%	
<b>Vapor pressure</b>	32 mm Hg @ 68°F	
<b>Vapor density</b>	2.1	Air = 1
<b>Relative density</b>	0.79 @ 77°F	
<b>Water solubility</b>	Soluble in water	
<b>Solubility(ies)</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>Density</b>	No information available
<b>Bulk density</b>	No information available
<b>SADT (self-accelerating decomposition temperature)</b>	No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**  
No information available

**Chemical stability**  
Stable under normal conditions

**Possibility of Hazardous Reactions**  
None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents

**Hazardous Decomposition Products**

Carbon oxides

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Inhalation** May cause irritation of respiratory tract.  
**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.  
**Skin contact** May cause skin irritation and/or dermatitis.  
**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-PROPANOL 67-63-0	5050 mg/kg	12800 mg/kg	= 72600 mg/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** No information available.  
**Target Organ Effects** Central nervous system, Eyes, kidney, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 5233 mg/kg  
**ATEmix (dermal)** 13264 mg/kg  
**ATEmix (inhalation-dust/mist)** 75.2 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

2.2 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility**

No information available.

Chemical Name	Partition coefficient
2-PROPANOL 67-63-0	0.05

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
2-PROPANOL 67-63-0	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN/ID No** 1219  
**Proper shipping name** (Isopropyl alcohol), Limited Quantity (LQ)  
**Hazard Class** 3  
**Packing Group** II  
**Emergency Response Guide Number** 129

**IATA**

**UN/ID No** ID 8000  
**Proper shipping name** Consumer commodity  
**Hazard Class** 9  
**ERG Code** 9L

**IMDG**

**UN/ID No** 1219  
**Proper shipping name** (Isopropyl alcohol), Limited Quantity (LQ)  
**Hazard Class** 3  
**Packing Group** II  
**EmS-No** F-E, S-D

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL/NDSL** Complies  
**EINECS/ELINCS** Complies  
**ENCS** Complies  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Complies  
**AICS** Not Listed

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

<b>Chemical Name</b>	<b>SARA 313 - Threshold Values %</b>
2-PROPANOL - 67-63-0	1.0

**SARA 311/312 Hazard Categories**

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

<b>Chemical Name</b>	<b>New Jersey</b>	<b>Massachusetts</b>	<b>Pennsylvania</b>
2-PROPANOL 67-63-0	X	X	X
MINERAL SPIRITS 8052-41-3	X	X	X
ORGANO-COPPER COMPOUND 22221-10-9	X	-	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**WHMIS Hazard Class**

B2 - Flammable liquid, D2B - Toxic materials

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b><u>NFPA</u></b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	-
<b><u>HMIS</u></b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Physical hazards</b> 0	<b>Personal protection</b> B

NFPA (National Fire Protection Association)  
 HMIS (Hazardous Material Information System)

**Revision Date** 14-May-2020

**Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled.

However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**