

STEALTH unit



Features and Benefits

- Inverse-Flow® Technology with 3½" filter depth
- Quick disconnect clamp ring design
- 1.0 micron final filtration
- Spin-on/spin-off element
- Equipped with brass petcock manual drain
- Rated for 60 SCFM
- Removes dirt, water and oil vapor
- Non-corrosive internal metal
- Pressure regulator/gauge standard
- Heavy duty metal bowl construction
- Cleaner compressed air with no contaminants to your applications
- Simple design requires no tools for maintenance
- Easy service of elements
- Extremely long element life
- 99.5% effective at water removal
- ½" BV-051 ball valve

Specifications

- Replacement Element: 6960-1
- Max. Air Pressure: 150 PSIG
- Max. Operating Temp: 125 ° F
- Max. Flow: to 60 SCFM

Applications

- Air Tools, Sand Blasting, Sanding Impacts, Buffing
- Ideal for Mechanical Section of Shop

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTIPBE



@rti_pbe



Removes:  

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"

STEALTH 6900B
STEALTH 6950B
STEALTH 6952B

No Regulator
Regulator w/ Gauge
Regulator w/ Gauge, (2) 1/4" Outlets

3/8"

STEALTH 3050B
STEALTH 3052B

Regulator w/ Gauge
Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6950-1

Removes:   

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"

STEALTH 6910B
STEALTH 6960B
STEALTH 6962B

No Regulator
Regulator w/ Gauge
Regulator w/ Gauge, (2) 1/4" Outlets

3/8"

STEALTH 3060B
STEALTH 3062B

Regulator w/ Gauge
Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6960-1

Removes:  

0.01 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"

STEALTH 7000B
STEALTH 7800B

Regulator w/ Gauge
No Regulator

1/2"

STEALTH 1000B
STEALTH 1500B

Regulator w/ Gauge
Regulator w/ Gauge and manifold

3/8"

STEALTH 7030B

Regulator w/ Gauge

Replacement Element: 3C-060

Removes:   

0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain
2nd Stage: Brass Manual Petcock Drain



3/8"

STEALTH 6060B

Regulator w/ Gauge

1st Stage Replacement Element: 6960-1
2nd Stage Replacement Element: 3C-060

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key:  Water  Dirt  Oil

CA PROPOSITION 65 WARNING



WARNING: Cancer and
Reproductive Harm

www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

