

## SIDEWINDER® FOR STEEL - Horizontal Application



Application	Product Features
<p><b>NO PRE-DRILLING REQUIRED</b></p>	<ul style="list-style-type: none"> <li>Made with TekS® self-drilling fasteners - no pre-drilling required.</li> <li>Installs into steel range from 20 gauge – 1/2" thicknesses.</li> <li>A standard screwgun with a depth sensitive nosepiece should be used to install TekS. For optimal fastener performance, the screwgun should be a minimum of 6 amps and have an RPM range of 0-2500.</li> <li>Saves time from traditional methods.</li> <li>Reduces installation costs.</li> <li>Quick to install using the Sammys Nut Driver with an 18V cordless drill/driver.</li> <li>Assembled in the U.S.A.</li> </ul> <p>View our installation videos! </p>

Approvals	Rod Size	Part Number	Model	Screw Descriptions	Ultimate Shear (lbs)	UL Test Load (lbs)	FM Test Load (lbs)	Min Thickness	Max Thickness	Box Qty	Case Qty
<b>HORIZONTAL MOUNT</b>											
	3/8"	8050957	SWD 10	1/4-14 x 1" TEKS 3	1477 (16 ga.)			.060"-16 ga	3/16"	25	125
	3/8"	8052957	SWD 20	1/4-14 x 2" TEKS 3	1477 (16 ga.)			.060"-16 ga	3/16"	25	125
	3/8"	8055957	SWDR 1 *	1/4-20 x 1" TEKS 3	1900 (20 ga.)	1500	1475	.036"-20 ga	3/16"	25	125
	3/8"	8054957	SWDR 1-1/2 *	12-24 x 1-1/2" TEKS 5	2375 (3/16")	1500	1475	.188"-3/16"	1/2"	25	125
	3/8"	8056957	SWDR 516 *	5/16-18 x 1-1/4" TEKS 3	2480 (20 ga.)	1500	1475	.036"-20 ga	3/16"	25	125

\*Includes retaining nut



#14 SW Red Nut Driver  
Part # 8114910

## SAMMYS SWIVEL HEAD™ FOR STEEL - Swivel Application



Application	Product Features
	<ul style="list-style-type: none"> <li>Eliminates distortion of threaded rod in sloped roof applications.</li> <li>Accommodates 3-1/2 x 12 pitch.</li> <li>Installs into angled z-purlin; allows threaded rod to hang plumb.</li> <li>Allows 17° deflection from vertical.</li> <li>Assembled in the U.S.A.</li> </ul> <p>View our installation videos! </p>

Approvals	Rod Size	Part Number	Model	Screw Descriptions	Ultimate Pullout (lbs)	UL Test Load (lbs)	FM Test Load (lbs)	Min Thick	Max Thick	Box Qty	Case Qty
<b>SWIVEL MOUNT</b>											
	3/8"	8137957	SH-DSTR 1*	1/4-20 X 1" TEKS 3	3220 (3/16")	1500	1475	.035"	3/16"	25	125
	3/8"	8268957	SH-TEK 50	12-24 x 1-5/8" TEKS 5	2368 (1/2" steel Vertical) 1306 (45° off Vertical) 2281 (3/16" HSS) 1585 (3/16" HSS 45° off Vertical)	1500 (Vertical) 850 (45° off Vertical)	4" 2-1/2"	3/16"	1/2"	25	125

\*Does not comply with ROHS requirements / Includes retaining nut



#14 Black Nut Driver  
Part # 8113910



#14 SH Orange Nut Driver  
Part # 8273910