



SharkBite® Check Valve

DESCRIPTION

The SharkBite® Check Valve is a general purpose spring check valve that prevents the reverse flow of water. The check valve can be installed horizontally and vertically and can be connected in seconds to copper tubing, and CTS CPVC, PEX and PE-RT. A water flow of 2 PSI is required to achieve cracking pressure (opening of the check).

FEATURES AND BENEFITS

Instant push-to-connect connections for increase ease of use:
No soldering, clamps, unions, or glue required.

Designed for vertical and horizontal installation:
Flexible installation options in new or existing plumbing systems.



U2008-0000LF


SPECIFICATION DATA

Performance:

Maximum pressure 150 psi
 Maximum temperature 200°F (93°C) (water)
 Service Water

SharkBite Materials:

Body DZR Lead Free Brass
 O-ring..... EPDM
 Cartridge & demount ring Acetal
 Protection ring Nylon
 Grab ring Stainless steel
 Tube Support Liner..... Veradel



Dimensions	A	B
1/2" (U2008-0000LF)	0.50"	2.66"
3/4" (U2016-0000LF)	0.75"	3.26"
1" (U2020-0000LF)	1.00"	3.88"

CONNECTIONS

SharkBite 1/2" through 1"

CERTIFICATIONS

The SharkBite Check Valve 1/2", 3/4" and 1" are certified to ASSE 1061, NSF/ANSI 61, NSF 372, NSF/ANSI 14 and listed by IAPMO.

