

Exterior Screws

Strong-Drive® SD CONNECTOR Screw

Simpson Strong-Tie® Connectors

The Strong-Drive SD Connector screw is specifically designed to replace nails in certain Simpson Strong-Tie connectors, and is the only screw approved for that application. The load-rated SD screw has been tested and approved for use in many popular Simpson Strong-Tie products. In certain applications screws are easier and more convenient to install than nails, and the single-fastener load values achieved by the SD screw exceed those of typical 10d common or 16d common nails. In addition, the galvanized coating makes the SD screw ideal for both interior and most exterior conditions.

Features:


- Specifically designed to replace nails in certain Simpson Strong-Tie connectors, and is the only screw approved for that application. The #9 and #10 SD screws replace 10d and 16d nails, respectively.
- Tested and approved for use in many of our most popular connectors for both interior and exterior applications.
- Ideal for use in connector applications where more control is desired or using a hammer is inconvenient.
- ¼" hex head with 0.37"-dia. integrated washer is stamped with the Simpson Strong-Tie "S" sign and the fastener size for easy identification after installation.
- Shank is specifically designed to match the fastener holes in Simpson Strong-Tie connectors.
- Optimized heat treating for ductility and strength.
- The single-fastener load capacity of the SD9 exceeds the capacity of a 10d common nail, while the single-fastener load capacity of the SD10 exceeds that of the 16d common nail.
- Hex driver bit included.

Mechanically-galvanized coating meets ASTM B695 Class 55, is recommended for use with certain preservative-treated woods and recognized as an alternate to hot-dip galvanized in ESR-3046; it is compliant with the 2015 and 2018 International Residential Code®.

Codes/Standards: ICC-ES ESR-3046, State of Florida FL9589

For Technical Data and Loads, see Technical Supplement

Mechanically-Galvanized Coating – Class 55



Size	Length (in.)	Retail Pack			Contractor Pack			Mini Bulk	
		Fasteners Per Pack	Packs Per Master Carton	Model No.	Fasteners Per Pack	Packs Per Master Carton	Model No.	Fasteners Per Pack	Model No.
#9	1½	100	10	SD9112R100	500	3	SD9112R500	3,000	SD9112MB
#9	2½	100	6	SD9212R100-R	500	2	SD9212R500	2,000	SD9212MB
#10	1½	100	10	SD10112R100	500	3	SD10112R500	3,000	SD10112MB
#10	2½	100	6	SD10212R100-R	500	2	SD10212R500	2,000	SD10212MB