

ADJUSTABLE ON-GRADE FLOOR DRAIN

» 832 SERIES

FinishLine™

SPECIFICATION

Sioux Chief 832 series FinishLine™ adjustable floor drain shall be used where necessary in drainage systems. Floor drain shall allow adjustment before and AFTER the concrete pour. Strainer shall meet applicable load requirements for intended use. Trap primer port shall be threaded 1/2" FIP for optional connection. Designed in accordance with ASME A112.6.3-2001.

MATERIALS

Ring/strainer: Nickel-bronze, stainless steel
Coring Plug: High-impact polymer
Head Adapter/Coring Sleeve: Gray ABS
Base Adapter: ABS, PVC

STRAINER LOAD RATING

Nickel-bronze: 1,500 lbs. (Light duty, heel-proof)
Stainless Steel: 2,000 lbs. (Light duty, heel-proof)

STRAINER FREE AREA

Round: 8.5 in²
Square: 12.75 in²

DIMENSIONS


A: Connection*	2 × 3", 3 × 4" Sch. 40 hub
B: Ring/strainer diameter	
Round	5½"
Square	5⅞"
C: Base adapter height	3½"
D: Pre-pour height	4⅝" – 5½"
E: After-pour height	
Round	0" – 1"
Square	⅝" – 1"
F: Trap primer port	½" FIP thread, for knockout connection

*Fits over 2" and inside 3" and inside 4" Sch. 40 pipe

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



832-25PNR



Create Item Number

832-ABC

e.g. 832-25PNRV: FinishLine™ floor drain with 2" PVC hub connection and vandal-resistant, nickel-bronze strainer

CONNECTION A

25A = 2×3" ABS Sch. 40 hub
25P = 2×3" PVC Sch. 40 hub
35A = 3×4" ABS Sch. 40 hub
35P = 3×4" PVC Sch. 40 hub

RING/STRAINER B

NR = Round nickel-bronze
NQ = Square nickel-bronze
SR = Round stainless steel
SQ = Square stainless steel

INSTALLED OPTIONS C

V = Vandal-resistant strainer screws
B = Complies with Buy American Act¹
E = 1¼" extended strainer rim

¹ Available for round nickel-bronze strainers only

Available separately:

- 832-S3: Leveling shim kit
- 832-EX3: Ductile extension adapter
- 832-W: Flexible locating bristle kit
- 863-FN: Round nickel-bronze condensate funnel
- 863-FA: Round aluminum condensate funnel