

OPTIONS**Power Type**

Battery

Body Type

Low

Mounting

Deck

Power Supply

Battery (BAT)

Battery + Turbine (TUR)

Sensor Type

Infrared (IR)

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM)

1.5 gpm (5.7 Lpm) (1.5GPM)

0.35 gpm (1.3 Lpm) (0.35GPM)

2.2 gpm (8.3 Lpm) (2.2GPM)

Spray Type

Multi-Laminar (MLM)

Laminar (LAM)

Trim Plate

4" (102mm) (4)

8" (203mm) (8)

Finish

Polished Chrome (CP)

Control Access

Below Deck

Mixer

Back-Check Tee (TEE)

Below Deck Manual Mixing Valve (BDM)

Below Deck Thermostatic Mixing Valve (BDT)

Above Deck Mixer (ADM)

Mixer Not Included

Compliances & Certifications

ADA Compliant

ASME A112.18.1 Compliant

EPD

HPD

Proposition 65

TAS

UPC Certified



Image for a standard EBF-615 shown

DESCRIPTION

Optima® Battery-Powered Deck-Mounted Low Body

FEATURES

- Commercial Grade Faucet
- ADA Compliant
- Cast Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- Wireless Settings Adjustment
- On-demand or Metered activation
- Hygienic Line Flush
- Water Usage and Battery Strength Reporting
- Self-adapting Sensor

SMART FAUCET ADDITIONAL OPTIONS

- 24VAC plug adapter, power harness assembly or box mount power supply
- Multi-unit gang adapter kit
- 110V or 230V/6VDC plug adapter
- Special PVD finishes available Brushed Stainless, Brushed Nickel, Polished Brass and Matte Black

DOWNLOADS

- [Optima Smart Faucet Below Deck Installation Instructions](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [ETF-610/EBF-615 Below Deck Repair and Maintenance Guide](#)
- [Trim Plate Guide](#)
- [Additional Downloads](#)

VIDEOS

UPC Low Lead Compliant
WELL Building Standard
cUPC Certified



Sloan Connect App®



Sloan Optima Below Deck Faucet

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.