

Mueller Streamline Co. Headquarters

150 Schilling Blvd Suite 201

Collierville, Tennessee 38017

United States

Details

Phone: 901 753 3200

Mueller Streamline Co. International

525 Okeechobee Blvd Suite 860 West Palm Beach, FL 33401 **United States**

Phone: 561 273 8300

ITEM # RP10146, ACR PRESS COUPLING W/STOP, P X P, 7/8" OD

Streamline® is the best known, most trusted name in the industry—with a nearly 100-year history of providing the best-in-class products you need to work more e ciently and productively. The ACR Press System is the latest example of the industry-leading innovation and commitment to customer needs that make Streamline® the standard for excellence.



Details | Specifications | Dimensions | Packaging

Approved for use with Type ACR, L, K hard and soft copper tube.

Indistry-leading Two Ring Advanced Press (T.R.A.P.) Technology

DuoSeal™ Ring Design provides superior sealing and joint strength with 200% more surface contact.

TrapZone™ Leak Barrier innovative vacuum-zone further ensures leak protection.

Force360™ Press Contour provides more uniform joint compression and sealing performance.

Tri-Lock™ Press Profile creates superior joint strength and pressure handling capabilities.

Compatible with R410A and other commonly used refrigerant gases and oils.

Propietary Streamline® ACR Press Jaws available from Milwaukee® Tool.

Compatible with leading full-size press tools on the market.

Includes a 10-year limited warranty against defects in material and workmanship.

Specifications	
----------------	--

Weight	0.19 lb
Material	COPPER
Operating Temperature [Min]	-40 °F
Operating Temperature [Max]	250 °F
Operating Pressure [Max]	700 psi
End Type	ACR Press
End Size	7/8 in
Second End Type	ACR Press
Second End Size	7/8 in

Dimensions -

Overall Length	2.80 in	
Overall Height	1.26 in	
Overall Width	1.26 in	
Dimension X	0.08 in	

Packaging		-
Qty Pcs / Bag	2	
Master Qty Pcs / Box	90	
UPC Code	685768444114	