

# Technical Data Sheet

Transtar's Aqua SCAT 2 Waterborne Degreaser is a specially formulated, water-based degreaser that can be used on all plastics, metal and pre-painted parts. Its unique mix of alcohol, surfactants and water make it ideal for cleaning and degreasing plastics prior to painting or priming. Aqua SCAT 2 also reduces the amount of dust contact by neutralizing static charge. Compliant across North America.

## SUITABLE SUBSTRATES

| Substrate                        |   | Substrate                           |   | Substrate                                    |   |
|----------------------------------|---|-------------------------------------|---|--|---|
| Bare Steel                       | ✓ | Raw Plastic - Rigid (SMC, BMC) +    | ✓ | Primer - Self-Etching                        | ✓ |
| Bare Galvanized                  | ✓ | Raw Plastic - Flexible (ABD, PPO) + | ✓ | Primer - 1K                                  | ✓ |
| Bare Aluminum                    | ✓ | Raw Plastic - Soft (PUR) +          | ✓ | Primer - 2K                                  | ✓ |
| OEM E-Coat**                     | ✓ | Plastic Part - Primed ++            | ✓ | OEM Finish & Old Paint Work - Reversible     | ✓ |
| Fiberglass/SMC Unbroken Gel Coat | ✓ | Body Filler                         | ✓ | OEM Finish & Old Paint Work - Non-Reversible | ✓ |

## MIXING



Mix Ratio: Ready to Spray

Pot Life: N/A

## SURFACE PREPARATION



Apply Aqua SCAT 2 to surface prior to grinding, sanding or painting to prevent contaminants from being worked into the substrate surface.

## APPLICATION



Ready to use. Spray or wipe on substrate. Wipe off with LINT-FREE cloth.

Note: Re-wiping (i.e. with tack cloth) after using Aqua SCAT 2 may increase static.

Aqua SCAT 2 can be used in your current multi-step process as a degreaser. It can also be used as a one-step process as an anti-static and degreaser.

## PRODUCT SPECIFICATIONS

|                                   |                     |
|-----------------------------------|---------------------|
| Color: Clear Liquid               | Shelf Life: 5 years |
| Size: Gallon (1391), Quart (1394) |                     |

## REGULATORY:

|                                       |                     |                              |      |
|---------------------------------------|---------------------|------------------------------|------|
| Category: Cleaner/Surface Preparation | 1391/1394           | Weight % of Exempt Compounds | 1.5  |
| VOC Actual                            | 0.21#/gal (25 g/l)  | Volume % of Exempt Compounds | 1.87 |
| VOC Regulatory                        | 5.01#/gal (600 g/l) | Density of Material #/gal    | 8.26 |
| Weight % of Volatiles                 | 99                  |                              |      |
| Weight % of Water                     | 95                  |                              |      |

## LIMITATIONS & PRECAUTIONS

- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.