



No. 20 Tee



No. 10 Elbow

1.0 PRODUCT DESCRIPTION

Available Sizes

- ¾ – 24"/DN20 – DN600

Pipe Material

- Carbon steel

Maximum Working Pressure

- Pressure ratings for Victaulic standard fittings conform to the ratings of Victaulic Style 77 couplings (refer to [publication 06.04](#) for more information).

Application

- Connects pipe, provides change in direction and adapts sizes or components
- Supplied with Victaulic Original Groove System (OGS) grooves
- Exclusively for use with Victaulic couplings, valves, accessories and pipe which feature ends formed with the Victaulic OGS groove profile

NOTES

- For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information.
- These fittings are not intended for use with Victaulic plain end couplings. Intended for use only in grooved piping systems. When connecting wafer or lug type butterfly valves directly to Victaulic fittings using Style 741 or Style 743 flange adapters, be sure to check disc clearance dimensions with I.D. dimension of fitting.

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.

2.0 CERTIFICATION/LISTINGS



EN 10311
CPR (EU)
No. 305/2011

BS EN 10311
CPR (UK)
2019 No. 465

NOTES

- When supplied as “hot dip galvanized” the following fittings are UL Classified in accordance with ANSI/NSF 61 and for use on cold +86°F/+30°C potable water service and ANSI/NSF 372: No. 10 90° Elbow, No. 11 45° Elbow, No. 12 22 ½° Elbow, No. 13 11 ¼° Elbow, No. 100 90° Long Radius Elbow, No. 110 45° Long Radius Elbow, No. 20 Tee, No. 25 Tee with Grooved Branch, No. 30 45° Lateral, No. 60 Cap, No. 50 Concentric Reducers, No. 51 Eccentric Reducers.
- The following Victaulic fittings are VdS approved: No.10 90° Elbow, No.11 45° Elbow, No.20 Tee and No.60 Cap.
- The following Victaulic fittings are LPCB approved: No.10 90° Elbow, No.11 45° Elbow, No.12 22 ½° Elbow, No.13 11 ¼° Elbow, No.30 45° Lateral, No.30-R Reducing Lateral, No.100 Long Radius Elbow, No.110 Long Radius Elbow, No.20 Tee, No.35 Cross, No.60 Cap, No.25 Reducing Tee, No.33 True Wye, No.50 Concentric Reducer, No.51 Eccentric Reducer and No.29M Tee with Threaded Branch.
- The following Victaulic fittings are FM approved: No.10 90° Elbow, No.11 45° Elbow, No.12 22 ½° Elbow, No.13 11 ¼° Elbow, No.30 45° Lateral, No.100 Long Radius Elbow, No.20 Tee, No.35 Cross, No.60 Cap, No.25 Reducing Tee and No.50 Concentric Reducer.
- Download [publication 10.01](#) for Fire Protection Certifications/Listings Reference Guide to view which sizes of the fittings listed above have active fire protection approvals.

3.0 SPECIFICATIONS – MATERIAL

Fitting: (specify choice)

Standard: Ductile iron conforming to ASTM A536, Grade 65-45-12.

Optional: Segmentally welded carbon steel, standard wall, conforming to ASTM A53, Type E or S, Gr. B

Nipples: (specify choice)

¾ – 6"/DN20 – DN150: Carbon steel, Schedule 40, conforming to ASTM A53, Type E or S, Gr. B

8 – 12"/DN200 – DN300: Carbon steel, standard wall, conforming to ASTM A53, Type E or S, Gr. B

Flanged Adapter Nipples: (specify choice)

Class 125 Flange: Cast iron conforming to ANSI B16.1

Class 150 Flange: Carbon steel conforming to ANSI B16.5, raised or flat face

Class 300 Flange: Carbon steel conforming to ANSI B16.5, raised or flat face

Fitting Coating: (specify choice)

Standard: Orange enamel

Optional: Hot dip galvanized and others. Some fittings supplied electroplated as standard – see product specifications

Flanged Adapter Nipple Coating: (specify choice)

Standard: None (Unfinished)



Optional: Orange enamel, hot dip galvanized and others

4.0 DIMENSIONS

Elbows

No. 10 90° Elbow

No. 11 45° Elbow



Size	No. 10 90° Elbow			No. 11 45° Elbow	
	Nominal inches DN	Actual Outside Diameter inches mm	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm
3/4 DN20	1.050 26.9	2.25 57	0.5 0.2	1.50 38	0.5 0.2
1 DN25	1.315 33.7	2.25 57	0.6 0.2	1.75 44	0.5 0.2
1 1/4 DN32	1.660 42.4	2.75 70	0.8 0.4	1.75 44	0.6 0.3
1 1/2 DN40	1.900 48.3	2.75 70	1.0 0.5	1.75 44	0.8 0.4
2 DN50	2.375 60.3	3.25 83	1.8 0.8	2.00 51	1.3 0.6
2 1/2	2.875 73.0	3.75 95	3.0 1.3	2.25 57	2.1 1.0
DN65	3.000 76.1	3.75 95	3.1 1.4	2.25 57	2.3 1.0
3 DN80	3.500 88.9	4.25 108	4.5 2.0	2.50 64	3.0 1.3
3 1/2 DN90	4.000 101.6	4.50 114	5.6 2.5	2.75 70	4.0 1.8
	4.250 108.0	5.00 127	6.2 2.8	3.00 76	4.6 2.1
4 DN100	4.500 114.3	5.00 127	6.8 3.1	3.00 76	5.2 2.4
4 1/2	5.000 127.0	5.00 127	8.6 3.9	3.13 79	5.9 2.7
	5.250 133.0	5.50 140	10.3 4.7	3.25 83	6.6 3.0
DN125	5.500 139.7	5.50 140	9.9 4.5	3.25 83	7.2 3.2
5	5.563 141.3	5.50 140	10.1 4.6	3.25 83	7.4 3.4
	6.000 152.4	6.50 (sw) 165	13.3 6.0	3.50 (sw) 89	9.5 4.3
	6.250 159.0	6.50 165	13.0 5.9	3.25 83	9.5 4.3
	6.500 165.1	6.50 165	15.5 7.0	3.50 89	9.7 4.4
6 DN150	6.625 168.3	6.50 165	15.3 6.9	3.50 89	10.2 4.6
200A	216.3	7.75 197	34.7 15.7	4.25 108	14.4 6.5

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(sw) = Carbon Steel Segmentally Welded

NOTE



- All fittings are ductile iron unless otherwise noted with an (sw).

4.0 DIMENSIONS (CONTINUED)

Elbows

No. 10 90° Elbow

No. 11 45° Elbow



Size	Actual Outside Diameter	No. 10 90° Elbow		No. 11 45° Elbow	
		C to E	Approx. Weight (Each)	C to E	Approx. Weight (Each)
Nominal inches DN	inches mm	inches mm	lb kg	inches mm	lb kg
8	8.625	7.75	27.5	4.25	18.6
DN200	219.1	197	12.5	108	8.4
250A	267.4	9.00	67.8	4.75	28.1
		229	30.7	121	12.7
10	10.750	9.00	50.0	4.75	37.5
DN250	273.0	229	22.7	121	17.0
300A	318.5	10.00	73.5	5.25	41.3
		254	33.3	133	18.7
12	12.750	10.00	79.3	5.25	45.0
DN300	323.9	254	36.0	133	20.4
14 ¹	14.000	14.00	146.0	5.80	78.0
DN350	355.6	356	66.2	147	35.4
	14.843	14.88	168.0	6.15	82.0
	377.0	378	76.2	156	37.2
16 ¹	16.000	16.00	190.0	6.63	88.2
DN400	406.4	406	86.2	168	40.0
	16.772	16.75	216.0	6.95	98.1
	426.0	425	98.0	177	44.5
18 ¹	18.000	18.00	241.0	7.46	123.0
DN450	457.2	457	109.3	189	55.8
	18.898	18.90	291.0	7.83	123.2
	480.0	480	132.0	199	55.9
20 ¹	20.000	20.00	296.0	8.28	151.0
DN500	508.0	508	134.3	210	68.5
	20.866	20.88	355.0	8.64	179.0
	530.0	530	161.0	219	81.2
22	22.000	25.00	386.0	12.11	210.0
DN550	558.8	635	175.1	308	95.3
24 ¹	24.000	24.00	475.0	9.94	240.0
DN600	609.6	610	215.5	252	108.9
	24.803	24.75	545.0	10.27	275.4
	630.0	629	247.2	261	124.9
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05				

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(sw) = Carbon Steel Segmentally Welded

NOTE




- All fittings are ductile iron unless otherwise noted with an (sw).

4.0 DIMENSIONS (CONTINUED)

Elbows

No. 12 22 1/2° Elbow

No. 13 11 1/4° Elbow



Size		No. 12 22 1/2° Elbow		No. 12G (GSNK) 22 1/2° Elbow		No. 13 11 1/4° Elbow	
Nominal inches DN	Actual Outside Diameter inches mm	C to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
3/4 DN20	1.050 26.9	1.63 (sw) 41	0.4 0.2	NA	NA	1.38 (sw) 35	0.4 0.2
1 DN25	1.315 33.7	1.63 (sw) 41	0.5 0.2	3.25 83	0.6 0.3	1.38 (sw) 35	0.4 0.2
1 1/4 DN32	1.660 42.4	1.75 44	0.8 0.4	NA	NA	1.38 35	0.6 0.3
1 1/2 DN40	1.900 48.3	1.75 44	1.0 0.4	NA	NA	1.38 35	0.6 0.3
2 DN50	2.375 60.3	1.88 48	1.2 0.5	3.75 95	1.4 0.6	1.38 35	1.0 0.4
2 1/2	2.875 73.0	2.00 (sw) 51	2.4 1.1	4.00 102	2.0 0.9	1.50 38	1.6 0.7
DN65	3.000 76.1	2.25 57	2.5 1.1	NA	NA	1.50 38	1.7 0.8
3 DN80	3.500 88.9	2.25 (sw) 57	3.1 1.4	4.50 114	3.1 1.4	1.50 38	2.0 0.9
3 1/2 DN90	4.000 101.6	2.50 (sw) 64	4.0 1.8	NA	NA	1.75 (sw) 44	2.8 1.3
	4.250 108.0	2.88 (sw) 73	+	NA	NA	1.75 (sw) 44	+
4 DN100	4.500 114.3	2.88 73	4.8 2.2	5.25 133	4.8 2.2	1.75 44	3.3 1.5
4 1/2	5.000 127.0	2.88 (sw) 73	+	NA	NA	1.88 (sw) 48	+
	5.250 133.0	2.88 (sw) 73	+	NA	NA	2.00 (sw) 51	+
DN125	5.500 139.7	2.88 73	6.3 2.9	NA	NA	2.00 51	4.6 2.1
5	5.563 141.3	2.88 (sw) 73	7.8 3.5	NA	NA	2.00 (sw) 51	5.0 2.3
	6.000 152.4	3.13 (sw) 79	+	NA	NA	2.00 (sw) 51	+
	6.250 159.0	3.13 (sw) 79	+	NA	NA	2.00 (sw) 51	+
	6.500 165.1	3.13 79	10.4 4.7	NA	NA	2.00 51	7.1 3.2
6 DN150	6.625 168.3	3.13 (sw) 79	12.2 5.5	6.25 159	12.2 5.5	2.00 51	6.4 2.9

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details

NOTE




- All fittings are ductile iron unless otherwise noted with an (sw).

4.0 DIMENSIONS (CONTINUED)

Elbows

No. 12 22 1/2° Elbow

No. 13 11 1/4° Elbow



Size		No. 12 22 1/2° Elbow		No. 12G (GSNK) 22 1/2° Elbow		No. 13 11 1/4° Elbow	
Nominal inches DN	Actual Outside Diameter inches mm	C to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
8 DN200	8.625 219.1	3.88 (sw) 98	20.0 9.1	7.50 191	18.1 8.2	2.00 51	8.2 3.7
10 DN250	10.750 273.0	4.38 111	30.0 13.6	NA	NA	2.13 54	11.8 5.3
12 DN300	12.750 323.9	4.88 124	40.0 18.1	NA	NA	2.25 57	29.3 13.3
14 ¹ DN350	14.000 355.6	5.00 (sw) 127	46.0 20.9	NA	NA	3.50 (sw) 89	32.0 14.5
16 ¹ DN400	16.000 406.4	5.00 (sw) 127	58.0 26.3	NA	NA	4.00 (sw) 102	42.0 19.1
18 ¹ DN450	18.000 457.2	5.50 (sw) 140	65.0 29.5	NA	NA	4.50 (sw) 114	53.0 24.0
20 ¹ DN500	20.000 508.0	6.00 (sw) 152	78.6 35.7	NA	NA	5.00 (sw) 127	65.0 29.5
22 DN550	22.000 558.8	6.50 (sw) 165	125.0 56.7	NA	NA	5.50 (sw) 140	80.0 36.3
24 ¹ DN600	24.000 609.6	7.00 (sw) 178	140.0 63.5	NA	NA	6.00 (sw) 152	94.5 42.9
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05 AGS™						

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details

NOTE



- All fittings are ductile iron unless otherwise noted with an (sw).

4.0 DIMENSIONS (CONTINUED)

Elbows

No. 100 90° Long Radius Elbow

No. 110 45° Long Radius Elbow



Size		No. 100 90° 1 ½D Long Radius Elbow		No. 110 45° 1 ½D Long Radius Elbow	
Nominal inches DN	Actual Outside Diameter inches mm	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
¾ DN20	1.050 26.9	2.50 (s) 64	0.4 0.2	1.75 (s) 44	0.4 0.2
1 DN25	1.315 33.7	2.88 (s) 73	0.8 0.4	2.25 (s) 57	0.6 0.3
1¼ DN32	1.660 42.4	3.25 (s) 83	1.1 0.5	2.38 (s) 60	0.9 0.4
1½ DN40	1.900 48.3	3.63 (s) 92	2.2 1.0	2.50 (s) 64	1.1 0.5
2 DN50	2.375 60.3	4.38 111	2.6 1.2	2.75 70	1.9 0.9
2½	2.875 73.0	5.13 130	3.4 1.5	3.13 (s) 79	3.0 1.4
3 DN80	3.500 88.9	5.88 149	6.0 2.7	3.38 86	3.8 1.7
3½ DN90	4.000 101.6	6.63 (s) 168	8.7 3.9	3.63 (s) 92	5.6 2.5
4 DN100	4.500 114.3	7.50 191	10.8 4.9	4.00 102	7.4 3.4
5	5.563 141.3	9.25 235	18.0 8.2	4.25 108	14.8 6.7
	6.500 165.1	10.75 273	25.8 11.7	5.50 140	15.8 7.2
6 DN150	6.625 168.3	10.75 273	30.4 13.8	5.38 137	16.7 7.6
8 DN200	8.625 219.1	14.25 362	68.5 31.1	7.25 184	36.0 16.3
10 DN250	10.750 273.0	15.00 381	81.6 37.0	6.25 159	40.1 18.2
12 DN300	12.750 323.9	18.00 457	138.0 62.6	7.50 191	69.6 31.6
14¹ DN350	14.000 355.6	21.00 533	222.7 101.0	8.75 222	112.4 51.0
16¹ DN400	16.000 406.4	24.00 610	302.0 137.0	10.00 254	158.7 72.0
18¹ DN450	18.000 457.2	27.00 686	421.8 191.3	11.25 286	224.9 102.0
20¹ DN500	20.000 508.0	30.00 762	498.2 226.0	12.50 318	246.9 112.0
22¹ DN550	22.000 558.8	36.00 (s) 914	400.0 181.4	16.50 (s) 419	205.0 93.0
24¹ DN600	24.000 609.6	36.00 914	765.0 347.0	15.00 381	370.4 168.0
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05				



¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel


NOTE

- All fittings are ductile iron unless otherwise noted with an (s).

4.1 DIMENSIONS

No. 10-DR

90° Drain Elbow




Size		No. 10-DR 90° Drain Elbow					Weight	
Nominal inches DN	Actual Outside Diameter inches mm	C to E inches mm	ØB inches mm	G inches mm	H inches mm	Drain Tap NPT inches mm	Approx. Weight (Each) lb kg	
2½	2.875 73.0	3.75 95	1.81 46	2.75 70	1.68 43	1 25	3.5 1.6	
3 DN80	3.500 88.9	4.25 108	1.81 46	2.75 70	2.13 54	1 25	4.8 2.2	
4 DN100	4.500 114.3	5.00 127	1.81 46	2.75 70	2.63 67	1 25	7.8 3.5	
6 DN150	6.625 168.3	6.50 165	1.81 46	2.75 70	3.65 93	1 25	18.1 8.2	

4.2 DIMENSIONS

Reducing Base Support Elbow

No. R-10G

No. R-10F



Size		No. R-10G 90° Reducing Base Support Elbow Groove x Groove							No. R-10F 90° Reducing Base Support Elbow Groove x Class 150 Flange*						
Nominal inches DN	Actual Outside Diameter inches mm	C to E inches mm	H1 inches mm	H2 inches mm	T1 inches mm	T2 inches mm	Approx. Weight (Each) lb kg	C to E inches mm	ØF inches mm	H1 inches mm	H2 inches mm	T1 inches mm	T2 inches mm	Approx. Weight (Each) lb kg	
6 x 4 DN150 x DN100	6.625 x 4.500	9.19	1.25	0.38	2.00	1.50	33.0	9.19	9.00	1.25	0.38	2.00	1.50	46.0	
	168.3 x 114.3	233	32	10	51	38	15.0	233	229	32	10	51	38	20.9	
	5	5.563	9.00	1.50	0.38	2.00	1.50	37.0	9.00	10.00	1.50	0.38	2.00	1.50	52.0
8 x 6 DN200 x DN150	8.625 x 6.625	10.50	2.13	0.38	2.00	1.50	51.0	10.50	11.00	2.13	0.38	2.00	1.50	70.0	
	219.1 x 168.3	267	54	10	51	38	23.1	267	279	54	10	51	38	31.8	
10 x 8 DN250 x DN200	10.750 x 8.625	12.00	2.38	0.38	2.00	1.50	88.0	12.00	13.50	2.38	0.38	2.00	1.50	118.0	
	273.0 x 219.1	305	60	10	51	38	39.9	305	343	60	10	51	38	53.5	

* Contact Victaulic for additional flange end options.



For long radius base support elbow options, please refer to [publication 07.13](#).

4.3 DIMENSIONS

Adapter Elbow

No. 18 90° Adapter Elbow

No. 19 45° Adapter Elbow



Size		No. 18 90° Adapter Elbow Groove x Male Thread ¹			No. 19 45° Adapter Elbow Groove x Male Thread ¹		
Nominal inches DN	Actual Outside Diameter inches mm	C to GE inches mm	C to TE inches mm	Approx. Weight (Each) inches mm	C to GE inches mm	C to TE inches mm	Approx. Weight (Each) lb kg
3/4 DN20	1.050 26.9	2.25 57	2.25 57	0.5 0.2	1.50 38	1.50 38	0.5 0.2
1 DN25	1.315 33.7	2.25 57	2.25 57	0.6 0.3	NA	NA	NA
1 1/4 DN32	1.660 42.4	2.75 70	2.75 70	1.2 0.5	NA	NA	NA
1 1/2 DN40	1.900 48.3	2.75 70	2.75 70	1.4 0.7	1.88 48	1.75 44	0.9 0.4
2 DN50	2.375 60.3	3.25 83	4.25 108	2.5 1.1	2.00 51	2.00 51	1.6 0.7
2 1/2	2.875 73.0	3.75 95	3.75 95	3.7 1.7	2.25 57	2.25 57	2.3 1.0
3 DN80	3.500 88.9	4.25 108	6.00 152	6.6 3.0	2.50 64	4.25 108	5.0 2.3
4 DN100	4.500 114.3	5.00 127	7.25 184	10.0 4.5	NA	NA	NA
6 DN150	6.625 168.3	6.50 165	6.50 165	19.0 8.6	3.50 89	3.50 89	10.8 4.9

¹ Available with British Standard Pipe Threads, specify "BSP" clearly on order.



NA = Not Available

4.4 DIMENSIONS

Tees, Crosses and True Wyes

No. 20

No. 29M



Size		No. 20 Tee		No. 29M Tee Groove x Male Thread ² Branch		
Nominal inches DN	Actual Outside Diameter inches mm	C to E inches mm	Approx. Weight (Each) lb kg	C to GE inches mm	C to TE lb kg	Approx. Weight (Each) inches mm
3/4 DN20	1.050 26.9	2.25 57	0.8 0.4	2.25 (sw) 57	2.25 (sw) 57	0.6 0.3
1 DN25	1.315 33.7	2.25 57	0.9 0.4	2.25 (sw) 57	2.25 (sw) 57	0.9 0.4
1 1/4 DN32	1.660 42.4	2.75 70	1.5 0.7	2.75 70	2.75 70	1.6 0.7
1 1/2 DN40	1.900 48.3	2.75 70	1.7 0.8	2.75 70	2.75 70	1.8 0.8
2 DN50	2.375 60.3	3.25 83	2.8 1.3	3.25 83	4.25 108	3.5 1.6
2 1/2	2.875 73.0	3.75 95	4.8 2.2	3.75 (sw) 95	3.75 (sw) 95	4.3 2.0
DN65	3.000 76.1	3.75 95	5.3 2.4	3.75 (sw) 95	3.75 (sw) 95	5.2 2.4
3 DN80	3.500 88.9	4.25 108	6.4 2.9	4.25 (sw) 108	4.25 (sw) 108	7.2 3.3
3 1/2 DN90	4.000 101.6	4.50 (sw) 114	7.9 3.6	4.50 (sw) 114	4.50 (sw) 114	7.9 3.6
	4.250 108.0	5.00 127	12.0 5.4	5.00 (sw) 127	5.00 (sw) 127	15.5 7.0
4 DN100	4.500 114.3	5.00 127	11.3 5.1	5.00 127	7.25 184	16.3 7.4
4 1/2	5.000 127.0	5.25 (sw) 133	15.0 6.8	5.25 (sw) 133	5.25 (sw) 133	15.0 6.8
	5.250 133.0	5.50 140	16.2 7.3	5.50 (sw) 140	5.50 (sw) 140	17.8 8.1
DN125	5.500 139.7	5.50 140	17.8 8.1	5.50 (sw) 140	5.50 (sw) 140	17.8 8.1
5	5.563 141.3	5.50 140	17.8 8.1	5.50 (sw) 140	5.50 (sw) 140	24.0 10.9
	6.000 152.4	6.50 (sw) 165	+	6.50 (sw) 165	6.50 (sw) 165	25.7 11.7
	6.250 159.0	6.50 (sw) 165	+	6.50 (sw) 165	6.50 (sw) 165	27.1 12.3
	6.500 165.1	6.50 165	25.0 11.3	6.50 (sw) 165	6.50 (sw) 165	28.0 12.7
6 DN150	6.625 168.3	6.50 165	25.7 11.7	6.50 (sw) 165	6.50 (sw) 165	33.0 15.0
200A	216.3	7.75 197	43.3 19.6	NA	NA	NA

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details



NOTES


- All fittings are ductile iron unless otherwise noted with an (sw).

4.3 DIMENSIONS (CONTINUED)

Tees, Crosses and True Wyes

No. 20
No. 29M



Size		No. 20 Tee		No. 29M Tee Groove x Male Thread ² Branch		
Nominal inches DN	Actual Outside Diameter inches mm	C to E inches mm	Approx. Weight (Each) lb kg	C to GE inches mm	C to TE lb kg	Approx. Weight (Each) inches mm
8 DN200	8.625 219.1	7.75 197	49.5 22.5	7.75 (sw) 197	7.75 (sw) 197	47.6 21.6
250A	267.4	9.00 229	66.0 29.9	NA	NA	NA
10 DN250	10.750 273.0	9.00 229	72.4 32.8	9.00 (sw) 229	9.00 (sw) 229	99.0 44.9
300A	318.5	10.00 254	95.0 43.1	NA	NA	NA
12 DN300	12.750 323.9	10.00 254	107.2 48.6	10.00 (sw) 254	10.00 (sw) 254	133.0 60.3
14 ¹ DN350	14.000 355.6	11.00 (sw) 279	150.0 68.0	11.00 (sw) 279	11.00 (sw) 279	+
	14.843 377.0	11.50 292	159.3 72.3	NA	NA	NA
16 ¹ DN400	16.000 406.4	12.00 (sw) 305	188.0 85.3	12.00 (sw) 305	12.00 (sw) 305	+
	16.772 426.0	13.00 330	211.6 96.0	NA	NA	NA
18 ¹ DN450	18.000 457.2	15.50 (sw) 394	200.0 90.7	15.50 (sw) 394	15.50 (sw) 394	+
	18.898 480.0	14.57 370	211.6 96.0	NA	NA	NA
20 ¹ DN500	20.000 508.0	17.25 (sw) 438	339.0 153.8	17.25 (sw) 438	17.25 (sw) 438	+
	20.866 530.0	15.39 391	382.0 173.3	NA	NA	NA
22 DN550	22.000 558.8	19.00 (sw) 483	468.0 212.3	19.00 (sw) 483	19.00 (sw) 483	+
24 ¹ DN600	24.000 609.6	20.00 (sw) 508	592.0 268.5	20.00 (sw) 508	20.00 (sw) 508	+
	24.803 630.0	17.37 441	502.0 227.7	NA	NA	NA
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05					
						

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details

NOTES



- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS

Tees, Crosses and True Wyes

No. 33

No. 35



Size		No. 33 True Wye			No. 35 Cross	
Nominal inches DN	Actual Outside Diameter inches mm	C to LE inches mm	C to SE inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
3/4 DN20	1.050 26.9	2.25 (sw) 57	2.00 (sw) 51	0.8 0.4	2.25 (sw) 57	0.9 0.4
1 DN25	1.315 33.7	2.25 (sw) 57	2.25 (sw) 57	1.1 0.5	2.25 (sw) 57	1.3 0.6
1 1/4 DN32	1.660 42.4	2.75 (sw) 70	2.50 (sw) 64	1.5 0.7	2.75 (sw) 70	2.1 1.0
1 1/2 DN40	1.900 48.3	2.75 (sw) 70	2.75 (sw) 70	1.8 0.8	2.75 (sw) 70	2.5 1.1
2 DN50	2.375 60.3	3.25 (sw) 83	2.75 (sw) 70	2.5 1.1	3.25 83	4.0 1.8
2 1/2	2.875 73.0	3.75 (sw) 95	3.00 (sw) 76	5.1 2.3	3.75 95	6.1 2.8
DN65	3.000 76.1	3.75 (sw) 95	3.25 (sw) 83	5.5 2.5	3.75 95	7.8 3.5
3 DN80	3.500 88.9	4.25 (sw) 108	3.25 (sw) 83	6.1 2.8	4.25 108	11.8 5.4
3 1/2 DN90	4.000 101.6	4.50 (sw) 114	3.50 (sw) 89	9.6 4.4	4.50 (sw) 114	11.5 5.2
	4.250 108.0	5.00 (sw) 127	3.75 (sw) 95	9.7 4.4	5.00 127	18.4 8.3
4 DN100	4.500 114.3	5.00 127	3.75 95	10.0 4.5	5.00 127	15.8 7.2
4 1/2	5.000 127.0	5.25 (sw) 133	4.00 (sw) 102	12.5 5.7	5.25 (sw) 133	18.5 8.4
	5.250 133.0	5.50 (sw) 140	4.00 (sw) 102	13.8 6.2	5.50 (sw) 140	19.0 8.6
DN125	5.500 139.7	5.50 (sw) 140	4.00 (sw) 102	15.0 6.8	5.50 (sw) 140	19.5 8.8
5	5.563 141.3	5.50 (sw) 140	4.00 (sw) 102	15.0 6.8	5.50 140	28.6 13.0
	6.000 152.4	6.50 (sw) 165	4.50 (sw) 114	17.5 7.9	6.50 (sw) 165	22.0 10.0
	6.250 159.0	6.50 (sw) 165	4.50 (sw) 114	19.9 9.0	6.50 165	41.4 18.8
	6.500 165.1	6.50 (sw) 165	4.50 (sw) 114	21.5 9.8	6.50 165	44.0 20.0
6 DN150	6.625 168.3	6.50 (sw) 165	4.50 (sw) 114	22.3 10.1	6.50 165	46.0 20.9
8 DN200	8.625 219.1	7.75 (sw) 197	6.00 (sw) 152	36.0 16.3	7.75 (sw) 197	48.0 21.8

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(sw) = Carbon Steel Segmentally Welded



NOTE

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Tees, Crosses and True Wyes

No. 33
No. 35



Size		No. 33 True Wye			No. 35 Cross	
Nominal inches DN	Actual Outside Diameter inches mm	C to LE inches mm	C to SE inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
10 DN250	10.750 273.0	9.00 (sw) 229	6.50 (sw) 165	54.5 24.7	9.00 (sw) 229	70.0 31.8
12 DN300	12.750 323.9	10.00 (sw) 254	7.00 (sw) 178	80.0 36.3	10.00 (sw) 254	110.0 49.9
14 ¹ DN350	14.000 355.6	11.00 (sw) 279	7.50 (sw) 191	134.2 60.9	11.00 (sw) 279	198.0 89.8
16 ¹ DN400	16.000 406.4	12.00 (sw) 305	8.00 (sw) 203	167.0 75.7	12.00 (sw) 305	250.0 113.4
18 ¹ DN450	18.000 457.2	15.50 (sw) 394	8.50 (sw) 216	180.0 81.6	15.50 (sw) 394	350.0 158.8
20 ¹ DN500	20.000 508.0	17.25 (sw) 438	9.00 (sw) 229	200.0 90.7	17.25 (sw) 438	452.0 205.0
22 DN550	22.000 558.8	19.00 (sw) 483	9.50 (sw) 241	225.0 102.1	19.00 (sw) 483	624.0 283.0
24 ¹ DN600	24.000 609.6	20.00 (sw) 508	10.00 (sw) 254	250.0 113.4	20.00 (sw) 508	795.0 360.6
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05					
						

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.
(sw) = Carbon Steel Segmentally Welded


NOTE

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ²		No. 29F ² Reducing Tee Groove x Female Thread ²	
Nominal inches DN	Actual Outside Diameter inches mm		C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
1 DN25 x 1 DN25 x 3/4 DN20	1.315 x 1.315 x 1.050	33.7 x 33.7 x 26.9	2.25 (sw) 57	0.8 0.4	2.25 (sw) 57	0.8 0.4	NA	NA
1 1/4 DN32 x 1 1/4 DN32 x 3/4 DN20	1.660 x 1.660 x 1.050	42.4 x 42.4 x 26.9	2.75 (sw) 70	1.0 0.5	2.75 (sw) 70	1.0 0.5	NA	NA
			2.75 (sw) 70	1.3 0.6	2.75 (sw) 70	1.5 0.7	NA	NA
1 1/2 DN40 x 1 1/2 DN40 x 3/4 DN20	1.900 x 1.900 x 1.050	48.3 x 48.3 x 26.9	2.75 (sw) 70	1.5 0.7	2.75 (sw) 70	1.5 0.7	NA	NA
			2.75 (sw) 70	1.5 0.7	2.75 (sw) 70	1.8 0.8	NA	NA
			2.75 (sw) 70	2.1 1.0	2.75 (sw) 70	1.7 0.8	NA	NA
			2.75 (sw) 70	2.1 1.0	2.75 (sw) 70	1.7 0.8	NA	NA
2 DN50 x 2 DN50 x 3/4 DN20	2.375 x 2.375 x 1.050	60.3 x 60.3 x 26.9	3.25 83	2.5 1.1	3.25 83	2.5 1.1	NA	NA
			3.25 83	2.7 1.2	3.25 83	2.7 1.2	NA	NA
			3.25 (sw) 83	2.3 1.0	3.25 (sw) 83	2.3 1.0	NA	NA
			3.25 83	3.2 1.5	3.25 83	3.2 1.5	NA	NA
			3.25 83	1.5 0.7	3.25 83	1.5 0.7	NA	NA
2 1/2 DN50 x 2 1/2 DN50 x 3/4 DN20	2.875 x 2.875 x 1.050	73.0 x 73.0 x 26.9	3.75 (sw) 95	3.9 1.8	3.75 (sw) 95	3.0 1.4	NA	NA
			3.75 95	3.8 1.7	3.75 95	3.8 1.7	NA	NA
			3.75 95	4.0 1.8	3.75 95	4.0 1.8	NA	NA
			3.75 95	4.8 2.2	3.75 95	4.8 2.2	NA	NA
			3.75 95	4.5 2.0	3.75 95	4.5 2.0	NA	NA
			3.75 95	2.0 0.9	3.75 95	2.0 0.9	NA	NA
DN65 x DN65 x 3/4 DN20	3.000 x 3.000 x 1.050	76.1 x 76.1 x 26.9	3.75 (sw) 95	+	3.75 (sw) 95	+	NA	NA
			3.75 (sw) 95	+	3.75 (sw) 95	+	NA	NA
			3.75 (sw) 95	+	3.75 (sw) 95	+	NA	NA
			3.75 (sw) 95	+	3.75 (sw) 95	+	NA	NA
			3.75 95	4.6 2.1	3.75 95	4.6 2.1	NA	NA

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch												
Nominal inches DN	Actual Outside Diameter inches mm		C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg											
3 DN80	x	3 DN80	x	¾ DN20	3.500	88.9	1.050	26.9	4.25 (sw)	108	5.7	2.6	4.25 (sw)	108	5.7	2.6	NA	NA	
					1	1.315	33.7	4.25	108	6.0	2.7	4.25	108	6.0	2.7	NA	NA		
					1 ¼	1.660	42.4	4.25	108	6.0	2.7	4.25	108	6.3	2.9	NA	NA		
					1 ½	1.900	48.3	4.25	108	6.6	3.0	4.25	108	6.6	3.0	NA	NA		
					2	2.375	60.3	4.25	108	6.2	2.8	4.25	108	6.2	2.8	4.25	108	6.2	2.8
					2 ½	2.875	73.0	4.25	108	6.6	3.0	4.25	108	6.6	3.0	NA	NA		
					3	3.000	76.1	4.25	108	6.8	3.1	4.25	108	11.6	5.3	NA	NA		
					3 ½	3.500	88.9	4.25	108	7.0	3.2	4.25	108	11.6	5.3	NA	NA		
3 ½ DN90	x	3 ½ DN90	x	¾ DN20	4.000	101.6	1.050	26.9	4.50 (sw)	114	+	+	4.50 (sw)	114	+	+	NA	NA	
					1	1.315	33.7	4.50 (sw)	114	+	+	4.50 (sw)	114	+	+	NA	NA		
					1 ¼	1.660	42.4	4.50 (sw)	114	+	+	4.50 (sw)	114	+	+	NA	NA		
					1 ½	1.900	48.3	4.50 (sw)	114	+	+	4.50 (sw)	114	+	+	NA	NA		
					2	2.375	60.3	4.50 (sw)	114	+	+	4.50 (sw)	114	+	+	NA	NA		
					2 ½	2.875	73.0	4.50 (sw)	114	+	+	4.50 (sw)	114	+	+	NA	NA		
					3	3.500	88.9	4.50 (sw)	114	+	+	4.50 (sw)	114	+	+	NA	NA		
					3 ½	4.000	101.6	4.50 (sw)	114	+	+	4.50 (sw)	114	+	+	NA	NA		
4	x	4	x	1 DN25	4.250	108.0	1.050	26.9	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	5.00 (sw)	127	+
					1.315	33.7	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	
					1.660	42.4	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	
					1.900	48.3	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	
					2.375	60.3	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	
					2.875	73.0	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	
					3	3.000	76.1	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+	5.00 (sw)	127	+	+
					3.500	88.9	5.00	127	9.5	4.3	5.00 (sw)	127	+	+	NA	NA	NA	NA	

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch		
Nominal inches DN	Actual Outside Diameter inches mm		C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	
4 x 4 x 3/4 DN100 x DN100 x DN20	4.500 x 4.500 x 1.050 114.3 x 114.3 x 26.9	1.315	5.00	8.0	5.00 (sw)	9.3	NA	NA	
		DN25	33.7	127	3.6	127	4.2	NA	NA
		1 1/4	1.660	5.00 (sw)	8.9	5.00 (sw)	10.0	NA	NA
		DN32	42.4	127	4.0	127	4.5	NA	NA
		1 1/2	1.900	5.00	10.2	5.00	10.2	NA	NA
		DN40	48.3	127	4.6	127	4.6	NA	NA
		2	2.375	5.00	11.2	5.00	11.2	NA	NA
		DN50	60.3	127	5.1	127	5.1	NA	NA
		2 1/2	2.875	5.00	11.5	5.00	11.5	NA	NA
		DN65	73.0	127	5.2	127	5.2	NA	NA
3 DN80	5.250 x 5.250 x 1.050 133.0 x 133.0 x 26.9	3.000	5.00	10.3	5.00	10.3	NA	NA	
		DN80	76.1	127	4.7	127	4.7	NA	NA
		3.500	5.00	11.6	5.00	11.6	NA	NA	
		DN80	88.9	127	5.3	127	5.3	NA	NA
		4.250	5.50 (sw)	12.9	5.50 (sw)	+	5.50 (sw)	+	NA
		108.0	140	5.9	140	+	140	+	NA
		1.315	5.50 (sw)	+	5.50 (sw)	+	5.50 (sw)	+	+
		33.7	140	+	140	+	140	+	+
1.660	5.50 (sw)	+	5.50 (sw)	+	5.50 (sw)	+	+		
42.4	140	+	140	+	140	+	+		
1.900	5.50 (sw)	+	5.50 (sw)	+	5.50 (sw)	+	+		
48.3	140	+	140	+	140	+	+		
2.375	5.50 (sw)	+	5.50 (sw)	+	NA	+	NA		
60.3	140	+	140	+	NA	+	NA		
3.000	5.50 (sw)	+	5.50 (sw)	+	5.50 (sw)	+	+		
76.1	140	+	140	+	140	+	+		
3.500	5.50 (sw)	+	5.50 (sw)	+	5.50 (sw)	+	+		
88.9	140	+	140	+	140	+	+		

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size			No. 25 Grooved Branch Reducing Tee			No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch				
Nominal inches DN		Actual Outside Diameter inches mm	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg				
DN125	x DN125	x 3/4 DN20	5.500	139.7	1.050	26.9	5.50 (sw) 140	+	5.50 (sw) 140	+	NA	NA
			1.315	33.7	5.50 (sw) 140	+	5.50 (sw) 140	+	NA	NA		
			1.660	42.4	5.50 (sw) 140	+	5.50 (sw) 140	+	NA	NA		
			1.900	48.3	5.50 (sw) 140	+	5.50 (sw) 140	+	NA	NA		
			2.375	60.3	5.50 (sw) 140	13.5 6.1	5.50 (sw) 140	+	NA	NA		
			3.000	76.1	5.50 (sw) 140	+	5.50 (sw) 140	+	NA	NA		
			3.500	88.9	5.50 (sw) 140	13.8 6.3	5.50 (sw) 140	+	NA	NA		
			4.250	108.0	5.50 (sw) 140	+	5.50 (sw) 140	+	NA	NA		
			4.500	114.3	5.50 (sw) 140	14.4 6.5	5.50 (sw) 140	+	NA	NA		
			5	x 5	x 3/4 DN20	5.563	141.3	1.050	26.9	5.50 (sw) 140	+	5.50 (sw) 140
1.315	33.7	5.50 (sw) 140				14.0 6.4	5.50 (sw) 140	14.0 6.4	NA	NA		
1.660	42.4	5.50 (sw) 140				+	5.50 (sw) 140	+	NA	NA		
1.900	48.3	5.50 (sw) 140				14.3 6.5	5.50 (sw) 140	14.5 6.6	NA	NA		
2.375	60.3	5.50 (sw) 140				14.5 6.6	5.50 (sw) 140	14.5 6.6	NA	NA		
2.875	73.0	5.50 (sw) 140				15.5 7.0	5.50 (sw) 140	15.8 7.2	NA	NA		
3.500	88.9	5.50 (sw) 140				12.6 5.7	5.50 (sw) 140	17.0 7.7	NA	NA		
4.500	114.3	5.50 (sw) 140				16.0 7.3	5.50 (sw) 140	16.0 7.3	NA	NA		

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
 No. 29T
 No. 29F



Size				No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch	
Nominal inches DN	Actual Outside Diameter inches mm			C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
6.000 152.4	x	6.000 152.4	1.050 26.9	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA
			1.315 33.7	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA
			1.660 42.4	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA
			1.900 48.3	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA
			2.375 60.3	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA
			3.000 76.1	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA
			3.500 88.9	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA
			4.250 108.0	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA
			4.500 114.3	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA
			5.250 133.0	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size				No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch		
Nominal inches DN	Actual Outside Diameter			C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	
6.250 159.0	x	6.250 159.0	x	1.050 26.9	6.50 (sw) 165	+	6.50 (sw) 165	+	6.50 (sw) 165	+
				1.315 33.7	6.50 (sw) 165	+	6.50 (sw) 165	+	6.50 (sw) 165	+
				1.660 42.4	6.50 (sw) 165	+	6.50 (sw) 165	+	6.50 (sw) 165	+
				1.900 48.3	6.50 (sw) 165	+	6.50 (sw) 165	+	6.50 (sw) 165	+
				2.375 60.3	6.50 (sw) 165	+	6.50 (sw) 165	+	6.50 (sw) 165	+
				3.000 76.1	6.50 (sw) 165	+	6.50 (sw) 165	+	6.50 (sw) 165	+
				3.500 88.9	6.50 165	18.5 8.4	6.50 (sw) 165	+	NA	NA
				4.250 108.0	6.50 165	18.5 8.4	6.50 (sw) 165	+	NA	NA
				4.500 114.3	6.50 165	12.1 5.5	6.50 (sw) 165	+	NA	NA
				5.250 133.0	6.50 165	19.0 8.6	6.50 (sw) 165	+	NA	NA
				6.500 165.1	x	6.500 165.1	x	1.050 26.9	6.50 (sw) 165	+
1.315 33.7	6.50 (sw) 165	10.8 4.9	6.50 (sw) 165					10.8 4.9	NA	NA
1.660 42.4	6.50 (sw) 165	11.0 5.0	6.50 (sw) 165					11.0 5.0	NA	NA
1.900 48.3	6.50 (sw) 165	11.3 5.1	6.50 (sw) 165					11.3 5.1	NA	NA
2.375 60.3	6.50 165	18.9 8.6	6.50 165					18.9 8.6	NA	NA
3.000 76.1	6.50 165	20.0 9.1	6.50 (sw) 165					+	NA	NA
3.500 88.9	6.50 165	24.3 11.0	6.50 (sw) 165					+	NA	NA
4.500 114.3	6.50 165	23.8 10.8	6.50 (sw) 165					+	NA	NA
5.500 139.7	6.50 165	26.0 11.8	6.50 (sw) 165					+	NA	NA

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch		
Nominal inches DN		Actual Outside Diameter inches mm	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	
6 x 6 x ¾ DN150 x DN150 x DN20	1	6.625 x 6.625 x 1.050 168.3 x 168.3 x 26.9	6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA	
	DN25		6.50 (sw) 165	23.0 10.4	6.50 (sw) 165	23.0 10.4	NA	NA	
	1¼		6.50 (sw) 165	25.0 11.3	6.50 (sw) 165	25.0 11.3	NA	NA	
	DN32		6.50 (sw) 165	25.0 11.3	6.50 (sw) 165	25.0 11.3	NA	NA	
	1½		6.50 (sw) 165	22.8 10.3	6.50 (sw) 165	22.8 10.3	NA	NA	
	DN40		6.50 (sw) 165	23.8 10.8	6.50 (sw) 165	25.2 11.4	NA	NA	
	2		6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA	
	DN50		6.50 (sw) 165	24.8 11.2	6.50 (sw) 165	24.9 11.3	NA	NA	
	2½		6.50 (sw) 165	24.8 11.2	6.50 (sw) 165	22.1 10.0	NA	NA	
	DN65		6.50 (sw) 165	+	6.50 (sw) 165	+	NA	NA	
	3		6.50 (sw) 165	26.7 12.1	6.50 (sw) 165	26.7 12.1	NA	NA	
	DN80		6.50 (sw) 165	26.7 12.1	6.50 (sw) 165	26.7 12.1	NA	NA	
	4		6.50 (sw) 165	7.75 (sw) 197	+	NA	NA	NA	NA
	DN100		6.50 (sw) 165	7.75 (sw) 197	+	NA	NA	NA	NA
5		6.50 (sw) 165	7.75 (sw) 197	50.0 22.7	NA	NA	NA	NA	
200A x 200A x 65A	216.3 x 216.3 x 76.3	7.75 (sw) 197	+	NA	NA	NA	NA	NA	
100A	114.3	7.75 (sw) 197	+	NA	NA	NA	NA	NA	
165A		7.75 (sw) 197	50.0 22.7	NA	NA	NA	NA	NA	

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch							
Nominal inches DN	Actual Outside Diameter inches mm		C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg						
8 DN200	x	8 DN200	8.625 219.1	x	8.625 219.1	x	1.050 26.9	7.75 (sw) 197	+	7.75 (sw) 197	+	7.75 (sw) 197	+	
		¾ DN25						1.315 33.7	7.75 (sw) 197	+	7.75 (sw) 197	+	7.80 (sw) 198	+
		1¼ DN32						1.660 42.4	7.75 (sw) 197	+	7.75 (sw) 197	+	7.80 (sw) 198	+
		1½ DN40						1.900 48.3	7.75 (sw) 197	33.0 15.0	7.75 (sw) 197	37.7 17.1	7.80 (sw) 198	+
		2 DN50						2.375 60.3	7.75 (sw) 197	33.5 15.2	7.75 (sw) 197	33.5 15.2	NA	NA
		2½						2.875 73.0	7.75 197	37.3 16.9	7.75 (sw) 197	34.0 15.4	NA	NA
		DN65						3.000 76.1	7.75 (sw) 197	37.5 17.0	NA	NA	7.80 (sw) 198	+
		3 DN80						3.500 88.9	7.75 197	37.5 17.0	7.75 (sw) 197	33.6 15.2	NA	NA
		4 DN100						4.250 108.0	7.75 197	48.9 22.2	NA	NA	NA	NA
								4.500 114.3	7.75 197	42.9 19.5	7.75 (sw) 197	35.0 15.9	NA	NA
								5.250 133.0	9.02 229	54.6 24.8	7.75 (sw) 197	+	NA	NA
								5.500 139.7	7.75 (sw) 197	+	NA	NA	NA	NA
								5 DN125	5.563 141.3	7.75 197	37.0 16.8	7.75 (sw) 197	37.0 16.8	NA
		6 DN150						6.250 159.0	7.75 197	51.6 23.4	7.75 (sw) 197	+	NA	NA
								6.500 165.1	7.75 197	43.2 19.6	7.75 (sw) 197	+	NA	NA
6.625 168.3	7.75 197		48.5 22.0	7.75 (sw) 197	43.0 19.5	NA	NA							
10.528 267.4	10.528 267.4		6.500 165.1	9.02 229	68.4 31.0	NA	NA	NA						
250A x	250A x	125A	267.4 x	267.4 x	139.8	9.00 (sw) 229	+	NA	NA	NA	NA			
		200A				216.3	9.00 229	82.0 37.2	NA	NA	NA	NA		

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch	
Nominal inches DN		Actual Outside Diameter inches mm	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
10 DN250	x 10 DN250	x 1.050 273.0	9.00 (sw) 229	+	9.00 (sw) 229	+	NA	NA
		x 1.315 33.7	9.00 (sw) 229	+	9.00 (sw) 229	+	NA	NA
		x 1.660 42.4	9.00 (sw) 229	+	9.00 (sw) 229	+	NA	NA
		x 1.900 48.3	9.00 (sw) 229	57.0 25.9	9.00 (sw) 229	57.0 25.9	NA	NA
		x 2.375 60.3	9.00 (sw) 229	62.0 28.1	9.00 (sw) 229	65.0 29.5	9.00 (sw) 229	+
		x 2.875 73.0	9.00 229	62.5 28.3	9.00 (sw) 229	53.0 24.0	NA	NA
		x 3.000 76.1	9.00 (sw) 229	71.2 32.3	NA	NA	NA	NA
		x 3.500 88.9	9.00 229	62.1 28.2	9.00 (sw) 229	60.0 27.2	NA	NA
		x 4.250 108.0	9.02 229	77.6 35.2	9.00 (sw) 229	+	NA	NA
		x 4.500 114.3	9.00 229	61.0 27.7	9.00 (sw) 229	61.0 27.7	NA	NA
		x 5.250 133.0	9.02 229	84.2 38.2	9.00 (sw) 229	+	NA	NA
		x 5.500 139.7	9.00 (sw) 229	+	9.00 (sw) 229	+	NA	NA
		x 6.250 159.0	9.02 229	84.9 38.5	9.00 (sw) 229	+	NA	NA
		x 5.563 141.3	9.00 (sw) 229	52.0 23.6	9.00 (sw) 229	52.0 23.6	NA	NA
		x 6.250 159.0	9.00 229	61.0 27.7	9.00 (sw) 229	+	NA	NA
		x 6.500 165.1	9.00 229	64.2 29.1	9.00 (sw) 229	+	NA	NA
		x 6.625 168.3	9.00 229	59.0 26.8	9.00 (sw) 229	60.0 27.2	NA	NA
		x 8.625 219.1	9.00 229	64.7 29.3	9.00 (sw) 229	64.7 29.3	NA	NA
300A	x 300A	x 150A	10.00 (sw) 254	+	NA	NA	NA	NA
		200A	10.00 (sw) 254	+	NA	NA	NA	NA
		250A	10.00 254	111.0 50.3	NA	NA	NA	NA

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available


"+" = Contact Victaulic for details

NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee
 No. 25
 No. 29T
 No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch								
Nominal inches DN	Actual Outside Diameter inches mm		C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg							
12 DN300	x	12 DN300	x	¾ DN20	12.750 323.9	x	12.750 323.9	x	1.050 26.9	10.00 (sw) 254	+	NA	NA	10.00 (sw) 254	+
		1 DN25			1.315 33.7				10.00 (sw) 254	70.0 31.8		10.00 (sw) 254	77.0	10.00 (sw) 254	+
		1¼ DN32			1.660 42.4				10.00 (sw) 254	+		10.00 (sw) 254	+	10.00 (sw) 254	+
		1½ DN40			1.900 48.3				10.00 (sw) 254	+		10.00 254	+	10.00 254	+
		2 DN50			2.375 60.3				10.00 (sw) 254	78.0 35.4		10.00 (sw) 254	78.0 35.4	10.00 (sw) 254	+
		2½			2.875 73.0				10.00 (sw) 254	80.0 36.3		10.00 (sw) 254	80.0 36.3	NA	NA
		DN65			3.000 76.1				10.00 (sw) 254	+		10.00 (sw) 254	+	10.00 (sw) 254	+
		3 DN80			3.500 88.9				10.00 (sw) 254	80.0 36.3		10.00 (sw) 254	86.5 39.2	NA	NA
		4 DN100			4.250 108.0				10.00 254	+		10.00 (sw) 254	+	NA	NA
		5 DN125			4.500 114.3				10.00 (sw) 254	86.7 39.3		10.00 (sw) 254	77.0 34.9	NA	NA
		6 DN150			5.250 133.0				10.00 254	130.0 59.0		10.00 (sw) 254	+	NA	NA
		8 DN200			5.500 139.7				10.00 (sw) 254	81.8 37.1		10.00 (sw) 254	+	NA	NA
		10 DN250			5.563 141.3				10.00 (sw) 254	75.0 34.0		10.00 (sw) 254	75.0 34.0	NA	NA
					6.250 159.0				10.00 254	125.6 57.0		10.00 (sw) 254	+	NA	NA
					6.500 165.1				10.00 (sw) 254	+		10.00 (sw) 254	+	NA	NA
					6.625 168.3				10.00 254	88.5 40.2		10.00 (sw) 254	75.0 34.0	NA	NA
					8.625 219.1				10.00 254	80.0 36.3		10.00 (sw) 254	80.0 36.3	NA	NA
					10.750 273.0				10.00 254	123.5 56.0		10.00 (sw) 254	84.0 38.1	NA	NA

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch				
Nominal inches DN	Actual Outside Diameter		C to E	Approx. Weight (Each)	C to E	Approx. Weight (Each)	C to E	Approx. Weight (Each)			
	inches	mm	inches mm	lb kg	inches mm	lb kg	inches mm	lb kg			
14 ¹ x 14 x 4 DN350 DN350 DN100	14.000 355.6	14.000 355.6	4.500 114.3	11.00 (sw) 279	102.0 46.3	11.00 (sw) 279	102.0 46.3	NA	NA		
			6.625 168.3	11.00 (sw) 279	108.2 49.1	11.00 (sw) 279	108.2 49.1	NA	NA		
			8.625 219.1	11.00 (sw) 279	112.0 50.8	11.00 (sw) 279	112.0 50.8	NA	NA		
			10.750 273.0	11.00 (sw) 279	120.0 54.4	11.00 (sw) 279	120.0 54.4	NA	NA		
			12.750 323.9	11.00 (sw) 279	129.1 58.6	11.00 (sw) 279	129.1 58.6	NA	NA		
			14.843 377.0	14.843 377.0	6.500 165.1	11.00 279	142.4 64.6	NA	NA	NA	NA
			8.625 219.1	11.00 279	145.5 66.0	NA	NA	NA	NA	NA	
10.750 273.0	11.00 279	149.9 68.0	NA	NA	NA	NA	NA				
12.750 323.9	11.00 279	144.6 65.6	NA	NA	NA	NA	NA				
16 ¹ x 16 x 4 DN400 DN400 DN100	16 DN400	16 DN400	4.500 114.3	12.00 (sw) 305	130.0 59.0	12.00 (sw) 305	130.0 59.0	NA	NA		
			6.625 168.3	12.00 (sw) 305	133.5 60.6	12.00 (sw) 305	133.5 60.6	NA	NA		
			8.625 219.1	12.00 (sw) 305	145.0 65.8	12.00 (sw) 305	145.0 65.8	NA	NA		
			10.750 273.0	12.00 (sw) 305	149.5 67.8	12.00 (sw) 305	149.5 67.8	NA	NA		
			12.750 323.9	12.00 (sw) 305	154.0 69.9	12.00 (sw) 305	154.0 69.9	NA	NA		
			14.000 355.6	12.00 (sw) 305	167.0 75.7	NA	NA	NA	NA		
			16.772 426.0	16.772 426.0	6.250 159.0	12.83 326	189.6 86.0	NA	NA	NA	NA
8.625 219.1	12.83 326	213.9 97.0	NA	NA	NA	NA					
10.750 273.0	12.83 326	224.9 102.0	NA	NA	NA	NA					
12.750 323.9	12.83 326	224.9 102.0	NA	NA	NA	NA					
14.843 377.0	12.83 326	227.1 103.0	NA	NA	NA	NA					

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

- No. 25
- No. 29T
- No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch	
Nominal inches DN		Actual Outside Diameter inches mm	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
18 ¹ DN450	x 18 DN450	x 4.500 114.3	15.50 (sw) 394	194.0 88.0	15.50 (sw) 394	194.0 88.0	NA	NA
		6 DN150	6.625 168.3	15.50 (sw) 394	200.0 90.7	200.0 90.7	NA	NA
		8 DN200	8.625 219.1	15.50 (sw) 394	202.6 91.9	202.0 91.6	NA	NA
		10 DN250	10.750 273.0	15.50 (sw) 394	212.0 96.2	212.0 96.2	NA	NA
		12 DN300	12.750 323.9	15.50 (sw) 394	222.6 101.0	222.6 101.0	NA	NA
		14 DN350	14.000 355.6	15.50 (sw) 394	230.1 104.4	NA	NA	NA
		16 DN400	16 DN400	15.50 (sw) 394	247.6 112.3	NA	NA	NA
		18.898 480.0	x 4.250 108.0	14.75 375	282.4 128.1	NA	NA	NA
		18.898 480.0	x 5.250 133.0	14.75 375	283.0 128.4	NA	NA	NA
			6.250 159.0	14.75 375	283.3 128.5	NA	NA	NA
			10.750 273.0	14.75 375	285.1 129.3	NA	NA	NA
			14.843 377.0	14.75 375	293.8 133.2	NA	NA	NA

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch	
Nominal inches DN	Actual Outside Diameter inches mm		C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
20 ¹ x 20 x 6 DN500 x DN500 x DN150	20.000 x 20.000 x 6.625 508.0 x 508.0 x 168.3		17.25 (sw) 438	240.0 108.9	17.25 (sw) 438	240.0 108.9	NA	NA
			17.25 (sw) 438	244.0 110.7	17.25 (sw) 438	244.0 110.7	NA	NA
			17.25 (sw) 438	256.0 116.1	17.25 (sw) 438	256.0 116.1	NA	NA
			17.25 (sw) 438	264.3 119.9	17.25 (sw) 438	264.0 119.7	NA	NA
			17.25 (sw) 438	275.0 124.7	NA	NA	NA	NA
			17.25 (sw) 438	288.6 130.9	NA	NA	NA	NA
			17.25 (sw) 438	297.0 134.7	NA	NA	NA	NA
	20.866 x 20.866 x 6.250 530.0 x 530.0 x 159.0		17.25 438	368.2 167.0	NA	NA	NA	NA
			17.25 438	401.3 182.0	NA	NA	NA	NA
			17.25 438	379.2 172.0	NA	NA	NA	NA
			17.25 438	401.2 182.0	NA	NA	NA	NA
			17.25 438	383.6 174.0	NA	NA	NA	NA
			17.25 438	401.2 182.0	NA	NA	NA	NA
			17.25 438	399.2 181.1	NA	NA	NA	NA

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.4 DIMENSIONS (CONTINUED)

Reducing Tee

No. 25
No. 29T
No. 29F



Size			No. 25 Grooved Branch Reducing Tee		No. 29T Reducing Tee Groove x Male Thread ² Branch		No. 29F ² Reducing Tee Groove x Female Thread ² Branch	
Nominal inches DN	Actual Outside Diameter inches mm		C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg	C to E inches mm	Approx. Weight (Each) lb kg
24 ¹ x 24 x 8 DN600 x DN600 x DN200	24.000 x 24.000 x 8.625 609.6 x 609.6 x 219.1		20.00 (sw) 508	340.0 154.2	20.00 (sw) 508	340.0 154.2	NA	NA
			20.00 (sw) 508	343.9 156.0	20.00 (sw) 508	343.9 156.0	NA	NA
			20.00 (sw) 508	352.8 160.0	20.00 (sw) 508	352.8 160.0	NA	NA
			20.00 508	+ 508	NA	NA	NA	NA
			20.00 (sw) 508	378.0 171.5	NA	NA	NA	NA
			20.00 508	+ 508	NA	NA	NA	NA
			20.00 (sw) 508	400.0 181.4	NA	NA	NA	NA
	24.803 x 24.803 x 6.250 630.0 x 630.0 x 159.0		20.00 508	559.2 253.6	NA	NA	NA	NA
			20.00 508	559.2 253.6	NA	NA	NA	NA
			20.00 508	562.2 255.0	NA	NA	NA	NA
			20.00 508	562.2 255.0	NA	NA	NA	NA
			20.00 508	586.4 266.0	NA	NA	NA	NA
			20.00 508	579.8 263.0	NA	NA	NA	NA
			20.00 508	568.8 258.0	NA	NA	NA	NA
			20.00 508	574.3 260.5	NA	NA	NA	NA
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05							



¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(sw) = Carbon Steel Segmentally Welded

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (sw).

4.6 DIMENSIONS

45° Lateral

No. 30



Size		No. 30 45° Lateral		
Nominal inches DN	Actual Outside Diameter inches mm	C to LE inches mm	C to SE inches mm	Approx. Weight (Each) lb kg
¾ DN20	1.050	4.50 (sw)	2.00 (sw)	0.9
	26.9	114	51	0.4
1 DN25	1.315	5.00 (sw)	2.25 (sw)	1.7
	33.7	127	57	0.8
1¼ DN32	1.660	5.75 (sw)	2.50 (sw)	2.5
	42.4	146	64	1.1
1½ DN40	1.900	6.25 (sw)	2.75 (sw)	3.5
	48.3	159	70	1.6
2 DN50	2.375	7.00 (sw)	2.75 (sw)	5.1
	60.3	178	70	2.3
2½	2.875	7.75 (sw)	3.00 (sw)	9.0
	73.0	197	76	4.1
DN65	3.000	8.50 (sw)	3.25 (sw)	9.8
	76.1	216	83	4.4
3 DN80	3.500	8.50	3.25	10.3
	88.9	216	83	4.6
3½ DN90	4.000	10.00 (sw)	3.50 (sw)	22.0
	101.6	254	89	10.0
	4.250	10.50 (sw)	3.75 (sw)	22.1
	108.0	267	95	10.0
4 DN100	4.500	10.50	3.75	17.9
	114.3	267	95	8.1
4½	5.000	12.50 (sw)	4.00 (sw)	23.8
	127.0	318	102	10.8
	5.250	12.50 (sw)	4.00 (sw)	25.3
	133.0	318	102	11.5
DN125	5.500	12.50 (sw)	4.00 (sw)	26.8
	139.7	318	102	12.1
5	5.563	12.50 (sw)	4.00 (sw)	29.8
	141.3	318	102	13.5
	6.000	14.00 (sw)	4.50 (sw)	33.8
	152.4	356	114	15.3
	6.250	14.00 (sw)	4.50 (sw)	36.8
	159.0	356	114	16.7
	6.500	14.00 (sw)	4.50 (sw)	43.6
	165.1	356	114	19.8
6 DN150	6.625	14.00	4.50	43.6
	168.3	356	114	19.8

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(sw) = Carbon Steel Segmentally Welded


NOTE

- All fittings are ductile iron unless otherwise noted with an (sw).

4.6 DIMENSIONS (CONTINUED)

45° Lateral

No. 30



Size		No. 30 45° Lateral		
Nominal inches DN	Actual Outside Diameter inches mm	C to LE inches mm	C to SE inches mm	Approx. Weight (Each) lb kg
8 DN200	8.625 219.1	18.00 (sw) 457	6.00 (sw) 152	73.0 33.1
10 DN250	10.750 273.0	20.50 (sw) 521	6.50 (sw) 165	105.0 47.6
12 DN300	12.750 323.9	23.00 (sw) 584	7.00 (sw) 178	165.0 74.8
14 ¹ DN350	14.000 355.6	26.50 (sw) 673	7.50 (sw) 191	276.0 125.2
16 ¹ DN400	16.000 406.4	29.00 (sw) 737	8.00 (sw) 203	344.2 156.1
18 ¹ DN450	18.000 457.2	32.00 (sw) 813	8.50 (sw) 216	429.0 194.6
20 ¹ DN500	20.000 508.0	35.00 (sw) 889	9.00 (sw) 229	500.0 226.8
22 DN550	22.000 558.8	38.00 (sw) 965	9.50 (sw) 241	610.0 276.7
24 ¹ DN600	24.000 609.6	40.00 (sw) 1016	10.00 (sw) 254	715.0 324.3

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(sw) = Carbon Steel Segmentally Welded


NOTE

- All fittings are ductile iron unless otherwise noted with an (sw).

4.7 DIMENSIONS

45° Reducing Lateral

No. 30-R SWS



Size				No. 30-R SWS 45° Reducing Lateral (sw)								
Nominal inches DN				Actual Outside Diameter inches DN			C to LE inches mm	C to SE inches mm	Approx. Weight (Each) lb kg			
3 DN80	x	3 DN80	x	2 DN50	3.500 88.9	x	3.500 88.9	x	2.375 60.3	8.50 216	3.25 83	9.8 4.4
									2.875 73.0	8.50 216	3.25 83	9.8 4.4
4 DN100	x	4 DN100	x	2 DN50	4.500 114.3	x	4.500 114.3	x	2.375 60.3	10.50 267	3.75 95	10.0 4.5
									2.875 73.0	10.50 267	3.75 95	10.0 4.5
				3 DN80					3.500 88.9	10.50 267	3.75 95	18.3 8.3
									4.500 114.3	12.50 318	4.00 102	27.0 12.2
5	x	5	x	2 DN50	5	x	5	x	2.375 60.3	12.50 318	4.00 102	24.0 10.9
									3.500 88.9	12.50 318	4.00 102	27.0 12.2
				4 DN100					4.500 114.3	12.50 318	4.00 102	26.5 12.0
									5.563 141.3	14.00 356	4.50 114	37.0 16.8
6 DN150	x	6 DN150	x	3 DN80	6.625 168.3	x	6.625 168.3	x	3.500 88.9	14.00 356	4.50 114	37.0 16.8
									4.500 114.3	14.00 356	4.50 114	36.0 16.3
				5					5.563 141.3	14.00 356	4.50 114	44.7 20.3
									6.625 168.3	18.00 457	6.00 152	58.0 26.3
8 DN200	x	8 DN200	x	4 DN100	8.625 219.1	x	8.625 219.1	x	4.500 114.3	18.00 457	6.00 152	62.0 28.1
									5.563 141.3	18.00 457	6.00 152	75.5 34.2
				6 DN150					6.625 168.3	18.00 457	6.00 152	82.0 37.2
									8.625 219.1	20.50 521	6.50 165	104.8 47.5
10 DN250	x	10 DN250	x	5	10.750 273.0	x	10.750 273.0	x	4.500 114.3	20.50 521	6.50 165	105.0 47.6
									5.563 141.3	20.50 521	6.50 165	105.8 48.0
				6 DN150					6.625 168.3	20.50 521	6.50 165	118.0 53.5
									8.625 219.1	23.00 584	7.00 178	135.0 61.2
12 DN300	x	12 DN300	x	4 DN100	12.750 323.9	x	12.750 323.9	x	4.500 114.3	23.00 584	7.00 178	122.0 55.3
									5.563 141.3	23.00 584	7.00 178	137.0 62.1
				6 DN150					6.625 168.3	23.00 584	7.00 178	147.0 66.7
									8.625 219.1	23.00 584	7.00 178	167.0 75.7
				8 DN200					10.750 273.0	23.00 584	7.00 178	
									12.750 323.9	23.00 584	7.00 178	


¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(sw) = Carbon Steel Segmentally Welded

4.7 DIMENSIONS (CONTINUED)

45° Reducing Lateral

No. 30-R SWS



Size				No. 30-R SWS 45° Reducing Lateral (sw)												
Nominal inches DN		Actual Outside Diameter inches DN		C to LE inches mm	C to SE inches mm	Approx. Weight (Each) lb kg										
14 ¹ DN350	x	14 DN350	x	4 DN100	14.000 355.6	x	14.000 355.6	x	4.500 114.3	26.50 673	7.50 191	176.0 79.8				
				6 DN150			6.625 168.3	26.50 673	7.50 191	187.0 84.8						
				8 DN200			8.625 219.1	26.50 673	7.50 191	210.0 95.3						
				10 DN250			10.750 273.0	26.50 673	7.50 191	235.0 106.6						
				12 DN300			12.750 323.9	26.50 673	7.50 191	252.0 114.3						
				16 ¹ DN400	x	16 DN400	x	6 DN150	16.000 406.4	x	16.000 406.4	x	6.625 168.3	29.00 737	8.00 203	215.0 97.5
								8 DN200			8.625 219.1	29.00 737	8.00 203	252.5 114.5		
10 DN250			10.750 273.0					29.00 737	8.00 203	265.0 120.2						
12 DN300			12.750 323.9					29.00 737	8.00 203	295.0 133.8						
14 DN350			16.000 406.4					29.00 737	8.00 203	305.0 138.3						
18 ¹ DN450	x	18 DN450	x					6 DN150	18.000 457.2	x	18.000 457.2	x	6.625 168.3	32.00 813	8.50 216	274.0 124.3
								8 DN200			8.625 219.1	32.00 813	8.50 216	275.0 124.7		
				10 DN250			10.750 273.0	32.00 813	8.50 216	285.0 129.3						
				12 DN300			12.750 323.9	32.00 813	8.50 216	347.0 157.4						
				14 DN350			14.000 355.6	32.00 813	8.50 216	350.0 158.8						
				16 DN400			16.000 406.4	32.00 813	8.50 216	362.0 164.2						
				20 ¹ DN500	x	20 DN500	x	10 DN250	20.000 508.0	x	20.000 508.0	x	10.750 273.0	35.00 889	9.00 229	410.0 186.0
								12 DN300			12.750 323.9	35.00 889	9.00 229	415.0 188.2		
								14 DN350			14.000 355.6	35.00 889	9.00 229	420.0 190.5		
16 DN400			16.000 406.4					35.00 889	9.00 229	425.0 192.8						
24 ¹ DN600	x	24 DN600	x					16 DN400	24.000 609.6	x	24.000 609.6	x	16.000 406.4	40.00 1016	10.00 254	556.0 252.2
				20 DN500			20.000 508.0	40.00 1016	10.00 254	715.0 324.3						
				For AGS fitting information, see publication 20.05												




¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.
(sw) = Carbon Steel Segmentally Welded

4.8 DIMENSIONS

Tee Wye

No. 32




Size				No. 32 Tee Wye (sw)					Approx. Weight (Each)					
Nominal inches DN		Actual Outside Diameter inches mm		G inches mm	H inches mm	E1 inches mm	E2 inches mm	lb	kg					
2 DN50	x	2 DN50	x	2 DN50	2.375 60.3	x	2.375 60.3	x	2.375 60.3	2.75 70	7.00 178	9.00 229	4.63 117	6.4 2.9
2½	x	2½	x	2½	2.875 73.0	x	2.875 73.0	x	2.875 73.0	3.00 76	7.75 197	10.50 267	5.75 146	11.5 5.2
3 DN80	x	3 DN80	x	2 DN50	3.500 88.9	x	3.500 88.9	x	2.375 60.3	3.25 83	8.50 216	10.38 264	6.00 152	12.5 5.7
				3 DN80					3.500 88.9	3.25 83	8.50 216	11.50 292	6.50 165	14.3 6.5
3½ DN90	x	3½ DN90	x	3½ DN90	4.000 101.6	x	4.000 101.6	x	4.000 101.6	3.25 83	10.00 254	13.00 330	7.75 197	15.0 6.8
4 DN100	x	4 DN100	x	1 DN25	4.500 114.3	x	4.500 114.3	x	1.315 33.7	3.75 95	10.50 267	12.25 311	8.38 213	17.0 7.7
				2 DN50					2.375 60.3	3.75 95	10.50 267	11.88 302	7.50 191	20.0 9.1
				3 DN80					3.500 88.9	3.75 95	10.50 267	12.88 327	7.88 200	23.0 10.4
				4 DN100					4.500 114.3	3.75 95	10.00 254	13.63 346	8.13 206	26.0 11.8
				5					5.563 141.3	4.00 102	12.50 318	13.13 333	8.75 222	29.0 13.2
5 DN150	x	5 DN150	x	2 DN50	5.563 141.3	x	5.563 141.3	x	2.375 60.3	4.00 102	12.50 318	13.13 333	8.75 222	29.0 13.2
				3 DN80					3.500 88.9	4.00 102	12.50 318	14.25 362	9.25 235	31.5 14.3
				4 DN100					4.500 114.3	4.00 102	12.50 318	15.13 384	9.63 244	36.7 16.6
				5					5.563 141.3	4.00 102	12.50 318	16.13 410	10.00 254	48.0 21.8
				6					6.625 168.3	4.50 114	14.00 356	14.13 359	9.75 248	29.0 13.2
				7					7.687 195.6	5.00 127	15.00 381	15.13 389	10.31 262	37.3 16.9
6 DN200	x	6 DN200	x	2 DN50	6.625 168.3	x	6.625 168.3	x	2.375 60.3	4.50 114	14.00 356	14.13 359	9.75 248	29.0 13.2
				3 DN80					3.500 88.9	4.50 114	14.00 356	15.31 389	10.31 262	37.3 16.9
				4 DN100					4.500 114.3	4.50 114	14.00 356	16.25 413	10.75 273	46.3 21.0
				5					5.563 141.3	4.50 114	14.00 356	17.25 438	11.13 283	55.0 25.0
				6 DN150					6.625 168.3	4.50 114	14.00 356	18.25 464	11.50 292	60.5 27.4
				7					7.687 195.6	5.00 127	15.00 381	19.25 489	11.88 303	70.0 31.8
				8					8.649 219.9	5.50 139	16.00 406	20.25 514	12.25 314	80.0 36.3
				9					9.611 244.2	6.00 152	17.00 430	21.25 539	12.63 325	90.0 40.8
8 DN200	x	8 DN200	x	2 DN50	8.625 219.1	x	8.625 219.1	x	2.375 60.3	6.00 152	18.00 457	17.00 432	12.63 321	70.0 31.8
				3 DN80					3.500 88.9	6.00 152	18.00 457	18.19 462	13.19 335	76.0 34.5
				4 DN100					4.500 114.3	6.00 152	18.00 457	19.00 483	13.50 343	76.4 34.6
				5					5.563 141.3	6.00 152	18.00 457	20.00 508	13.88 352	85.6 38.8
				6 DN150					6.625 168.3	6.00 152	18.00 457	21.13 537	14.38 365	112.0 50.8
				7					7.687 195.6	6.50 165	19.00 481	22.13 562	14.76 373	127.9 58.0
				8					8.649 219.9	7.00 178	20.00 508	23.13 587	15.14 380	147.0 66.7
				9					9.611 244.2	7.50 190	21.00 533	24.13 612	15.52 388	166.0 75.3

(sw) = Carbon Steel Segmentally Welded

4.8 DIMENSIONS

Tee Wye

No. 32






Size				No. 32 Tee Wye (sw)				Approx. Weight (Each) lb kg						
Nominal inches DN		Actual Outside Diameter inches mm		G inches mm	H inches mm	E1 inches mm	E2 inches mm							
10 DN250	x	10 DN250	x	2 DN50	10.750 273.0	x	10.750 273.0	x	2.375 60.3	6.50 165	20.50 521	18.75 476	14.38 365	90.0 40.8
				3 DN80			3.500 88.9	6.50 165	20.50 521	19.88 505	14.88 378	96.0 43.5		
				4 DN100			4.500 114.3	6.50 165	20.50 521	20.75 527	15.25 387	97.4 44.2		
				5			5.563 141.3	6.50 165	20.50 521	21.88 556	15.75 400	115.0 52.2		
				6 DN150			6.625 168.3	6.50 165	20.50 521	22.88 581	16.13 410	133.1 60.4		
				8 DN200			8.625 219.1	6.50 165	20.50 521	27.25 692	19.25 489	156.0 70.8		
				10 DN250			10.750 273.0	6.50 165	20.50 521	27.25 692	18.00 457	190.0 86.2		
				12 DN300			12.750 323.9	7.00 178	23.00 584	20.75 527	16.38 416	120.0 54.4		
				3 DN80			3.500 88.9	7.00 178	23.00 584	21.75 552	16.75 425	125.0 56.7		
				4 DN100			4.500 114.3	7.00 178	23.00 584	22.63 575	17.13 435	127.0 57.6		
5			5.563 141.3	7.00 178	23.00 584	23.63 600	17.50 445	143.0 64.9						
6 DN150			6.625 168.3	7.00 178	23.00 584	24.78 629	18.03 458	165.0 74.8						
8 DN200			8.625 219.1	7.00 178	23.00 584	26.92 684	18.92 481	176.0 79.8						
10 DN250			10.750 273.0	7.00 178	23.00 584	29.00 737	19.75 502	200.0 90.7						
12 DN300			12.750 323.9	7.00 178	23.00 584	31.00 787	20.50 521	240.0 108.9						

(sw) = Carbon Steel Segmentally Welded

4.9 DIMENSIONS

Adapter Nipple

No. 40
No. 42
No. 43



Size		No. 40 Adapter Nipple Groove x Male Thread ² (s)		No. 42 Adapter Nipple Groove x Bevel (s)		No. 43 Adapter Nipple Groove x Groove (s)	
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
¾ DN20	1.050 26.9	3.00 76	0.3 0.1	3.00 76	0.3 0.1	3.00 76	0.3 0.1
1 DN25	1.315 33.7	3.00 76	0.4 0.2	3.00 76	0.4 0.2	3.00 76	0.4 0.2
1¼ DN32	1.660 42.4	4.00 102	0.8 0.3	4.00 102	0.8 0.3	4.00 102	0.8 0.3
1½ DN40	1.900 48.3	4.00 102	0.9 0.4	4.00 102	0.9 0.4	4.00 102	0.9 0.4
2 DN50	2.375 60.3	4.00 102	1.2 0.6	4.00 102	1.2 0.6	4.00 102	1.2 0.6
2½	2.875 73.0	4.00 102	1.9 0.9	4.00 102	1.9 0.9	4.00 102	1.9 0.9
DN65	3.000 76.1	4.00 102	2.0 0.9	4.00 102	2.0 0.9	4.00 102	2.0 0.9
3 DN80	3.500 88.9	4.00 102	2.5 1.1	4.00 102	2.5 1.1	4.00 102	2.5 1.1
3½ DN90	4.000 101.6	4.00 102	3.0 1.4	4.00 102	3.0 1.4	4.00 102	3.0 1.4
	4.250 108.0	6.00 152	4.9 2.2	6.00 152	4.9 2.2	6.00 152	4.9 2.2
4 DN100	4.500 114.3	6.00 152	5.4 2.5	6.00 152	5.4 2.5	6.00 152	5.4 2.5
4½	5.000 127.0	6.00 152	6.3 2.8	6.00 152	6.3 2.8	6.00 152	6.3 2.8
	5.250 133.0	6.00 152	6.9 3.1	6.00 152	6.9 3.1	6.00 152	6.9 3.1
DN125	5.500 139.7	6.00 152	7.2 3.3	6.00 152	7.2 3.3	6.00 152	7.2 3.3
5	5.563 141.3	6.00 152	7.3 3.3	6.00 152	7.3 3.3	6.00 152	7.3 3.3
	6.000 152.4	6.00 152	8.6 3.9	6.00 152	8.6 3.9	6.00 152	8.6 3.9
	6.250 159.0	6.00 152	9.0 4.1	6.00 152	9.0 4.1	6.00 152	9.0 4.1
	6.500 165.1	6.00 152	9.3 4.2	6.00 152	9.3 4.2	6.00 152	9.3 4.2
6 DN150	6.625 168.3	6.00 152	9.5 4.3	6.00 152	9.5 4.3	6.00 152	9.5 4.3
8 DN200	8.625 219.1	6.00 152	14.3 6.5	6.00 152	14.3 6.5	6.00 152	14.3 6.5
10 DN250	10.750 273.0	8.00 203	22.8 10.3	8.00 203	22.8 10.3	8.00 203	22.8 10.3
12 DN300	12.750 323.9	8.00 203	33.1 15.0	8.00 203	33.1 15.0	8.00 203	33.1 15.0

¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(s) = Carbon Steel Segmentally Welded




NOTE

- For pump package nipples with 1½"/40mm hole cut to receive Style 923 Vic-Let or Style 924 Vic-O-Well request special No. 40, 42 or 43 nipples and specify No. 40-H, 42-H or 43-H on order. Note: 4 – 12"/DN100 – N300 diameter – 8"/200mm length required.

4.9 DIMENSIONS (CONTINUED)

Adapter Nipple

No. 40
No. 42
No. 43



Size		No. 40 Adapter Nipple Groove x Male Thread ² (s)		No. 42 Adapter Nipple Groove x Bevel (s)		No. 43 Adapter Nipple Groove x Groove (s)	
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
14 ¹ DN350	14.000 355.6	8.00 203	36.5 16.5	8.00 203	36.5 16.5	8.00 203	36.5 16.5
16 ¹ DN400	16.000 406.4	8.00 203	41.8 19.0	8.00 203	41.8 19.0	8.00 203	41.8 19.0
18 ¹ DN450	18.000 457.2	8.00 203	47.2 21.4	8.00 203	47.2 21.4	8.00 203	47.2 21.4
20 ¹ DN500	20.000 508.0	8.00 203	52.5 23.8	8.00 203	52.5 23.8	8.00 203	52.5 23.8
22 DN550	22.000 558.8	8.00 203	57.9 26.3	8.00 203	57.9 26.3	8.00 203	57.9 26.3
24 ¹ DN600	24.000 609.6	8.00 203	63.2 28.7	8.00 203	63.2 28.7	8.00 203	63.2 28.7
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05						



¹ For 14"/DN350 and larger roll grooved systems for carbon steel pipe, Victaulic offers fittings for the Advanced Groove System (AGS). Refer to [publication 20.05](#) for more information. For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

² Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(s) = Carbon Steel Segmentally Welded

NOTE

- For pump package nipples with 1 1/2"/40mm hole cut to receive Style 923 Vic-Let or Style 924 Vic-O-Well request special No. 40, 42 or 43 nipples and specify No. 40-H, 42-H or 43-H on order. Note: 4 – 12"/DN100 – N300 diameter – 8"/200mm length required.


4.10 DIMENSIONS

Cap

No. 60

Bull Plug

No. 61



Size		No. 60 Cap		No. 61 Bull Plug (s)	
Nominal	Actual Outside Diameter	T	Approx. Weight (Each)	E to E	Approx. Weight (Each)
inches DN	inches mm	inches mm	lb kg	inches mm	lb kg
¾ DN20	1.050 26.9	0.91 (s) 23	0.2 0.1	NA	NA
1 DN25	1.315 33.7	0.79 20	0.2 0.1	NA	NA
1 ¼ DN32	1.660 42.4	0.79 20	0.4 0.2	NA	NA
1 ½ DN40	1.900 48.3	0.79 20	0.4 0.2	NA	NA
2 DN50	2.375 60.3	0.88 22	0.7 0.3	4.00 102	2.6 1.2
2 ½	2.875 73.0	0.88 22	1.2 0.5	5.00 127	3.0 1.4
DN65	3.000 76.1	0.88 22	1.2 0.5	NA	NA
3 DN80	3.500 88.9	0.88 22	1.7 0.7	6.00 152	4.5 2.0
3 ½ DN90	4.000 101.6	0.88 22	1.9 0.9	NA	NA
	4.250 108.0	0.92 23	2.6 1.2	NA	NA
4 DN100	4.500 114.3	0.92 23	3.1 1.4	7.00 178	7.5 3.4
4 ½	5.000 127.0	1.00 (s) 25	5.4 2.4	NA	NA
	5.250 133.0	0.92 23	3.9 1.8	NA	NA
DN125	5.500 139.7	0.92 23	4.5 2.0	NA	NA
5	5.563 141.3	0.92 23	4.9 2.2	8.00 203	11.5 5.2
	6.250 159.0	0.92 23	5.7 2.6	NA	NA
	6.500 165.1	0.92 23	6.2 2.8	NA	NA
6 DN150	6.625 168.3	0.92 23	6.4 2.9	10.00 254	18.0 8.2
200A	216.3	1.13 29	17.4 7.9	NA	NA

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details

NOTES

- All fittings are ductile iron unless otherwise noted with an (s).
- No. 60 cap is not suitable for use in vacuum service with Style 72 or Style 750 couplings. No. 61 bull plugs should be used.
- Steel dish caps available through 24"/DN600, contact Victaulic.
- No. 61 Bull Plugs should be used in vacuum service with Style 72 or Style 750 couplings.


4.10 DIMENSIONS


Cap

No. 60

Bull Plug

No. 61



Size		No. 60 Cap		No. 61 Bull Plug (s)	
Nominal inches DN	Actual Outside Diameter inches mm	T inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
8 DN200	8.625 219.1	1.13 29	13.6 6.2	12.00 305	29.0 13.2
10 DN250	10.750 273.0	1.13 29	23.6 10.7	10.00 254	39.0 17.7
12 DN300	12.750 323.9	1.25 32	38.5 17.5	NA	NA
14 ¹ DN350	14.000 355.6	9.50 (s) 241	42.0 19.1	NA	NA
16 ¹ DN400	16.000 406.4	10.00 (s) 254	45.0 20.4	NA	NA
18 ¹ DN450	18.000 457.2	11.00 (s) 279	58.0 26.3	NA	NA
20 ¹ DN500	20.000 508.0	12.00 (s) 305	67.5 30.6	NA	NA
22 DN550	22.000 558.8	13.00 (s) 330	+	NA	NA
24 ¹ DN600	24.000 609.6	13.50 (s) 343	105.0 47.6	NA	NA
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05 				

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (s).
- No. 60 cap is not suitable for use in vacuum service with Style 72 or Style 750 couplings. No. 61 bull plugs should be used.
- Steel dish caps available through 24"/DN600, contact Victaulic.
- No. 61 Bull Plugs should be used in vacuum service with Style 72 or Style 750 couplings.

4.11 DIMENSIONS

Flanged Adapter Nipple

No. 41



Size		No. 41 ANSI Class 125 Flange Adapter Nipple Flat Face (s)		No. 41-DN PN10/16 Flange Adapter Nipple Flat Face (s)	
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
3/4 DN20	1.050 26.9	3.00 76	+ 2.0 0.9	NA 3.00 76	NA 2.6 1.2
1 DN25	1.315 33.7	3.00 76	2.0 0.9	3.00 76	2.6 1.2
1 1/4 DN32	1.660 42.4	4.00 102	3.0 1.4	3.00 76	4.1 1.9
1 1/2 DN40	1.900 48.3	4.00 102	3.5 1.6	NA	NA
2 DN50	2.375 60.3	4.00 102	5.5 2.5	4.00 102	6.2 2.8
2 1/2	2.875 73.0	4.00 102	8.0 3.6	NA	NA
DN65	3.000 76.1	NA	NA	4.00 102	7.1 3.2
3 DN80	3.500 88.9	4.00 102	9.5 4.3	4.00 102	9.0 4.1
3 1/2 DN90	4.000 101.6	4.00 102	+ NA	NA	NA
	4.250 108.0	NA	NA	NA	NA
4 DN100	4.500 114.3	6.00 152	16.7 7.6	6.00 152	12.8 5.8
4 1/2	5.000 127.0	NA	NA	NA	NA
	5.250 133.0	NA	NA	NA	NA
DN125	5.500 139.7	NA	NA	6.00 152	16.8 7.6
5	5.563 141.3	6.00 152	21.5 9.8	NA	NA
	6.500 165.1	NA	NA	NA	NA
6 DN150	6.625 168.3	6.00 152	26.5 12.0	6.00 152	20.5 9.3
200A	216.3	NA	NA	NA	NA

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel


NA = Not Available

"+" = Contact Victaulic for details

4.11 DIMENSIONS (CONTINUED)

Flanged Adapter Nipple

No. 41



Size		No. 41 ANSI Class 125 Flange Adapter Nipple Flat Face (s)		No. 41-DN PN10/16 Flange Adapter Nipple Flat Face (s)	
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
8 DN200	8.625 219.1	6.00 152	39.0 17.7	6.00 152	30.8 14.0
250A	267.4	NA	NA	NA	NA
10 DN250	10.750 273.0	8.00 203	64.2 29.1	8.00 203	46.3 21.0
300A	318.5	NA	NA	NA	NA
12 DN300	12.750 323.9	8.00 203	87.0 39.5	8.00 203	58.7 26.6

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel


NA = Not Available

"+" = Contact Victaulic for details

4.11 DIMENSIONS (CONTINUED)

Flanged Adapter Nipple

No. 45F
 No. 45R
 No. 45FE



Size		No. 45F ANSI Class 150 Flange Adapter Nipple Flat Face		No. 45R ANSI Class 150 Flange Adapter Nipple Raised Face		No. 45FE PN10/16 Flange Adapter Nipple Flat Face	
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
¾ DN20	1.050 26.9	3.00 (s) 76	2.0 0.9	3.00 (s) 76	2.0 0.9	NA	NA
1 DN25	1.315 33.7	3.00 (s) 76	2.7 1.2	3.00 (s) 76	2.7 1.2	NA	NA
1¼ DN32	1.660 42.4	4.00 (s) 102	3.6 1.6	4.00 (s) 102	3.6 1.6	NA	NA
1½ DN40	1.900 48.3	4.00 (s) 102	3.9 1.8	4.00 (s) 102	3.9 1.8	2.52 64	+
2 DN50	2.375 60.3	4.00 102	6.0 2.7	4.00 102	6.0 2.7	2.52 64	+
2½	2.875 73.0	4.00 102	9.9 4.5	4.00 102	9.9 4.5	NA	NA
DN65	3.000 76.1	NA	NA	NA	NA	2.52 64	+
3 DN80	3.500 88.9	4.00 102	11.7 5.3	4.00 102	11.7 5.3	2.52 64	+
3½ DN90	4.000 101.6	4.00 (s) 102	13.8 6.3	4.00 (s) 102	13.8 6.3	NA	NA
	4.250 108.0	NA	NA	NA	NA	NA	NA
4 DN100	4.500 114.3	6.00 152	18.5 8.4	6.00 152	18.5 8.4	2.76 70	+
DN125	5.500 139.7	NA	NA	NA	NA	2.76 70	+
5	5.563 141.3	6.00 (s) 152	21.4 9.7	6.00 (s) 152	21.4 9.7	NA	NA
	6.500 165.1	NA	NA	NA	NA	2.76 70	+
6 DN150	6.625 168.3	6.00 (s) 152	29.0 13.2	6.00 (s) 152	29.0 13.2	2.76 70	+
8 DN200	8.625 219.1	6.00 (s) 152	42.0 19.1	6.00 (s) 152	42.0 19.1	3.15 80	0.0 0.0
10 DN250	10.750 273.0	8.00 (s) 203	64.2 29.1	8.00 (s) 203	64.2 29.1	3.15 80	0.0 0.0
12 DN300	12.750 323.9	8.00 (s) 203	88.2 40.0	8.00 (s) 203	88.2 40.0	3.15 80	0.0 0.0
14 ¹ DN350	14.000 355.6	8.00 (s) 203	126.4 57.3	8.00 (s) 203	126.4 57.3	NA	NA
16 ¹ DN400	16.000 406.4	8.00 (s) 203	150.0 68.0	8.00 (s) 203	150.0 68.0	NA	NA

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details


NOTE

- All fittings are ductile iron unless otherwise noted with an (s).

4.11 DIMENSIONS (CONTINUED)

Flanged Adapter Nipple

No. 45F
 No. 45R
 No. 45FE



Size		No. 45F ANSI Class 150 Flange Adapter Nipple Flat Face		No. 45R ANSI Class 150 Flange Adapter Nipple Raised Face		No. 45FE PN10/16 Flange Adapter Nipple Flat Face	
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
18 ¹	18.000	8.00 (s)	177.0	8.00 (s)	177.0	NA	NA
DN450	457.2	203	80.3	203	80.3	NA	NA
20 ¹	20.000	8.00 (s)	218.0	8.00 (s)	218.0	NA	NA
DN500	508.0	203	98.9	203	98.9	NA	NA
24 ¹	24.000	8.00 (s)	283.0	8.00 (s)	283.0	NA	NA
DN600	609.6	203	128.4	203	128.4	NA	NA
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05						

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details



NOTE


- All fittings are ductile iron unless otherwise noted with an (s).

4.16 DIMENSIONS (CONTINUED)

Flange Adapter Nipple

No 46F
No 46R



Size		No. 46F ANSI Class 300 Flange Adapter Nipple Flat Face (s)		No. 46R ANSI Class 300 Flange Adapter Nipple Raised Face (s)	
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
3/4 DN20	1.050 26.9	3.00 76	3.3 1.5	3.00 76	+ +
1 DN25	1.315 33.7	3.00 76	3.9 1.8	3.00 76	3.9 1.8
1 1/4 DN32	1.660 42.4	4.00 102	4.8 2.2	4.00 102	4.8 2.2
1 1/2 DN40	1.900 48.3	4.00 102	6.9 3.1	4.00 102	6.9 3.1
2 DN50	2.375 60.3	4.00 102	8.1 3.7	4.00 102	8.1 3.7
2 1/2	2.875 73.0	4.00 102	11.9 5.4	4.00 102	11.9 5.4
3 DN80	3.500 88.9	4.00 102	16.5 7.5	4.00 102	16.5 7.5
3 1/2 DN90	4.000 101.6	4.00 102	20.1 9.1	4.00 102	20.1 9.1
4 DN100	4.500 114.3	6.00 152	27.4 12.4	6.00 152	27.4 12.4
5	5.563 141.3	6.00 152	35.3 16.0	6.00 152	35.3 16.0
6 DN150	6.625 168.3	6.00 152	47.5 21.5	6.00 152	47.5 21.5
8 DN200	8.625 219.1	6.00 152	68.0 30.8	6.00 152	68.0 30.8
10 DN250	10.750 273.0	8.00 203	100.8 45.7	8.00 203	100.8 45.7
12 DN300	12.750 323.9	8.00 203	148.0 67.1	8.00 203	148.0 67.1
14 ¹ DN350	14.000 355.6	8.00 203	180.0 81.8	NA	NA
16 ¹ DN400	16.000 406.4	8.00 203	237.0 107.5	NA	NA
18 ¹ DN450	18.000 457.2	8.00 203	297.0 134.7	NA	NA
20 ¹ DN500	20.000 508.0	8.00 203	+ +	NA	NA
22 DN550	22.000 558.8	8.00 203	+ +	NA	NA
24 ¹ DN600	24.000 609.6	8.00 203	+ +	NA	NA
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05 				

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

+ = Contact Victaulic for details




4.12 DIMENSIONS

Swaged Nipple

No. 53

No. 54

No. 55



Size		No. 53 Swage Nipple Groove x Groove (s)		No. 54 Swage Nipple Groove x Male Thread ¹ (s)		No. 55 Swage Nipple Male Thread ¹ x Groove (s)	
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
2 DN50	x ¾ DN20 2.375 60.3	1.050 26.9	6.50 165	2.0 0.9	NA	NA	NA
		1.315 33.7	6.50 165	2.0 0.9	6.50 165	2.0 0.9	6.50 165
		1.660 42.4	6.50 165	2.0 0.9	6.50 165	2.0 0.9	6.50 165
		1.900 48.3	6.50 165	2.0 0.9	6.50 165	2.0 0.9	6.50 165
		2.375 60.3	6.50 165	2.0 0.9	6.50 165	2.0 0.9	6.50 165
2½	x 1 DN25 2.875 73.0	1.315 33.7	7.00 178	3.0 1.4	7.00 178	3.0 1.4	7.00 178
		1.660 42.4	7.00 178	3.0 1.4	7.00 178	3.0 1.4	7.00 178
		1.900 48.3	7.00 178	3.0 1.4	7.00 178	3.0 1.4	7.00 178
		2.375 60.3	7.00 178	3.0 1.4	7.00 178	3.0 1.4	7.00 178
		2.875 73.0	7.00 178	3.0 1.4	7.00 178	3.0 1.4	7.00 178
DN65	x 1½ DN40 3.000 76.1	1.900 48.3	NA	NA	8.00 203	4.0 1.8	NA
		2.375 60.3	8.00 203	4.0 1.8	NA	NA	NA
		2.875 73.0	8.00 203	4.5 2.0	8.00 203	4.5 2.0	8.00 203
3 DN80	x 1 DN25 3.500 88.9	1.315 33.7	8.00 203	4.5 2.0	8.00 203	4.5 2.0	8.00 203
		1.660 42.4	8.00 203	4.5 2.0	8.00 203	4.5 2.0	8.00 203
		1.900 48.3	8.00 203	4.5 2.0	8.00 203	4.5 2.0	8.00 203
		2.375 60.3	8.00 203	4.5 2.0	8.00 203	4.5 2.0	8.00 203
		2.875 73.0	8.00 203	4.5 2.0	8.00 203	4.5 2.0	8.00 203
		3.000 76.1	8.00 203	4.5 2.0	8.00 203	4.5 2.0	8.00 203
		3.500 88.9	8.00 203	4.5 2.0	8.00 203	4.5 2.0	8.00 203
		4.000 101.6	8.00 203	4.5 2.0	8.00 203	4.5 2.0	8.00 203
3½ DN90	x 3 DN80 4.000 101.6	3.500 88.9	8.00 203	6.8 3.1	8.00 203	6.8 3.1	8.00 203
		4.500 114.3	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229
4 DN100	x 1 DN25 4.500 114.3	1.315 33.7	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229
		1.660 42.4	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229
		1.900 48.3	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229
		2.375 60.3	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229
		2.875 73.0	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229
		3.000 76.1	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229
		3.500 88.9	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229
		4.000 101.6	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229
		4.500 114.3	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229
		5.000 127.0	9.00 229	7.5 3.4	9.00 229	7.5 3.4	9.00 229

¹ Available with British Standard Pipe Threads, specify BSP clearly on order.

(s) = Carbon Steel

NA = Not Available




4.12 DIMENSIONS

Swaged Nipple

No. 53

No. 54

No. 55



Size		No. 53 Swage Nipple Groove x Groove (s)		No. 54 Swage Nipple Groove x Male Thread ¹ (s)		No. 55 Swage Nipple Male Thread ¹ x Groove (s)			
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg		
5 x 2 DN50	5.563 x 2.375 141.3 x 60.3	11.00	11.5 5.2	11.00	11.5 5.2	11.00	11.5 5.2		
	3 DN80	3.500	11.00	11.00	11.5	11.00	11.5		
		88.9	279	279	5.2	279	279	5.2	
	4 DN100	4.500 114.3	11.00 279	11.5 5.2	11.00 279	11.5 5.2	11.00 279	11.5 5.2	
6 x 1 DN150	x 1.315 x 33.7	12.00	17.0	12.00	17.0	12.00	17.0		
		305	7.7	305	7.7	305	7.7		
		1 ¼ DN32	1.660	12.00	17.0	12.00	17.0	12.00	17.0
			42.4	305	7.7	305	7.7	305	7.7
		1 ½ DN40	1.900	12.00	17.2	12.00	17.2	12.00	17.0
			48.3	305	7.8	305	7.8	305	7.7
		2 DN50	2.375	12.00	17.4	12.00	17.4	12.00	17.4
			60.3	305	7.9	305	7.9	305	7.9
		2 ½	2.875	12.00	17.4	12.00	17.4	12.00	17.4
			73.0	305	7.9	305	7.9	305	7.9
		3 DN80	3.500	12.00	17.4	12.00	17.4	12.00	17.4
			88.9	305	7.9	305	7.9	305	7.9
		3 ½ DN90	4.000	12.00	17.5	12.00	17.5	NA	NA
			101.6	305	7.9	305	7.9	NA	NA
4 DN100	4.500	12.00	17.5	12.00	17.5	12.00	17.5		
	114.3	305	7.9	305	7.9	305	7.9		
4 ½	5.000	12.00	17.5	12.00	17.5	NA	NA		
	127.0	305	7.9	305	7.9	NA	NA		
5	5.563	12.00	17.5	12.00	17.5	12.00	17.5		
	141.3	305	7.9	305	7.9	305	7.9		
8 x 6 DN200 DN150	8.625 x 6.625 219.1 x 168.3	12.00	29.0	12.00	29.0	12.00	29.0		
		305	13.2	305	13.2	305	13.2		

¹ Available with British Standard Pipe Threads, specify BSP clearly on order.


(s) = Carbon Steel

NA = Not Available

4.13 DIMENSIONS

Female Threaded Adapter

No. 80



Size		No. 80 Adapter Groove x Female Thread ¹		
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	
¾ DN20	1.050 26.9	2.00 (s) 51	0.6 0.3	
1 DN25	1.315 33.7	2.08 53	0.4 0.2	
1¼ DN32	1.660 42.4	2.29 58	0.6 0.3	
1½ DN40	1.900 48.3	2.29 58	1.0 0.5	
2 DN50	2.375 60.3	2.50 64	1.5 0.7	
2½	2.875 73.0	2.75 70	1.8 0.8	
DN65	3.000 76.1	2.75 70	2.2 1.0	
3 DN80	3.500 88.9	2.75 70	2.8 1.3	
4 DN100	4.500 114.3	3.25 83	4.5 2.0	

¹ Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(s) = Carbon Steel

NOTE


- All fittings are ductile iron unless otherwise noted with an (s).

4.15 DIMENSIONS

Concentric/Eccentric Reducer

No. 50

No. 51



Size			No. 50 Concentric Reducer		No. 51 Eccentric Reducer			
Nominal inches DN			Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	
1 DN25	x	¾ DN20	1.315 33.7	x 1.050 26.9	8.00 (s) 203	+	8.00 (s) 203	+
1 ¼ DN32	x	¾ DN20	1.660 42.4	x 1.050 26.9	8.00 (s) 203	1.3 0.6	8.00 (s) 203	1.3 0.6
					2.50 64	0.6 0.3	8.00 (s) 203	1.4 0.6
1 ½ DN40	x	¾ DN20	1.900 48.3	x 1.050 26.9	8.50 (s) 216	1.5 0.7	8.50 (s) 216	1.5 0.7
					2.50 64	0.8 0.4	8.50 (s) 216	1.7 0.8
					2.50 64	0.9 0.4	8.50 (s) 216	1.8 0.8
					2.50 64	0.9 0.4	8.50 (s) 216	1.8 0.8
2 DN50	x	¾ DN20	2.375 60.3	x 1.050 26.9	2.56 65	0.8 0.4	9.00 (s) 229	2.2 1.0
					2.50 64	0.7 0.3	9.00 (s) 229	2.3 1.0
					2.50 64	0.8 0.4	9.00 (s) 229	2.5 1.1
					2.50 64	1.2 0.5	3.50 89	1.1 0.5
					2.50 64	1.2 0.5	3.50 89	1.1 0.5
2 ½	x	¾ DN20	2.875 73.0	x 1.050 26.9	9.50 (s) 241	+	9.50 (s) 241	+
					2.50 64	1.4 0.6	9.50 (s) 241	3.4 1.5
					2.50 64	1.4 0.6	3.50 89	1.3 0.6
					2.50 64	1.4 0.6	9.50 (s) 241	3.8 1.7
					2.50 64	1.5 0.7	3.50 89	1.6 0.7
					2.50 64	1.5 0.7	3.50 89	1.6 0.7
					2.50 64	1.5 0.7	3.50 89	1.6 0.7
DN65	x	1 DN25	3.000 76.1	x 1.315 33.7	2.50 64	+	NA	NA
					2.50 64	+	NA	NA
					2.50 64	+	NA	NA
					2.50 64	+	NA	NA
					2.75 (s) 70	+	NA	NA

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details


NOTES

- All fittings are ductile iron unless otherwise noted with an (s).
- Available with make threaded small end No. 52
- Steel eccentric reducers available through 30"/DN750, contact Victaulic for dimensions.

4.15 DIMENSIONS (CONTINUED)

Concentric/Eccentric Reducer

No. 50
No. 51



Size		No. 50 Concentric Reducer		No. 51 Eccentric Reducer				
Nominal inches DN		Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg		
3 DN80	x ¾ DN20	3.500 88.9	1.050 26.9	9.50 (s) 241	+	9.50 (s) 241	+	
	1 DN25		1.315 33.7	2.50 64	1.8 0.8	9.50 (s) 241	4.8 2.2	
	1¼ DN32		1.660 42.4	2.50 64	1.4 0.6	9.50 (s) 241	5.0 2.3	
	1½ DN40		1.900 48.3	2.50 64	2.0 0.9	9.50 (s) 241	5.1 2.3	
	2 DN50		2.375 60.3	2.50 64	1.6 0.7	3.50 89	1.9 0.9	
	2½		2.875 73.0	2.50 64	1.7 0.7	3.50 89	2.1 1.0	
			3.000 76.1	2.50 64	2.1 1.0	9.50 (s) 241	5.4 2.4	
		DN65						
	3½ DN90	x 3 DN80	4.000 101.6	3.500 88.9	2.50 64	2.1 1.0	10.00 (s) 254	7.0 3.2
		4.250 108.0	2.875 73.0	3.50 89	+	NA	NA	
			3.000 76.1	3.50 89	+	NA	NA	
			3.500 88.9	3.50 89	+	NA	NA	
4 DN100	x 1 DN25	4.500 114.3	1.315 33.7	3.00 76	3.0 1.4	10.00 (s) 254	6.5 2.9	
	1¼ DN32		1.660 42.4	10.00 (s) 254	+	10.00 (s) 254	+	
	1½ DN40		1.900 48.3	3.00 76	2.6 1.2	10.00 (s) 254	6.9 3.1	
	2 DN50		2.375 60.3	3.00 76	3.4 1.5	4.00 102	2.9 1.3	
	DN65		3.000 76.1	3.00 76	3.3 1.5	4.00 102	3.2 1.4	
		2½	2.875 73.0	3.00 76	3.3 1.5	4.00 102	3.1 1.4	
	3 DN80		3.500 88.9	3.00 76	3.2 1.5	4.00 102	3.4 1.5	
	3½ DN90		4.000 101.6	3.00 76	3.0 1.4	10.00 (s) 254	8.1 3.7	
			5.250 133.0	4.250 108.0	4.50 114	+	NA	NA

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details

NOTES


- All fittings are ductile iron unless otherwise noted with an (s).
- Available with make threaded small end No. 52
- Steel eccentric reducers available through 30"/DN750, contact Victaulic for dimensions.

4.15 DIMENSIONS

Concentric/Eccentric Reducer

No. 50

No. 51



Size		No. 50 Concentric Reducer		No. 51 Eccentric Reducer	
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
DN125 x DN65	5.500 139.7	3.000 76.1	4.50 114	10.00 (s) 254	10.7 4.9
		3.500 88.9	4.50 114	NA	NA
		4.500 114.3	4.50 114	5.00 127	+
5 x 2 DN50	5.563 141.3	2.375 60.3	11.00 (s) 279	11.00 (s) 279	10.1 4.6
		2.875 73.0	4.00 102	11.00 279	10.8 4.9
		3.500 88.9	4.00 102	11.00 (s) 279	11.1 5.0
		4.000 101.6	11.00 (s) 279	11.00 (s) 279	+
		4.500 114.3	3.50 89	4.3 2.0	5.5 2.5
	6.250 159.0	3.500 88.9	4.50 114	NA	NA
		4.250 108.0	4.00 102	NA	NA
		4.500 114.3	4.00 102	NA	NA
		5.250 133.0	4.00 102	NA	NA
	6.500 165.1	2.375 60.3	4.00 102	NA	NA
		3.000 76.1	4.00 102	10.50 (s) 292	18.1 8.2
		3.500 88.9	4.00 102	5.50 140	6.1 2.8
		4.500 114.3	4.00 102	5.50 140	6.8 3.1
		5.500 139.7	4.00 102	5.50 140	8.0 3.6
		5.563 141.3	4.00 102	5.50 140	7.5 3.4
		6.250 159.0	4.00 102	6.6 3.0	NA

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details

NOTES


- All fittings are ductile iron unless otherwise noted with an (s).
- Available with make threaded small end No. 52
- Steel eccentric reducers available through 30"/DN750, contact Victaulic for dimensions.

4.15 DIMENSIONS

Concentric/Eccentric Reducer

No. 50

No. 51



Size		No. 50 Concentric Reducer		No. 51 Eccentric Reducer				
Nominal inches DN		Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg		
6 DN150	x	1.315 33.7	4.00	6.2	11.50 (s)	+		
			1.900	2.8	292			
			1 ½ DN40	11.50 (s)	+	11.50 (s)	+	
			48.3	292		292		
			2 DN50	4.00	6.6	11.50 (s)	14.2	
			60.3	102	3.0	292	6.4	
			2 ½	2.875	6.4	11.50 (s)	14.2	
			73.0	102	2.9	292	6.4	
			3.000	11.50 (s)	+	11.50 (s)	+	
			76.1	292		292		
			3 DN80	3.500	6.4	5.50	7.4	
			88.9	102	2.9	140	3.4	
			4 DN100	4.500	5.8	5.50	7.8	
			114.3	102	2.6	140	3.5	
	5.500	NA	NA	5.50	8.1			
	139.7			140	3.7			
	5 DN125	5.563	4.00	6.4	5.50	8.1		
		141.3	102	2.9	140	3.7		
		6.500	4.00	7.2	11.50 (s)	+		
		165.1	102	3.3	292			
		8.515 216.3	5.00	+	NA	NA		
			127					
			4.500	5.00	NA	NA		
			114.3	127				
			5.500	4.50	NA	NA		
			139.7	114				
200A	x	165A	216.3	6.500	5.00	9.5	NA	NA
			165.1	127	4.3			

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details

NOTES


- All fittings are ductile iron unless otherwise noted with an (s).
- Available with make threaded small end No. 52
- Steel eccentric reducers available through 30"/DN750, contact Victaulic for dimensions.

4.15 DIMENSIONS

Concentric/Eccentric Reducer

No. 50

No. 51



Size		Actual Outside Diameter		No. 50 Concentric Reducer		No. 51 Eccentric Reducer	
Nominal inches DN		inches	mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
8 DN200	x 2 1/2	8.625	2.875	12.00 (s)	+	12.00 (s)	+
		219.1	73.0	305		305	
	3 DN80	3.500	114.3	5.00	9.3	12.00 (s)	22.0
		88.9	108.0	127	4.2	305	10.0
	4 DN100	4.250	108.0	5.00	11.5	NA	NA
		108.0	114.3	127	5.2	NA	NA
	5 DN125	4.500	114.3	5.00	10.4	6.00	10.5
		114.3	139.7	127	4.7	152	4.8
	6 DN150	5.500	139.7	5.00	11.7	12.00 (s)	24.5
		139.7	141.3	127	5.3	305	11.1
	7 DN175	5.563	141.3	5.00	11.6	12.00 (s)	23.8
		141.3	159.0	127	5.3	305	10.8
8 DN200	6.250	159.0	4.50	11.9	NA	NA	
	159.0	165.1	114	5.4	NA	NA	
9 DN225	6.500	165.1	5.00	12.6	6.00	12.8	
	165.1	168.3	127	5.7	152	5.8	
10 DN250	6.625	168.3	5.00	11.9	6.00	13.2	
	168.3	178	127	5.4	152	6.0	
10 DN250	x 4 DN100	10.750	4.500	6.25	20.1	13.00 (s)	33.8
		273.0	114.3	159	9.1	330	15.3
	5 DN125	5.500	139.7	NA	NA	13.00 (s)	35.7
		139.7	141.3	330	NA	330	16.2
	6 DN150	5.563	141.3	13.00 (s)	35.8	13.00 (s)	35.8
		141.3	165.1	330	16.2	330	16.2
8 DN200	6.500	165.1	6.00	+	13.00 (s)	+	
	165.1	168.3	152	+	330	+	
250A	x 200A	267.4	216.3	6.00	23.0	NA	NA
		267.4	216.3	152	10.4	NA	NA
12 DN300	x 4 DN100	12.750	4.500	14.00 (s)	48.0	14.00 (s)	48.0
		323.9	114.3	356	21.8	356	21.8
	6 DN150	6.500	165.1	14.00 (s)	+	14.00 (s)	+
		165.1	168.3	356	+	356	+
	8 DN200	6.625	168.3	7.00	25.0	14.00 (s)	50.2
		168.3	178	178	11.3	356	22.8
	10 DN200	8.625	178	7.00	38.0	14.00 (s)	53.5
		178	219.1	178	17.2	356	24.3
12 DN200	10.750	219.1	7.00	38.0	14.00 (s)	56.5	
	219.1	273.0	178	17.2	356	25.6	

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details

NOTES


- All fittings are ductile iron unless otherwise noted with an (s).
- Available with make threaded small end No. 52
- Steel eccentric reducers available through 30"/DN750, contact Victaulic for dimensions.

4.15 DIMENSIONS

Concentric/Eccentric Reducer

No. 50

No. 51



Size			No. 50 Concentric Reducer		No. 51 Eccentric Reducer				
Nominal inches DN		Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg			
300A	x	250A	318.5	x	216.3	7.00 178	38.0 17.2	NA	NA
14 ¹ DN350	x	6 DN150	14.000 355.6	x	6.625 168.3	13.00 330	63.1 28.6	13.00 330	77.2 35.0
		8 DN200			8.625 219.1	13.00 330	72.7 33.0	13.00 330	81.6 37.0
					10.528 267.4	13.00 330	80.5 36.5	13.00 330	88.2 40.0
		10 DN200			10.750 273.0	13.00 330	80.5 36.5	13.00 330	88.2 40.0
					12.539 318.5	13.00 330	81.6 37.0	13.00 330	90.4 41.0
		12 DN300			12.750 323.9	13.00 330	81.6 37.0	13.00 330	90.4 41.0
16 ¹ DN400	x	8 DN200	16.000 406.4	x	8.625 219.1	14.00 356	80.5 36.5	14.00 356	99.2 45.0
		250A			267.4	14.00 356	93.0 42.2	NA	NA
					10.750 273.0	14.00 356	93.0 42.2	14.00 356	99.2 45.0
		10 DN200			12.539 318.5	14.00 356	100.3 45.5	14.00 356	103.6 47.0
					12.750 323.9	14.00 356	100.3 45.5	14.00 356	103.6 47.0
		12 DN300			14.000 355.6	14.00 356	100.3 45.5	14.00 356	108.0 49.0
		14 DN350							
18 ¹ DN450	x	10 DN200	18.000 457.2	x	10.750 273.0	15.00 381	112.4 51.0	15.00 381	125.7 57.0
		12 DN300			12.750 323.9	15.00 381	122.4 55.5	15.00 381	134.5 61.0
		14 DN350			14.000 355.6	15.00 381	122.4 55.5	15.00 381	136.7 62.0
		16 DN400			16.000 406.4	15.00 381	126.8 57.5	15.00 381	143.3 65.0

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details

NOTES


- All fittings are ductile iron unless otherwise noted with an (s).
- Available with make threaded small end No. 52
- Steel eccentric reducers available through 30"/DN750, contact Victaulic for dimensions.


4.15 DIMENSIONS

Concentric/Eccentric Reducer

No. 50

No. 51



Size		No. 50 Concentric Reducer		No. 51 Eccentric Reducer			
Nominal inches DN		Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	
20 ¹ DN500	x 10 DN200	20.000 508.0	x 10.750 273.0	20.00 508	160.0 72.6	20.00 508	172.0 78.0
	300A		318.5	20.00 508	162.3 73.6	NA	NA
	12		12.750	20.00 508	162.3 73.6	20.00 508	183.0 83.0
	14		14.000	20.00 508	177.5 80.5	20.00 508	191.8 87.0
	16		16.000	20.00 508	176.4 80.0	20.00 508	200.6 91.0
	18		18.000	20.00 508	205.0 93.0	20.00 508	209.4 95.0
	18		18.000	20.00 508	205.0 93.0	20.00 508	209.4 95.0
	18		18.000	20.00 508	205.0 93.0	20.00 508	209.4 95.0
24 ¹ DN600	x 10 DN200	24.000 609.6	x 10.750 273.0	20.00 508	222.7 101.0	20.00 508	222.7 101.0
	12		12.750	20.00 508	209.4 95.0	20.00 508	238.1 108.0
	14		14.000	20.00 508	213.8 97.0	20.00 508	246.9 112.0
	16		16.000	20.00 508	215.8 97.9	20.00 508	251.3 114.0
	18		18.000	20.00 508	229.3 104.0	20.00 508	244.7 111.0
	20		20.000	20.00 508	+	20.00 508	275.6 125.0
	20		20.000	20.00 508	+	20.00 508	275.6 125.0
	20		20.000	20.00 508	+	20.00 508	275.6 125.0
14 – 60 DN350 – DN1500	For AGS fitting information, see publication 20.05 						

¹ For 14"/DN350 and larger roll grooved systems, Victaulic offers the Advanced Groove System (AGS). For pricing and availability of cut groove fittings in this size, contact your nearest Victaulic sales representative.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details

NOTES

- All fittings are ductile iron unless otherwise noted with an (s).
- Available with make threaded small end No. 52
- Steel eccentric reducers available through 30"/DN750, contact Victaulic for dimensions.

4.16 DIMENSIONS

Small Threaded Reducer

No. 52

No. 52F



Size			No. 52 Concentric Reducer Groove x Male Thread ¹		No. 52F Concentric Reducer Groove x Female BSPT Thread			
Nominal inches DN		Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg		
1 ¼ DN32	x	1 DN25	1.660 42.4	x 1.315 33.7	NA	NA	2.50 64	0.4 0.2
1 ½ DN40	x	1 DN25	1.900 48.3	x 1.315 33.7	2.50 64	0.8 0.4	NA	NA
		1 ¼ DN32		1.660 42.4	2.50 64	0.9 0.4	NA	NA
2 DN50	x	¾ DN20	2.375 60.3	x 1.050 26.9	2.56 65	0.8 0.4	NA	NA
		1 DN25		1.315 33.7	2.50 64	0.9 0.4	NA	NA
		1 ¼ DN32		1.660 42.4	2.50 64	0.9 0.4	NA	NA
		1 ½ DN40		1.900 48.3	2.50 64	1.0 0.5	NA	NA
2 ½	x	1 DN25	2.875 73.0	x 1.315 33.7	2.50 64	1.1 0.5	NA	NA
		1 ¼ DN32		1.660 42.4	2.50 64	1.6 0.7	NA	NA
		1 ½ DN40		1.900 48.3	2.50 64	1.6 0.7	NA	NA
		2 DN50		2.375 60.3	2.50 64	1.8 0.8	NA	NA
DN65	x	1 DN25	3.000 76.1	x 1.315 33.7	2.50 64	1.8 0.8	NA	NA
		1 ¼ DN32		1.660 42.4	2.50 64	1.8 0.8	NA	NA
		1 ½ DN40		1.900 48.3	2.50 64	1.8 0.8	2.50 64	1.8 0.8
		2 DN50		2.375 60.3	2.50 64	1.8 0.8	2.50 64	2.0 0.9

¹ Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(s) = Carbon Steel

NA = Not Available



"+" = Contact Victaulic for details

NOTE

- All fittings are ductile iron unless otherwise noted with an (s).

4.16 DIMENSIONS

Small Threaded Reducer No. 52 No. 52F



Size				No. 52 Concentric Reducer Groove x Male Thread ¹		No. 52F Concentric Reducer Groove x Female BSPT Thread	
Nominal inches DN		Actual Outside Diameter inches mm		E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
3 DN80	x ¾ DN25	3.500 88.9	1.050	9.50 (s)	+	NA	NA
			26.9	241			
	1 DN25		1.315	2.50	1.8	NA	NA
			33.7	64	0.8		
	1 ¼ DN32		1.660	2.50	1.5	2.50	2.0
			42.4	64	0.7	64	0.9
	1 ½ DN40		1.900	2.50	2.2	2.50	2.0
			48.3	64	1.0	64	0.9
	2 DN50		2.375	2.50	2.0	2.50	2.0
			60.3	64	0.9	64	0.9
2 ½		2.875	2.50	2.4	NA	NA	
		73.0	64	1.1			
DN65		3.000	2.50	2.4	2.50	2.0	
		76.1	64	1.1	64	0.9	
		4.250 108.0	1.660	NA	NA	3.00	2.9
			42.4			76	1.3
			1.900	NA	NA	3.00	3.1
			48.3			76	1.4
			2.375	3.00	1.3	3.00	3.1
			60.3	76	0.6	76	1.4
			2.875	3.00	1.3	NA	NA
			73.0	76	0.6		
3.000	3.00	1.3	NA	NA			
76.1	76	0.6					
3.500	3.50	3.4	NA	NA			
88.9	89	1.5					
4 DN100	x 1 DN25	4.500 114.3	1.315	3.00	3.0	NA	NA
			33.7	76	1.4		
	1 ¼ DN32		1.660	NA	NA	3.00	3.3
			42.4			76	1.5
	1 ½ DN40		1.900	3.00	2.7	3.00	3.3
			48.3	76	1.2	76	1.5
	2 DN50		2.375	3.00	3.5	3.00	3.5
			60.3	76	1.6	76	1.6
	2 ½		2.875	3.00	3.5	NA	NA
			73.0	76	1.6		
DN65		3.000	3.00	2.9	NA	NA	
		76.1	76	1.3			
3 DN80		3.500	3.00	3.5	NA	NA	
		88.9	76	1.6			

¹ Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details

NOTE

- All fittings are ductile iron unless otherwise noted with an (s).

4.16 DIMENSIONS

Small Threaded Reducer No. 52 No. 52F



Size			No. 52 Concentric Reducer Groove x Male Thread ¹		No. 52F Concentric Reducer Groove x Female BSPT Thread		
Nominal inches DN	Actual Outside Diameter inches mm		E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg	
	5.250 133.0	x 3.500 88.9	4.50 114	4.6 2.1	NA	NA	
DN125	x DN65	5.500 139.7	x 3.000 76.1	4.50 114	4.4 2.0	NA	
			3.500 88.9	4.50 114	4.4 2.0	NA	
5	x 2 DN50	5.563 141.3	x 2.375 60.3	11.00 (s) 279	3.5 1.6	NA	
			3.500 88.9	11.00 (s) 279	3.6 1.6	NA	
			4.500 114.3	11.00 (s) 279	11.9 5.4	NA	
	6.250 159.0	x	1.660 42.4	NA	NA	4.50 114	5.5 2.5
			1.900 48.3	NA	NA	4.50 114	5.5 2.5
			2.375 60.3	NA	NA	4.50 114	5.5 2.5
			3.000 76.1	4.50 114	5.1 2.3	NA	NA
			3.500 88.9	4.75 121	5.5 2.5	NA	NA
	6.500 165.1	x	1.660 42.4	NA	NA	4.00 102	6.4 2.9
			1.900 48.3	NA	NA	4.00 102	6.6 3.0
			2.375 60.3	4.00 102	5.5 2.5	4.00 102	6.6 3.0
			3.000 76.1	4.00 102	5.9 2.7	NA	NA
			3.500 88.9	4.00 102	6.6 3.0	NA	NA

¹ Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(s) = Carbon Steel

NA = Not Available

"+" = Contact Victaulic for details

NOTE

- All fittings are ductile iron unless otherwise noted with an (s).

4.16 DIMENSIONS

Small Threaded Reducer No. 52 No. 52F



Size				No. 52 Concentric Reducer Groove x Male Thread ¹		No. 52F Concentric Reducer Groove x Female BSPT Thread	
Nominal inches DN		Actual Outside Diameter inches mm		E to E inches mm	Approx. Weight (Each) lb kg	E to E inches mm	Approx. Weight (Each) lb kg
6 DN150	x 1 DN25	6.625 168.3	1.315	4.00	5.5	NA	NA
			33.7	102	2.5	NA	NA
	2 DN50		2.375	4.00	6.7	NA	NA
			60.3	102	3.0	NA	NA
	2½		2.875	4.00	5.8	NA	NA
			73.0	102	2.6	NA	NA
3 DN80		3.500	4.00	8.0	NA	NA	
4 DN100		4.500	11.50 (s)	15.9	NA	NA	
		114.3	292	7.2	NA	NA	
		5.563	11.50 (s)	20.0	NA	NA	
8 DN200	x 4 DN100		4.500	12.00 (s)	22.9	NA	NA
			114.3	305	10.4	NA	NA
	6 DN150		6.625	12.00 (s)	25.0	NA	NA
		168.3	305	11.3	NA	NA	

¹ Available with British Standard Pipe Threads, specify "BSP" clearly on order.

(s) = Carbon Steel

NA = Not Available


"+" = Contact Victaulic for details

NOTE

- All fittings are ductile iron unless otherwise noted with an (s).

4.16 DIMENSIONS (CONTINUED)

Hose Nipple
No. 48



Size		No. 48 Hose Nipple (s)		
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	Approx. Weight (Each) lb kg	
¾ DN20	1.050 26.9	3.13 79	0.3 0.1	
1 DN25	1.315 33.7	3.38 86	0.4 0.2	
1¼ DN32	1.660 42.4	3.88 98	0.6 0.3	
1½ DN40	1.900 48.3	3.88 98	0.8 0.4	
2 DN50	2.375 60.3	4.50 114	1.0 0.4	
2½	2.875 73.0	5.38 137	2.0 0.9	
3 DN80	3.500 88.9	5.75 146	3.1 1.4	
4 DN100	4.500 114.3	7.00 178	4.9 2.2	
5	5.563 141.3	8.75 222	8.0 3.6	
6 DN150	6.625 168.3	10.13 257	14.3 6.5	
8 DN200	8.625 219.1	11.88 302	24.7 11.2	
10 DN250	10.750 273.0	12.50 318	41.0 18.6	
12 DN300	12.750 323.9	14.50 368	62.0 28.1	

(s) = Carbon Steel

5.0 PERFORMANCE

Flow Data

(Frictional Resistance)

The chart expresses the frictional resistance of various Victaulic fittings as equivalent feet of straight pipe. Fittings not listed can be estimated from the data given, for example, a 22½° elbow is approximately one-half the resistance of a 45° elbow. Values of mid-sizes can be interpolated.

Size		90° Elbows		45° Elbows		Tees	
Nominal inches DN	Actual Outside Diameter inches mm	No. 10 Std. Radius feet meters	No. 100 1 ½ D Long Radius inches mm	No. 11 Std. Radius feet meters	No. 110 1 ½ D Long Radius inches mm	Branch feet meters	Run feet meters
¾ DN20	1.050 26.9	1.4 0.4	–	0.7 0.2	–	3.3 1.0	1.4 0.4
1 DN25	1.315 33.7	1.7 0.5	–	0.8 0.2	–	4.2 1.3	1.7 0.5
1 ¼ DN32	1.660 42.4	2.1 0.6	–	1.0 0.3	–	5.3 1.6	2.1 0.6
1 ½ DN40	1.900 48.3	2.7 0.8	–	1.3 0.4	–	6.6 2.0	2.7 0.8
2 DN50	2.375 60.3	3.6 1.1	2.5 0.8	1.8 0.5	1.1 0.3	8.5 2.6	3.6 1.1
DN65	3.000 76.1	4.3 1.3	–	2.3 0.7	–	10.8 3.3	4.3 1.3
3 DN80	3.500 88.9	5.0 1.5	3.8 1.2	2.6 0.8	1.6 0.5	13.0 4.0	5.0 1.5
	4.250 108.0	6.4 2.0	–	3.2 1.0	–	15.3 4.7	6.4 2.0
4 DN100	4.500 114.3	6.8 2.1	5.0 1.5	3.4 1.0	2.1 0.6	16.0 4.9	6.8 2.1
	5.250 133.0	8.1 2.5	–	4.1 1.3	–	20.0 6.1	8.1 2.5
DN125	5.500 139.7	8.5 2.6	–	4.2 1.3	–	21.0 6.4	8.5 2.6
5	5.563 141.3	8.5 2.6	–	4.2 1.3	–	21.0 6.4	8.5 2.6
	6.250 159.0	9.4 2.9	–	4.9 1.5	–	25.0 7.6	9.6 2.9
	6.500 165.1	9.6 2.9	–	5.0 1.5	–	25.0 7.6	10.0 3.0
6 DN150	6.625 168.3	10.0 3.0	7.5 2.3	5.0 1.5	3.0 0.9	25.0 7.6	10.0 3.0
8 DN200	8.625 219.1	13.1 4.0	9.8 3.0	6.5 2.0	4.0 1.2	33.1 10.1	13.1 4.0
10 DN250	10.750 273.0	17.0 5.2	12.0 3.7	8.3 2.5	5.0 1.5	41.0 12.5	17.0 5.2
12 DN300	12.750 323.9	20.0 6.1	14.5 4.4	10.0 3.0	6.0 1.8	50.0 15.2	20.0 6.1
14 DN350	14.000 355.6	24.5 ¹ 7.5	15.8 4.8	18.5 ¹ 5.6	11.0 3.4	70.0 21.3	23.0 7.0
16 DN400	16.000 406.4	28.0 ¹ 8.5	18.0 5.5	21.0 ¹ 6.4	13.0 4.0	80.0 24.4	27.0 8.2
18 DN450	18.000 457.2	31.0 ¹ 9.4	20.0 6.1	23.5 ¹ 7.2	14.0 4.3	90.0 27.4	30.0 9.1
20 DN500	20.000 508.0	34.0 ¹ 10.4	22.5 6.9	25.5 ¹ 7.8	16.0 4.9	100.0 30.5	33.0 10.1
24 DN600	24.000 609.6	42.0 ¹ 12.8	27.0 8.2	29.5 ¹ 9.0	19.0 5.8	120.0 36.6	40.0 12.2

¹ Fitting flow data for 14-24/DN350-DN600 size No. 10 and No. 11 Elbows is based on fittings for Style 07 and Style 77 couplings. For flow data on AGS fittings (No. W10 and No. W11 Elbows), refer to publication 20.05.

6.0 NOTIFICATIONS

WARNING



- Read and understand all instructions before attempting to install any Victaulic products.
- Always verify that the piping system has been completely depressurized and drained immediately prior to installation, removal, adjustment, or maintenance of any Victaulic products.
- Confirm that any equipment, branch lines, or sections of piping that may have been isolated for/during testing or due to valve closures/positioning are identified, depressurized, and drained immediately prior to installation, removal, adjustment, or maintenance of any Victaulic products.
- The installer shall understand the use of this product and why it was specified for the particular application.
- The installer shall understand common industry safety standards and potential consequences of improper product installation.

- Wear safety glasses, hardhat, and foot protection.

Failure to follow these instructions could result in death or serious personal injury and property damage.

7.0 REFERENCE MATERIALS



Galvanized
[Publication 07.01](#) for Original Groove Fittings
[Publication 20.05](#) for AGS Fittings



Plain End
[Publication 14.04](#)



Extra Heavy EndSeal "ES"
[Publication 07.03](#)



Stainless Steel
[Publication 17.16](#)



Fabricated Steel Fittings
[Publication 07.04](#)



AGS - Advanced Groove System
from 14 – 60"/DN350 – DN1500
[Publication 20.05](#)



Shouldered Ends
[Publication 07.06](#)



Aluminum
[Publication 21.03](#)



xl fittings for abrasive services
[Publication 07.07](#)



Copper
[Publication 22.04](#)



Victaulic Base Support Elbows
[Publication 07.13](#)



Ductile Iron for AWWA size pipe
[Publication 23.05](#)

User Responsibility for Product Selection and Suitability

Each user bears final responsibility for making a determination as to the suitability of Victaulic products for a particular end-use application, in accordance with industry standards and project specifications, and the applicable building codes and related regulations as well as Victaulic performance, maintenance, safety, and warning instructions. Nothing in this or any other document, nor any verbal recommendation, advice, or opinion from any Victaulic employee, shall be deemed to alter, vary, supersede, or waive any provision of Victaulic Company's standard conditions of sale, installation guide, or this disclaimer.

Intellectual Property Rights

No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Victaulic or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right. The terms "Patented" or "Patent Pending" refer to design or utility patents or patent applications for articles and/or methods of use in the United States and/or other countries.

Note

This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

Installation

Reference should always be made to the Victaulic installation handbook or installation instructions of the product you are installing. Handbooks are included with each shipment of Victaulic products, providing complete installation and assembly data, and are available in PDF format on our website at www.victaulic.com.

Warranty

Refer to the Warranty section of the current Price List or contact Victaulic for details.

Trademarks

Victaulic and all other Victaulic marks are the trademarks or registered trademarks of Victaulic Company, and/or its affiliated entities, in the U.S. and/or other countries.